Data sheets - Siemens SIMOTICS GP motors

0.09 kW / 1000 rpm - 6 article numbers in this file

Article No.	Page
1LA7063-6AB10	2
1LA7063-6AB11	3
1LA7063-6AB12	4
1LE1002-0BC22-2AA4	5
1LE1002-0BC22-2FA4	6
1LE1002-0BC22-2KA4	7

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Data sheet

1LA7063-6AB10

SIMOTICS GP low-voltage motor - aluminum series 1LA7

0.09 kW / 1000 rpm

Frame size 063 M | Article No. 1LA7063-6AB10 | mounting IM B3

GENERAL DATA

Motor series	**1LA7 (aluminum)**
Article No.	**1LA7063-6AB10**
Frame size	**063 M**
Number of poles	**6**
Housing material	**Aluminum**
Degree of protection	**IP55**
Cooling	**Self-ventilated (IC 411)**
Insulation / utilization	**Thermal class 155 (F) / utilized to 130 (B)**
Duty type	**S1 (continuous duty)**
Rotor	**Squirrel-cage**
Efficiency class (IEC 60034-30)	**not classified (below IE1 range)**
Voltage / connection	**230 V D / 400 V Y (50 Hz), 460 V Y (60 Hz)**
Type of construction	**IM B3 (also B6, B7, B8, V5, V6)**
Net weight (IM B3)	**4 kg**

ELECTRICAL DATA - 400 V, 50 HZ

Rated power, 50 Hz	**0.09 kW (0.12 HP)**
Rated speed, 50 Hz	**850 rpm (synchronous 1000 rpm)**
Rated torque	**1 Nm**
Rated current at 400 V	**0.39 A**
No-load current	**0.46 A**
Power factor cos phi	**0.66**
Efficiency at 4/4 | 3/4 | 2/4 load	**50.2 | 48.7 | 44.2 %**
Locked-rotor current ratio (I_LR/I_N)	**2**
Locked-rotor torque ratio (T_LR/T_N)	**1.8**
Breakdown torque ratio (T_B/T_N)	**1.9**
Moment of inertia J	**0.00037 kgm2**
Torque class	**13**

60 HZ OPERATION

Rated power at 60 Hz (460 V)	**not listed in the catalog (DT Configurator)**
Synchronous speed at 60 Hz	**1200 rpm**
Speed / efficiency / current at 60 Hz	**not listed in the catalog (DT Configurator)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Source: Siemens Distribution brochure (07/2014), Chapter 2, p. 18. Dimensions: see the same catalog.
Compiled from the manufacturer's catalog data for reference. It is not an official Siemens document -
verify against the current Siemens data sheet before ordering. 60 Hz power, speed and efficiency for this code are not listed in the source.
Data at rated power, 400 V / 50 Hz, ambient 40 deg C, altitude up to 1000 m.

Data sheet

1LA7063-6AB11

SIMOTICS GP low-voltage motor - aluminum series 1LA7

0.09 kW / 1000 rpm

Frame size 063 M | Article No. 1LA7063-6AB11 | mounting IM B5

GENERAL DATA

Motor series	**1LA7 (aluminum)**
Article No.	**1LA7063-6AB11**
Frame size	**063 M**
Number of poles	**6**
Housing material	**Aluminum**
Degree of protection	**IP55**
Cooling	**Self-ventilated (IC 411)**
Insulation / utilization	**Thermal class 155 (F) / utilized to 130 (B)**
Duty type	**S1 (continuous duty)**
Rotor	**Squirrel-cage**
Efficiency class (IEC 60034-30)	**not classified (below IE1 range)**
Voltage / connection	**230 V D / 400 V Y (50 Hz), 460 V Y (60 Hz)**
Type of construction	**IM B5 (also V1, V3)**
Net weight (IM B3)	**4 kg**

ELECTRICAL DATA - 400 V, 50 HZ

Rated power, 50 Hz	**0.09 kW (0.12 HP)**
Rated speed, 50 Hz	**850 rpm (synchronous 1000 rpm)**
Rated torque	**1 Nm**
Rated current at 400 V	**0.39 A**
No-load current	**0.46 A**
Power factor cos phi	**0.66**
Efficiency at 4/4 | 3/4 | 2/4 load	**50.2 | 48.7 | 44.2 %**
Locked-rotor current ratio (I_LR/I_N)	**2**
Locked-rotor torque ratio (T_LR/T_N)	**1.8**
Breakdown torque ratio (T_B/T_N)	**1.9**
Moment of inertia J	**0.00037 kgm2**
Torque class	**13**

60 HZ OPERATION

Rated power at 60 Hz (460 V)	**not listed in the catalog (DT Configurator)**
Synchronous speed at 60 Hz	**1200 rpm**
Speed / efficiency / current at 60 Hz	**not listed in the catalog (DT Configurator)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Source: Siemens Distribution brochure (07/2014), Chapter 2, p. 18. Dimensions: see the same catalog.
Compiled from the manufacturer's catalog data for reference. It is not an official Siemens document -
verify against the current Siemens data sheet before ordering. 60 Hz power, speed and efficiency for this code are not listed in the source.
Data at rated power, 400 V / 50 Hz, ambient 40 deg C, altitude up to 1000 m.

Data sheet

1LA7063-6AB12

SIMOTICS GP low-voltage motor - aluminum series 1LA7

0.09 kW / 1000 rpm

Frame size 063 M | Article No. 1LA7063-6AB12 | mounting IM B14

GENERAL DATA

Motor series	**1LA7 (aluminum)**
Article No.	**1LA7063-6AB12**
Frame size	**063 M**
Number of poles	**6**
Housing material	**Aluminum**
Degree of protection	**IP55**
Cooling	**Self-ventilated (IC 411)**
Insulation / utilization	**Thermal class 155 (F) / utilized to 130 (B)**
Duty type	**S1 (continuous duty)**
Rotor	**Squirrel-cage**
Efficiency class (IEC 60034-30)	**not classified (below IE1 range)**
Voltage / connection	**230 V D / 400 V Y (50 Hz), 460 V Y (60 Hz)**
Type of construction	**IM B14 (also V18, V19)**
Net weight (IM B3)	**4 kg**

ELECTRICAL DATA - 400 V, 50 HZ

Rated power, 50 Hz	**0.09 kW (0.12 HP)**
Rated speed, 50 Hz	**850 rpm (synchronous 1000 rpm)**
Rated torque	**1 Nm**
Rated current at 400 V	**0.39 A**
No-load current	**0.46 A**
Power factor cos phi	**0.66**
Efficiency at 4/4 | 3/4 | 2/4 load	**50.2 | 48.7 | 44.2 %**
Locked-rotor current ratio (I_LR/I_N)	**2**
Locked-rotor torque ratio (T_LR/T_N)	**1.8**
Breakdown torque ratio (T_B/T_N)	**1.9**
Moment of inertia J	**0.00037 kgm2**
Torque class	**13**

60 HZ OPERATION

Rated power at 60 Hz (460 V)	**not listed in the catalog (DT Configurator)**
Synchronous speed at 60 Hz	**1200 rpm**
Speed / efficiency / current at 60 Hz	**not listed in the catalog (DT Configurator)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Source: Siemens Distribution brochure (07/2014), Chapter 2, p. 18. Dimensions: see the same catalog.
Compiled from the manufacturer's catalog data for reference. It is not an official Siemens document -
verify against the current Siemens data sheet before ordering. 60 Hz power, speed and efficiency for this code are not listed in the source.
Data at rated power, 400 V / 50 Hz, ambient 40 deg C, altitude up to 1000 m.

0.09 kW / 1000 rpm

Frame 63 M | 6 poles | IM B3 | Article No. 1LE1002-0BC22-2AA4

GENERAL DATA

Series / efficiency class	**1LE1002 / IE1**
Housing	**Aluminum**
Frame size	**63 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**4 kg**

ELECTRICAL DATA

Rated power 50 Hz	**0.09 kW (about 0.12 HP)**
Rated power 60 Hz	**0.11 kW**
Rated speed (50 Hz)	**895 rpm**
Rated torque	**0.96 Nm**
Rated current (400 V)	**0.48 A**
Power factor	**0.63**
Efficiency 4/4 | 3/4 | 2/4	**42.7 | 38.5 | 30.4 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**2.0 | 1.8 | 1.9**
Moment of inertia J	**0.00037 kgm2**
Sound pressure / power LpfA | LWA	**56 | 62 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (12/2021), table 1LE1002, p. 3/52**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

0.09 kW / 1000 rpm

Frame 63 M | 6 poles | IM B5 | Article No. 1LE1002-0BC22-2FA4

GENERAL DATA

Series / efficiency class	**1LE1002 / IE1**
Housing	**Aluminum**
Frame size	**63 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**4 kg**

ELECTRICAL DATA

Rated power 50 Hz	**0.09 kW (about 0.12 HP)**
Rated power 60 Hz	**0.11 kW**
Rated speed (50 Hz)	**895 rpm**
Rated torque	**0.96 Nm**
Rated current (400 V)	**0.48 A**
Power factor	**0.63**
Efficiency 4/4 | 3/4 | 2/4	**42.7 | 38.5 | 30.4 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**2.0 | 1.8 | 1.9**
Moment of inertia J	**0.00037 kgm2**
Sound pressure / power LpfA | LWA	**56 | 62 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (12/2021), table 1LE1002, p. 3/52**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

0.09 kW / 1000 rpm

Frame 63 M | 6 poles | IM B14 | Article No. 1LE1002-0BC22-2KA4

GENERAL DATA

Series / efficiency class	**1LE1002 / IE1**
Housing	**Aluminum**
Frame size	**63 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**4 kg**

ELECTRICAL DATA

Rated power 50 Hz	**0.09 kW (about 0.12 HP)**
Rated power 60 Hz	**0.11 kW**
Rated speed (50 Hz)	**895 rpm**
Rated torque	**0.96 Nm**
Rated current (400 V)	**0.48 A**
Power factor	**0.63**
Efficiency 4/4 | 3/4 | 2/4	**42.7 | 38.5 | 30.4 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**2.0 | 1.8 | 1.9**
Moment of inertia J	**0.00037 kgm2**
Sound pressure / power LpfA | LWA	**56 | 62 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (12/2021), table 1LE1002, p. 3/52**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).