Data sheets - Siemens SIMOTICS GP motors

0.37 kW / 1000 rpm - 16 article numbers in this file

Article No.	Page
1LA7080-6AA10	2
1LA7080-6AA11	3
1LA7080-6AA12	4
1LE1002-0DC22-2AA4	5
1LE1002-0DC22-2FA4	6
1LE1002-0DC22-2KA4	7
1LE1001-0DC22-2AA4	8
1LE1001-0DC22-2FA4	9
1LE1001-0DC22-2KA4	10
1LE1003-0DC22-2AA4	11
1LE1003-0DC22-2FA4	12
1LE1003-0DC22-2KA4	13
1LE1501-0DC22-2AA4	14
1LE1501-0DC22-2FA4	15
1LE1503-0DC22-2AA4	16
1LE1503-0DC22-2FA4	17

محور نیرو

Tel: 0935 186 4634

info@mehvarniro.com | mehvarniro.com

Data sheet

SIMOTICS GP low-voltage motor - aluminum series 1LA7

1LA7080-6AA10

0.37 kW / 1000 rpm

Frame size 080 M | Article No. 1LA7080-6AA10 | mounting IM B3

GENERAL DATA

Motor series	**1LA7 (aluminum)**
Article No.	**1LA7080-6AA10**
Frame size	**080 M**
Number of poles	**6**
Housing material	**Aluminum**
Degree of protection	**IP55**
Cooling	**Self-ventilated (IC 411)**
Insulation / utilization	**Thermal class 155 (F) / utilized to 130 (B)**
Duty type	**S1 (continuous duty)**
Rotor	**Squirrel-cage**
Efficiency class (IEC 60034-30)	**not classified (below IE1 range)**
Voltage / connection	**230 V Δ / 400 V Y (50 Hz), 460 V Y (60 Hz)**
Type of construction	**IM B3 (also B6, B7, B8, V5, V6)**
Net weight (IM B3)	**8.6 kg**

ELECTRICAL DATA - 400 V, 50 HZ

Rated power, 50 Hz	**0.37 kW (0.5 HP)**
Rated speed, 50 Hz	**920 rpm (synchronous 1000 rpm)**
Rated torque	**3.8 Nm**
Rated current at 400 V	**1.16 A**
No-load current	**1.18 A**
Power factor cos φ	**0.72**
Efficiency at 4/4 | 3/4 | 2/4 load	**64.1 | 63.1 | 59.1 %**
Locked-rotor current ratio (I_LR/I_N)	**3.1**
Locked-rotor torque ratio (T_LR/T_N)	**1.9**
Breakdown torque ratio (T_B/T_N)	**2.1**
Moment of inertia J	**0.0014 kgm²**
Torque class	**16**

60 HZ OPERATION

Rated power at 60 Hz (460 V)	**0.43 kW**
Synchronous speed at 60 Hz	**1200 rpm**
Speed / efficiency / current at 60 Hz	**not listed in the catalog (DT Configurator)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Source: Siemens Distribution brochure (07/2014), Chapter 2, p. 18. Dimensions: see the same catalog.
Compiled from the manufacturer's catalog data for reference. It is not an official Siemens document - verify against the current Siemens data sheet before ordering.
Data at rated power, 400 V / 50 Hz, ambient 40 °C, altitude up to 1000 m.

Data sheet

1LA7080-6AA11

SIMOTICS GP low-voltage motor - aluminum series 1LA7

0.37 kW / 1000 rpm

Frame size 080 M | Article No. 1LA7080-6AA11 | mounting IM B5

GENERAL DATA

Motor series	**1LA7 (aluminum)**
Article No.	**1LA7080-6AA11**
Frame size	**080 M**
Number of poles	**6**
Housing material	**Aluminum**
Degree of protection	**IP55**
Cooling	**Self-ventilated (IC 411)**
Insulation / utilization	**Thermal class 155 (F) / utilized to 130 (B)**
Duty type	**S1 (continuous duty)**
Rotor	**Squirrel-cage**
Efficiency class (IEC 60034-30)	**not classified (below IE1 range)**
Voltage / connection	**230 V Δ / 400 V Y (50 Hz), 460 V Y (60 Hz)**
Type of construction	**IM B5 (also V1, V3)**
Net weight (IM B3)	**8.6 kg**

ELECTRICAL DATA - 400 V, 50 HZ

Rated power, 50 Hz	**0.37 kW (0.5 HP)**
Rated speed, 50 Hz	**920 rpm (synchronous 1000 rpm)**
Rated torque	**3.8 Nm**
Rated current at 400 V	**1.16 A**
No-load current	**1.18 A**
Power factor cos φ	**0.72**
Efficiency at 4/4 | 3/4 | 2/4 load	**64.1 | 63.1 | 59.1 %**
Locked-rotor current ratio (I_LR/I_N)	**3.1**
Locked-rotor torque ratio (T_LR/T_N)	**1.9**
Breakdown torque ratio (T_B/T_N)	**2.1**
Moment of inertia J	**0.0014 kgm²**
Torque class	**16**

60 HZ OPERATION

Rated power at 60 Hz (460 V)	**0.43 kW**
Synchronous speed at 60 Hz	**1200 rpm**
Speed / efficiency / current at 60 Hz	**not listed in the catalog (DT Configurator)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Source: Siemens Distribution brochure (07/2014), Chapter 2, p. 18. Dimensions: see the same catalog.
Compiled from the manufacturer's catalog data for reference. It is not an official Siemens document - verify against the current Siemens data sheet before ordering.
Data at rated power, 400 V / 50 Hz, ambient 40 °C, altitude up to 1000 m.

Data sheet

1LA7080-6AA12

SIMOTICS GP low-voltage motor - aluminum series 1LA7

0.37 kW / 1000 rpm

Frame size 080 M | Article No. 1LA7080-6AA12 | mounting IM B14

GENERAL DATA

Motor series	**1LA7 (aluminum)**
Article No.	**1LA7080-6AA12**
Frame size	**080 M**
Number of poles	**6**
Housing material	**Aluminum**
Degree of protection	**IP55**
Cooling	**Self-ventilated (IC 411)**
Insulation / utilization	**Thermal class 155 (F) / utilized to 130 (B)**
Duty type	**S1 (continuous duty)**
Rotor	**Squirrel-cage**
Efficiency class (IEC 60034-30)	**not classified (below IE1 range)**
Voltage / connection	**230 V Δ / 400 V Y (50 Hz), 460 V Y (60 Hz)**
Type of construction	**IM B14 (also V18, V19)**
Net weight (IM B3)	**8.6 kg**

ELECTRICAL DATA - 400 V, 50 HZ

Rated power, 50 Hz	**0.37 kW (0.5 HP)**
Rated speed, 50 Hz	**920 rpm (synchronous 1000 rpm)**
Rated torque	**3.8 Nm**
Rated current at 400 V	**1.16 A**
No-load current	**1.18 A**
Power factor cos φ	**0.72**
Efficiency at 4/4 | 3/4 | 2/4 load	**64.1 | 63.1 | 59.1 %**
Locked-rotor current ratio (I_LR/I_N)	**3.1**
Locked-rotor torque ratio (T_LR/T_N)	**1.9**
Breakdown torque ratio (T_B/T_N)	**2.1**
Moment of inertia J	**0.0014 kgm²**
Torque class	**16**

60 HZ OPERATION

Rated power at 60 Hz (460 V)	**0.43 kW**
Synchronous speed at 60 Hz	**1200 rpm**
Speed / efficiency / current at 60 Hz	**not listed in the catalog (DT Configurator)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Source: Siemens Distribution brochure (07/2014), Chapter 2, p. 18. Dimensions: see the same catalog.
Compiled from the manufacturer's catalog data for reference. It is not an official Siemens document - verify against the current Siemens data sheet before ordering.
Data at rated power, 400 V / 50 Hz, ambient 40 °C, altitude up to 1000 m.

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1002 (IE1)

1LE1002-0DC22-2AA4

0.37 kW / 1000 rpm

Frame 80 M | 6 poles | IM B3 | Article No. 1LE1002-0DC22-2AA4

GENERAL DATA

Series / efficiency class	**1LE1002 / IE1**
Housing	**Aluminum**
Frame size	**80 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**9 kg**

ELECTRICAL DATA

Rated power 50 Hz	**0.37 kW (about 0.5 HP)**
Rated power 60 Hz	**0.43 kW**
Rated speed (50 Hz)	**915 rpm**
Rated torque	**3.85 Nm**
Rated current	**1.28 A**
Power factor	**0.7**
Efficiency 4/4 | 3/4 | 2/4	**59.7 | 58.6 | 52.7 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**2.7 | 1.6 | 1.8**
Moment of inertia J	**0.001976 kgm2**
Sound pressure / power LpfA | LWA	**56 | 64 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (09/2023), table 1LE1002, p. 3/53**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1002 (IE1)

1LE1002-0DC22-2FA4

0.37 kW / 1000 rpm

Frame 80 M | 6 poles | IM B5 | Article No. 1LE1002-0DC22-2FA4

GENERAL DATA

Series / efficiency class	**1LE1002 / IE1**
Housing	**Aluminum**
Frame size	**80 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**9 kg**

ELECTRICAL DATA

Rated power 50 Hz	**0.37 kW (about 0.5 HP)**
Rated power 60 Hz	**0.43 kW**
Rated speed (50 Hz)	**915 rpm**
Rated torque	**3.85 Nm**
Rated current	**1.28 A**
Power factor	**0.7**
Efficiency 4/4 | 3/4 | 2/4	**59.7 | 58.6 | 52.7 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**2.7 | 1.6 | 1.8**
Moment of inertia J	**0.001976 kgm2**
Sound pressure / power LpfA | LWA	**56 | 64 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (09/2023), table 1LE1002, p. 3/53**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1002 (IE1)

1LE1002-0DC22-2KA4

0.37 kW / 1000 rpm

Frame 80 M | 6 poles | IM B14 | Article No. 1LE1002-0DC22-2KA4

GENERAL DATA

Series / efficiency class	**1LE1002 / IE1**
Housing	**Aluminum**
Frame size	**80 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**9 kg**

ELECTRICAL DATA

Rated power 50 Hz	**0.37 kW (about 0.5 HP)**
Rated power 60 Hz	**0.43 kW**
Rated speed (50 Hz)	**915 rpm**
Rated torque	**3.85 Nm**
Rated current	**1.28 A**
Power factor	**0.7**
Efficiency 4/4 | 3/4 | 2/4	**59.7 | 58.6 | 52.7 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**2.7 | 1.6 | 1.8**
Moment of inertia J	**0.001976 kgm2**
Sound pressure / power LpfA | LWA	**56 | 64 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (09/2023), table 1LE1002, p. 3/53**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1001 (IE2)

1LE1001-0DC22-2AA4

0.37 kW / 1000 rpm

Frame 80 M | 6 poles | IM B3 | Article No. 1LE1001-0DC22-2AA4

GENERAL DATA

Series / efficiency class	**1LE1001 / IE2**
Housing	**Aluminum**
Frame size	**80 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**9 kg**

ELECTRICAL DATA

Rated power 50 Hz	**0.37 kW (about 0.5 HP)**
Rated power 60 Hz	**0.43 kW**
Rated speed (50 Hz)	**925 rpm**
Rated torque	**3.8 Nm**
Rated current	**1.14 A**
Power factor	**0.69**
Efficiency 4/4 | 3/4 | 2/4	**67.6 | 67.9 | 64.4 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**4 | 2.1 | 2.4**
Moment of inertia J	**0.0017 kgm2**
Sound pressure / power LpfA | LWA	**42 | 53 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1001, p. 2/28 (PDF 146)**
Catalog 2	**Brochure 07/2014 (14050629), p. 19 (PDF 19)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1001 (IE2)

1LE1001-0DC22-2FA4

0.37 kW / 1000 rpm

Frame 80 M | 6 poles | IM B5 | Article No. 1LE1001-0DC22-2FA4

GENERAL DATA

Series / efficiency class	**1LE1001 / IE2**
Housing	**Aluminum**
Frame size	**80 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**9 kg**

ELECTRICAL DATA

Rated power 50 Hz	**0.37 kW (about 0.5 HP)**
Rated power 60 Hz	**0.43 kW**
Rated speed (50 Hz)	**925 rpm**
Rated torque	**3.8 Nm**
Rated current	**1.14 A**
Power factor	**0.69**
Efficiency 4/4 | 3/4 | 2/4	**67.6 | 67.9 | 64.4 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**4 | 2.1 | 2.4**
Moment of inertia J	**0.0017 kgm2**
Sound pressure / power LpfA | LWA	**42 | 53 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1001, p. 2/28 (PDF 146)**
Catalog 2	**Brochure 07/2014 (14050629), p. 19 (PDF 19)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1001 (IE2)

1LE1001-0DC22-2KA4

0.37 kW / 1000 rpm

Frame 80 M | 6 poles | IM B14 | Article No. 1LE1001-0DC22-2KA4

GENERAL DATA

Series / efficiency class	**1LE1001 / IE2**
Housing	**Aluminum**
Frame size	**80 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**9 kg**

ELECTRICAL DATA

Rated power 50 Hz	**0.37 kW (about 0.5 HP)**
Rated power 60 Hz	**0.43 kW**
Rated speed (50 Hz)	**925 rpm**
Rated torque	**3.8 Nm**
Rated current	**1.14 A**
Power factor	**0.69**
Efficiency 4/4 | 3/4 | 2/4	**67.6 | 67.9 | 64.4 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**4 | 2.1 | 2.4**
Moment of inertia J	**0.0017 kgm2**
Sound pressure / power LpfA | LWA	**42 | 53 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1001, p. 2/28 (PDF 146)**
Catalog 2	**Brochure 07/2014 (14050629), p. 19 (PDF 19)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1003 (IE3)

1LE1003-0DC22-2AA4

0.37 kW / 1000 rpm

Frame 80 M | 6 poles | IM B3 | Article No. 1LE1003-0DC22-2AA4

GENERAL DATA

Series / efficiency class	**1LE1003 / IE3**
Housing	**Aluminum**
Frame size	**80 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**12 kg**

ELECTRICAL DATA

Rated power 50 Hz	**0.37 kW (about 0.5 HP)**
Rated power 60 Hz	**not listed (catalog 09/2023)**
Rated speed (50 Hz)	**940 rpm**
Rated torque	**3.75 Nm**
Rated current	**1.1 A**
Power factor	**0.66**
Efficiency 4/4 | 3/4 | 2/4	**73.5 | 73.1 | 69.4 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**4.2 | 2.3 | 2.7**
Moment of inertia J	**0.0025 kgm2**
Sound pressure / power LpfA | LWA	**42 | 53 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (09/2023), table 1LE1003, p. 3/15**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1003 (IE3)

1LE1003-0DC22-2FA4

0.37 kW / 1000 rpm

Frame 80 M | 6 poles | IM B5 | Article No. 1LE1003-0DC22-2FA4

GENERAL DATA

Series / efficiency class	**1LE1003 / IE3**
Housing	**Aluminum**
Frame size	**80 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**12 kg**

ELECTRICAL DATA

Rated power 50 Hz	**0.37 kW (about 0.5 HP)**
Rated power 60 Hz	**not listed (catalog 09/2023)**
Rated speed (50 Hz)	**940 rpm**
Rated torque	**3.75 Nm**
Rated current	**1.1 A**
Power factor	**0.66**
Efficiency 4/4 | 3/4 | 2/4	**73.5 | 73.1 | 69.4 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**4.2 | 2.3 | 2.7**
Moment of inertia J	**0.0025 kgm2**
Sound pressure / power LpfA | LWA	**42 | 53 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (09/2023), table 1LE1003, p. 3/15**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1003 (IE3)

1LE1003-0DC22-2KA4

0.37 kW / 1000 rpm

Frame 80 M | 6 poles | IM B14 | Article No. 1LE1003-0DC22-2KA4

GENERAL DATA

Series / efficiency class	**1LE1003 / IE3**
Housing	**Aluminum**
Frame size	**80 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**12 kg**

ELECTRICAL DATA

Rated power 50 Hz	**0.37 kW (about 0.5 HP)**
Rated power 60 Hz	**not listed (catalog 09/2023)**
Rated speed (50 Hz)	**940 rpm**
Rated torque	**3.75 Nm**
Rated current	**1.1 A**
Power factor	**0.66**
Efficiency 4/4 | 3/4 | 2/4	**73.5 | 73.1 | 69.4 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**4.2 | 2.3 | 2.7**
Moment of inertia J	**0.0025 kgm2**
Sound pressure / power LpfA | LWA	**42 | 53 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (09/2023), table 1LE1003, p. 3/15**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1501 (IE2)

1LE1501-0DC22-2AA4

0.37 kW / 1000 rpm

Frame 80 M | 6 poles | IM B3 | Article No. 1LE1501-0DC22-2AA4

GENERAL DATA

Series / efficiency class	**1LE1501 / IE2**
Housing	**Cast iron**
Frame size	**80 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**17 kg**

ELECTRICAL DATA

Rated power 50 Hz	**0.37 kW (about 0.5 HP)**
Rated power 60 Hz	**0.43 kW**
Rated speed (50 Hz)	**925 rpm**
Rated torque	**3.8 Nm**
Rated current	**1.14 A**
Power factor	**0.69**
Efficiency 4/4 | 3/4 | 2/4	**67.6 | 67.9 | 64.4 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**4 | 2.1 | 2.4**
Moment of inertia J	**0.0017 kgm2**
Sound pressure / power LpfA | LWA	**42 | 53 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1501, p. 2/34 (PDF 152)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1501 (IE2)

1LE1501-0DC22-2FA4

0.37 kW / 1000 rpm

Frame 80 M | 6 poles | IM B5 | Article No. 1LE1501-0DC22-2FA4

GENERAL DATA

Series / efficiency class	**1LE1501 / IE2**
Housing	**Cast iron**
Frame size	**80 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**17 kg**

ELECTRICAL DATA

Rated power 50 Hz	**0.37 kW (about 0.5 HP)**
Rated power 60 Hz	**0.43 kW**
Rated speed (50 Hz)	**925 rpm**
Rated torque	**3.8 Nm**
Rated current	**1.14 A**
Power factor	**0.69**
Efficiency 4/4 | 3/4 | 2/4	**67.6 | 67.9 | 64.4 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**4 | 2.1 | 2.4**
Moment of inertia J	**0.0017 kgm2**
Sound pressure / power LpfA | LWA	**42 | 53 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1501, p. 2/34 (PDF 152)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1503 (IE3)

1LE1503-0DC22-2AA4

0.37 kW / 1000 rpm

Frame 80 M | 6 poles | IM B3 | Article No. 1LE1503-0DC22-2AA4

GENERAL DATA

Series / efficiency class	**1LE1503 / IE3**
Housing	**Cast iron**
Frame size	**80 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**19 kg**

ELECTRICAL DATA

Rated power 50 Hz	**0.37 kW (about 0.5 HP)**
Rated power 60 Hz	**not listed (catalog 09/2023)**
Rated speed (50 Hz)	**940 rpm**
Rated torque	**3.75 Nm**
Rated current	**1.1 A**
Power factor	**0.66**
Efficiency 4/4 | 3/4 | 2/4	**73.5 | 73.1 | 69.4 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**4.2 | 2.3 | 2.7**
Moment of inertia J	**0.0025 kgm2**
Sound pressure / power LpfA | LWA	**42 | 53 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (09/2023), table 1LE1503, p. 3/21**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1503 (IE3)

1LE1503-0DC22-2FA4

0.37 kW / 1000 rpm

Frame 80 M | 6 poles | IM B5 | Article No. 1LE1503-0DC22-2FA4

GENERAL DATA

Series / efficiency class	**1LE1503 / IE3**
Housing	**Cast iron**
Frame size	**80 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**19 kg**

ELECTRICAL DATA

Rated power 50 Hz	**0.37 kW (about 0.5 HP)**
Rated power 60 Hz	**not listed (catalog 09/2023)**
Rated speed (50 Hz)	**940 rpm**
Rated torque	**3.75 Nm**
Rated current	**1.1 A**
Power factor	**0.66**
Efficiency 4/4 | 3/4 | 2/4	**73.5 | 73.1 | 69.4 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**4.2 | 2.3 | 2.7**
Moment of inertia J	**0.0025 kgm2**
Sound pressure / power LpfA | LWA	**42 | 53 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (09/2023), table 1LE1503, p. 3/21**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).