Data sheets - Siemens SIMOTICS GP motors

0.75 kW / 1000 rpm - 33 article numbers in this file

Article No.	Page
1LA7090-6AA12	2
1LE1002-0EC02-2AA4	3
1LE1002-0EC02-2FA4	4
1LE1002-0EC02-2KA4	5
1LE1001-0EC02-2AA4	6
1LE1001-0EC02-2FA4	7
1LE1001-0EC02-2KA4	8
1LE1041-0EC02-2FA4	9
1LE1041-0EC02-2KA4	10
1LE1003-0EC02-2AA4	11
1LE1003-0EC02-2FA4	12
1LE1003-0EC02-2KA4	13
1LE1043-0EC02-2AA4	14
1LE1043-0EC02-2FA4	15
1LE1043-0EC02-2KA4	16
1LE0102-0EC02-2AA4	17
1LE0102-0EC02-2FA4	18
1LE0102-0EC02-2KA4	19
1LE0102-0EC04-1AA4	20
1LE0102-0EC04-1FA4	21
1LE0102-0EC04-1KA4	22
1LE0101-0EC02-2AA4	23
1LE0101-0EC02-2FA4	24
1LE0101-0EC02-2KA4	25
1LE0101-0EC04-1AA4	26
1LE0101-0EC04-1FA4	27
1LE0101-0EC04-1KA4	28
1LE1501-0EC02-2AA4	29
1LE1501-0EC02-2FA4	30
1LE1503-0EC02-2AA4	31
1LE1503-0EC02-2FA4	32
1LE1543-0EC02-2AA4	33
1LE1543-0EC02-2FA4	34

محور نیرو

Tel: 0935 186 4634

info@mehvarniro.com | mehvarniro.com

Data sheet

SIMOTICS GP low-voltage motor - series 1LA7090 (IE1)

1LA7090-6AA12

0.75 kW / 1000 rpm

Frame 90 S | 6 poles | IM B14 | Article No. 1LA7090-6AA12

GENERAL DATA

Series / efficiency class	**1LA7090 / IE1**
Housing	**Aluminum**
Frame size	**90 S**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y (50 Hz), 460 Y (60 Hz)**
Net weight (IM B3)	**12.6 kg**

ELECTRICAL DATA

Rated power 50 Hz	**0.75 kW (about 1 HP)**
Rated power 60 Hz	**0.86 kW**
Rated speed (50 Hz)	**915 rpm**
Rated torque	**7.8 Nm**
Rated current	**2.05 A**
Power factor	**0.76**
Efficiency 4/4 | 3/4 | 2/4	**70 | 70 | 66 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**3.7 | 2.2 | 2.2**
Moment of inertia J	**0.0024 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LA7090, p. 18 (PDF 18)**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1002 (IE1)

1LE1002-0EC02-2AA4

0.75 kW / 1000 rpm

Frame 90 S | 6 poles | IM B3 | Article No. 1LE1002-0EC02-2AA4

GENERAL DATA

Series / efficiency class	**1LE1002 / IE1**
Housing	**Aluminum**
Frame size	**90 S**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**13 kg**

ELECTRICAL DATA

Rated power 50 Hz	**0.75 kW (about 1 HP)**
Rated power 60 Hz	**0.86 kW**
Rated speed (50 Hz)	**940 rpm**
Rated torque	**7.6 Nm**
Rated current	**2.3 A**
Power factor	**0.67**
Efficiency 4/4 | 3/4 | 2/4	**70 | 70 | 66 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**3.8 | 2 | 2.2**
Moment of inertia J	**0.0033 kgm2**
Sound pressure / power LpfA | LWA	**59 | 70 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1002, p. 2/46 (PDF 164)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1002 (IE1)

1LE1002-0EC02-2FA4

0.75 kW / 1000 rpm

Frame 90 S | 6 poles | IM B5 | Article No. 1LE1002-0EC02-2FA4

GENERAL DATA

Series / efficiency class	**1LE1002 / IE1**
Housing	**Aluminum**
Frame size	**90 S**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**13 kg**

ELECTRICAL DATA

Rated power 50 Hz	**0.75 kW (about 1 HP)**
Rated power 60 Hz	**0.86 kW**
Rated speed (50 Hz)	**940 rpm**
Rated torque	**7.6 Nm**
Rated current	**2.3 A**
Power factor	**0.67**
Efficiency 4/4 | 3/4 | 2/4	**70 | 70 | 66 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**3.8 | 2 | 2.2**
Moment of inertia J	**0.0033 kgm2**
Sound pressure / power LpfA | LWA	**59 | 70 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1002, p. 2/46 (PDF 164)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1002 (IE1)

1LE1002-0EC02-2KA4

0.75 kW / 1000 rpm

Frame 90 S | 6 poles | IM B14 | Article No. 1LE1002-0EC02-2KA4

GENERAL DATA

Series / efficiency class	**1LE1002 / IE1**
Housing	**Aluminum**
Frame size	**90 S**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**13 kg**

ELECTRICAL DATA

Rated power 50 Hz	**0.75 kW (about 1 HP)**
Rated power 60 Hz	**0.86 kW**
Rated speed (50 Hz)	**940 rpm**
Rated torque	**7.6 Nm**
Rated current	**2.3 A**
Power factor	**0.67**
Efficiency 4/4 | 3/4 | 2/4	**70 | 70 | 66 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**3.8 | 2 | 2.2**
Moment of inertia J	**0.0033 kgm2**
Sound pressure / power LpfA | LWA	**59 | 70 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1002, p. 2/46 (PDF 164)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1001 (IE2)

1LE1001-0EC02-2AA4

0.75 kW / 1000 rpm

Frame 90 S | 6 poles | IM B3 | Article No. 1LE1001-0EC02-2AA4

GENERAL DATA

Series / efficiency class	**1LE1001 / IE2**
Housing	**Aluminum**
Frame size	**90 S**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**13 kg**

ELECTRICAL DATA

Rated power 50 Hz	**0.75 kW (about 1 HP)**
Rated power 60 Hz	**0.86 kW**
Rated speed (50 Hz)	**935 rpm**
Rated torque	**7.7 Nm**
Rated current	**2.05 A**
Power factor	**0.7**
Efficiency 4/4 | 3/4 | 2/4	**75.9 | 76.8 | 74.5 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**4.1 | 2 | 2.5**
Moment of inertia J	**0.003 kgm2**
Sound pressure / power LpfA | LWA	**43 | 55 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1001, p. 2/28 (PDF 146)**
Catalog 2	**Brochure 07/2014 (14050629), p. 19 (PDF 19)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1001 (IE2)

1LE1001-0EC02-2FA4

0.75 kW / 1000 rpm

Frame 90 S | 6 poles | IM B5 | Article No. 1LE1001-0EC02-2FA4

GENERAL DATA

Series / efficiency class	**1LE1001 / IE2**
Housing	**Aluminum**
Frame size	**90 S**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**13 kg**

ELECTRICAL DATA

Rated power 50 Hz	**0.75 kW (about 1 HP)**
Rated power 60 Hz	**0.86 kW**
Rated speed (50 Hz)	**935 rpm**
Rated torque	**7.7 Nm**
Rated current	**2.05 A**
Power factor	**0.7**
Efficiency 4/4 | 3/4 | 2/4	**75.9 | 76.8 | 74.5 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**4.1 | 2 | 2.5**
Moment of inertia J	**0.003 kgm2**
Sound pressure / power LpfA | LWA	**43 | 55 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1001, p. 2/28 (PDF 146)**
Catalog 2	**Brochure 07/2014 (14050629), p. 19 (PDF 19)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1001 (IE2)

1LE1001-0EC02-2KA4

0.75 kW / 1000 rpm

Frame 90 S | 6 poles | IM B14 | Article No. 1LE1001-0EC02-2KA4

GENERAL DATA

Series / efficiency class	**1LE1001 / IE2**
Housing	**Aluminum**
Frame size	**90 S**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**13 kg**

ELECTRICAL DATA

Rated power 50 Hz	**0.75 kW (about 1 HP)**
Rated power 60 Hz	**0.86 kW**
Rated speed (50 Hz)	**935 rpm**
Rated torque	**7.7 Nm**
Rated current	**2.05 A**
Power factor	**0.7**
Efficiency 4/4 | 3/4 | 2/4	**75.9 | 76.8 | 74.5 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**4.1 | 2 | 2.5**
Moment of inertia J	**0.003 kgm2**
Sound pressure / power LpfA | LWA	**43 | 55 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1001, p. 2/28 (PDF 146)**
Catalog 2	**Brochure 07/2014 (14050629), p. 19 (PDF 19)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1041 (IE2)

1LE1041-0EC02-2FA4

0.75 kW / 1000 rpm

Frame 90 S | 6 poles | IM B5 | Article No. 1LE1041-0EC02-2FA4

GENERAL DATA

Series / efficiency class	**1LE1041 / IE2**
Housing	**Aluminum**
Frame size	**90 S**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**13 kg**

ELECTRICAL DATA - CATALOG VALUES AT 60 HZ (APAC LINE)

Rated power (P50 rating)	**0.75 kW (about 1 HP)**
Rated power (P60 rating)	**0.86 kW**
Rated speed (60 Hz)	**1145 rpm**
Rated torque (60 Hz)	**6.3 Nm**
Rated current (460 V, 60 Hz)	**1.98 A**
Power factor (60 Hz)	**0.65**
Efficiency 4/4 | 3/4 | 2/4 (60 Hz)	**73 | 72.7 | 69.7 %**
I_LR/I_N | T_LR/T_N | T_B/T_N (60 Hz)	**4.5 | 2.2 | 3**
Moment of inertia J	**0.003 kgm2**
Sound pressure / power LpfA | LWA (60 Hz)	**46 | 58 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1041, p. 2/66 (PDF 184)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
APAC Line: the catalog lists operating values at 60 Hz only; 50 Hz speed/efficiency are not listed (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1041 (IE2)

1LE1041-0EC02-2KA4

0.75 kW / 1000 rpm

Frame 90 S | 6 poles | IM B14 | Article No. 1LE1041-0EC02-2KA4

GENERAL DATA

Series / efficiency class	**1LE1041 / IE2**
Housing	**Aluminum**
Frame size	**90 S**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**13 kg**

ELECTRICAL DATA - CATALOG VALUES AT 60 HZ (APAC LINE)

Rated power (P50 rating)	**0.75 kW (about 1 HP)**
Rated power (P60 rating)	**0.86 kW**
Rated speed (60 Hz)	**1145 rpm**
Rated torque (60 Hz)	**6.3 Nm**
Rated current (460 V, 60 Hz)	**1.98 A**
Power factor (60 Hz)	**0.65**
Efficiency 4/4 | 3/4 | 2/4 (60 Hz)	**73 | 72.7 | 69.7 %**
I_LR/I_N | T_LR/T_N | T_B/T_N (60 Hz)	**4.5 | 2.2 | 3**
Moment of inertia J	**0.003 kgm2**
Sound pressure / power LpfA | LWA (60 Hz)	**46 | 58 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1041, p. 2/66 (PDF 184)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
APAC Line: the catalog lists operating values at 60 Hz only; 50 Hz speed/efficiency are not listed (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1003 (IE3)

1LE1003-0EC02-2AA4

0.75 kW / 1000 rpm

Frame 90 S | 6 poles | IM B3 | Article No. 1LE1003-0EC02-2AA4

GENERAL DATA

Series / efficiency class	**1LE1003 / IE3**
Housing	**Aluminum**
Frame size	**90 S**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**16 kg**

ELECTRICAL DATA

Rated power 50 Hz	**0.75 kW (about 1 HP)**
Rated power 60 Hz	**not listed (catalog 09/2023)**
Rated speed (50 Hz)	**945 rpm**
Rated torque	**7.6 Nm**
Rated current	**1.96 A**
Power factor	**0.7**
Efficiency 4/4 | 3/4 | 2/4	**78.9 | 80 | 78.8 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**4.6 | 2.2 | 2.6**
Moment of inertia J	**0.004 kgm2**
Sound pressure / power LpfA | LWA	**43 | 55 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (09/2023), table 1LE1003, p. 3/15**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1003 (IE3)

1LE1003-0EC02-2FA4

0.75 kW / 1000 rpm

Frame 90 S | 6 poles | IM B5 | Article No. 1LE1003-0EC02-2FA4

GENERAL DATA

Series / efficiency class	**1LE1003 / IE3**
Housing	**Aluminum**
Frame size	**90 S**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**16 kg**

ELECTRICAL DATA

Rated power 50 Hz	**0.75 kW (about 1 HP)**
Rated power 60 Hz	**not listed (catalog 09/2023)**
Rated speed (50 Hz)	**945 rpm**
Rated torque	**7.6 Nm**
Rated current	**1.96 A**
Power factor	**0.7**
Efficiency 4/4 | 3/4 | 2/4	**78.9 | 80 | 78.8 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**4.6 | 2.2 | 2.6**
Moment of inertia J	**0.004 kgm2**
Sound pressure / power LpfA | LWA	**43 | 55 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (09/2023), table 1LE1003, p. 3/15**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1003 (IE3)

1LE1003-0EC02-2KA4

0.75 kW / 1000 rpm

Frame 90 S | 6 poles | IM B14 | Article No. 1LE1003-0EC02-2KA4

GENERAL DATA

Series / efficiency class	**1LE1003 / IE3**
Housing	**Aluminum**
Frame size	**90 S**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**16 kg**

ELECTRICAL DATA

Rated power 50 Hz	**0.75 kW (about 1 HP)**
Rated power 60 Hz	**not listed (catalog 09/2023)**
Rated speed (50 Hz)	**945 rpm**
Rated torque	**7.6 Nm**
Rated current	**1.96 A**
Power factor	**0.7**
Efficiency 4/4 | 3/4 | 2/4	**78.9 | 80 | 78.8 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**4.6 | 2.2 | 2.6**
Moment of inertia J	**0.004 kgm2**
Sound pressure / power LpfA | LWA	**43 | 55 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (09/2023), table 1LE1003, p. 3/15**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1043 (IE3)

1LE1043-0EC02-2AA4

0.75 kW / 1000 rpm

Frame 90 S | 6 poles | IM B3 | Article No. 1LE1043-0EC02-2AA4

GENERAL DATA

Series / efficiency class	**1LE1043 / IE3**
Housing	**Aluminum**
Frame size	**90 S**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**16 kg**

ELECTRICAL DATA - CATALOG VALUES AT 60 HZ (APAC LINE)

Rated power (P50 rating)	**0.75 kW (about 1 HP)**
Rated power (P60 rating)	**0.86 kW**
Rated speed (60 Hz)	**1155 rpm**
Rated torque (60 Hz)	**6.2 Nm**
Rated current (460 V, 60 Hz)	**1.76 A**
Power factor (60 Hz)	**0.65**
Efficiency 4/4 | 3/4 | 2/4 (60 Hz)	**82.5 | 82.4 | 79.9 %**
I_LR/I_N | T_LR/T_N | T_B/T_N (60 Hz)	**5.3 | 2.4 | 3.1**
Moment of inertia J	**0.004 kgm2**
Sound pressure / power LpfA | LWA (60 Hz)	**46 | 58 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1043, p. 2/55 (PDF 173)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
APAC Line: the catalog lists operating values at 60 Hz only; 50 Hz speed/efficiency are not listed (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1043 (IE3)

1LE1043-0EC02-2FA4

0.75 kW / 1000 rpm

Frame 90 S | 6 poles | IM B5 | Article No. 1LE1043-0EC02-2FA4

GENERAL DATA

Series / efficiency class	**1LE1043 / IE3**
Housing	**Aluminum**
Frame size	**90 S**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**16 kg**

ELECTRICAL DATA - CATALOG VALUES AT 60 HZ (APAC LINE)

Rated power (P50 rating)	**0.75 kW (about 1 HP)**
Rated power (P60 rating)	**0.86 kW**
Rated speed (60 Hz)	**1155 rpm**
Rated torque (60 Hz)	**6.2 Nm**
Rated current (460 V, 60 Hz)	**1.76 A**
Power factor (60 Hz)	**0.65**
Efficiency 4/4 | 3/4 | 2/4 (60 Hz)	**82.5 | 82.4 | 79.9 %**
I_LR/I_N | T_LR/T_N | T_B/T_N (60 Hz)	**5.3 | 2.4 | 3.1**
Moment of inertia J	**0.004 kgm2**
Sound pressure / power LpfA | LWA (60 Hz)	**46 | 58 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1043, p. 2/55 (PDF 173)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
APAC Line: the catalog lists operating values at 60 Hz only; 50 Hz speed/efficiency are not listed (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1043 (IE3)

1LE1043-0EC02-2KA4

0.75 kW / 1000 rpm

Frame 90 S | 6 poles | IM B14 | Article No. 1LE1043-0EC02-2KA4

GENERAL DATA

Series / efficiency class	**1LE1043 / IE3**
Housing	**Aluminum**
Frame size	**90 S**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**16 kg**

ELECTRICAL DATA - CATALOG VALUES AT 60 HZ (APAC LINE)

Rated power (P50 rating)	**0.75 kW (about 1 HP)**
Rated power (P60 rating)	**0.86 kW**
Rated speed (60 Hz)	**1155 rpm**
Rated torque (60 Hz)	**6.2 Nm**
Rated current (460 V, 60 Hz)	**1.76 A**
Power factor (60 Hz)	**0.65**
Efficiency 4/4 | 3/4 | 2/4 (60 Hz)	**82.5 | 82.4 | 79.9 %**
I_LR/I_N | T_LR/T_N | T_B/T_N (60 Hz)	**5.3 | 2.4 | 3.1**
Moment of inertia J	**0.004 kgm2**
Sound pressure / power LpfA | LWA (60 Hz)	**46 | 58 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1043, p. 2/55 (PDF 173)**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
APAC Line: the catalog lists operating values at 60 Hz only; 50 Hz speed/efficiency are not listed (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0102 (IE1)

1LE0102-0EC02-2AA4

0.75 kW / 1000 rpm

Frame 90 S | 6 poles | IM B3 | Article No. 1LE0102-0EC02-2AA4

GENERAL DATA

Series / efficiency class	**1LE0102 / IE1**
Housing	**Cast iron**
Frame size	**90 S**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**25 kg**

ELECTRICAL DATA

Rated power 50 Hz	**0.75 kW (about 1 HP)**
Rated power 60 Hz	**0.86 kW**
Rated speed (50 Hz)	**925 rpm**
Rated torque	**7.7 Nm**
Rated current	**2.1 A**
Power factor	**0.74**
Efficiency 4/4 | 3/4 | 2/4	**70 | 71.5 | 68.9 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**3.9 | 2 | 2.5**
Moment of inertia J	**0.0028 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0102, p. 22 (PDF 22)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0102 (IE1)

1LE0102-0EC02-2FA4

0.75 kW / 1000 rpm

Frame 90 S | 6 poles | IM B5 | Article No. 1LE0102-0EC02-2FA4

GENERAL DATA

Series / efficiency class	**1LE0102 / IE1**
Housing	**Cast iron**
Frame size	**90 S**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**25 kg**

ELECTRICAL DATA

Rated power 50 Hz	**0.75 kW (about 1 HP)**
Rated power 60 Hz	**0.86 kW**
Rated speed (50 Hz)	**925 rpm**
Rated torque	**7.7 Nm**
Rated current	**2.1 A**
Power factor	**0.74**
Efficiency 4/4 | 3/4 | 2/4	**70 | 71.5 | 68.9 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**3.9 | 2 | 2.5**
Moment of inertia J	**0.0028 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0102, p. 22 (PDF 22)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0102 (IE1)

1LE0102-0EC02-2KA4

0.75 kW / 1000 rpm

Frame 90 S | 6 poles | IM B14 | Article No. 1LE0102-0EC02-2KA4

GENERAL DATA

Series / efficiency class	**1LE0102 / IE1**
Housing	**Cast iron**
Frame size	**90 S**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**25 kg**

ELECTRICAL DATA

Rated power 50 Hz	**0.75 kW (about 1 HP)**
Rated power 60 Hz	**0.86 kW**
Rated speed (50 Hz)	**925 rpm**
Rated torque	**7.7 Nm**
Rated current	**2.1 A**
Power factor	**0.74**
Efficiency 4/4 | 3/4 | 2/4	**70 | 71.5 | 68.9 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**3.9 | 2 | 2.5**
Moment of inertia J	**0.0028 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0102, p. 22 (PDF 22)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0102 (IE1)

1LE0102-0EC04-1AA4

0.75 kW / 1000 rpm

Frame 90 S | 6 poles | IM B3 | Article No. 1LE0102-0EC04-1AA4

GENERAL DATA

Series / efficiency class	**1LE0102 / IE1**
Housing	**Cast iron**
Frame size	**90 S**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**525 V D**
Net weight (IM B3)	**25 kg**

ELECTRICAL DATA

Rated power 50 Hz	**0.75 kW (about 1 HP)**
Rated power 60 Hz	**0.86 kW**
Rated speed (50 Hz)	**925 rpm**
Rated torque	**7.7 Nm**
Rated current	**1.59 A**
Power factor	**0.74**
Efficiency 4/4 | 3/4 | 2/4	**70 | 71.5 | 68.9 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**3.9 | 2 | 2.5**
Moment of inertia J	**0.0028 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0102, p. 27 (PDF 27)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0102 (IE1)

1LE0102-0EC04-1FA4

0.75 kW / 1000 rpm

Frame 90 S | 6 poles | IM B5 | Article No. 1LE0102-0EC04-1FA4

GENERAL DATA

Series / efficiency class	**1LE0102 / IE1**
Housing	**Cast iron**
Frame size	**90 S**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**525 V D**
Net weight (IM B3)	**25 kg**

ELECTRICAL DATA

Rated power 50 Hz	**0.75 kW (about 1 HP)**
Rated power 60 Hz	**0.86 kW**
Rated speed (50 Hz)	**925 rpm**
Rated torque	**7.7 Nm**
Rated current	**1.59 A**
Power factor	**0.74**
Efficiency 4/4 | 3/4 | 2/4	**70 | 71.5 | 68.9 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**3.9 | 2 | 2.5**
Moment of inertia J	**0.0028 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0102, p. 27 (PDF 27)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0102 (IE1)

1LE0102-0EC04-1KA4

0.75 kW / 1000 rpm

Frame 90 S | 6 poles | IM B14 | Article No. 1LE0102-0EC04-1KA4

GENERAL DATA

Series / efficiency class	**1LE0102 / IE1**
Housing	**Cast iron**
Frame size	**90 S**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**525 V D**
Net weight (IM B3)	**25 kg**

ELECTRICAL DATA

Rated power 50 Hz	**0.75 kW (about 1 HP)**
Rated power 60 Hz	**0.86 kW**
Rated speed (50 Hz)	**925 rpm**
Rated torque	**7.7 Nm**
Rated current	**1.59 A**
Power factor	**0.74**
Efficiency 4/4 | 3/4 | 2/4	**70 | 71.5 | 68.9 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**3.9 | 2 | 2.5**
Moment of inertia J	**0.0028 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0102, p. 27 (PDF 27)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0101 (IE2)

1LE0101-0EC02-2AA4

0.75 kW / 1000 rpm

Frame 90 S | 6 poles | IM B3 | Article No. 1LE0101-0EC02-2AA4

GENERAL DATA

Series / efficiency class	**1LE0101 / IE2**
Housing	**Cast iron**
Frame size	**90 S**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**26 kg**

ELECTRICAL DATA

Rated power 50 Hz	**0.75 kW (about 1 HP)**
Rated power 60 Hz	**0.86 kW**
Rated speed (50 Hz)	**935 rpm**
Rated torque	**7.7 Nm**
Rated current	**2 A**
Power factor	**0.71**
Efficiency 4/4 | 3/4 | 2/4	**75.9 | 76.5 | 72.7 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**3.9 | 2 | 2.5**
Moment of inertia J	**0.0038 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0101, p. 25 (PDF 25)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0101 (IE2)

1LE0101-0EC02-2FA4

0.75 kW / 1000 rpm

Frame 90 S | 6 poles | IM B5 | Article No. 1LE0101-0EC02-2FA4

GENERAL DATA

Series / efficiency class	**1LE0101 / IE2**
Housing	**Cast iron**
Frame size	**90 S**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**26 kg**

ELECTRICAL DATA

Rated power 50 Hz	**0.75 kW (about 1 HP)**
Rated power 60 Hz	**0.86 kW**
Rated speed (50 Hz)	**935 rpm**
Rated torque	**7.7 Nm**
Rated current	**2 A**
Power factor	**0.71**
Efficiency 4/4 | 3/4 | 2/4	**75.9 | 76.5 | 72.7 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**3.9 | 2 | 2.5**
Moment of inertia J	**0.0038 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0101, p. 25 (PDF 25)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0101 (IE2)

1LE0101-0EC02-2KA4

0.75 kW / 1000 rpm

Frame 90 S | 6 poles | IM B14 | Article No. 1LE0101-0EC02-2KA4

GENERAL DATA

Series / efficiency class	**1LE0101 / IE2**
Housing	**Cast iron**
Frame size	**90 S**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**26 kg**

ELECTRICAL DATA

Rated power 50 Hz	**0.75 kW (about 1 HP)**
Rated power 60 Hz	**0.86 kW**
Rated speed (50 Hz)	**935 rpm**
Rated torque	**7.7 Nm**
Rated current	**2 A**
Power factor	**0.71**
Efficiency 4/4 | 3/4 | 2/4	**75.9 | 76.5 | 72.7 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**3.9 | 2 | 2.5**
Moment of inertia J	**0.0038 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0101, p. 25 (PDF 25)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0101 (IE2)

1LE0101-0EC04-1AA4

0.75 kW / 1000 rpm

Frame 90 S | 6 poles | IM B3 | Article No. 1LE0101-0EC04-1AA4

GENERAL DATA

Series / efficiency class	**1LE0101 / IE2**
Housing	**Cast iron**
Frame size	**90 S**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**525 V D**
Net weight (IM B3)	**26 kg**

ELECTRICAL DATA

Rated power 50 Hz	**0.75 kW (about 1 HP)**
Rated power 60 Hz	**0.86 kW**
Rated speed (50 Hz)	**935 rpm**
Rated torque	**7.7 Nm**
Rated current	**1.52 A**
Power factor	**0.71**
Efficiency 4/4 | 3/4 | 2/4	**75.9 | 76.5 | 72.7 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**3.9 | 2 | 2.5**
Moment of inertia J	**0.0038 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0101, p. 29 (PDF 29)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0101 (IE2)

1LE0101-0EC04-1FA4

0.75 kW / 1000 rpm

Frame 90 S | 6 poles | IM B5 | Article No. 1LE0101-0EC04-1FA4

GENERAL DATA

Series / efficiency class	**1LE0101 / IE2**
Housing	**Cast iron**
Frame size	**90 S**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**525 V D**
Net weight (IM B3)	**26 kg**

ELECTRICAL DATA

Rated power 50 Hz	**0.75 kW (about 1 HP)**
Rated power 60 Hz	**0.86 kW**
Rated speed (50 Hz)	**935 rpm**
Rated torque	**7.7 Nm**
Rated current	**1.52 A**
Power factor	**0.71**
Efficiency 4/4 | 3/4 | 2/4	**75.9 | 76.5 | 72.7 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**3.9 | 2 | 2.5**
Moment of inertia J	**0.0038 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0101, p. 29 (PDF 29)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0101 (IE2)

1LE0101-0EC04-1KA4

0.75 kW / 1000 rpm

Frame 90 S | 6 poles | IM B14 | Article No. 1LE0101-0EC04-1KA4

GENERAL DATA

Series / efficiency class	**1LE0101 / IE2**
Housing	**Cast iron**
Frame size	**90 S**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**525 V D**
Net weight (IM B3)	**26 kg**

ELECTRICAL DATA

Rated power 50 Hz	**0.75 kW (about 1 HP)**
Rated power 60 Hz	**0.86 kW**
Rated speed (50 Hz)	**935 rpm**
Rated torque	**7.7 Nm**
Rated current	**1.52 A**
Power factor	**0.71**
Efficiency 4/4 | 3/4 | 2/4	**75.9 | 76.5 | 72.7 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**3.9 | 2 | 2.5**
Moment of inertia J	**0.0038 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0101, p. 29 (PDF 29)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1501 (IE2)

1LE1501-0EC02-2AA4

0.75 kW / 1000 rpm

Frame 90 S | 6 poles | IM B3 | Article No. 1LE1501-0EC02-2AA4

GENERAL DATA

Series / efficiency class	**1LE1501 / IE2**
Housing	**Cast iron**
Frame size	**90 S**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**23 kg**

ELECTRICAL DATA

Rated power 50 Hz	**0.75 kW (about 1 HP)**
Rated power 60 Hz	**0.86 kW**
Rated speed (50 Hz)	**935 rpm**
Rated torque	**7.7 Nm**
Rated current	**2.05 A**
Power factor	**0.7**
Efficiency 4/4 | 3/4 | 2/4	**75.9 | 76.8 | 74.5 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**4.1 | 2 | 2.5**
Moment of inertia J	**0.003 kgm2**
Sound pressure / power LpfA | LWA	**43 | 55 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1501, p. 2/34 (PDF 152)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1501 (IE2)

1LE1501-0EC02-2FA4

0.75 kW / 1000 rpm

Frame 90 S | 6 poles | IM B5 | Article No. 1LE1501-0EC02-2FA4

GENERAL DATA

Series / efficiency class	**1LE1501 / IE2**
Housing	**Cast iron**
Frame size	**90 S**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**23 kg**

ELECTRICAL DATA

Rated power 50 Hz	**0.75 kW (about 1 HP)**
Rated power 60 Hz	**0.86 kW**
Rated speed (50 Hz)	**935 rpm**
Rated torque	**7.7 Nm**
Rated current	**2.05 A**
Power factor	**0.7**
Efficiency 4/4 | 3/4 | 2/4	**75.9 | 76.8 | 74.5 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**4.1 | 2 | 2.5**
Moment of inertia J	**0.003 kgm2**
Sound pressure / power LpfA | LWA	**43 | 55 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1501, p. 2/34 (PDF 152)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1503 (IE3)

1LE1503-0EC02-2AA4

0.75 kW / 1000 rpm

Frame 90 S | 6 poles | IM B3 | Article No. 1LE1503-0EC02-2AA4

GENERAL DATA

Series / efficiency class	**1LE1503 / IE3**
Housing	**Cast iron**
Frame size	**90 S**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**26 kg**

ELECTRICAL DATA

Rated power 50 Hz	**0.75 kW (about 1 HP)**
Rated power 60 Hz	**not listed (catalog 09/2023)**
Rated speed (50 Hz)	**945 rpm**
Rated torque	**7.6 Nm**
Rated current	**1.96 A**
Power factor	**0.7**
Efficiency 4/4 | 3/4 | 2/4	**78.9 | 80 | 78.8 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**4.6 | 2.2 | 2.6**
Moment of inertia J	**0.004 kgm2**
Sound pressure / power LpfA | LWA	**43 | 55 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (09/2023), table 1LE1503, p. 3/21**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1503 (IE3)

1LE1503-0EC02-2FA4

0.75 kW / 1000 rpm

Frame 90 S | 6 poles | IM B5 | Article No. 1LE1503-0EC02-2FA4

GENERAL DATA

Series / efficiency class	**1LE1503 / IE3**
Housing	**Cast iron**
Frame size	**90 S**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**26 kg**

ELECTRICAL DATA

Rated power 50 Hz	**0.75 kW (about 1 HP)**
Rated power 60 Hz	**not listed (catalog 09/2023)**
Rated speed (50 Hz)	**945 rpm**
Rated torque	**7.6 Nm**
Rated current	**1.96 A**
Power factor	**0.7**
Efficiency 4/4 | 3/4 | 2/4	**78.9 | 80 | 78.8 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**4.6 | 2.2 | 2.6**
Moment of inertia J	**0.004 kgm2**
Sound pressure / power LpfA | LWA	**43 | 55 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (09/2023), table 1LE1503, p. 3/21**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1543 (IE3)

1LE1543-0EC02-2AA4

0.75 kW / 1000 rpm

Frame 90 S | 6 poles | IM B3 | Article No. 1LE1543-0EC02-2AA4

GENERAL DATA

Series / efficiency class	**1LE1543 / IE3**
Housing	**Cast iron**
Frame size	**90 S**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**27 kg**

ELECTRICAL DATA - CATALOG VALUES AT 60 HZ (APAC LINE)

Rated power (P50 rating)	**0.75 kW (about 1 HP)**
Rated power (P60 rating)	**0.86 kW**
Rated speed (60 Hz)	**1155 rpm**
Rated torque (60 Hz)	**6.2 Nm**
Rated current (460 V, 60 Hz)	**3.05 A**
Power factor (60 Hz)	**0.65**
Efficiency 4/4 | 3/4 | 2/4 (60 Hz)	**82.5 | 82.4 | 79.9 %**
I_LR/I_N | T_LR/T_N | T_B/T_N (60 Hz)	**5.3 | 2.4 | 3.1**
Moment of inertia J	**0.004 kgm2**
Sound pressure / power LpfA | LWA (60 Hz)	**46 | 58 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1543, p. 2/59 (PDF 177)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
APAC Line: the catalog lists operating values at 60 Hz only; 50 Hz speed/efficiency are not listed (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1543 (IE3)

1LE1543-0EC02-2FA4

0.75 kW / 1000 rpm

Frame 90 S | 6 poles | IM B5 | Article No. 1LE1543-0EC02-2FA4

GENERAL DATA

Series / efficiency class	**1LE1543 / IE3**
Housing	**Cast iron**
Frame size	**90 S**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**27 kg**

ELECTRICAL DATA - CATALOG VALUES AT 60 HZ (APAC LINE)

Rated power (P50 rating)	**0.75 kW (about 1 HP)**
Rated power (P60 rating)	**0.86 kW**
Rated speed (60 Hz)	**1155 rpm**
Rated torque (60 Hz)	**6.2 Nm**
Rated current (460 V, 60 Hz)	**3.05 A**
Power factor (60 Hz)	**0.65**
Efficiency 4/4 | 3/4 | 2/4 (60 Hz)	**82.5 | 82.4 | 79.9 %**
I_LR/I_N | T_LR/T_N | T_B/T_N (60 Hz)	**5.3 | 2.4 | 3.1**
Moment of inertia J	**0.004 kgm2**
Sound pressure / power LpfA | LWA (60 Hz)	**46 | 58 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1543, p. 2/59 (PDF 177)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
APAC Line: the catalog lists operating values at 60 Hz only; 50 Hz speed/efficiency are not listed (see Siemens DT Configurator).