Data sheets - Siemens SIMOTICS GP motors

0.75 kW / 1500 rpm - 32 article numbers in this file

Article No.	Page
1LE1002-0DB32-2AA4	2
1LE1002-0DB32-2FA4	3
1LE1002-0DB32-2KA4	4
1LE1001-0DB32-2AA4	5
1LE1001-0DB32-2FA4	6
1LE1001-0DB32-2KA4	7
1LE1041-0DB32-2FA4	8
1LE1041-0DB32-2KA4	9
1LE1003-0DB32-2AA4	10
1LE1003-0DB32-2FA4	11
1LE1003-0DB32-2KA4	12
1LE1043-0DB32-2AA4	13
1LE1043-0DB32-2FA4	14
1LE1043-0DB32-2KA4	15
1LE0102-0DB32-2AA4	16
1LE0102-0DB32-2FA4	17
1LE0102-0DB32-2KA4	18
1LE0102-0DB34-1AA4	19
1LE0102-0DB34-1FA4	20
1LE0102-0DB34-1KA4	21
1LE0101-0DB32-2AA4	22
1LE0101-0DB32-2FA4	23
1LE0101-0DB32-2KA4	24
1LE0101-0DB34-1AA4	25
1LE0101-0DB34-1FA4	26
1LE0101-0DB34-1KA4	27
1LE1501-0DB32-2AA4	28
1LE1501-0DB32-2FA4	29
1LE1503-0DB32-2AA4	30
1LE1503-0DB32-2FA4	31
1LE1543-0DB32-2AA4	32
1LE1543-0DB32-2FA4	33

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1002 (IE1)

1LE1002-0DB32-2AA4

0.75 kW / 1500 rpm

Frame 80 M | 4 poles | IM B3 | Article No. 1LE1002-0DB32-2AA4

GENERAL DATA

Series / efficiency class	**1LE1002 / IE1**
Housing	**Aluminum**
Frame size	**80 M**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**11 kg**

ELECTRICAL DATA

Rated power 50 Hz	**0.75 kW (about 1 HP)**
Rated power 60 Hz	**0.86 kW**
Rated speed (50 Hz)	**1385 rpm**
Rated torque	**5.2 Nm**
Rated current	**1.85 A**
Power factor	**0.76**
Efficiency 4/4 | 3/4 | 2/4	**72.1 | 72 | 67 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**3.6 | 2.1 | 2.3**
Moment of inertia J	**0.0017 kgm2**
Sound pressure / power LpfA | LWA	**59 | 66 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1002, p. 2/45 (PDF 163)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1002 (IE1)

1LE1002-0DB32-2FA4

0.75 kW / 1500 rpm

Frame 80 M | 4 poles | IM B5 | Article No. 1LE1002-0DB32-2FA4

GENERAL DATA

Series / efficiency class	**1LE1002 / IE1**
Housing	**Aluminum**
Frame size	**80 M**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**11 kg**

ELECTRICAL DATA

Rated power 50 Hz	**0.75 kW (about 1 HP)**
Rated power 60 Hz	**0.86 kW**
Rated speed (50 Hz)	**1385 rpm**
Rated torque	**5.2 Nm**
Rated current	**1.85 A**
Power factor	**0.76**
Efficiency 4/4 | 3/4 | 2/4	**72.1 | 72 | 67 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**3.6 | 2.1 | 2.3**
Moment of inertia J	**0.0017 kgm2**
Sound pressure / power LpfA | LWA	**59 | 66 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1002, p. 2/45 (PDF 163)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1002 (IE1)

1LE1002-0DB32-2KA4

0.75 kW / 1500 rpm

Frame 80 M | 4 poles | IM B14 | Article No. 1LE1002-0DB32-2KA4

GENERAL DATA

Series / efficiency class	**1LE1002 / IE1**
Housing	**Aluminum**
Frame size	**80 M**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**11 kg**

ELECTRICAL DATA

Rated power 50 Hz	**0.75 kW (about 1 HP)**
Rated power 60 Hz	**0.86 kW**
Rated speed (50 Hz)	**1385 rpm**
Rated torque	**5.2 Nm**
Rated current	**1.85 A**
Power factor	**0.76**
Efficiency 4/4 | 3/4 | 2/4	**72.1 | 72 | 67 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**3.6 | 2.1 | 2.3**
Moment of inertia J	**0.0017 kgm2**
Sound pressure / power LpfA | LWA	**59 | 66 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1002, p. 2/45 (PDF 163)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1001 (IE2)

1LE1001-0DB32-2AA4

0.75 kW / 1500 rpm

Frame 80 M | 4 poles | IM B3 | Article No. 1LE1001-0DB32-2AA4

GENERAL DATA

Series / efficiency class	**1LE1001 / IE2**
Housing	**Aluminum**
Frame size	**80 M**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**11 kg**

ELECTRICAL DATA

Rated power 50 Hz	**0.75 kW (about 1 HP)**
Rated power 60 Hz	**0.86 kW**
Rated speed (50 Hz)	**1440 rpm**
Rated torque	**5 Nm**
Rated current	**1.79 A**
Power factor	**0.76**
Efficiency 4/4 | 3/4 | 2/4	**79.6 | 79.9 | 77.5 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5.6 | 2.2 | 3.1**
Moment of inertia J	**0.0021 kgm2**
Sound pressure / power LpfA | LWA	**53 | 64 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1001, p. 2/27 (PDF 145)**
Catalog 2	**Brochure 07/2014 (14050629), p. 19 (PDF 19)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1001 (IE2)

1LE1001-0DB32-2FA4

0.75 kW / 1500 rpm

Frame 80 M | 4 poles | IM B5 | Article No. 1LE1001-0DB32-2FA4

GENERAL DATA

Series / efficiency class	**1LE1001 / IE2**
Housing	**Aluminum**
Frame size	**80 M**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**11 kg**

ELECTRICAL DATA

Rated power 50 Hz	**0.75 kW (about 1 HP)**
Rated power 60 Hz	**0.86 kW**
Rated speed (50 Hz)	**1440 rpm**
Rated torque	**5 Nm**
Rated current	**1.79 A**
Power factor	**0.76**
Efficiency 4/4 | 3/4 | 2/4	**79.6 | 79.9 | 77.5 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5.6 | 2.2 | 3.1**
Moment of inertia J	**0.0021 kgm2**
Sound pressure / power LpfA | LWA	**53 | 64 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1001, p. 2/27 (PDF 145)**
Catalog 2	**Brochure 07/2014 (14050629), p. 19 (PDF 19)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1001 (IE2)

1LE1001-0DB32-2KA4

0.75 kW / 1500 rpm

Frame 80 M | 4 poles | IM B14 | Article No. 1LE1001-0DB32-2KA4

GENERAL DATA

Series / efficiency class	**1LE1001 / IE2**
Housing	**Aluminum**
Frame size	**80 M**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**11 kg**

ELECTRICAL DATA

Rated power 50 Hz	**0.75 kW (about 1 HP)**
Rated power 60 Hz	**0.86 kW**
Rated speed (50 Hz)	**1440 rpm**
Rated torque	**5 Nm**
Rated current	**1.79 A**
Power factor	**0.76**
Efficiency 4/4 | 3/4 | 2/4	**79.6 | 79.9 | 77.5 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5.6 | 2.2 | 3.1**
Moment of inertia J	**0.0021 kgm2**
Sound pressure / power LpfA | LWA	**53 | 64 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1001, p. 2/27 (PDF 145)**
Catalog 2	**Brochure 07/2014 (14050629), p. 19 (PDF 19)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1041 (IE2)

1LE1041-0DB32-2FA4

0.75 kW / 1500 rpm

Frame 80 M | 4 poles | IM B5 | Article No. 1LE1041-0DB32-2FA4

GENERAL DATA

Series / efficiency class	**1LE1041 / IE2**
Housing	**Aluminum**
Frame size	**80 M**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**11 kg**

ELECTRICAL DATA - CATALOG VALUES AT 60 HZ (APAC LINE)

Rated power (P50 rating)	**0.75 kW (about 1 HP)**
Rated power (P60 rating)	**0.86 kW**
Rated speed (60 Hz)	**1750 rpm**
Rated torque (60 Hz)	**4.1 Nm**
Rated current (460 V, 60 Hz)	**1.68 A**
Power factor (60 Hz)	**0.72**
Efficiency 4/4 | 3/4 | 2/4 (60 Hz)	**78 | 77.4 | 74.6 %**
I_LR/I_N | T_LR/T_N | T_B/T_N (60 Hz)	**6.8 | 2.5 | 3.8**
Moment of inertia J	**0.0021 kgm2**
Sound pressure / power LpfA | LWA (60 Hz)	**55 | 66 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1041, p. 2/65 (PDF 183)**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
APAC Line: the catalog lists operating values at 60 Hz only; 50 Hz speed/efficiency are not listed (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1041 (IE2)

1LE1041-0DB32-2KA4

0.75 kW / 1500 rpm

Frame 80 M | 4 poles | IM B14 | Article No. 1LE1041-0DB32-2KA4

GENERAL DATA

Series / efficiency class	**1LE1041 / IE2**
Housing	**Aluminum**
Frame size	**80 M**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**11 kg**

ELECTRICAL DATA - CATALOG VALUES AT 60 HZ (APAC LINE)

Rated power (P50 rating)	**0.75 kW (about 1 HP)**
Rated power (P60 rating)	**0.86 kW**
Rated speed (60 Hz)	**1750 rpm**
Rated torque (60 Hz)	**4.1 Nm**
Rated current (460 V, 60 Hz)	**1.68 A**
Power factor (60 Hz)	**0.72**
Efficiency 4/4 | 3/4 | 2/4 (60 Hz)	**78 | 77.4 | 74.6 %**
I_LR/I_N | T_LR/T_N | T_B/T_N (60 Hz)	**6.8 | 2.5 | 3.8**
Moment of inertia J	**0.0021 kgm2**
Sound pressure / power LpfA | LWA (60 Hz)	**55 | 66 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1041, p. 2/65 (PDF 183)**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
APAC Line: the catalog lists operating values at 60 Hz only; 50 Hz speed/efficiency are not listed (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1003 (IE3)

1LE1003-0DB32-2AA4

0.75 kW / 1500 rpm

Frame 80 M | 4 poles | IM B3 | Article No. 1LE1003-0DB32-2AA4

GENERAL DATA

Series / efficiency class	**1LE1003 / IE3**
Housing	**Aluminum**
Frame size	**80 M**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**14 kg**

ELECTRICAL DATA

Rated power 50 Hz	**0.75 kW (about 1 HP)**
Rated power 60 Hz	**0.86 kW**
Rated speed (50 Hz)	**1450 rpm**
Rated torque	**4.9 Nm**
Rated current	**1.75 A**
Power factor	**0.75**
Efficiency 4/4 | 3/4 | 2/4	**82.5 | 82.3 | 79.9 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**7.1 | 2.7 | 3.9**
Moment of inertia J	**0.0029 kgm2**
Sound pressure / power LpfA | LWA	**53 | 64 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1003, p. 2/14 (PDF 132)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1003 (IE3)

1LE1003-0DB32-2FA4

0.75 kW / 1500 rpm

Frame 80 M | 4 poles | IM B5 | Article No. 1LE1003-0DB32-2FA4

GENERAL DATA

Series / efficiency class	**1LE1003 / IE3**
Housing	**Aluminum**
Frame size	**80 M**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**14 kg**

ELECTRICAL DATA

Rated power 50 Hz	**0.75 kW (about 1 HP)**
Rated power 60 Hz	**0.86 kW**
Rated speed (50 Hz)	**1450 rpm**
Rated torque	**4.9 Nm**
Rated current	**1.75 A**
Power factor	**0.75**
Efficiency 4/4 | 3/4 | 2/4	**82.5 | 82.3 | 79.9 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**7.1 | 2.7 | 3.9**
Moment of inertia J	**0.0029 kgm2**
Sound pressure / power LpfA | LWA	**53 | 64 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1003, p. 2/14 (PDF 132)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1003 (IE3)

1LE1003-0DB32-2KA4

0.75 kW / 1500 rpm

Frame 80 M | 4 poles | IM B14 | Article No. 1LE1003-0DB32-2KA4

GENERAL DATA

Series / efficiency class	**1LE1003 / IE3**
Housing	**Aluminum**
Frame size	**80 M**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**14 kg**

ELECTRICAL DATA

Rated power 50 Hz	**0.75 kW (about 1 HP)**
Rated power 60 Hz	**0.86 kW**
Rated speed (50 Hz)	**1450 rpm**
Rated torque	**4.9 Nm**
Rated current	**1.75 A**
Power factor	**0.75**
Efficiency 4/4 | 3/4 | 2/4	**82.5 | 82.3 | 79.9 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**7.1 | 2.7 | 3.9**
Moment of inertia J	**0.0029 kgm2**
Sound pressure / power LpfA | LWA	**53 | 64 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1003, p. 2/14 (PDF 132)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1043 (IE3)

1LE1043-0DB32-2AA4

0.75 kW / 1500 rpm

Frame 80 M | 4 poles | IM B3 | Article No. 1LE1043-0DB32-2AA4

GENERAL DATA

Series / efficiency class	**1LE1043 / IE3**
Housing	**Aluminum**
Frame size	**80 M**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**14 kg**

ELECTRICAL DATA - CATALOG VALUES AT 60 HZ (APAC LINE)

Rated power (P50 rating)	**0.75 kW (about 1 HP)**
Rated power (P60 rating)	**0.86 kW**
Rated speed (60 Hz)	**1760 rpm**
Rated torque (60 Hz)	**4.1 Nm**
Rated current (460 V, 60 Hz)	**1.59 A**
Power factor (60 Hz)	**0.71**
Efficiency 4/4 | 3/4 | 2/4 (60 Hz)	**83.5 | 82.6 | 79.3 %**
I_LR/I_N | T_LR/T_N | T_B/T_N (60 Hz)	**8.3 | 3.1 | 4.7**
Moment of inertia J	**0.0021 kgm2**
Sound pressure / power LpfA | LWA (60 Hz)	**55 | 66 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1043, p. 2/54 (PDF 172)**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
APAC Line: the catalog lists operating values at 60 Hz only; 50 Hz speed/efficiency are not listed (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1043 (IE3)

1LE1043-0DB32-2FA4

0.75 kW / 1500 rpm

Frame 80 M | 4 poles | IM B5 | Article No. 1LE1043-0DB32-2FA4

GENERAL DATA

Series / efficiency class	**1LE1043 / IE3**
Housing	**Aluminum**
Frame size	**80 M**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**14 kg**

ELECTRICAL DATA - CATALOG VALUES AT 60 HZ (APAC LINE)

Rated power (P50 rating)	**0.75 kW (about 1 HP)**
Rated power (P60 rating)	**0.86 kW**
Rated speed (60 Hz)	**1760 rpm**
Rated torque (60 Hz)	**4.1 Nm**
Rated current (460 V, 60 Hz)	**1.59 A**
Power factor (60 Hz)	**0.71**
Efficiency 4/4 | 3/4 | 2/4 (60 Hz)	**83.5 | 82.6 | 79.3 %**
I_LR/I_N | T_LR/T_N | T_B/T_N (60 Hz)	**8.3 | 3.1 | 4.7**
Moment of inertia J	**0.0021 kgm2**
Sound pressure / power LpfA | LWA (60 Hz)	**55 | 66 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1043, p. 2/54 (PDF 172)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
APAC Line: the catalog lists operating values at 60 Hz only; 50 Hz speed/efficiency are not listed (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1043 (IE3)

1LE1043-0DB32-2KA4

0.75 kW / 1500 rpm

Frame 80 M | 4 poles | IM B14 | Article No. 1LE1043-0DB32-2KA4

GENERAL DATA

Series / efficiency class	**1LE1043 / IE3**
Housing	**Aluminum**
Frame size	**80 M**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**14 kg**

ELECTRICAL DATA - CATALOG VALUES AT 60 HZ (APAC LINE)

Rated power (P50 rating)	**0.75 kW (about 1 HP)**
Rated power (P60 rating)	**0.86 kW**
Rated speed (60 Hz)	**1760 rpm**
Rated torque (60 Hz)	**4.1 Nm**
Rated current (460 V, 60 Hz)	**1.59 A**
Power factor (60 Hz)	**0.71**
Efficiency 4/4 | 3/4 | 2/4 (60 Hz)	**83.5 | 82.6 | 79.3 %**
I_LR/I_N | T_LR/T_N | T_B/T_N (60 Hz)	**8.3 | 3.1 | 4.7**
Moment of inertia J	**0.0021 kgm2**
Sound pressure / power LpfA | LWA (60 Hz)	**55 | 66 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1043, p. 2/54 (PDF 172)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
APAC Line: the catalog lists operating values at 60 Hz only; 50 Hz speed/efficiency are not listed (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0102 (IE1)

1LE0102-0DB32-2AA4

0.75 kW / 1500 rpm

Frame 80 M | 4 poles | IM B3 | Article No. 1LE0102-0DB32-2AA4

GENERAL DATA

Series / efficiency class	**1LE0102 / IE1**
Housing	**Cast iron**
Frame size	**80 M**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**18.5 kg**

ELECTRICAL DATA

Rated power 50 Hz	**0.75 kW (about 1 HP)**
Rated power 60 Hz	**0.86 kW**
Rated speed (50 Hz)	**1405 rpm**
Rated torque	**5.1 Nm**
Rated current	**1.87 A**
Power factor	**0.81**
Efficiency 4/4 | 3/4 | 2/4	**72.1 | 73.7 | 71.8 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**4.8 | 2 | 2.6**
Moment of inertia J	**0.0019 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0102, p. 21 (PDF 21)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0102 (IE1)

1LE0102-0DB32-2FA4

0.75 kW / 1500 rpm

Frame 80 M | 4 poles | IM B5 | Article No. 1LE0102-0DB32-2FA4

GENERAL DATA

Series / efficiency class	**1LE0102 / IE1**
Housing	**Cast iron**
Frame size	**80 M**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**18.5 kg**

ELECTRICAL DATA

Rated power 50 Hz	**0.75 kW (about 1 HP)**
Rated power 60 Hz	**0.86 kW**
Rated speed (50 Hz)	**1405 rpm**
Rated torque	**5.1 Nm**
Rated current	**1.87 A**
Power factor	**0.81**
Efficiency 4/4 | 3/4 | 2/4	**72.1 | 73.7 | 71.8 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**4.8 | 2 | 2.6**
Moment of inertia J	**0.0019 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0102, p. 21 (PDF 21)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0102 (IE1)

1LE0102-0DB32-2KA4

0.75 kW / 1500 rpm

Frame 80 M | 4 poles | IM B14 | Article No. 1LE0102-0DB32-2KA4

GENERAL DATA

Series / efficiency class	**1LE0102 / IE1**
Housing	**Cast iron**
Frame size	**80 M**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**18.5 kg**

ELECTRICAL DATA

Rated power 50 Hz	**0.75 kW (about 1 HP)**
Rated power 60 Hz	**0.86 kW**
Rated speed (50 Hz)	**1405 rpm**
Rated torque	**5.1 Nm**
Rated current	**1.87 A**
Power factor	**0.81**
Efficiency 4/4 | 3/4 | 2/4	**72.1 | 73.7 | 71.8 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**4.8 | 2 | 2.6**
Moment of inertia J	**0.0019 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0102, p. 21 (PDF 21)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0102 (IE1)

1LE0102-0DB34-1AA4

0.75 kW / 1500 rpm

Frame 80 M | 4 poles | IM B3 | Article No. 1LE0102-0DB34-1AA4

GENERAL DATA

Series / efficiency class	**1LE0102 / IE1**
Housing	**Cast iron**
Frame size	**80 M**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**525 V D**
Net weight (IM B3)	**18.5 kg**

ELECTRICAL DATA

Rated power 50 Hz	**0.75 kW (about 1 HP)**
Rated power 60 Hz	**0.86 kW**
Rated speed (50 Hz)	**1405 rpm**
Rated torque	**5.1 Nm**
Rated current	**1.41 A**
Power factor	**0.81**
Efficiency 4/4 | 3/4 | 2/4	**72.1 | 73.7 | 71.8 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**4.8 | 2 | 2.6**
Moment of inertia J	**0.0019 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0102, p. 26 (PDF 26)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0102 (IE1)

1LE0102-0DB34-1FA4

0.75 kW / 1500 rpm

Frame 80 M | 4 poles | IM B5 | Article No. 1LE0102-0DB34-1FA4

GENERAL DATA

Series / efficiency class	**1LE0102 / IE1**
Housing	**Cast iron**
Frame size	**80 M**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**525 V D**
Net weight (IM B3)	**18.5 kg**

ELECTRICAL DATA

Rated power 50 Hz	**0.75 kW (about 1 HP)**
Rated power 60 Hz	**0.86 kW**
Rated speed (50 Hz)	**1405 rpm**
Rated torque	**5.1 Nm**
Rated current	**1.41 A**
Power factor	**0.81**
Efficiency 4/4 | 3/4 | 2/4	**72.1 | 73.7 | 71.8 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**4.8 | 2 | 2.6**
Moment of inertia J	**0.0019 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0102, p. 26 (PDF 26)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0102 (IE1)

1LE0102-0DB34-1KA4

0.75 kW / 1500 rpm

Frame 80 M | 4 poles | IM B14 | Article No. 1LE0102-0DB34-1KA4

GENERAL DATA

Series / efficiency class	**1LE0102 / IE1**
Housing	**Cast iron**
Frame size	**80 M**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**525 V D**
Net weight (IM B3)	**18.5 kg**

ELECTRICAL DATA

Rated power 50 Hz	**0.75 kW (about 1 HP)**
Rated power 60 Hz	**0.86 kW**
Rated speed (50 Hz)	**1405 rpm**
Rated torque	**5.1 Nm**
Rated current	**1.41 A**
Power factor	**0.81**
Efficiency 4/4 | 3/4 | 2/4	**72.1 | 73.7 | 71.8 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**4.8 | 2 | 2.6**
Moment of inertia J	**0.0019 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0102, p. 26 (PDF 26)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0101 (IE2)

1LE0101-0DB32-2AA4

0.75 kW / 1500 rpm

Frame 80 M | 4 poles | IM B3 | Article No. 1LE0101-0DB32-2AA4

GENERAL DATA

Series / efficiency class	**1LE0101 / IE2**
Housing	**Cast iron**
Frame size	**80 M**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**19 kg**

ELECTRICAL DATA

Rated power 50 Hz	**0.75 kW (about 1 HP)**
Rated power 60 Hz	**0.86 kW**
Rated speed (50 Hz)	**1440 rpm**
Rated torque	**5 Nm**
Rated current	**1.82 A**
Power factor	**0.75**
Efficiency 4/4 | 3/4 | 2/4	**79.6 | 79.6 | 76.8 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**6.5 | 2.8 | 3.5**
Moment of inertia J	**0.0027 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0101, p. 24 (PDF 24)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0101 (IE2)

1LE0101-0DB32-2FA4

0.75 kW / 1500 rpm

Frame 80 M | 4 poles | IM B5 | Article No. 1LE0101-0DB32-2FA4

GENERAL DATA

Series / efficiency class	**1LE0101 / IE2**
Housing	**Cast iron**
Frame size	**80 M**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**19 kg**

ELECTRICAL DATA

Rated power 50 Hz	**0.75 kW (about 1 HP)**
Rated power 60 Hz	**0.86 kW**
Rated speed (50 Hz)	**1440 rpm**
Rated torque	**5 Nm**
Rated current	**1.82 A**
Power factor	**0.75**
Efficiency 4/4 | 3/4 | 2/4	**79.6 | 79.6 | 76.8 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**6.5 | 2.8 | 3.5**
Moment of inertia J	**0.0027 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0101, p. 24 (PDF 24)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0101 (IE2)

1LE0101-0DB32-2KA4

0.75 kW / 1500 rpm

Frame 80 M | 4 poles | IM B14 | Article No. 1LE0101-0DB32-2KA4

GENERAL DATA

Series / efficiency class	**1LE0101 / IE2**
Housing	**Cast iron**
Frame size	**80 M**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**19 kg**

ELECTRICAL DATA

Rated power 50 Hz	**0.75 kW (about 1 HP)**
Rated power 60 Hz	**0.86 kW**
Rated speed (50 Hz)	**1440 rpm**
Rated torque	**5 Nm**
Rated current	**1.82 A**
Power factor	**0.75**
Efficiency 4/4 | 3/4 | 2/4	**79.6 | 79.6 | 76.8 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**6.5 | 2.8 | 3.5**
Moment of inertia J	**0.0027 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0101, p. 24 (PDF 24)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0101 (IE2)

1LE0101-0DB34-1AA4

0.75 kW / 1500 rpm

Frame 80 M | 4 poles | IM B3 | Article No. 1LE0101-0DB34-1AA4

GENERAL DATA

Series / efficiency class	**1LE0101 / IE2**
Housing	**Cast iron**
Frame size	**80 M**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**525 V D**
Net weight (IM B3)	**19 kg**

ELECTRICAL DATA

Rated power 50 Hz	**0.75 kW (about 1 HP)**
Rated power 60 Hz	**0.86 kW**
Rated speed (50 Hz)	**1440 rpm**
Rated torque	**5 Nm**
Rated current	**1.38 A**
Power factor	**0.75**
Efficiency 4/4 | 3/4 | 2/4	**79.6 | 79.6 | 76.8 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**6.5 | 2.8 | 3.5**
Moment of inertia J	**0.0027 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0101, p. 28 (PDF 28)**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0101 (IE2)

1LE0101-0DB34-1FA4

0.75 kW / 1500 rpm

Frame 80 M | 4 poles | IM B5 | Article No. 1LE0101-0DB34-1FA4

GENERAL DATA

Series / efficiency class	**1LE0101 / IE2**
Housing	**Cast iron**
Frame size	**80 M**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**525 V D**
Net weight (IM B3)	**19 kg**

ELECTRICAL DATA

Rated power 50 Hz	**0.75 kW (about 1 HP)**
Rated power 60 Hz	**0.86 kW**
Rated speed (50 Hz)	**1440 rpm**
Rated torque	**5 Nm**
Rated current	**1.38 A**
Power factor	**0.75**
Efficiency 4/4 | 3/4 | 2/4	**79.6 | 79.6 | 76.8 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**6.5 | 2.8 | 3.5**
Moment of inertia J	**0.0027 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0101, p. 28 (PDF 28)**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0101 (IE2)

1LE0101-0DB34-1KA4

0.75 kW / 1500 rpm

Frame 80 M | 4 poles | IM B14 | Article No. 1LE0101-0DB34-1KA4

GENERAL DATA

Series / efficiency class	**1LE0101 / IE2**
Housing	**Cast iron**
Frame size	**80 M**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**525 V D**
Net weight (IM B3)	**19 kg**

ELECTRICAL DATA

Rated power 50 Hz	**0.75 kW (about 1 HP)**
Rated power 60 Hz	**0.86 kW**
Rated speed (50 Hz)	**1440 rpm**
Rated torque	**5 Nm**
Rated current	**1.38 A**
Power factor	**0.75**
Efficiency 4/4 | 3/4 | 2/4	**79.6 | 79.6 | 76.8 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**6.5 | 2.8 | 3.5**
Moment of inertia J	**0.0027 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0101, p. 28 (PDF 28)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1501 (IE2)

1LE1501-0DB32-2AA4

0.75 kW / 1500 rpm

Frame 80 M | 4 poles | IM B3 | Article No. 1LE1501-0DB32-2AA4

GENERAL DATA

Series / efficiency class	**1LE1501 / IE2**
Housing	**Cast iron**
Frame size	**80 M**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**18 kg**

ELECTRICAL DATA

Rated power 50 Hz	**0.75 kW (about 1 HP)**
Rated power 60 Hz	**0.86 kW**
Rated speed (50 Hz)	**1440 rpm**
Rated torque	**5 Nm**
Rated current	**1.79 A**
Power factor	**0.76**
Efficiency 4/4 | 3/4 | 2/4	**79.6 | 79.9 | 77.5 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5.6 | 2.2 | 3.1**
Moment of inertia J	**0.0021 kgm2**
Sound pressure / power LpfA | LWA	**53 | 64 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1501, p. 2/33 (PDF 151)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1501 (IE2)

1LE1501-0DB32-2FA4

0.75 kW / 1500 rpm

Frame 80 M | 4 poles | IM B5 | Article No. 1LE1501-0DB32-2FA4

GENERAL DATA

Series / efficiency class	**1LE1501 / IE2**
Housing	**Cast iron**
Frame size	**80 M**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**18 kg**

ELECTRICAL DATA

Rated power 50 Hz	**0.75 kW (about 1 HP)**
Rated power 60 Hz	**0.86 kW**
Rated speed (50 Hz)	**1440 rpm**
Rated torque	**5 Nm**
Rated current	**1.79 A**
Power factor	**0.76**
Efficiency 4/4 | 3/4 | 2/4	**79.6 | 79.9 | 77.5 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5.6 | 2.2 | 3.1**
Moment of inertia J	**0.0021 kgm2**
Sound pressure / power LpfA | LWA	**53 | 64 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1501, p. 2/33 (PDF 151)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1503 (IE3)

1LE1503-0DB32-2AA4

0.75 kW / 1500 rpm

Frame 80 M | 4 poles | IM B3 | Article No. 1LE1503-0DB32-2AA4

GENERAL DATA

Series / efficiency class	**1LE1503 / IE3**
Housing	**Cast iron**
Frame size	**80 M**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**22 kg**

ELECTRICAL DATA

Rated power 50 Hz	**0.75 kW (about 1 HP)**
Rated power 60 Hz	**0.86 kW**
Rated speed (50 Hz)	**1450 rpm**
Rated torque	**4.9 Nm**
Rated current	**1.75 A**
Power factor	**0.75**
Efficiency 4/4 | 3/4 | 2/4	**82.5 | 82.3 | 79.9 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**7.1 | 2.7 | 3.9**
Moment of inertia J	**0.0029 kgm2**
Sound pressure / power LpfA | LWA	**53 | 64 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1503, p. 2/18 (PDF 136)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1503 (IE3)

1LE1503-0DB32-2FA4

0.75 kW / 1500 rpm

Frame 80 M | 4 poles | IM B5 | Article No. 1LE1503-0DB32-2FA4

GENERAL DATA

Series / efficiency class	**1LE1503 / IE3**
Housing	**Cast iron**
Frame size	**80 M**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**22 kg**

ELECTRICAL DATA

Rated power 50 Hz	**0.75 kW (about 1 HP)**
Rated power 60 Hz	**0.86 kW**
Rated speed (50 Hz)	**1450 rpm**
Rated torque	**4.9 Nm**
Rated current	**1.75 A**
Power factor	**0.75**
Efficiency 4/4 | 3/4 | 2/4	**82.5 | 82.3 | 79.9 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**7.1 | 2.7 | 3.9**
Moment of inertia J	**0.0029 kgm2**
Sound pressure / power LpfA | LWA	**53 | 64 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1503, p. 2/18 (PDF 136)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1543 (IE3)

1LE1543-0DB32-2AA4

0.75 kW / 1500 rpm

Frame 80 M | 4 poles | IM B3 | Article No. 1LE1543-0DB32-2AA4

GENERAL DATA

Series / efficiency class	**1LE1543 / IE3**
Housing	**Cast iron**
Frame size	**80 M**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**22 kg**

ELECTRICAL DATA - CATALOG VALUES AT 60 HZ (APAC LINE)

Rated power (P50 rating)	**0.75 kW (about 1 HP)**
Rated power (P60 rating)	**0.86 kW**
Rated speed (60 Hz)	**1760 rpm**
Rated torque (60 Hz)	**4.1 Nm**
Rated current (460 V, 60 Hz)	**1.59 A**
Power factor (60 Hz)	**0.71**
Efficiency 4/4 | 3/4 | 2/4 (60 Hz)	**83.5 | 82.6 | 79.3 %**
I_LR/I_N | T_LR/T_N | T_B/T_N (60 Hz)	**8.3 | 3.1 | 4.7**
Moment of inertia J	**0.0029 kgm2**
Sound pressure / power LpfA | LWA (60 Hz)	**55 | 66 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1543, p. 2/58 (PDF 176)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
APAC Line: the catalog lists operating values at 60 Hz only; 50 Hz speed/efficiency are not listed (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1543 (IE3)

1LE1543-0DB32-2FA4

0.75 kW / 1500 rpm

Frame 80 M | 4 poles | IM B5 | Article No. 1LE1543-0DB32-2FA4

GENERAL DATA

Series / efficiency class	**1LE1543 / IE3**
Housing	**Cast iron**
Frame size	**80 M**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**22 kg**

ELECTRICAL DATA - CATALOG VALUES AT 60 HZ (APAC LINE)

Rated power (P50 rating)	**0.75 kW (about 1 HP)**
Rated power (P60 rating)	**0.86 kW**
Rated speed (60 Hz)	**1760 rpm**
Rated torque (60 Hz)	**4.1 Nm**
Rated current (460 V, 60 Hz)	**1.59 A**
Power factor (60 Hz)	**0.71**
Efficiency 4/4 | 3/4 | 2/4 (60 Hz)	**83.5 | 82.6 | 79.3 %**
I_LR/I_N | T_LR/T_N | T_B/T_N (60 Hz)	**8.3 | 3.1 | 4.7**
Moment of inertia J	**0.0029 kgm2**
Sound pressure / power LpfA | LWA (60 Hz)	**55 | 66 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1543, p. 2/58 (PDF 176)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
APAC Line: the catalog lists operating values at 60 Hz only; 50 Hz speed/efficiency are not listed (see Siemens DT Configurator).