Data sheets - Siemens SIMOTICS GP motors

18.5 kW / 1000 rpm - 37 article numbers in this file

Article No.	Page
1LE1001-2AC43-4AA4	2
1LE1001-2AC43-4FA4	3
1LE1002-2AC43-4AA4	4
1LE1002-2AC43-4FA4	5
1LE1001-1EC63-4AA4	6
1LE1001-1EC63-4FA4	7
1LE1003-2AC43-4AA4	8
1LE1003-2AC43-4FA4	9
1LE1043-2AC43-4AA4	10
1LE1043-2AC43-4FA4	11
1LE1003-1EC63-4AA4	12
1LE1003-1EC63-4FA4	13
1LE0102-2AC43-4AA4	14
1LE0102-2AC43-4FA4	15
1LE0102-2AC44-1AA4	16
1LE0102-2AC44-1FA4	17
1LE1501-2AC43-4AA4	18
1LE1501-2AC43-4FA4	19
1LE1502-2AC43-4FA4	20
1LE1502-1EC63-4AA4	21
1LE1502-1EC63-4FA4	22
1LE1541-2AC43-4FA4	23
1LE0101-2AC43-4AB4	24
1LE0101-2AC43-4FB4	25
1LE0101-2AC44-1AB4	26
1LE0101-2AC44-1FB4	27
1LE1501-1EC63-4AA4	28
1LE1501-1EC63-4FA4	29
1LE1503-2AC43-4AA4	30
1LE1503-2AC43-4FA4	31
1LE1541-1EC63-4FA4	32
1LE1543-2AC43-4AA4	33
1LE1543-2AC43-4FA4	34
1LE1503-1EC63-4AA4	35
1LE1503-1EC63-4FA4	36
1LE1543-1EC63-4AA4	37
1LE1543-1EC63-4FA4	38

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1001 (IE2)

1LE1001-2AC43-4AA4

18.5 kW / 1000 rpm

Frame 200 L | 6 poles | IM B3 | Article No. 1LE1001-2AC43-4AA4

GENERAL DATA

Series / efficiency class	**1LE1001 / IE2**
Housing	**Aluminum**
Frame size	**200 L**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**151 kg**

ELECTRICAL DATA

Rated power 50 Hz	**18.5 kW (about 25 HP)**
Rated power 60 Hz	**22 kW**
Rated speed (50 Hz)	**978 rpm**
Rated torque	**181 Nm**
Rated current	**36 A**
Power factor	**0.82**
Efficiency 4/4 | 3/4 | 2/4	**90.4 | 91.4 | 91.3 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5.8 | 2.4 | 2.6**
Moment of inertia J	**0.25 kgm2**
Sound pressure / power LpfA | LWA	**63 | 76 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1001, p. 2/28 (PDF 146)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1001 (IE2)

1LE1001-2AC43-4FA4

18.5 kW / 1000 rpm

Frame 200 L | 6 poles | IM B5 | Article No. 1LE1001-2AC43-4FA4

GENERAL DATA

Series / efficiency class	**1LE1001 / IE2**
Housing	**Aluminum**
Frame size	**200 L**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**151 kg**

ELECTRICAL DATA

Rated power 50 Hz	**18.5 kW (about 25 HP)**
Rated power 60 Hz	**22 kW**
Rated speed (50 Hz)	**978 rpm**
Rated torque	**181 Nm**
Rated current	**36 A**
Power factor	**0.82**
Efficiency 4/4 | 3/4 | 2/4	**90.4 | 91.4 | 91.3 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5.8 | 2.4 | 2.6**
Moment of inertia J	**0.25 kgm2**
Sound pressure / power LpfA | LWA	**63 | 76 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1001, p. 2/28 (PDF 146)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1002 (IE1)

1LE1002-2AC43-4AA4

18.5 kW / 1000 rpm

Frame 200 L | 6 poles | IM B3 | Article No. 1LE1002-2AC43-4AA4

GENERAL DATA

Series / efficiency class	**1LE1002 / IE1**
Housing	**Aluminum**
Frame size	**200 L**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**149 kg**

ELECTRICAL DATA

Rated power 50 Hz	**18.5 kW (about 25 HP)**
Rated power 60 Hz	**22 kW**
Rated speed (50 Hz)	**978 rpm**
Rated torque	**181 Nm**
Rated current	**38 A**
Power factor	**0.79**
Efficiency 4/4 | 3/4 | 2/4	**88.6 | 89.8 | 89.8 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**6.3 | 2.5 | 2.6**
Moment of inertia J	**0.25 kgm2**
Sound pressure / power LpfA | LWA	**59 | 72 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (09/2023), table 1LE1002, p. 3/53**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1002 (IE1)

1LE1002-2AC43-4FA4

18.5 kW / 1000 rpm

Frame 200 L | 6 poles | IM B5 | Article No. 1LE1002-2AC43-4FA4

GENERAL DATA

Series / efficiency class	**1LE1002 / IE1**
Housing	**Aluminum**
Frame size	**200 L**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**149 kg**

ELECTRICAL DATA

Rated power 50 Hz	**18.5 kW (about 25 HP)**
Rated power 60 Hz	**22 kW**
Rated speed (50 Hz)	**978 rpm**
Rated torque	**181 Nm**
Rated current	**38 A**
Power factor	**0.79**
Efficiency 4/4 | 3/4 | 2/4	**88.6 | 89.8 | 89.8 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**6.3 | 2.5 | 2.6**
Moment of inertia J	**0.25 kgm2**
Sound pressure / power LpfA | LWA	**59 | 72 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (09/2023), table 1LE1002, p. 3/53**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1001 (IE2)

1LE1001-1EC63-4AA4

18.5 kW / 1000 rpm

Frame 180 L | 6 poles | IM B3 | Article No. 1LE1001-1EC63-4AA4

GENERAL DATA

Series / efficiency class	**1LE1001 / IE2**
Housing	**Aluminum**
Frame size	**180 L**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**130 kg**

ELECTRICAL DATA

Rated power 50 Hz	**18.5 kW (about 25 HP)**
Rated power 60 Hz	**22 kW**
Rated speed (50 Hz)	**975 rpm**
Rated torque	**181 Nm**
Rated current	**38.5 A**
Power factor	**0.77**
Efficiency 4/4 | 3/4 | 2/4	**90.4 | 90.9 | 90.5 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**6 | 2.3 | 2.9**
Moment of inertia J	**0.206 kgm2**
Sound pressure / power LpfA | LWA	**67 | 80 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1001, p. 2/31 (PDF 149)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1001 (IE2)

1LE1001-1EC63-4FA4

18.5 kW / 1000 rpm

Frame 180 L | 6 poles | IM B5 | Article No. 1LE1001-1EC63-4FA4

GENERAL DATA

Series / efficiency class	**1LE1001 / IE2**
Housing	**Aluminum**
Frame size	**180 L**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**130 kg**

ELECTRICAL DATA

Rated power 50 Hz	**18.5 kW (about 25 HP)**
Rated power 60 Hz	**22 kW**
Rated speed (50 Hz)	**975 rpm**
Rated torque	**181 Nm**
Rated current	**38.5 A**
Power factor	**0.77**
Efficiency 4/4 | 3/4 | 2/4	**90.4 | 90.9 | 90.5 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**6 | 2.3 | 2.9**
Moment of inertia J	**0.206 kgm2**
Sound pressure / power LpfA | LWA	**67 | 80 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1001, p. 2/31 (PDF 149)**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1003 (IE3)

1LE1003-2AC43-4AA4

18.5 kW / 1000 rpm

Frame 200 L | 6 poles | IM B3 | Article No. 1LE1003-2AC43-4AA4

GENERAL DATA

Series / efficiency class	**1LE1003 / IE3**
Housing	**Aluminum**
Frame size	**200 L**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**166 kg**

ELECTRICAL DATA

Rated power 50 Hz	**18.5 kW (about 25 HP)**
Rated power 60 Hz	**not listed (catalog 09/2023)**
Rated speed (50 Hz)	**978 rpm**
Rated torque	**181 Nm**
Rated current	**37 A**
Power factor	**0.79**
Efficiency 4/4 | 3/4 | 2/4	**91.7 | 92.5 | 92.4 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5.6 | 2.5 | 2.6**
Moment of inertia J	**0.28 kgm2**
Sound pressure / power LpfA | LWA	**64 | 71 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (09/2023), table 1LE1003, p. 3/15**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1003 (IE3)

1LE1003-2AC43-4FA4

18.5 kW / 1000 rpm

Frame 200 L | 6 poles | IM B5 | Article No. 1LE1003-2AC43-4FA4

GENERAL DATA

Series / efficiency class	**1LE1003 / IE3**
Housing	**Aluminum**
Frame size	**200 L**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**166 kg**

ELECTRICAL DATA

Rated power 50 Hz	**18.5 kW (about 25 HP)**
Rated power 60 Hz	**not listed (catalog 09/2023)**
Rated speed (50 Hz)	**978 rpm**
Rated torque	**181 Nm**
Rated current	**37 A**
Power factor	**0.79**
Efficiency 4/4 | 3/4 | 2/4	**91.7 | 92.5 | 92.4 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5.6 | 2.5 | 2.6**
Moment of inertia J	**0.28 kgm2**
Sound pressure / power LpfA | LWA	**64 | 71 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (09/2023), table 1LE1003, p. 3/15**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1043 (IE3)

1LE1043-2AC43-4AA4

18.5 kW / 1000 rpm

Frame 200 L | 6 poles | IM B3 | Article No. 1LE1043-2AC43-4AA4

GENERAL DATA

Series / efficiency class	**1LE1043 / IE3**
Housing	**Aluminum**
Frame size	**200 L**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**166 kg**

ELECTRICAL DATA - CATALOG VALUES AT 60 HZ (APAC LINE)

Rated power (P50 rating)	**18.5 kW (about 25 HP)**
Rated power (P60 rating)	**22 kW**
Rated speed (60 Hz)	**1180 rpm**
Rated torque (60 Hz)	**150 Nm**
Rated current (460 V, 60 Hz)	**32 A**
Power factor (60 Hz)	**0.78**
Efficiency 4/4 | 3/4 | 2/4 (60 Hz)	**93 | 93.8 | 93.8 %**
I_LR/I_N | T_LR/T_N | T_B/T_N (60 Hz)	**6.5 | 2.8 | 3**
Moment of inertia J	**0.28 kgm2**
Sound pressure / power LpfA | LWA (60 Hz)	**64 | 71 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1043, p. 2/55 (PDF 173)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
APAC Line: the catalog lists operating values at 60 Hz only; 50 Hz speed/efficiency are not listed (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1043 (IE3)

1LE1043-2AC43-4FA4

18.5 kW / 1000 rpm

Frame 200 L | 6 poles | IM B5 | Article No. 1LE1043-2AC43-4FA4

GENERAL DATA

Series / efficiency class	**1LE1043 / IE3**
Housing	**Aluminum**
Frame size	**200 L**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**166 kg**

ELECTRICAL DATA - CATALOG VALUES AT 60 HZ (APAC LINE)

Rated power (P50 rating)	**18.5 kW (about 25 HP)**
Rated power (P60 rating)	**22 kW**
Rated speed (60 Hz)	**1180 rpm**
Rated torque (60 Hz)	**150 Nm**
Rated current (460 V, 60 Hz)	**32 A**
Power factor (60 Hz)	**0.78**
Efficiency 4/4 | 3/4 | 2/4 (60 Hz)	**93 | 93.8 | 93.8 %**
I_LR/I_N | T_LR/T_N | T_B/T_N (60 Hz)	**6.5 | 2.8 | 3**
Moment of inertia J	**0.28 kgm2**
Sound pressure / power LpfA | LWA (60 Hz)	**64 | 71 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1043, p. 2/55 (PDF 173)**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
APAC Line: the catalog lists operating values at 60 Hz only; 50 Hz speed/efficiency are not listed (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1003 (IE3)

1LE1003-1EC63-4AA4

18.5 kW / 1000 rpm

Frame 180 L | 6 poles | IM B3 | Article No. 1LE1003-1EC63-4AA4

GENERAL DATA

Series / efficiency class	**1LE1003 / IE3**
Housing	**Aluminum**
Frame size	**180 L**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**148 kg**

ELECTRICAL DATA

Rated power 50 Hz	**18.5 kW (about 25 HP)**
Rated power 60 Hz	**not listed (catalog 09/2023)**
Rated speed (50 Hz)	**975 rpm**
Rated torque	**181 Nm**
Rated current	**38 A**
Power factor	**0.77**
Efficiency 4/4 | 3/4 | 2/4	**91.7 | 92.3 | 91.9 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**6.9 | 2.6 | 3.3**
Moment of inertia J	**0.247 kgm2**
Sound pressure / power LpfA | LWA	**68 | 80 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (09/2023), table 1LE1003, p. 3/17**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1003 (IE3)

1LE1003-1EC63-4FA4

18.5 kW / 1000 rpm

Frame 180 L | 6 poles | IM B5 | Article No. 1LE1003-1EC63-4FA4

GENERAL DATA

Series / efficiency class	**1LE1003 / IE3**
Housing	**Aluminum**
Frame size	**180 L**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**148 kg**

ELECTRICAL DATA

Rated power 50 Hz	**18.5 kW (about 25 HP)**
Rated power 60 Hz	**not listed (catalog 09/2023)**
Rated speed (50 Hz)	**975 rpm**
Rated torque	**181 Nm**
Rated current	**38 A**
Power factor	**0.77**
Efficiency 4/4 | 3/4 | 2/4	**91.7 | 92.3 | 91.9 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**6.9 | 2.6 | 3.3**
Moment of inertia J	**0.247 kgm2**
Sound pressure / power LpfA | LWA	**68 | 80 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (09/2023), table 1LE1003, p. 3/17**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0102 (IE1)

1LE0102-2AC43-4AA4

18.5 kW / 1000 rpm

Frame 200 L | 6 poles | IM B3 | Article No. 1LE0102-2AC43-4AA4

GENERAL DATA

Series / efficiency class	**1LE0102 / IE1**
Housing	**Cast iron**
Frame size	**200 L**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**218 kg**

ELECTRICAL DATA

Rated power 50 Hz	**18.5 kW (about 25 HP)**
Rated power 60 Hz	**22 kW**
Rated speed (50 Hz)	**975 rpm**
Rated torque	**182.1 Nm**
Rated current	**36.5 A**
Power factor	**0.82**
Efficiency 4/4 | 3/4 | 2/4	**88.6 | 90 | 90.1 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5.8 | 2.2 | 2.8**
Moment of inertia J	**0.26 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0102, p. 22 (PDF 22)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0102 (IE1)

1LE0102-2AC43-4FA4

18.5 kW / 1000 rpm

Frame 200 L | 6 poles | IM B5 | Article No. 1LE0102-2AC43-4FA4

GENERAL DATA

Series / efficiency class	**1LE0102 / IE1**
Housing	**Cast iron**
Frame size	**200 L**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**218 kg**

ELECTRICAL DATA

Rated power 50 Hz	**18.5 kW (about 25 HP)**
Rated power 60 Hz	**22 kW**
Rated speed (50 Hz)	**975 rpm**
Rated torque	**182.1 Nm**
Rated current	**36.5 A**
Power factor	**0.82**
Efficiency 4/4 | 3/4 | 2/4	**88.6 | 90 | 90.1 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5.8 | 2.2 | 2.8**
Moment of inertia J	**0.26 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0102, p. 22 (PDF 22)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0102 (IE1)

1LE0102-2AC44-1AA4

18.5 kW / 1000 rpm

Frame 200 L | 6 poles | IM B3 | Article No. 1LE0102-2AC44-1AA4

GENERAL DATA

Series / efficiency class	**1LE0102 / IE1**
Housing	**Cast iron**
Frame size	**200 L**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**525 V D**
Net weight (IM B3)	**218 kg**

ELECTRICAL DATA

Rated power 50 Hz	**18.5 kW (about 25 HP)**
Rated power 60 Hz	**22 kW**
Rated speed (50 Hz)	**975 rpm**
Rated torque	**182.1 Nm**
Rated current	**28 A**
Power factor	**0.82**
Efficiency 4/4 | 3/4 | 2/4	**88.6 | 90 | 90.1 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5.8 | 2.2 | 2.8**
Moment of inertia J	**0.26 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0102, p. 27 (PDF 27)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0102 (IE1)

1LE0102-2AC44-1FA4

18.5 kW / 1000 rpm

Frame 200 L | 6 poles | IM B5 | Article No. 1LE0102-2AC44-1FA4

GENERAL DATA

Series / efficiency class	**1LE0102 / IE1**
Housing	**Cast iron**
Frame size	**200 L**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**525 V D**
Net weight (IM B3)	**218 kg**

ELECTRICAL DATA

Rated power 50 Hz	**18.5 kW (about 25 HP)**
Rated power 60 Hz	**22 kW**
Rated speed (50 Hz)	**975 rpm**
Rated torque	**182.1 Nm**
Rated current	**28 A**
Power factor	**0.82**
Efficiency 4/4 | 3/4 | 2/4	**88.6 | 90 | 90.1 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5.8 | 2.2 | 2.8**
Moment of inertia J	**0.26 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0102, p. 27 (PDF 27)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1501 (IE2)

1LE1501-2AC43-4AA4

18.5 kW / 1000 rpm

Frame 200 L | 6 poles | IM B3 | Article No. 1LE1501-2AC43-4AA4

GENERAL DATA

Series / efficiency class	**1LE1501 / IE2**
Housing	**Cast iron**
Frame size	**200 L**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**200 kg**

ELECTRICAL DATA

Rated power 50 Hz	**18.5 kW (about 25 HP)**
Rated power 60 Hz	**22 kW**
Rated speed (50 Hz)	**978 rpm**
Rated torque	**181 Nm**
Rated current	**36 A**
Power factor	**0.82**
Efficiency 4/4 | 3/4 | 2/4	**90.4 | 91.4 | 91.3 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5.8 | 2.4 | 2.6**
Moment of inertia J	**0.25 kgm2**
Sound pressure / power LpfA | LWA	**63 | 76 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1501, p. 2/34 (PDF 152)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1501 (IE2)

1LE1501-2AC43-4FA4

18.5 kW / 1000 rpm

Frame 200 L | 6 poles | IM B5 | Article No. 1LE1501-2AC43-4FA4

GENERAL DATA

Series / efficiency class	**1LE1501 / IE2**
Housing	**Cast iron**
Frame size	**200 L**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**200 kg**

ELECTRICAL DATA

Rated power 50 Hz	**18.5 kW (about 25 HP)**
Rated power 60 Hz	**22 kW**
Rated speed (50 Hz)	**978 rpm**
Rated torque	**181 Nm**
Rated current	**36 A**
Power factor	**0.82**
Efficiency 4/4 | 3/4 | 2/4	**90.4 | 91.4 | 91.3 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5.8 | 2.4 | 2.6**
Moment of inertia J	**0.25 kgm2**
Sound pressure / power LpfA | LWA	**63 | 76 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1501, p. 2/34 (PDF 152)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1502 (IE1)

1LE1502-2AC43-4FA4

18.5 kW / 1000 rpm

Frame 200 L | 6 poles | IM B5 | Article No. 1LE1502-2AC43-4FA4

GENERAL DATA

Series / efficiency class	**1LE1502 / IE1**
Housing	**Cast iron**
Frame size	**200 L**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**200 kg**

ELECTRICAL DATA

Rated power 50 Hz	**18.5 kW (about 25 HP)**
Rated power 60 Hz	**22 kW**
Rated speed (50 Hz)	**978 rpm**
Rated torque	**181 Nm**
Rated current	**38 A**
Power factor	**0.79**
Efficiency 4/4 | 3/4 | 2/4	**88.6 | 89.8 | 89.8 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**6.3 | 2.5 | 2.6**
Moment of inertia J	**0.25 kgm2**
Sound pressure / power LpfA | LWA	**59 | 72 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1502, p. 2/50 (PDF 168)**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1502 (IE1)

1LE1502-1EC63-4AA4

18.5 kW / 1000 rpm

Frame 180 L | 6 poles | IM B3 | Article No. 1LE1502-1EC63-4AA4

GENERAL DATA

Series / efficiency class	**1LE1502 / IE1**
Housing	**Cast iron**
Frame size	**180 L**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**165 kg**

ELECTRICAL DATA

Rated power 50 Hz	**18.5 kW (about 25 HP)**
Rated power 60 Hz	**22 kW**
Rated speed (50 Hz)	**970 rpm**
Rated torque	**182 Nm**
Rated current	**39 A**
Power factor	**0.77**
Efficiency 4/4 | 3/4 | 2/4	**88.6 | 89.4 | 89.1 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5.9 | 2.2 | 2.9**
Moment of inertia J	**0.206 kgm2**
Sound pressure / power LpfA | LWA	**56 | 69 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1502, p. 2/53 (PDF 171)**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1502 (IE1)

1LE1502-1EC63-4FA4

18.5 kW / 1000 rpm

Frame 180 L | 6 poles | IM B5 | Article No. 1LE1502-1EC63-4FA4

GENERAL DATA

Series / efficiency class	**1LE1502 / IE1**
Housing	**Cast iron**
Frame size	**180 L**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**165 kg**

ELECTRICAL DATA

Rated power 50 Hz	**18.5 kW (about 25 HP)**
Rated power 60 Hz	**22 kW**
Rated speed (50 Hz)	**970 rpm**
Rated torque	**182 Nm**
Rated current	**39 A**
Power factor	**0.77**
Efficiency 4/4 | 3/4 | 2/4	**88.6 | 89.4 | 89.1 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5.9 | 2.2 | 2.9**
Moment of inertia J	**0.206 kgm2**
Sound pressure / power LpfA | LWA	**56 | 69 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1502, p. 2/53 (PDF 171)**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1541 (IE2)

1LE1541-2AC43-4FA4

18.5 kW / 1000 rpm

Frame 200 L | 6 poles | IM B5 | Article No. 1LE1541-2AC43-4FA4

GENERAL DATA

Series / efficiency class	**1LE1541 / IE2**
Housing	**Cast iron**
Frame size	**200 L**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**200 kg**

ELECTRICAL DATA - CATALOG VALUES AT 60 HZ (APAC LINE)

Rated power (P50 rating)	**18.5 kW (about 25 HP)**
Rated power (P60 rating)	**22 kW**
Rated speed (60 Hz)	**1182 rpm**
Rated torque (60 Hz)	**149 Nm**
Rated current (460 V, 60 Hz)	**31.5 A**
Power factor (60 Hz)	**0.81**
Efficiency 4/4 | 3/4 | 2/4 (60 Hz)	**91.7 | 92 | 91.5 %**
I_LR/I_N | T_LR/T_N | T_B/T_N (60 Hz)	**6.7 | 2.6 | 3**
Moment of inertia J	**0.25 kgm2**
Sound pressure / power LpfA | LWA (60 Hz)	**66 | 79 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1541, p. 2/69 (PDF 187)**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
APAC Line: the catalog lists operating values at 60 Hz only; 50 Hz speed/efficiency are not listed (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0101 (IE2)

1LE0101-2AC43-4AB4

18.5 kW / 1000 rpm

Frame 200 L | 6 poles | IM B3 | Article No. 1LE0101-2AC43-4AB4

GENERAL DATA

Series / efficiency class	**1LE0101 / IE2**
Housing	**Cast iron**
Frame size	**200 L**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**220 kg**

ELECTRICAL DATA

Rated power 50 Hz	**18.5 kW (about 25 HP)**
Rated power 60 Hz	**22 kW**
Rated speed (50 Hz)	**975 rpm**
Rated torque	**181 Nm**
Rated current	**36.5 A**
Power factor	**0.81**
Efficiency 4/4 | 3/4 | 2/4	**90.4 | 91 | 91.8 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5.8 | 2.2 | 2.8**
Moment of inertia J	**0.27 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0101, p. 25 (PDF 25)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0101 (IE2)

1LE0101-2AC43-4FB4

18.5 kW / 1000 rpm

Frame 200 L | 6 poles | IM B5 | Article No. 1LE0101-2AC43-4FB4

GENERAL DATA

Series / efficiency class	**1LE0101 / IE2**
Housing	**Cast iron**
Frame size	**200 L**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**220 kg**

ELECTRICAL DATA

Rated power 50 Hz	**18.5 kW (about 25 HP)**
Rated power 60 Hz	**22 kW**
Rated speed (50 Hz)	**975 rpm**
Rated torque	**181 Nm**
Rated current	**36.5 A**
Power factor	**0.81**
Efficiency 4/4 | 3/4 | 2/4	**90.4 | 91 | 91.8 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5.8 | 2.2 | 2.8**
Moment of inertia J	**0.27 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0101, p. 25 (PDF 25)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0101 (IE2)

1LE0101-2AC44-1AB4

18.5 kW / 1000 rpm

Frame 200 L | 6 poles | IM B3 | Article No. 1LE0101-2AC44-1AB4

GENERAL DATA

Series / efficiency class	**1LE0101 / IE2**
Housing	**Cast iron**
Frame size	**200 L**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**525 V D**
Net weight (IM B3)	**220 kg**

ELECTRICAL DATA

Rated power 50 Hz	**18.5 kW (about 25 HP)**
Rated power 60 Hz	**22 kW**
Rated speed (50 Hz)	**975 rpm**
Rated torque	**181 Nm**
Rated current	**28 A**
Power factor	**0.81**
Efficiency 4/4 | 3/4 | 2/4	**90.4 | 91 | 91.8 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5.8 | 2.2 | 2.8**
Moment of inertia J	**0.27 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0101, p. 29 (PDF 29)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0101 (IE2)

1LE0101-2AC44-1FB4

18.5 kW / 1000 rpm

Frame 200 L | 6 poles | IM B5 | Article No. 1LE0101-2AC44-1FB4

GENERAL DATA

Series / efficiency class	**1LE0101 / IE2**
Housing	**Cast iron**
Frame size	**200 L**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**525 V D**
Net weight (IM B3)	**220 kg**

ELECTRICAL DATA

Rated power 50 Hz	**18.5 kW (about 25 HP)**
Rated power 60 Hz	**22 kW**
Rated speed (50 Hz)	**975 rpm**
Rated torque	**181 Nm**
Rated current	**28 A**
Power factor	**0.81**
Efficiency 4/4 | 3/4 | 2/4	**90.4 | 91 | 91.8 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5.8 | 2.2 | 2.8**
Moment of inertia J	**0.27 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0101, p. 29 (PDF 29)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1501 (IE2)

1LE1501-1EC63-4AA4

18.5 kW / 1000 rpm

Frame 180 L | 6 poles | IM B3 | Article No. 1LE1501-1EC63-4AA4

GENERAL DATA

Series / efficiency class	**1LE1501 / IE2**
Housing	**Cast iron**
Frame size	**180 L**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**165 kg**

ELECTRICAL DATA

Rated power 50 Hz	**18.5 kW (about 25 HP)**
Rated power 60 Hz	**22 kW**
Rated speed (50 Hz)	**975 rpm**
Rated torque	**181 Nm**
Rated current	**38.5 A**
Power factor	**0.77**
Efficiency 4/4 | 3/4 | 2/4	**90.4 | 90.9 | 90.5 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**6 | 2.3 | 2.9**
Moment of inertia J	**0.206 kgm2**
Sound pressure / power LpfA | LWA	**67 | 80 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1501, p. 2/41 (PDF 159)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1501 (IE2)

1LE1501-1EC63-4FA4

18.5 kW / 1000 rpm

Frame 180 L | 6 poles | IM B5 | Article No. 1LE1501-1EC63-4FA4

GENERAL DATA

Series / efficiency class	**1LE1501 / IE2**
Housing	**Cast iron**
Frame size	**180 L**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**165 kg**

ELECTRICAL DATA

Rated power 50 Hz	**18.5 kW (about 25 HP)**
Rated power 60 Hz	**22 kW**
Rated speed (50 Hz)	**975 rpm**
Rated torque	**181 Nm**
Rated current	**38.5 A**
Power factor	**0.77**
Efficiency 4/4 | 3/4 | 2/4	**90.4 | 90.9 | 90.5 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**6 | 2.3 | 2.9**
Moment of inertia J	**0.206 kgm2**
Sound pressure / power LpfA | LWA	**67 | 80 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1501, p. 2/41 (PDF 159)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1503 (IE3)

1LE1503-2AC43-4AA4

18.5 kW / 1000 rpm

Frame 200 L | 6 poles | IM B3 | Article No. 1LE1503-2AC43-4AA4

GENERAL DATA

Series / efficiency class	**1LE1503 / IE3**
Housing	**Cast iron**
Frame size	**200 L**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**215 kg**

ELECTRICAL DATA

Rated power 50 Hz	**18.5 kW (about 25 HP)**
Rated power 60 Hz	**not listed (catalog 09/2023)**
Rated speed (50 Hz)	**978 rpm**
Rated torque	**181 Nm**
Rated current	**37 A**
Power factor	**0.79**
Efficiency 4/4 | 3/4 | 2/4	**91.7 | 92.5 | 92.4 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5.6 | 2.5 | 2.6**
Moment of inertia J	**0.28 kgm2**
Sound pressure / power LpfA | LWA	**64 | 71 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (09/2023), table 1LE1503, p. 3/21**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1503 (IE3)

1LE1503-2AC43-4FA4

18.5 kW / 1000 rpm

Frame 200 L | 6 poles | IM B5 | Article No. 1LE1503-2AC43-4FA4

GENERAL DATA

Series / efficiency class	**1LE1503 / IE3**
Housing	**Cast iron**
Frame size	**200 L**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**215 kg**

ELECTRICAL DATA

Rated power 50 Hz	**18.5 kW (about 25 HP)**
Rated power 60 Hz	**not listed (catalog 09/2023)**
Rated speed (50 Hz)	**978 rpm**
Rated torque	**181 Nm**
Rated current	**37 A**
Power factor	**0.79**
Efficiency 4/4 | 3/4 | 2/4	**91.7 | 92.5 | 92.4 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5.6 | 2.5 | 2.6**
Moment of inertia J	**0.28 kgm2**
Sound pressure / power LpfA | LWA	**64 | 71 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (09/2023), table 1LE1503, p. 3/21**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1541 (IE2)

1LE1541-1EC63-4FA4

18.5 kW / 1000 rpm

Frame 180 L | 6 poles | IM B5 | Article No. 1LE1541-1EC63-4FA4

GENERAL DATA

Series / efficiency class	**1LE1541 / IE2**
Housing	**Cast iron**
Frame size	**180 L**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**165 kg**

ELECTRICAL DATA - CATALOG VALUES AT 60 HZ (APAC LINE)

Rated power (P50 rating)	**18.5 kW (about 25 HP)**
Rated power (P60 rating)	**22 kW**
Rated speed (60 Hz)	**1180 rpm**
Rated torque (60 Hz)	**150 Nm**
Rated current (460 V, 60 Hz)	**34 A**
Power factor (60 Hz)	**0.75**
Efficiency 4/4 | 3/4 | 2/4 (60 Hz)	**91.7 | 91.8 | 90.9 %**
I_LR/I_N | T_LR/T_N | T_B/T_N (60 Hz)	**7 | 2.6 | 3.4**
Moment of inertia J	**0.206 kgm2**
Sound pressure / power LpfA | LWA (60 Hz)	**70 | 83 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1541, p. 2/70 (PDF 188)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
APAC Line: the catalog lists operating values at 60 Hz only; 50 Hz speed/efficiency are not listed (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1543 (IE3)

1LE1543-2AC43-4AA4

18.5 kW / 1000 rpm

Frame 200 L | 6 poles | IM B3 | Article No. 1LE1543-2AC43-4AA4

GENERAL DATA

Series / efficiency class	**1LE1543 / IE3**
Housing	**Cast iron**
Frame size	**200 L**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**215 kg**

ELECTRICAL DATA - CATALOG VALUES AT 60 HZ (APAC LINE)

Rated power (P50 rating)	**18.5 kW (about 25 HP)**
Rated power (P60 rating)	**22 kW**
Rated speed (60 Hz)	**1180 rpm**
Rated torque (60 Hz)	**150 Nm**
Rated current (460 V, 60 Hz)	**32 A**
Power factor (60 Hz)	**0.78**
Efficiency 4/4 | 3/4 | 2/4 (60 Hz)	**93 | 93.8 | 93.8 %**
I_LR/I_N | T_LR/T_N | T_B/T_N (60 Hz)	**6.5 | 2.8 | 3**
Moment of inertia J	**0.28 kgm2**
Sound pressure / power LpfA | LWA (60 Hz)	**64 | 71 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1543, p. 2/59 (PDF 177)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
APAC Line: the catalog lists operating values at 60 Hz only; 50 Hz speed/efficiency are not listed (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1543 (IE3)

1LE1543-2AC43-4FA4

18.5 kW / 1000 rpm

Frame 200 L | 6 poles | IM B5 | Article No. 1LE1543-2AC43-4FA4

GENERAL DATA

Series / efficiency class	**1LE1543 / IE3**
Housing	**Cast iron**
Frame size	**200 L**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**215 kg**

ELECTRICAL DATA - CATALOG VALUES AT 60 HZ (APAC LINE)

Rated power (P50 rating)	**18.5 kW (about 25 HP)**
Rated power (P60 rating)	**22 kW**
Rated speed (60 Hz)	**1180 rpm**
Rated torque (60 Hz)	**150 Nm**
Rated current (460 V, 60 Hz)	**32 A**
Power factor (60 Hz)	**0.78**
Efficiency 4/4 | 3/4 | 2/4 (60 Hz)	**93 | 93.8 | 93.8 %**
I_LR/I_N | T_LR/T_N | T_B/T_N (60 Hz)	**6.5 | 2.8 | 3**
Moment of inertia J	**0.28 kgm2**
Sound pressure / power LpfA | LWA (60 Hz)	**64 | 71 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1543, p. 2/59 (PDF 177)**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
APAC Line: the catalog lists operating values at 60 Hz only; 50 Hz speed/efficiency are not listed (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1503 (IE3)

1LE1503-1EC63-4AA4

18.5 kW / 1000 rpm

Frame 180 L | 6 poles | IM B3 | Article No. 1LE1503-1EC63-4AA4

GENERAL DATA

Series / efficiency class	**1LE1503 / IE3**
Housing	**Cast iron**
Frame size	**180 L**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**185 kg**

ELECTRICAL DATA

Rated power 50 Hz	**18.5 kW (about 25 HP)**
Rated power 60 Hz	**not listed (catalog 09/2023)**
Rated speed (50 Hz)	**975 rpm**
Rated torque	**181 Nm**
Rated current	**38 A**
Power factor	**0.77**
Efficiency 4/4 | 3/4 | 2/4	**91.7 | 92.3 | 91.9 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**6.9 | 2.6 | 3.3**
Moment of inertia J	**0.247 kgm2**
Sound pressure / power LpfA | LWA	**68 | 80 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (09/2023), table 1LE1503, p. 3/28**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1503 (IE3)

1LE1503-1EC63-4FA4

18.5 kW / 1000 rpm

Frame 180 L | 6 poles | IM B5 | Article No. 1LE1503-1EC63-4FA4

GENERAL DATA

Series / efficiency class	**1LE1503 / IE3**
Housing	**Cast iron**
Frame size	**180 L**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**185 kg**

ELECTRICAL DATA

Rated power 50 Hz	**18.5 kW (about 25 HP)**
Rated power 60 Hz	**not listed (catalog 09/2023)**
Rated speed (50 Hz)	**975 rpm**
Rated torque	**181 Nm**
Rated current	**38 A**
Power factor	**0.77**
Efficiency 4/4 | 3/4 | 2/4	**91.7 | 92.3 | 91.9 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**6.9 | 2.6 | 3.3**
Moment of inertia J	**0.247 kgm2**
Sound pressure / power LpfA | LWA	**68 | 80 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (09/2023), table 1LE1503, p. 3/28**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1543 (IE3)

1LE1543-1EC63-4AA4

18.5 kW / 1000 rpm

Frame 180 L | 6 poles | IM B3 | Article No. 1LE1543-1EC63-4AA4

GENERAL DATA

Series / efficiency class	**1LE1543 / IE3**
Housing	**Cast iron**
Frame size	**180 L**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**185 kg**

ELECTRICAL DATA - CATALOG VALUES AT 60 HZ (APAC LINE)

Rated power (P50 rating)	**18.5 kW (about 25 HP)**
Rated power (P60 rating)	**22 kW**
Rated speed (60 Hz)	**1180 rpm**
Rated torque (60 Hz)	**150 Nm**
Rated current (460 V, 60 Hz)	**33.5 A**
Power factor (60 Hz)	**0.75**
Efficiency 4/4 | 3/4 | 2/4 (60 Hz)	**93 | 93.2 | 92.6 %**
I_LR/I_N | T_LR/T_N | T_B/T_N (60 Hz)	**7.9 | 2.9 | 3.7**
Moment of inertia J	**0.247 kgm2**
Sound pressure / power LpfA | LWA (60 Hz)	**69 | 81 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1543, p. 2/63 (PDF 181)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
APAC Line: the catalog lists operating values at 60 Hz only; 50 Hz speed/efficiency are not listed (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1543 (IE3)

1LE1543-1EC63-4FA4

18.5 kW / 1000 rpm

Frame 180 L | 6 poles | IM B5 | Article No. 1LE1543-1EC63-4FA4

GENERAL DATA

Series / efficiency class	**1LE1543 / IE3**
Housing	**Cast iron**
Frame size	**180 L**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**185 kg**

ELECTRICAL DATA - CATALOG VALUES AT 60 HZ (APAC LINE)

Rated power (P50 rating)	**18.5 kW (about 25 HP)**
Rated power (P60 rating)	**22 kW**
Rated speed (60 Hz)	**1180 rpm**
Rated torque (60 Hz)	**150 Nm**
Rated current (460 V, 60 Hz)	**33.5 A**
Power factor (60 Hz)	**0.75**
Efficiency 4/4 | 3/4 | 2/4 (60 Hz)	**93 | 93.2 | 92.6 %**
I_LR/I_N | T_LR/T_N | T_B/T_N (60 Hz)	**7.9 | 2.9 | 3.7**
Moment of inertia J	**0.247 kgm2**
Sound pressure / power LpfA | LWA (60 Hz)	**69 | 81 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1543, p. 2/63 (PDF 181)**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
APAC Line: the catalog lists operating values at 60 Hz only; 50 Hz speed/efficiency are not listed (see Siemens DT Configurator).