Data sheets - Siemens SIMOTICS GP motors

2.2 kW / 1000 rpm - 53 article numbers in this file

Article No.	Page
1LE1001-1AC62-2AA4	2
1LE1001-1AC62-2FA4	3
1LE1001-1AC62-2KA4	4
1LE1002-1BC22-2FA4	5
1LE1002-1BC22-2KA4	6
1LE1002-1AC62-2AA4	7
1LE1002-1AC62-2FA4	8
1LE1002-1AC62-2KA4	9
1LE1001-1BC22-2AA4	10
1LE1001-1BC22-2FA4	11
1LE1001-1BC22-2KA4	12
1LE1003-1BC22-2AA4	13
1LE1003-1BC22-2FA4	14
1LE1003-1BC22-2KA4	15
1LE1041-1BC22-2FA4	16
1LE1041-1BC22-2KA4	17
1LE1043-1CC13-4AA4	18
1LE1043-1CC13-4FA4	19
1LE1043-1CC13-4KA4	20
1LE0102-1BC22-2AA4	21
1LE0102-1BC22-2FA4	22
1LE0102-1BC22-2KA4	23
1LE0102-1BC23-4AA4	24
1LE0102-1BC23-4FA4	25
1LE0102-1BC23-4KA4	26
1LE0102-1BC24-1AA4	27
1LE0102-1BC24-1FA4	28
1LE0102-1BC24-1KA4	29
1LE1501-1AC62-2AA4	30
1LE1501-1AC62-2FA4	31
1LE1501-1AC62-2KA4	32
1LE1502-1BC22-2AA4	33
1LE1502-1BC22-2FA4	34
1LE1502-1BC22-2KA4	35
1LE1502-1AC62-2AA4	36
1LE1502-1AC62-2FA4	37
1LE1502-1AC62-2KA4	38
1LE0101-1BC22-2AA4	39
1LE0101-1BC22-2FA4	40
1LE0101-1BC22-2KA4	41
1LE0101-1BC23-4AA4	42
1LE0101-1BC23-4FA4	43
1LE0101-1BC23-4KA4	44
1LE0101-1BC24-1AA4	45
1LE0101-1BC24-1FA4	46
1LE0101-1BC24-1KA4	47
1LE1501-1BC22-2AA4	48
1LE1501-1BC22-2FA4	49
1LE1501-1BC22-2KA4	50
1LE1503-1BC22-2AA4	51
1LE1503-1BC22-2FA4	52
1LE1543-1CC13-4AA4	53
1LE1543-1CC13-4FA4	54

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1001 (IE2)

1LE1001-1AC62-2AA4

2.2 kW / 1000 rpm

Frame 100 L | 6 poles | IM B3 | Article No. 1LE1001-1AC62-2AA4

GENERAL DATA

Series / efficiency class	**1LE1001 / IE2**
Housing	**Aluminum**
Frame size	**100 L**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**30 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**2.55 kW**
Rated speed (50 Hz)	**965 rpm**
Rated torque	**22 Nm**
Rated current	**5.1 A**
Power factor	**0.76**
Efficiency 4/4 | 3/4 | 2/4	**81.8 | 83.3 | 82.7 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**4.9 | 1.7 | 2.5**
Moment of inertia J	**0.014 kgm2**
Sound pressure / power LpfA | LWA	**59 | 71 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1001, p. 2/31 (PDF 149)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1001 (IE2)

1LE1001-1AC62-2FA4

2.2 kW / 1000 rpm

Frame 100 L | 6 poles | IM B5 | Article No. 1LE1001-1AC62-2FA4

GENERAL DATA

Series / efficiency class	**1LE1001 / IE2**
Housing	**Aluminum**
Frame size	**100 L**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**30 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**2.55 kW**
Rated speed (50 Hz)	**965 rpm**
Rated torque	**22 Nm**
Rated current	**5.1 A**
Power factor	**0.76**
Efficiency 4/4 | 3/4 | 2/4	**81.8 | 83.3 | 82.7 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**4.9 | 1.7 | 2.5**
Moment of inertia J	**0.014 kgm2**
Sound pressure / power LpfA | LWA	**59 | 71 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1001, p. 2/31 (PDF 149)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1001 (IE2)

1LE1001-1AC62-2KA4

2.2 kW / 1000 rpm

Frame 100 L | 6 poles | IM B14 | Article No. 1LE1001-1AC62-2KA4

GENERAL DATA

Series / efficiency class	**1LE1001 / IE2**
Housing	**Aluminum**
Frame size	**100 L**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**30 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**2.55 kW**
Rated speed (50 Hz)	**965 rpm**
Rated torque	**22 Nm**
Rated current	**5.1 A**
Power factor	**0.76**
Efficiency 4/4 | 3/4 | 2/4	**81.8 | 83.3 | 82.7 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**4.9 | 1.7 | 2.5**
Moment of inertia J	**0.014 kgm2**
Sound pressure / power LpfA | LWA	**59 | 71 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1001, p. 2/31 (PDF 149)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1002 (IE1)

1LE1002-1BC22-2FA4

2.2 kW / 1000 rpm

Frame 112 M | 6 poles | IM B5 | Article No. 1LE1002-1BC22-2FA4

GENERAL DATA

Series / efficiency class	**1LE1002 / IE1**
Housing	**Aluminum**
Frame size	**112 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**25 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**2.55 kW**
Rated speed (50 Hz)	**940 rpm**
Rated torque	**22 Nm**
Rated current	**5.7 A**
Power factor	**0.72**
Efficiency 4/4 | 3/4 | 2/4	**77.7 | 78.5 | 76.3 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**4.6 | 2.6 | 2.7**
Moment of inertia J	**0.0092 kgm2**
Sound pressure / power LpfA | LWA	**57 | 69 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1002, p. 2/46 (PDF 164)**
Catalog 2	**Brochure 07/2014 (14050629), p. 18 (PDF 18)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1002 (IE1)

1LE1002-1BC22-2KA4

2.2 kW / 1000 rpm

Frame 112 M | 6 poles | IM B14 | Article No. 1LE1002-1BC22-2KA4

GENERAL DATA

Series / efficiency class	**1LE1002 / IE1**
Housing	**Aluminum**
Frame size	**112 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**25 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**2.55 kW**
Rated speed (50 Hz)	**940 rpm**
Rated torque	**22 Nm**
Rated current	**5.7 A**
Power factor	**0.72**
Efficiency 4/4 | 3/4 | 2/4	**77.7 | 78.5 | 76.3 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**4.6 | 2.6 | 2.7**
Moment of inertia J	**0.0092 kgm2**
Sound pressure / power LpfA | LWA	**57 | 69 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1002, p. 2/46 (PDF 164)**
Catalog 2	**Brochure 07/2014 (14050629), p. 18 (PDF 18)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1002 (IE1)

1LE1002-1AC62-2AA4

2.2 kW / 1000 rpm

Frame 100 L | 6 poles | IM B3 | Article No. 1LE1002-1AC62-2AA4

GENERAL DATA

Series / efficiency class	**1LE1002 / IE1**
Housing	**Aluminum**
Frame size	**100 L**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**24 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**2.55 kW**
Rated speed (50 Hz)	**930 rpm**
Rated torque	**23 Nm**
Rated current	**5.2 A**
Power factor	**0.78**
Efficiency 4/4 | 3/4 | 2/4	**77.7 | 79.5 | 78.1 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**4 | 2 | 2.2**
Moment of inertia J	**0.0084 kgm2**
Sound pressure / power LpfA | LWA	**59 | 71 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1002, p. 2/47 (PDF 165)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1002 (IE1)

1LE1002-1AC62-2FA4

2.2 kW / 1000 rpm

Frame 100 L | 6 poles | IM B5 | Article No. 1LE1002-1AC62-2FA4

GENERAL DATA

Series / efficiency class	**1LE1002 / IE1**
Housing	**Aluminum**
Frame size	**100 L**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**24 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**2.55 kW**
Rated speed (50 Hz)	**930 rpm**
Rated torque	**23 Nm**
Rated current	**5.2 A**
Power factor	**0.78**
Efficiency 4/4 | 3/4 | 2/4	**77.7 | 79.5 | 78.1 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**4 | 2 | 2.2**
Moment of inertia J	**0.0084 kgm2**
Sound pressure / power LpfA | LWA	**59 | 71 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1002, p. 2/47 (PDF 165)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1002 (IE1)

1LE1002-1AC62-2KA4

2.2 kW / 1000 rpm

Frame 100 L | 6 poles | IM B14 | Article No. 1LE1002-1AC62-2KA4

GENERAL DATA

Series / efficiency class	**1LE1002 / IE1**
Housing	**Aluminum**
Frame size	**100 L**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**24 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**2.55 kW**
Rated speed (50 Hz)	**930 rpm**
Rated torque	**23 Nm**
Rated current	**5.2 A**
Power factor	**0.78**
Efficiency 4/4 | 3/4 | 2/4	**77.7 | 79.5 | 78.1 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**4 | 2 | 2.2**
Moment of inertia J	**0.0084 kgm2**
Sound pressure / power LpfA | LWA	**59 | 71 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1002, p. 2/47 (PDF 165)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1001 (IE2)

1LE1001-1BC22-2AA4

2.2 kW / 1000 rpm

Frame 112 M | 6 poles | IM B3 | Article No. 1LE1001-1BC22-2AA4

GENERAL DATA

Series / efficiency class	**1LE1001 / IE2**
Housing	**Aluminum**
Frame size	**112 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**29 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**2.55 kW**
Rated speed (50 Hz)	**965 rpm**
Rated torque	**22 Nm**
Rated current	**5.2 A**
Power factor	**0.75**
Efficiency 4/4 | 3/4 | 2/4	**81.8 | 82.7 | 81.7 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5 | 2 | 2.8**
Moment of inertia J	**0.014 kgm2**
Sound pressure / power LpfA | LWA	**62 | 74 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1001, p. 2/28 (PDF 146)**
Catalog 2	**Brochure 07/2014 (14050629), p. 19 (PDF 19)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1001 (IE2)

1LE1001-1BC22-2FA4

2.2 kW / 1000 rpm

Frame 112 M | 6 poles | IM B5 | Article No. 1LE1001-1BC22-2FA4

GENERAL DATA

Series / efficiency class	**1LE1001 / IE2**
Housing	**Aluminum**
Frame size	**112 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**29 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**2.55 kW**
Rated speed (50 Hz)	**965 rpm**
Rated torque	**22 Nm**
Rated current	**5.2 A**
Power factor	**0.75**
Efficiency 4/4 | 3/4 | 2/4	**81.8 | 82.7 | 81.7 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5 | 2 | 2.8**
Moment of inertia J	**0.014 kgm2**
Sound pressure / power LpfA | LWA	**62 | 74 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1001, p. 2/28 (PDF 146)**
Catalog 2	**Brochure 07/2014 (14050629), p. 19 (PDF 19)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1001 (IE2)

1LE1001-1BC22-2KA4

2.2 kW / 1000 rpm

Frame 112 M | 6 poles | IM B14 | Article No. 1LE1001-1BC22-2KA4

GENERAL DATA

Series / efficiency class	**1LE1001 / IE2**
Housing	**Aluminum**
Frame size	**112 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**29 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**2.55 kW**
Rated speed (50 Hz)	**965 rpm**
Rated torque	**22 Nm**
Rated current	**5.2 A**
Power factor	**0.75**
Efficiency 4/4 | 3/4 | 2/4	**81.8 | 82.7 | 81.7 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5 | 2 | 2.8**
Moment of inertia J	**0.014 kgm2**
Sound pressure / power LpfA | LWA	**62 | 74 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1001, p. 2/28 (PDF 146)**
Catalog 2	**Brochure 07/2014 (14050629), p. 19 (PDF 19)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1003 (IE3)

1LE1003-1BC22-2AA4

2.2 kW / 1000 rpm

Frame 112 M | 6 poles | IM B3 | Article No. 1LE1003-1BC22-2AA4

GENERAL DATA

Series / efficiency class	**1LE1003 / IE3**
Housing	**Aluminum**
Frame size	**112 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**34 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**not listed (catalog 09/2023)**
Rated speed (50 Hz)	**970 rpm**
Rated torque	**21.5 Nm**
Rated current	**5 A**
Power factor	**0.75**
Efficiency 4/4 | 3/4 | 2/4	**84.3 | 85 | 83.9 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5.6 | 2.2 | 2.8**
Moment of inertia J	**0.017 kgm2**
Sound pressure / power LpfA | LWA	**65 | 74 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (09/2023), table 1LE1003, p. 3/15**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1003 (IE3)

1LE1003-1BC22-2FA4

2.2 kW / 1000 rpm

Frame 112 M | 6 poles | IM B5 | Article No. 1LE1003-1BC22-2FA4

GENERAL DATA

Series / efficiency class	**1LE1003 / IE3**
Housing	**Aluminum**
Frame size	**112 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**34 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**not listed (catalog 09/2023)**
Rated speed (50 Hz)	**970 rpm**
Rated torque	**21.5 Nm**
Rated current	**5 A**
Power factor	**0.75**
Efficiency 4/4 | 3/4 | 2/4	**84.3 | 85 | 83.9 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5.6 | 2.2 | 2.8**
Moment of inertia J	**0.017 kgm2**
Sound pressure / power LpfA | LWA	**65 | 74 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (09/2023), table 1LE1003, p. 3/15**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1003 (IE3)

1LE1003-1BC22-2KA4

2.2 kW / 1000 rpm

Frame 112 M | 6 poles | IM B14 | Article No. 1LE1003-1BC22-2KA4

GENERAL DATA

Series / efficiency class	**1LE1003 / IE3**
Housing	**Aluminum**
Frame size	**112 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**34 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**not listed (catalog 09/2023)**
Rated speed (50 Hz)	**970 rpm**
Rated torque	**21.5 Nm**
Rated current	**5 A**
Power factor	**0.75**
Efficiency 4/4 | 3/4 | 2/4	**84.3 | 85 | 83.9 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5.6 | 2.2 | 2.8**
Moment of inertia J	**0.017 kgm2**
Sound pressure / power LpfA | LWA	**65 | 74 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (09/2023), table 1LE1003, p. 3/15**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1041 (IE2)

1LE1041-1BC22-2FA4

2.2 kW / 1000 rpm

Frame 112 M | 6 poles | IM B5 | Article No. 1LE1041-1BC22-2FA4

GENERAL DATA

Series / efficiency class	**1LE1041 / IE2**
Housing	**Aluminum**
Frame size	**112 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**29 kg**

ELECTRICAL DATA - CATALOG VALUES AT 60 HZ (APAC LINE)

Rated power (P50 rating)	**2.2 kW (about 3 HP)**
Rated power (P60 rating)	**2.55 kW**
Rated speed (60 Hz)	**1170 rpm**
Rated torque (60 Hz)	**18 Nm**
Rated current (460 V, 60 Hz)	**4.3 A**
Power factor (60 Hz)	**0.73**
Efficiency 4/4 | 3/4 | 2/4 (60 Hz)	**87.5 | 87.6 | 86 %**
I_LR/I_N | T_LR/T_N | T_B/T_N (60 Hz)	**6.3 | 2.1 | 3.2**
Moment of inertia J	**0.014 kgm2**
Sound pressure / power LpfA | LWA (60 Hz)	**65 | 77 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1041, p. 2/66 (PDF 184)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
APAC Line: the catalog lists operating values at 60 Hz only; 50 Hz speed/efficiency are not listed (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1041 (IE2)

1LE1041-1BC22-2KA4

2.2 kW / 1000 rpm

Frame 112 M | 6 poles | IM B14 | Article No. 1LE1041-1BC22-2KA4

GENERAL DATA

Series / efficiency class	**1LE1041 / IE2**
Housing	**Aluminum**
Frame size	**112 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**29 kg**

ELECTRICAL DATA - CATALOG VALUES AT 60 HZ (APAC LINE)

Rated power (P50 rating)	**2.2 kW (about 3 HP)**
Rated power (P60 rating)	**2.55 kW**
Rated speed (60 Hz)	**1170 rpm**
Rated torque (60 Hz)	**18 Nm**
Rated current (460 V, 60 Hz)	**4.3 A**
Power factor (60 Hz)	**0.73**
Efficiency 4/4 | 3/4 | 2/4 (60 Hz)	**87.5 | 87.6 | 86 %**
I_LR/I_N | T_LR/T_N | T_B/T_N (60 Hz)	**6.3 | 2.1 | 3.2**
Moment of inertia J	**0.014 kgm2**
Sound pressure / power LpfA | LWA (60 Hz)	**65 | 77 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1041, p. 2/66 (PDF 184)**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
APAC Line: the catalog lists operating values at 60 Hz only; 50 Hz speed/efficiency are not listed (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1043 (IE3)

1LE1043-1CC13-4AA4

2.2 kW / 1000 rpm

Frame 132 S | 6 poles | IM B3 | Article No. 1LE1043-1CC13-4AA4

GENERAL DATA

Series / efficiency class	**1LE1043 / IE3**
Housing	**Aluminum**
Frame size	**132 S**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**52 kg**

ELECTRICAL DATA - CATALOG VALUES AT 60 HZ (APAC LINE)

Rated power (P50 rating)	**2.2 kW (about 3 HP)**
Rated power (P60 rating)	**2.55 kW**
Rated speed (60 Hz)	**1180 rpm**
Rated torque (60 Hz)	**21 Nm**
Rated current (460 V, 60 Hz)	**4.65 A**
Power factor (60 Hz)	**0.77**
Efficiency 4/4 | 3/4 | 2/4 (60 Hz)	**89.5 | 89.8 | 88.8 %**
I_LR/I_N | T_LR/T_N | T_B/T_N (60 Hz)	**7.1 | 2 | 3.1**
Moment of inertia J	**0.037 kgm2**
Sound pressure / power LpfA | LWA (60 Hz)	**67 | 79 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1043, p. 2/55 (PDF 173)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
APAC Line: the catalog lists operating values at 60 Hz only; 50 Hz speed/efficiency are not listed (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1043 (IE3)

1LE1043-1CC13-4FA4

2.2 kW / 1000 rpm

Frame 132 S | 6 poles | IM B5 | Article No. 1LE1043-1CC13-4FA4

GENERAL DATA

Series / efficiency class	**1LE1043 / IE3**
Housing	**Aluminum**
Frame size	**132 S**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**52 kg**

ELECTRICAL DATA - CATALOG VALUES AT 60 HZ (APAC LINE)

Rated power (P50 rating)	**2.2 kW (about 3 HP)**
Rated power (P60 rating)	**2.55 kW**
Rated speed (60 Hz)	**1180 rpm**
Rated torque (60 Hz)	**21 Nm**
Rated current (460 V, 60 Hz)	**4.65 A**
Power factor (60 Hz)	**0.77**
Efficiency 4/4 | 3/4 | 2/4 (60 Hz)	**89.5 | 89.8 | 88.8 %**
I_LR/I_N | T_LR/T_N | T_B/T_N (60 Hz)	**7.1 | 2 | 3.1**
Moment of inertia J	**0.037 kgm2**
Sound pressure / power LpfA | LWA (60 Hz)	**67 | 79 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1043, p. 2/55 (PDF 173)**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
APAC Line: the catalog lists operating values at 60 Hz only; 50 Hz speed/efficiency are not listed (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1043 (IE3)

1LE1043-1CC13-4KA4

2.2 kW / 1000 rpm

Frame 132 S | 6 poles | IM B14 | Article No. 1LE1043-1CC13-4KA4

GENERAL DATA

Series / efficiency class	**1LE1043 / IE3**
Housing	**Aluminum**
Frame size	**132 S**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**52 kg**

ELECTRICAL DATA - CATALOG VALUES AT 60 HZ (APAC LINE)

Rated power (P50 rating)	**2.2 kW (about 3 HP)**
Rated power (P60 rating)	**2.55 kW**
Rated speed (60 Hz)	**1180 rpm**
Rated torque (60 Hz)	**21 Nm**
Rated current (460 V, 60 Hz)	**4.65 A**
Power factor (60 Hz)	**0.77**
Efficiency 4/4 | 3/4 | 2/4 (60 Hz)	**89.5 | 89.8 | 88.8 %**
I_LR/I_N | T_LR/T_N | T_B/T_N (60 Hz)	**7.1 | 2 | 3.1**
Moment of inertia J	**0.037 kgm2**
Sound pressure / power LpfA | LWA (60 Hz)	**67 | 79 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1043, p. 2/55 (PDF 173)**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
APAC Line: the catalog lists operating values at 60 Hz only; 50 Hz speed/efficiency are not listed (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0102 (IE1)

1LE0102-1BC22-2AA4

2.2 kW / 1000 rpm

Frame 112 M | 6 poles | IM B3 | Article No. 1LE0102-1BC22-2AA4

GENERAL DATA

Series / efficiency class	**1LE0102 / IE1**
Housing	**Cast iron**
Frame size	**112 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**42 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**2.55 kW**
Rated speed (50 Hz)	**940 rpm**
Rated torque	**22.3 Nm**
Rated current	**5.5 A**
Power factor	**0.75**
Efficiency 4/4 | 3/4 | 2/4	**77.7 | 79.2 | 78.1 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5.2 | 2.4 | 3**
Moment of inertia J	**0.01 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0102, p. 22 (PDF 22)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0102 (IE1)

1LE0102-1BC22-2FA4

2.2 kW / 1000 rpm

Frame 112 M | 6 poles | IM B5 | Article No. 1LE0102-1BC22-2FA4

GENERAL DATA

Series / efficiency class	**1LE0102 / IE1**
Housing	**Cast iron**
Frame size	**112 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**42 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**2.55 kW**
Rated speed (50 Hz)	**940 rpm**
Rated torque	**22.3 Nm**
Rated current	**5.5 A**
Power factor	**0.75**
Efficiency 4/4 | 3/4 | 2/4	**77.7 | 79.2 | 78.1 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5.2 | 2.4 | 3**
Moment of inertia J	**0.01 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0102, p. 22 (PDF 22)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0102 (IE1)

1LE0102-1BC22-2KA4

2.2 kW / 1000 rpm

Frame 112 M | 6 poles | IM B14 | Article No. 1LE0102-1BC22-2KA4

GENERAL DATA

Series / efficiency class	**1LE0102 / IE1**
Housing	**Cast iron**
Frame size	**112 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**42 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**2.55 kW**
Rated speed (50 Hz)	**940 rpm**
Rated torque	**22.3 Nm**
Rated current	**5.5 A**
Power factor	**0.75**
Efficiency 4/4 | 3/4 | 2/4	**77.7 | 79.2 | 78.1 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5.2 | 2.4 | 3**
Moment of inertia J	**0.01 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0102, p. 22 (PDF 22)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0102 (IE1)

1LE0102-1BC23-4AA4

2.2 kW / 1000 rpm

Frame 112 M | 6 poles | IM B3 | Article No. 1LE0102-1BC23-4AA4

GENERAL DATA

Series / efficiency class	**1LE0102 / IE1**
Housing	**Cast iron**
Frame size	**112 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**42 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**2.55 kW**
Rated speed (50 Hz)	**940 rpm**
Rated torque	**22.3 Nm**
Rated current	**5.4 A**
Power factor	**0.75**
Efficiency 4/4 | 3/4 | 2/4	**77.7 | 79.2 | 78.1 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5.2 | 2.4 | 3**
Moment of inertia J	**0.01 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0102, p. 22 (PDF 22)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0102 (IE1)

1LE0102-1BC23-4FA4

2.2 kW / 1000 rpm

Frame 112 M | 6 poles | IM B5 | Article No. 1LE0102-1BC23-4FA4

GENERAL DATA

Series / efficiency class	**1LE0102 / IE1**
Housing	**Cast iron**
Frame size	**112 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**42 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**2.55 kW**
Rated speed (50 Hz)	**940 rpm**
Rated torque	**22.3 Nm**
Rated current	**5.4 A**
Power factor	**0.75**
Efficiency 4/4 | 3/4 | 2/4	**77.7 | 79.2 | 78.1 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5.2 | 2.4 | 3**
Moment of inertia J	**0.01 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0102, p. 22 (PDF 22)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0102 (IE1)

1LE0102-1BC23-4KA4

2.2 kW / 1000 rpm

Frame 112 M | 6 poles | IM B14 | Article No. 1LE0102-1BC23-4KA4

GENERAL DATA

Series / efficiency class	**1LE0102 / IE1**
Housing	**Cast iron**
Frame size	**112 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**42 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**2.55 kW**
Rated speed (50 Hz)	**940 rpm**
Rated torque	**22.3 Nm**
Rated current	**5.4 A**
Power factor	**0.75**
Efficiency 4/4 | 3/4 | 2/4	**77.7 | 79.2 | 78.1 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5.2 | 2.4 | 3**
Moment of inertia J	**0.01 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0102, p. 22 (PDF 22)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0102 (IE1)

1LE0102-1BC24-1AA4

2.2 kW / 1000 rpm

Frame 112 M | 6 poles | IM B3 | Article No. 1LE0102-1BC24-1AA4

GENERAL DATA

Series / efficiency class	**1LE0102 / IE1**
Housing	**Cast iron**
Frame size	**112 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**525 V D**
Net weight (IM B3)	**42 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**2.55 kW**
Rated speed (50 Hz)	**940 rpm**
Rated torque	**22.3 Nm**
Rated current	**4.15 A**
Power factor	**0.75**
Efficiency 4/4 | 3/4 | 2/4	**77.7 | 79.2 | 78.1 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5.2 | 2.4 | 3**
Moment of inertia J	**0.01 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0102, p. 27 (PDF 27)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0102 (IE1)

1LE0102-1BC24-1FA4

2.2 kW / 1000 rpm

Frame 112 M | 6 poles | IM B5 | Article No. 1LE0102-1BC24-1FA4

GENERAL DATA

Series / efficiency class	**1LE0102 / IE1**
Housing	**Cast iron**
Frame size	**112 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**525 V D**
Net weight (IM B3)	**42 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**2.55 kW**
Rated speed (50 Hz)	**940 rpm**
Rated torque	**22.3 Nm**
Rated current	**4.15 A**
Power factor	**0.75**
Efficiency 4/4 | 3/4 | 2/4	**77.7 | 79.2 | 78.1 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5.2 | 2.4 | 3**
Moment of inertia J	**0.01 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0102, p. 27 (PDF 27)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0102 (IE1)

1LE0102-1BC24-1KA4

2.2 kW / 1000 rpm

Frame 112 M | 6 poles | IM B14 | Article No. 1LE0102-1BC24-1KA4

GENERAL DATA

Series / efficiency class	**1LE0102 / IE1**
Housing	**Cast iron**
Frame size	**112 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**525 V D**
Net weight (IM B3)	**42 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**2.55 kW**
Rated speed (50 Hz)	**940 rpm**
Rated torque	**22.3 Nm**
Rated current	**4.15 A**
Power factor	**0.75**
Efficiency 4/4 | 3/4 | 2/4	**77.7 | 79.2 | 78.1 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5.2 | 2.4 | 3**
Moment of inertia J	**0.01 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0102, p. 27 (PDF 27)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1501 (IE2)

1LE1501-1AC62-2AA4

2.2 kW / 1000 rpm

Frame 100 L | 6 poles | IM B3 | Article No. 1LE1501-1AC62-2AA4

GENERAL DATA

Series / efficiency class	**1LE1501 / IE2**
Housing	**Cast iron**
Frame size	**100 L**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**49 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**2.55 kW**
Rated speed (50 Hz)	**965 rpm**
Rated torque	**22 Nm**
Rated current	**5.1 A**
Power factor	**0.76**
Efficiency 4/4 | 3/4 | 2/4	**81.8 | 83.3 | 82.7 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**4.9 | 1.7 | 2.5**
Moment of inertia J	**0.014 kgm2**
Sound pressure / power LpfA | LWA	**59 | 71 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1501, p. 2/41 (PDF 159)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1501 (IE2)

1LE1501-1AC62-2FA4

2.2 kW / 1000 rpm

Frame 100 L | 6 poles | IM B5 | Article No. 1LE1501-1AC62-2FA4

GENERAL DATA

Series / efficiency class	**1LE1501 / IE2**
Housing	**Cast iron**
Frame size	**100 L**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**49 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**2.55 kW**
Rated speed (50 Hz)	**965 rpm**
Rated torque	**22 Nm**
Rated current	**5.1 A**
Power factor	**0.76**
Efficiency 4/4 | 3/4 | 2/4	**81.8 | 83.3 | 82.7 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**4.9 | 1.7 | 2.5**
Moment of inertia J	**0.014 kgm2**
Sound pressure / power LpfA | LWA	**59 | 71 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1501, p. 2/41 (PDF 159)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1501 (IE2)

1LE1501-1AC62-2KA4

2.2 kW / 1000 rpm

Frame 100 L | 6 poles | IM B14 | Article No. 1LE1501-1AC62-2KA4

GENERAL DATA

Series / efficiency class	**1LE1501 / IE2**
Housing	**Cast iron**
Frame size	**100 L**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**49 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**2.55 kW**
Rated speed (50 Hz)	**965 rpm**
Rated torque	**22 Nm**
Rated current	**5.1 A**
Power factor	**0.76**
Efficiency 4/4 | 3/4 | 2/4	**81.8 | 83.3 | 82.7 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**4.9 | 1.7 | 2.5**
Moment of inertia J	**0.014 kgm2**
Sound pressure / power LpfA | LWA	**59 | 71 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1501, p. 2/41 (PDF 159)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1502 (IE1)

1LE1502-1BC22-2AA4

2.2 kW / 1000 rpm

Frame 112 M | 6 poles | IM B3 | Article No. 1LE1502-1BC22-2AA4

GENERAL DATA

Series / efficiency class	**1LE1502 / IE1**
Housing	**Cast iron**
Frame size	**112 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**37 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**2.55 kW**
Rated speed (50 Hz)	**940 rpm**
Rated torque	**22 Nm**
Rated current	**5.7 A**
Power factor	**0.72**
Efficiency 4/4 | 3/4 | 2/4	**77.7 | 78.5 | 76.3 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**4.6 | 2.6 | 2.7**
Moment of inertia J	**0.0092 kgm2**
Sound pressure / power LpfA | LWA	**59 | 71 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1502, p. 2/50 (PDF 168)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1502 (IE1)

1LE1502-1BC22-2FA4

2.2 kW / 1000 rpm

Frame 112 M | 6 poles | IM B5 | Article No. 1LE1502-1BC22-2FA4

GENERAL DATA

Series / efficiency class	**1LE1502 / IE1**
Housing	**Cast iron**
Frame size	**112 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**37 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**2.55 kW**
Rated speed (50 Hz)	**940 rpm**
Rated torque	**22 Nm**
Rated current	**5.7 A**
Power factor	**0.72**
Efficiency 4/4 | 3/4 | 2/4	**77.7 | 78.5 | 76.3 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**4.6 | 2.6 | 2.7**
Moment of inertia J	**0.0092 kgm2**
Sound pressure / power LpfA | LWA	**59 | 71 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1502, p. 2/50 (PDF 168)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1502 (IE1)

1LE1502-1BC22-2KA4

2.2 kW / 1000 rpm

Frame 112 M | 6 poles | IM B14 | Article No. 1LE1502-1BC22-2KA4

GENERAL DATA

Series / efficiency class	**1LE1502 / IE1**
Housing	**Cast iron**
Frame size	**112 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**37 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**2.55 kW**
Rated speed (50 Hz)	**940 rpm**
Rated torque	**22 Nm**
Rated current	**5.7 A**
Power factor	**0.72**
Efficiency 4/4 | 3/4 | 2/4	**77.7 | 78.5 | 76.3 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**4.6 | 2.6 | 2.7**
Moment of inertia J	**0.0092 kgm2**
Sound pressure / power LpfA | LWA	**59 | 71 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1502, p. 2/50 (PDF 168)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1502 (IE1)

1LE1502-1AC62-2AA4

2.2 kW / 1000 rpm

Frame 100 L | 6 poles | IM B3 | Article No. 1LE1502-1AC62-2AA4

GENERAL DATA

Series / efficiency class	**1LE1502 / IE1**
Housing	**Cast iron**
Frame size	**100 L**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**35 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**2.55 kW**
Rated speed (50 Hz)	**930 rpm**
Rated torque	**23 Nm**
Rated current	**5.2 A**
Power factor	**0.78**
Efficiency 4/4 | 3/4 | 2/4	**77.7 | 79.5 | 78.1 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**4 | 2 | 2.2**
Moment of inertia J	**0.0084 kgm2**
Sound pressure / power LpfA | LWA	**59 | 71 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1502, p. 2/53 (PDF 171)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1502 (IE1)

1LE1502-1AC62-2FA4

2.2 kW / 1000 rpm

Frame 100 L | 6 poles | IM B5 | Article No. 1LE1502-1AC62-2FA4

GENERAL DATA

Series / efficiency class	**1LE1502 / IE1**
Housing	**Cast iron**
Frame size	**100 L**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**35 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**2.55 kW**
Rated speed (50 Hz)	**930 rpm**
Rated torque	**23 Nm**
Rated current	**5.2 A**
Power factor	**0.78**
Efficiency 4/4 | 3/4 | 2/4	**77.7 | 79.5 | 78.1 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**4 | 2 | 2.2**
Moment of inertia J	**0.0084 kgm2**
Sound pressure / power LpfA | LWA	**59 | 71 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1502, p. 2/53 (PDF 171)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1502 (IE1)

1LE1502-1AC62-2KA4

2.2 kW / 1000 rpm

Frame 100 L | 6 poles | IM B14 | Article No. 1LE1502-1AC62-2KA4

GENERAL DATA

Series / efficiency class	**1LE1502 / IE1**
Housing	**Cast iron**
Frame size	**100 L**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**35 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**2.55 kW**
Rated speed (50 Hz)	**930 rpm**
Rated torque	**23 Nm**
Rated current	**5.2 A**
Power factor	**0.78**
Efficiency 4/4 | 3/4 | 2/4	**77.7 | 79.5 | 78.1 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**4 | 2 | 2.2**
Moment of inertia J	**0.0084 kgm2**
Sound pressure / power LpfA | LWA	**59 | 71 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1502, p. 2/53 (PDF 171)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0101 (IE2)

1LE0101-1BC22-2AA4

2.2 kW / 1000 rpm

Frame 112 M | 6 poles | IM B3 | Article No. 1LE0101-1BC22-2AA4

GENERAL DATA

Series / efficiency class	**1LE0101 / IE2**
Housing	**Cast iron**
Frame size	**112 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**44 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**2.55 kW**
Rated speed (50 Hz)	**950 rpm**
Rated torque	**22.1 Nm**
Rated current	**5.4 A**
Power factor	**0.73**
Efficiency 4/4 | 3/4 | 2/4	**81.8 | 82.5 | 81 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5.2 | 2.4 | 3**
Moment of inertia J	**0.012 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0101, p. 25 (PDF 25)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0101 (IE2)

1LE0101-1BC22-2FA4

2.2 kW / 1000 rpm

Frame 112 M | 6 poles | IM B5 | Article No. 1LE0101-1BC22-2FA4

GENERAL DATA

Series / efficiency class	**1LE0101 / IE2**
Housing	**Cast iron**
Frame size	**112 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**44 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**2.55 kW**
Rated speed (50 Hz)	**950 rpm**
Rated torque	**22.1 Nm**
Rated current	**5.4 A**
Power factor	**0.73**
Efficiency 4/4 | 3/4 | 2/4	**81.8 | 82.5 | 81 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5.2 | 2.4 | 3**
Moment of inertia J	**0.012 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0101, p. 25 (PDF 25)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0101 (IE2)

1LE0101-1BC22-2KA4

2.2 kW / 1000 rpm

Frame 112 M | 6 poles | IM B14 | Article No. 1LE0101-1BC22-2KA4

GENERAL DATA

Series / efficiency class	**1LE0101 / IE2**
Housing	**Cast iron**
Frame size	**112 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**44 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**2.55 kW**
Rated speed (50 Hz)	**950 rpm**
Rated torque	**22.1 Nm**
Rated current	**5.4 A**
Power factor	**0.73**
Efficiency 4/4 | 3/4 | 2/4	**81.8 | 82.5 | 81 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5.2 | 2.4 | 3**
Moment of inertia J	**0.012 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0101, p. 25 (PDF 25)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0101 (IE2)

1LE0101-1BC23-4AA4

2.2 kW / 1000 rpm

Frame 112 M | 6 poles | IM B3 | Article No. 1LE0101-1BC23-4AA4

GENERAL DATA

Series / efficiency class	**1LE0101 / IE2**
Housing	**Cast iron**
Frame size	**112 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**44 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**2.55 kW**
Rated speed (50 Hz)	**950 rpm**
Rated torque	**22.1 Nm**
Rated current	**5.3 A**
Power factor	**0.73**
Efficiency 4/4 | 3/4 | 2/4	**81.8 | 82.5 | 81 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5.2 | 2.4 | 3**
Moment of inertia J	**0.012 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0101, p. 25 (PDF 25)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0101 (IE2)

1LE0101-1BC23-4FA4

2.2 kW / 1000 rpm

Frame 112 M | 6 poles | IM B5 | Article No. 1LE0101-1BC23-4FA4

GENERAL DATA

Series / efficiency class	**1LE0101 / IE2**
Housing	**Cast iron**
Frame size	**112 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**44 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**2.55 kW**
Rated speed (50 Hz)	**950 rpm**
Rated torque	**22.1 Nm**
Rated current	**5.3 A**
Power factor	**0.73**
Efficiency 4/4 | 3/4 | 2/4	**81.8 | 82.5 | 81 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5.2 | 2.4 | 3**
Moment of inertia J	**0.012 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0101, p. 25 (PDF 25)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0101 (IE2)

1LE0101-1BC23-4KA4

2.2 kW / 1000 rpm

Frame 112 M | 6 poles | IM B14 | Article No. 1LE0101-1BC23-4KA4

GENERAL DATA

Series / efficiency class	**1LE0101 / IE2**
Housing	**Cast iron**
Frame size	**112 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**44 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**2.55 kW**
Rated speed (50 Hz)	**950 rpm**
Rated torque	**22.1 Nm**
Rated current	**5.3 A**
Power factor	**0.73**
Efficiency 4/4 | 3/4 | 2/4	**81.8 | 82.5 | 81 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5.2 | 2.4 | 3**
Moment of inertia J	**0.012 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0101, p. 25 (PDF 25)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0101 (IE2)

1LE0101-1BC24-1AA4

2.2 kW / 1000 rpm

Frame 112 M | 6 poles | IM B3 | Article No. 1LE0101-1BC24-1AA4

GENERAL DATA

Series / efficiency class	**1LE0101 / IE2**
Housing	**Cast iron**
Frame size	**112 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**525 V D**
Net weight (IM B3)	**44 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**2.55 kW**
Rated speed (50 Hz)	**950 rpm**
Rated torque	**22.1 Nm**
Rated current	**4.05 A**
Power factor	**0.73**
Efficiency 4/4 | 3/4 | 2/4	**81.8 | 82.5 | 81 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5.2 | 2.4 | 3**
Moment of inertia J	**0.012 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0101, p. 29 (PDF 29)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0101 (IE2)

1LE0101-1BC24-1FA4

2.2 kW / 1000 rpm

Frame 112 M | 6 poles | IM B5 | Article No. 1LE0101-1BC24-1FA4

GENERAL DATA

Series / efficiency class	**1LE0101 / IE2**
Housing	**Cast iron**
Frame size	**112 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**525 V D**
Net weight (IM B3)	**44 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**2.55 kW**
Rated speed (50 Hz)	**950 rpm**
Rated torque	**22.1 Nm**
Rated current	**4.05 A**
Power factor	**0.73**
Efficiency 4/4 | 3/4 | 2/4	**81.8 | 82.5 | 81 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5.2 | 2.4 | 3**
Moment of inertia J	**0.012 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0101, p. 29 (PDF 29)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0101 (IE2)

1LE0101-1BC24-1KA4

2.2 kW / 1000 rpm

Frame 112 M | 6 poles | IM B14 | Article No. 1LE0101-1BC24-1KA4

GENERAL DATA

Series / efficiency class	**1LE0101 / IE2**
Housing	**Cast iron**
Frame size	**112 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**525 V D**
Net weight (IM B3)	**44 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**2.55 kW**
Rated speed (50 Hz)	**950 rpm**
Rated torque	**22.1 Nm**
Rated current	**4.05 A**
Power factor	**0.73**
Efficiency 4/4 | 3/4 | 2/4	**81.8 | 82.5 | 81 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5.2 | 2.4 | 3**
Moment of inertia J	**0.012 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0101, p. 29 (PDF 29)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1501 (IE2)

1LE1501-1BC22-2AA4

2.2 kW / 1000 rpm

Frame 112 M | 6 poles | IM B3 | Article No. 1LE1501-1BC22-2AA4

GENERAL DATA

Series / efficiency class	**1LE1501 / IE2**
Housing	**Cast iron**
Frame size	**112 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**41 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**2.55 kW**
Rated speed (50 Hz)	**965 rpm**
Rated torque	**22 Nm**
Rated current	**5.2 A**
Power factor	**0.75**
Efficiency 4/4 | 3/4 | 2/4	**81.8 | 82.7 | 81.7 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5 | 2 | 2.8**
Moment of inertia J	**0.014 kgm2**
Sound pressure / power LpfA | LWA	**62 | 74 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1501, p. 2/34 (PDF 152)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1501 (IE2)

1LE1501-1BC22-2FA4

2.2 kW / 1000 rpm

Frame 112 M | 6 poles | IM B5 | Article No. 1LE1501-1BC22-2FA4

GENERAL DATA

Series / efficiency class	**1LE1501 / IE2**
Housing	**Cast iron**
Frame size	**112 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**41 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**2.55 kW**
Rated speed (50 Hz)	**965 rpm**
Rated torque	**22 Nm**
Rated current	**5.2 A**
Power factor	**0.75**
Efficiency 4/4 | 3/4 | 2/4	**81.8 | 82.7 | 81.7 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5 | 2 | 2.8**
Moment of inertia J	**0.014 kgm2**
Sound pressure / power LpfA | LWA	**62 | 74 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1501, p. 2/34 (PDF 152)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1501 (IE2)

1LE1501-1BC22-2KA4

2.2 kW / 1000 rpm

Frame 112 M | 6 poles | IM B14 | Article No. 1LE1501-1BC22-2KA4

GENERAL DATA

Series / efficiency class	**1LE1501 / IE2**
Housing	**Cast iron**
Frame size	**112 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**41 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**2.55 kW**
Rated speed (50 Hz)	**965 rpm**
Rated torque	**22 Nm**
Rated current	**5.2 A**
Power factor	**0.75**
Efficiency 4/4 | 3/4 | 2/4	**81.8 | 82.7 | 81.7 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5 | 2 | 2.8**
Moment of inertia J	**0.014 kgm2**
Sound pressure / power LpfA | LWA	**62 | 74 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1501, p. 2/34 (PDF 152)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1503 (IE3)

1LE1503-1BC22-2AA4

2.2 kW / 1000 rpm

Frame 112 M | 6 poles | IM B3 | Article No. 1LE1503-1BC22-2AA4

GENERAL DATA

Series / efficiency class	**1LE1503 / IE3**
Housing	**Cast iron**
Frame size	**112 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**53 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**not listed (catalog 09/2023)**
Rated speed (50 Hz)	**970 rpm**
Rated torque	**21.5 Nm**
Rated current	**5 A**
Power factor	**0.75**
Efficiency 4/4 | 3/4 | 2/4	**84.3 | 85 | 83.9 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5.6 | 2.2 | 2.8**
Moment of inertia J	**0.017 kgm2**
Sound pressure / power LpfA | LWA	**65 | 74 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (09/2023), table 1LE1503, p. 3/21**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1503 (IE3)

1LE1503-1BC22-2FA4

2.2 kW / 1000 rpm

Frame 112 M | 6 poles | IM B5 | Article No. 1LE1503-1BC22-2FA4

GENERAL DATA

Series / efficiency class	**1LE1503 / IE3**
Housing	**Cast iron**
Frame size	**112 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**53 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**not listed (catalog 09/2023)**
Rated speed (50 Hz)	**970 rpm**
Rated torque	**21.5 Nm**
Rated current	**5 A**
Power factor	**0.75**
Efficiency 4/4 | 3/4 | 2/4	**84.3 | 85 | 83.9 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5.6 | 2.2 | 2.8**
Moment of inertia J	**0.017 kgm2**
Sound pressure / power LpfA | LWA	**65 | 74 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (09/2023), table 1LE1503, p. 3/21**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1543 (IE3)

1LE1543-1CC13-4AA4

2.2 kW / 1000 rpm

Frame 132 S | 6 poles | IM B3 | Article No. 1LE1543-1CC13-4AA4

GENERAL DATA

Series / efficiency class	**1LE1543 / IE3**
Housing	**Cast iron**
Frame size	**132 S**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**60 kg**

ELECTRICAL DATA - CATALOG VALUES AT 60 HZ (APAC LINE)

Rated power (P50 rating)	**2.2 kW (about 3 HP)**
Rated power (P60 rating)	**2.55 kW**
Rated speed (60 Hz)	**1180 rpm**
Rated torque (60 Hz)	**17.8 Nm**
Rated current (460 V, 60 Hz)	**4.3 A**
Power factor (60 Hz)	**0.72**
Efficiency 4/4 | 3/4 | 2/4 (60 Hz)	**89.5 | 89.2 | 87.7 %**
I_LR/I_N | T_LR/T_N | T_B/T_N (60 Hz)	**7.3 | 2.4 | 3.5**
Moment of inertia J	**0.033 kgm2**
Sound pressure / power LpfA | LWA (60 Hz)	**63 | 71 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (09/2023), table 1LE1543, p. 3/67**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
APAC Line: the catalog lists operating values at 60 Hz only; 50 Hz speed/efficiency are not listed (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1543 (IE3)

1LE1543-1CC13-4FA4

2.2 kW / 1000 rpm

Frame 132 S | 6 poles | IM B5 | Article No. 1LE1543-1CC13-4FA4

GENERAL DATA

Series / efficiency class	**1LE1543 / IE3**
Housing	**Cast iron**
Frame size	**132 S**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**60 kg**

ELECTRICAL DATA - CATALOG VALUES AT 60 HZ (APAC LINE)

Rated power (P50 rating)	**2.2 kW (about 3 HP)**
Rated power (P60 rating)	**2.55 kW**
Rated speed (60 Hz)	**1180 rpm**
Rated torque (60 Hz)	**17.8 Nm**
Rated current (460 V, 60 Hz)	**4.3 A**
Power factor (60 Hz)	**0.72**
Efficiency 4/4 | 3/4 | 2/4 (60 Hz)	**89.5 | 89.2 | 87.7 %**
I_LR/I_N | T_LR/T_N | T_B/T_N (60 Hz)	**7.3 | 2.4 | 3.5**
Moment of inertia J	**0.033 kgm2**
Sound pressure / power LpfA | LWA (60 Hz)	**63 | 71 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (09/2023), table 1LE1543, p. 3/67**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
APAC Line: the catalog lists operating values at 60 Hz only; 50 Hz speed/efficiency are not listed (see Siemens DT Configurator).