Data sheets - Siemens SIMOTICS GP motors

2.2 kW / 1500 rpm - 48 article numbers in this file

Article No.	Page	Article No.	Page
1LE1001-0EB62-2AA4	2		
1LE1001-0EB62-2FA4	3		
1LE1001-0EB62-2KA4	4		
1LE1001-1AB42-2AA4	5		
1LE1001-1AB42-2FA4	6		
1LE1001-1AB42-2KA4	7		
1LE1003-1AB42-2AA4	8		
1LE1003-1AB42-2FA4	9		
1LE1003-1AB42-2KA4	10		
1LE1041-1AB42-2FA4	11		
1LE1041-1AB42-2KA4	12		
1LE1043-1AB42-2AA4	13		
1LE1043-1AB42-2FA4	14		
1LE1043-1AB42-2KA4	15		
1LE1004-1AB42-2AA4	16		
1LE1004-1AB42-2FA4	17		
1LE1004-1AB42-2KA4	18		
1LE0102-1AB42-2AA4	19		
1LE0102-1AB42-2FA4	20		
1LE0102-1AB42-2KA4	21		
1LE0102-1AB43-4AA4	22		
1LE0102-1AB43-4FA4	23		
1LE0102-1AB43-4KA4	24		
1LE0102-1AB44-1AA4	25		
1LE0102-1AB44-1FA4	26		
1LE0102-1AB44-1KA4	27		
1LE1502-1AB42-2AA4	28		
1LE1502-1AB42-2FA4	29		
1LE1502-1AB42-2KA4	30		
1LE0101-1AB42-2AA4	31		
1LE0101-1AB42-2FA4	32		
1LE0101-1AB42-2KA4	33		
1LE0101-1AB43-4AA4	34		
1LE0101-1AB43-4FA4	35		
1LE0101-1AB43-4KA4	36		
1LE0101-1AB44-1AA4	37		
1LE0101-1AB44-1FA4	38		
1LE0101-1AB44-1KA4	39		
1LE1501-1AB42-2AA4	40		
1LE1501-1AB42-2FA4	41		
1LE1501-1AB42-2KA4	42		
1LE1503-1AB42-2AA4	43		
1LE1503-1AB42-2FA4	44		
1LE1543-1AB42-2AA4	45		
1LE1543-1AB42-2FA4	46		
1LE1504-1AB42-2AA4	47		
1LE1504-1AB42-2FA4	48		
1LE1504-1AB42-2KA4	49		

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1001 (IE2)

1LE1001-0EB62-2AA4

2.2 kW / 1500 rpm

Frame 90 L | 4 poles | IM B3 | Article No. 1LE1001-0EB62-2AA4

GENERAL DATA

Series / efficiency class	**1LE1001 / IE2**
Housing	**Aluminum**
Frame size	**90 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**16 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**2.55 kW**
Rated speed (50 Hz)	**1425 rpm**
Rated torque	**15 Nm**
Rated current	**4.65 A**
Power factor	**0.81**
Efficiency 4/4 | 3/4 | 2/4	**84.3 | 85.6 | 85 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**6.1 | 2.8 | 3.1**
Moment of inertia J	**0.0049 kgm2**
Sound pressure / power LpfA | LWA	**56 | 68 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1001, p. 2/30 (PDF 148)**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1001 (IE2)

1LE1001-0EB62-2FA4

2.2 kW / 1500 rpm

Frame 90 L | 4 poles | IM B5 | Article No. 1LE1001-0EB62-2FA4

GENERAL DATA

Series / efficiency class	**1LE1001 / IE2**
Housing	**Aluminum**
Frame size	**90 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**16 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**2.55 kW**
Rated speed (50 Hz)	**1425 rpm**
Rated torque	**15 Nm**
Rated current	**4.65 A**
Power factor	**0.81**
Efficiency 4/4 | 3/4 | 2/4	**84.3 | 85.6 | 85 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**6.1 | 2.8 | 3.1**
Moment of inertia J	**0.0049 kgm2**
Sound pressure / power LpfA | LWA	**56 | 68 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1001, p. 2/30 (PDF 148)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1001 (IE2)

1LE1001-0EB62-2KA4

2.2 kW / 1500 rpm

Frame 90 L | 4 poles | IM B14 | Article No. 1LE1001-0EB62-2KA4

GENERAL DATA

Series / efficiency class	**1LE1001 / IE2**
Housing	**Aluminum**
Frame size	**90 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**16 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**2.55 kW**
Rated speed (50 Hz)	**1425 rpm**
Rated torque	**15 Nm**
Rated current	**4.65 A**
Power factor	**0.81**
Efficiency 4/4 | 3/4 | 2/4	**84.3 | 85.6 | 85 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**6.1 | 2.8 | 3.1**
Moment of inertia J	**0.0049 kgm2**
Sound pressure / power LpfA | LWA	**56 | 68 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1001, p. 2/30 (PDF 148)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1001 (IE2)

1LE1001-1AB42-2AA4

2.2 kW / 1500 rpm

Frame 100 L | 4 poles | IM B3 | Article No. 1LE1001-1AB42-2AA4

GENERAL DATA

Series / efficiency class	**1LE1001 / IE2**
Housing	**Aluminum**
Frame size	**100 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**21 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**2.55 kW**
Rated speed (50 Hz)	**1455 rpm**
Rated torque	**14 Nm**
Rated current	**4.65 A**
Power factor	**0.81**
Efficiency 4/4 | 3/4 | 2/4	**84.3 | 85.1 | 84.2 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**6.9 | 2.1 | 3.3**
Moment of inertia J	**0.0086 kgm2**
Sound pressure / power LpfA | LWA	**60 | 72 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1001, p. 2/27 (PDF 145)**
Catalog 2	**Brochure 07/2014 (14050629), p. 19 (PDF 19)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1001 (IE2)

1LE1001-1AB42-2FA4

2.2 kW / 1500 rpm

Frame 100 L | 4 poles | IM B5 | Article No. 1LE1001-1AB42-2FA4

GENERAL DATA

Series / efficiency class	**1LE1001 / IE2**
Housing	**Aluminum**
Frame size	**100 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**21 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**2.55 kW**
Rated speed (50 Hz)	**1455 rpm**
Rated torque	**14 Nm**
Rated current	**4.65 A**
Power factor	**0.81**
Efficiency 4/4 | 3/4 | 2/4	**84.3 | 85.1 | 84.2 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**6.9 | 2.1 | 3.3**
Moment of inertia J	**0.0086 kgm2**
Sound pressure / power LpfA | LWA	**60 | 72 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1001, p. 2/27 (PDF 145)**
Catalog 2	**Brochure 07/2014 (14050629), p. 19 (PDF 19)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1001 (IE2)

1LE1001-1AB42-2KA4

2.2 kW / 1500 rpm

Frame 100 L | 4 poles | IM B14 | Article No. 1LE1001-1AB42-2KA4

GENERAL DATA

Series / efficiency class	**1LE1001 / IE2**
Housing	**Aluminum**
Frame size	**100 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**21 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**2.55 kW**
Rated speed (50 Hz)	**1455 rpm**
Rated torque	**14 Nm**
Rated current	**4.65 A**
Power factor	**0.81**
Efficiency 4/4 | 3/4 | 2/4	**84.3 | 85.1 | 84.2 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**6.9 | 2.1 | 3.3**
Moment of inertia J	**0.0086 kgm2**
Sound pressure / power LpfA | LWA	**60 | 72 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1001, p. 2/27 (PDF 145)**
Catalog 2	**Brochure 07/2014 (14050629), p. 19 (PDF 19)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1003 (IE3)

1LE1003-1AB42-2AA4

2.2 kW / 1500 rpm

Frame 100 L | 4 poles | IM B3 | Article No. 1LE1003-1AB42-2AA4

GENERAL DATA

Series / efficiency class	**1LE1003 / IE3**
Housing	**Aluminum**
Frame size	**100 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**25 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**2.55 kW**
Rated speed (50 Hz)	**1455 rpm**
Rated torque	**14.4 Nm**
Rated current	**4.45 A**
Power factor	**0.82**
Efficiency 4/4 | 3/4 | 2/4	**86.7 | 87.2 | 86.3 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**8.3 | 3 | 3.8**
Moment of inertia J	**0.0101 kgm2**
Sound pressure / power LpfA | LWA	**67 | 75 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (09/2023), table 1LE1003, p. 3/14**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1003 (IE3)

1LE1003-1AB42-2FA4

2.2 kW / 1500 rpm

Frame 100 L | 4 poles | IM B5 | Article No. 1LE1003-1AB42-2FA4

GENERAL DATA

Series / efficiency class	**1LE1003 / IE3**
Housing	**Aluminum**
Frame size	**100 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**25 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**2.55 kW**
Rated speed (50 Hz)	**1455 rpm**
Rated torque	**14.4 Nm**
Rated current	**4.45 A**
Power factor	**0.82**
Efficiency 4/4 | 3/4 | 2/4	**86.7 | 87.2 | 86.3 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**8.3 | 3 | 3.8**
Moment of inertia J	**0.0101 kgm2**
Sound pressure / power LpfA | LWA	**67 | 75 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (09/2023), table 1LE1003, p. 3/14**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1003 (IE3)

1LE1003-1AB42-2KA4

2.2 kW / 1500 rpm

Frame 100 L | 4 poles | IM B14 | Article No. 1LE1003-1AB42-2KA4

GENERAL DATA

Series / efficiency class	**1LE1003 / IE3**
Housing	**Aluminum**
Frame size	**100 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**25 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**2.55 kW**
Rated speed (50 Hz)	**1455 rpm**
Rated torque	**14.4 Nm**
Rated current	**4.45 A**
Power factor	**0.82**
Efficiency 4/4 | 3/4 | 2/4	**86.7 | 87.2 | 86.3 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**8.3 | 3 | 3.8**
Moment of inertia J	**0.0101 kgm2**
Sound pressure / power LpfA | LWA	**67 | 75 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (09/2023), table 1LE1003, p. 3/14**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1041 (IE2)

1LE1041-1AB42-2FA4

2.2 kW / 1500 rpm

Frame 100 L | 4 poles | IM B5 | Article No. 1LE1041-1AB42-2FA4

GENERAL DATA

Series / efficiency class	**1LE1041 / IE2**
Housing	**Aluminum**
Frame size	**100 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**21 kg**

ELECTRICAL DATA - CATALOG VALUES AT 60 HZ (APAC LINE)

Rated power (P50 rating)	**2.2 kW (about 3 HP)**
Rated power (P60 rating)	**2.55 kW**
Rated speed (60 Hz)	**1760 rpm**
Rated torque (60 Hz)	**12 Nm**
Rated current (460 V, 60 Hz)	**4.05 A**
Power factor (60 Hz)	**0.78**
Efficiency 4/4 | 3/4 | 2/4 (60 Hz)	**87.5 | 88.3 | 87.4 %**
I_LR/I_N | T_LR/T_N | T_B/T_N (60 Hz)	**8.1 | 2.5 | 3.9**
Moment of inertia J	**0.0086 kgm2**
Sound pressure / power LpfA | LWA (60 Hz)	**62 | 74 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1041, p. 2/65 (PDF 183)**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
APAC Line: the catalog lists operating values at 60 Hz only; 50 Hz speed/efficiency are not listed (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1041 (IE2)

1LE1041-1AB42-2KA4

2.2 kW / 1500 rpm

Frame 100 L | 4 poles | IM B14 | Article No. 1LE1041-1AB42-2KA4

GENERAL DATA

Series / efficiency class	**1LE1041 / IE2**
Housing	**Aluminum**
Frame size	**100 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**21 kg**

ELECTRICAL DATA - CATALOG VALUES AT 60 HZ (APAC LINE)

Rated power (P50 rating)	**2.2 kW (about 3 HP)**
Rated power (P60 rating)	**2.55 kW**
Rated speed (60 Hz)	**1760 rpm**
Rated torque (60 Hz)	**12 Nm**
Rated current (460 V, 60 Hz)	**4.05 A**
Power factor (60 Hz)	**0.78**
Efficiency 4/4 | 3/4 | 2/4 (60 Hz)	**87.5 | 88.3 | 87.4 %**
I_LR/I_N | T_LR/T_N | T_B/T_N (60 Hz)	**8.1 | 2.5 | 3.9**
Moment of inertia J	**0.0086 kgm2**
Sound pressure / power LpfA | LWA (60 Hz)	**62 | 74 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1041, p. 2/65 (PDF 183)**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
APAC Line: the catalog lists operating values at 60 Hz only; 50 Hz speed/efficiency are not listed (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1043 (IE3)

1LE1043-1AB42-2AA4

2.2 kW / 1500 rpm

Frame 100 L | 4 poles | IM B3 | Article No. 1LE1043-1AB42-2AA4

GENERAL DATA

Series / efficiency class	**1LE1043 / IE3**
Housing	**Aluminum**
Frame size	**100 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**25 kg**

ELECTRICAL DATA - CATALOG VALUES AT 60 HZ (APAC LINE)

Rated power (P50 rating)	**2.2 kW (about 3 HP)**
Rated power (P60 rating)	**2.55 kW**
Rated speed (60 Hz)	**1760 rpm**
Rated torque (60 Hz)	**11.9 Nm**
Rated current (460 V, 60 Hz)	**3.85 A**
Power factor (60 Hz)	**0.8**
Efficiency 4/4 | 3/4 | 2/4 (60 Hz)	**89.5 | 89.5 | 88 %**
I_LR/I_N | T_LR/T_N | T_B/T_N (60 Hz)	**9.9 | 3.5 | 4.6**
Moment of inertia J	**0.01 kgm2**
Sound pressure / power LpfA | LWA (60 Hz)	**70 | 78 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (09/2023), table 1LE1043, p. 3/62**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
APAC Line: the catalog lists operating values at 60 Hz only; 50 Hz speed/efficiency are not listed (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1043 (IE3)

1LE1043-1AB42-2FA4

2.2 kW / 1500 rpm

Frame 100 L | 4 poles | IM B5 | Article No. 1LE1043-1AB42-2FA4

GENERAL DATA

Series / efficiency class	**1LE1043 / IE3**
Housing	**Aluminum**
Frame size	**100 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**25 kg**

ELECTRICAL DATA - CATALOG VALUES AT 60 HZ (APAC LINE)

Rated power (P50 rating)	**2.2 kW (about 3 HP)**
Rated power (P60 rating)	**2.55 kW**
Rated speed (60 Hz)	**1760 rpm**
Rated torque (60 Hz)	**11.9 Nm**
Rated current (460 V, 60 Hz)	**3.85 A**
Power factor (60 Hz)	**0.8**
Efficiency 4/4 | 3/4 | 2/4 (60 Hz)	**89.5 | 89.5 | 88 %**
I_LR/I_N | T_LR/T_N | T_B/T_N (60 Hz)	**9.9 | 3.5 | 4.6**
Moment of inertia J	**0.01 kgm2**
Sound pressure / power LpfA | LWA (60 Hz)	**70 | 78 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (09/2023), table 1LE1043, p. 3/62**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
APAC Line: the catalog lists operating values at 60 Hz only; 50 Hz speed/efficiency are not listed (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1043 (IE3)

1LE1043-1AB42-2KA4

2.2 kW / 1500 rpm

Frame 100 L | 4 poles | IM B14 | Article No. 1LE1043-1AB42-2KA4

GENERAL DATA

Series / efficiency class	**1LE1043 / IE3**
Housing	**Aluminum**
Frame size	**100 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**30 kg**

ELECTRICAL DATA - CATALOG VALUES AT 60 HZ (APAC LINE)

Rated power (P50 rating)	**2.2 kW (about 3 HP)**
Rated power (P60 rating)	**2.55 kW**
Rated speed (60 Hz)	**1770 rpm**
Rated torque (60 Hz)	**11.9 Nm**
Rated current (460 V, 60 Hz)	**3.8 A**
Power factor (60 Hz)	**0.81**
Efficiency 4/4 | 3/4 | 2/4 (60 Hz)	**89.5 | 89.2 | 87.2 %**
I_LR/I_N | T_LR/T_N | T_B/T_N (60 Hz)	**9.6 | 3.5 | 5.1**
Moment of inertia J	**0.014 kgm2**
Sound pressure / power LpfA | LWA (60 Hz)	**62 | 74 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1043, p. 2/54 (PDF 172)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
APAC Line: the catalog lists operating values at 60 Hz only; 50 Hz speed/efficiency are not listed (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1004 (IE4)

1LE1004-1AB42-2AA4

2.2 kW / 1500 rpm

Frame 100 L | 4 poles | IM B3 | Article No. 1LE1004-1AB42-2AA4

GENERAL DATA

Series / efficiency class	**1LE1004 / IE4**
Housing	**Aluminum**
Frame size	**100 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**30 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**2.55 kW**
Rated speed (50 Hz)	**1465 rpm**
Rated torque	**14 Nm**
Rated current	**4.5 A**
Power factor	**0.79**
Efficiency 4/4 | 3/4 | 2/4	**89.5 | 89.6 | 88.3 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**8.5 | 3.3 | 4.7**
Moment of inertia J	**0.014 kgm2**
Sound pressure / power LpfA | LWA	**59 | 71 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1004, p. 2/8 (PDF 126)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1004 (IE4)

1LE1004-1AB42-2FA4

2.2 kW / 1500 rpm

Frame 100 L | 4 poles | IM B5 | Article No. 1LE1004-1AB42-2FA4

GENERAL DATA

Series / efficiency class	**1LE1004 / IE4**
Housing	**Aluminum**
Frame size	**100 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**30 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**2.55 kW**
Rated speed (50 Hz)	**1465 rpm**
Rated torque	**14 Nm**
Rated current	**4.5 A**
Power factor	**0.79**
Efficiency 4/4 | 3/4 | 2/4	**89.5 | 89.6 | 88.3 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**8.5 | 3.3 | 4.7**
Moment of inertia J	**0.014 kgm2**
Sound pressure / power LpfA | LWA	**59 | 71 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1004, p. 2/8 (PDF 126)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1004 (IE4)

1LE1004-1AB42-2KA4

2.2 kW / 1500 rpm

Frame 100 L | 4 poles | IM B14 | Article No. 1LE1004-1AB42-2KA4

GENERAL DATA

Series / efficiency class	**1LE1004 / IE4**
Housing	**Aluminum**
Frame size	**100 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**30 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**2.55 kW**
Rated speed (50 Hz)	**1465 rpm**
Rated torque	**14 Nm**
Rated current	**4.5 A**
Power factor	**0.79**
Efficiency 4/4 | 3/4 | 2/4	**89.5 | 89.6 | 88.3 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**8.5 | 3.3 | 4.7**
Moment of inertia J	**0.014 kgm2**
Sound pressure / power LpfA | LWA	**59 | 71 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1004, p. 2/8 (PDF 126)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0102 (IE1)

1LE0102-1AB42-2AA4

2.2 kW / 1500 rpm

Frame 100 L | 4 poles | IM B3 | Article No. 1LE0102-1AB42-2AA4

GENERAL DATA

Series / efficiency class	**1LE0102 / IE1**
Housing	**Cast iron**
Frame size	**100 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**30 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**2.55 kW**
Rated speed (50 Hz)	**1425 rpm**
Rated torque	**14.8 Nm**
Rated current	**4.95 A**
Power factor	**0.81**
Efficiency 4/4 | 3/4 | 2/4	**79.7 | 80.7 | 78.7 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5.8 | 2.4 | 2.9**
Moment of inertia J	**0.0063 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0102, p. 21 (PDF 21)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0102 (IE1)

1LE0102-1AB42-2FA4

2.2 kW / 1500 rpm

Frame 100 L | 4 poles | IM B5 | Article No. 1LE0102-1AB42-2FA4

GENERAL DATA

Series / efficiency class	**1LE0102 / IE1**
Housing	**Cast iron**
Frame size	**100 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**30 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**2.55 kW**
Rated speed (50 Hz)	**1425 rpm**
Rated torque	**14.8 Nm**
Rated current	**4.95 A**
Power factor	**0.81**
Efficiency 4/4 | 3/4 | 2/4	**79.7 | 80.7 | 78.7 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5.8 | 2.4 | 2.9**
Moment of inertia J	**0.0063 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0102, p. 21 (PDF 21)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0102 (IE1)

1LE0102-1AB42-2KA4

2.2 kW / 1500 rpm

Frame 100 L | 4 poles | IM B14 | Article No. 1LE0102-1AB42-2KA4

GENERAL DATA

Series / efficiency class	**1LE0102 / IE1**
Housing	**Cast iron**
Frame size	**100 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**30 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**2.55 kW**
Rated speed (50 Hz)	**1425 rpm**
Rated torque	**14.8 Nm**
Rated current	**4.95 A**
Power factor	**0.81**
Efficiency 4/4 | 3/4 | 2/4	**79.7 | 80.7 | 78.7 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5.8 | 2.4 | 2.9**
Moment of inertia J	**0.0063 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0102, p. 21 (PDF 21)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0102 (IE1)

1LE0102-1AB43-4AA4

2.2 kW / 1500 rpm

Frame 100 L | 4 poles | IM B3 | Article No. 1LE0102-1AB43-4AA4

GENERAL DATA

Series / efficiency class	**1LE0102 / IE1**
Housing	**Cast iron**
Frame size	**100 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**30 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**2.55 kW**
Rated speed (50 Hz)	**1425 rpm**
Rated torque	**14.8 Nm**
Rated current	**4.9 A**
Power factor	**0.81**
Efficiency 4/4 | 3/4 | 2/4	**79.7 | 80.7 | 78.7 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5.8 | 2.4 | 2.9**
Moment of inertia J	**0.0063 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0102, p. 21 (PDF 21)**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0102 (IE1)

1LE0102-1AB43-4FA4

2.2 kW / 1500 rpm

Frame 100 L | 4 poles | IM B5 | Article No. 1LE0102-1AB43-4FA4

GENERAL DATA

Series / efficiency class	**1LE0102 / IE1**
Housing	**Cast iron**
Frame size	**100 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**30 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**2.55 kW**
Rated speed (50 Hz)	**1425 rpm**
Rated torque	**14.8 Nm**
Rated current	**4.9 A**
Power factor	**0.81**
Efficiency 4/4 | 3/4 | 2/4	**79.7 | 80.7 | 78.7 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5.8 | 2.4 | 2.9**
Moment of inertia J	**0.0063 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0102, p. 21 (PDF 21)**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0102 (IE1)

1LE0102-1AB43-4KA4

2.2 kW / 1500 rpm

Frame 100 L | 4 poles | IM B14 | Article No. 1LE0102-1AB43-4KA4

GENERAL DATA

Series / efficiency class	**1LE0102 / IE1**
Housing	**Cast iron**
Frame size	**100 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**30 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**2.55 kW**
Rated speed (50 Hz)	**1425 rpm**
Rated torque	**14.8 Nm**
Rated current	**4.9 A**
Power factor	**0.81**
Efficiency 4/4 | 3/4 | 2/4	**79.7 | 80.7 | 78.7 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5.8 | 2.4 | 2.9**
Moment of inertia J	**0.0063 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0102, p. 21 (PDF 21)**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0102 (IE1)

1LE0102-1AB44-1AA4

2.2 kW / 1500 rpm

Frame 100 L | 4 poles | IM B3 | Article No. 1LE0102-1AB44-1AA4

GENERAL DATA

Series / efficiency class	**1LE0102 / IE1**
Housing	**Cast iron**
Frame size	**100 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**525 V D**
Net weight (IM B3)	**30 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**2.55 kW**
Rated speed (50 Hz)	**1425 rpm**
Rated torque	**14.8 Nm**
Rated current	**3.75 A**
Power factor	**0.81**
Efficiency 4/4 | 3/4 | 2/4	**79.7 | 80.7 | 78.7 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5.8 | 2.4 | 2.9**
Moment of inertia J	**0.0063 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0102, p. 26 (PDF 26)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0102 (IE1)

1LE0102-1AB44-1FA4

2.2 kW / 1500 rpm

Frame 100 L | 4 poles | IM B5 | Article No. 1LE0102-1AB44-1FA4

GENERAL DATA

Series / efficiency class	**1LE0102 / IE1**
Housing	**Cast iron**
Frame size	**100 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**525 V D**
Net weight (IM B3)	**30 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**2.55 kW**
Rated speed (50 Hz)	**1425 rpm**
Rated torque	**14.8 Nm**
Rated current	**3.75 A**
Power factor	**0.81**
Efficiency 4/4 | 3/4 | 2/4	**79.7 | 80.7 | 78.7 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5.8 | 2.4 | 2.9**
Moment of inertia J	**0.0063 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0102, p. 26 (PDF 26)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0102 (IE1)

1LE0102-1AB44-1KA4

2.2 kW / 1500 rpm

Frame 100 L | 4 poles | IM B14 | Article No. 1LE0102-1AB44-1KA4

GENERAL DATA

Series / efficiency class	**1LE0102 / IE1**
Housing	**Cast iron**
Frame size	**100 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**525 V D**
Net weight (IM B3)	**30 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**2.55 kW**
Rated speed (50 Hz)	**1425 rpm**
Rated torque	**14.8 Nm**
Rated current	**3.75 A**
Power factor	**0.81**
Efficiency 4/4 | 3/4 | 2/4	**79.7 | 80.7 | 78.7 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5.8 | 2.4 | 2.9**
Moment of inertia J	**0.0063 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0102, p. 26 (PDF 26)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1502 (IE1)

1LE1502-1AB42-2AA4

2.2 kW / 1500 rpm

Frame 100 L | 4 poles | IM B3 | Article No. 1LE1502-1AB42-2AA4

GENERAL DATA

Series / efficiency class	**1LE1502 / IE1**
Housing	**Cast iron**
Frame size	**100 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**29 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**2.55 kW**
Rated speed (50 Hz)	**1425 rpm**
Rated torque	**15 Nm**
Rated current	**4.9 A**
Power factor	**0.81**
Efficiency 4/4 | 3/4 | 2/4	**79.7 | 80.3 | 78.1 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5.1 | 2.3 | 2.7**
Moment of inertia J	**0.0059 kgm2**
Sound pressure / power LpfA | LWA	**60 | 72 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1502, p. 2/49 (PDF 167)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1502 (IE1)

1LE1502-1AB42-2FA4

2.2 kW / 1500 rpm

Frame 100 L | 4 poles | IM B5 | Article No. 1LE1502-1AB42-2FA4

GENERAL DATA

Series / efficiency class	**1LE1502 / IE1**
Housing	**Cast iron**
Frame size	**100 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**29 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**2.55 kW**
Rated speed (50 Hz)	**1425 rpm**
Rated torque	**15 Nm**
Rated current	**4.9 A**
Power factor	**0.81**
Efficiency 4/4 | 3/4 | 2/4	**79.7 | 80.3 | 78.1 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5.1 | 2.3 | 2.7**
Moment of inertia J	**0.0059 kgm2**
Sound pressure / power LpfA | LWA	**60 | 72 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1502, p. 2/49 (PDF 167)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1502 (IE1)

1LE1502-1AB42-2KA4

2.2 kW / 1500 rpm

Frame 100 L | 4 poles | IM B14 | Article No. 1LE1502-1AB42-2KA4

GENERAL DATA

Series / efficiency class	**1LE1502 / IE1**
Housing	**Cast iron**
Frame size	**100 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**29 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**2.55 kW**
Rated speed (50 Hz)	**1425 rpm**
Rated torque	**15 Nm**
Rated current	**4.9 A**
Power factor	**0.81**
Efficiency 4/4 | 3/4 | 2/4	**79.7 | 80.3 | 78.1 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5.1 | 2.3 | 2.7**
Moment of inertia J	**0.0059 kgm2**
Sound pressure / power LpfA | LWA	**60 | 72 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1502, p. 2/49 (PDF 167)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0101 (IE2)

1LE0101-1AB42-2AA4

2.2 kW / 1500 rpm

Frame 100 L | 4 poles | IM B3 | Article No. 1LE0101-1AB42-2AA4

GENERAL DATA

Series / efficiency class	**1LE0101 / IE2**
Housing	**Cast iron**
Frame size	**100 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**33 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**2.55 kW**
Rated speed (50 Hz)	**1435 rpm**
Rated torque	**14.6 Nm**
Rated current	**4.8 A**
Power factor	**0.79**
Efficiency 4/4 | 3/4 | 2/4	**84.3 | 85 | 83.1 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**7 | 3 | 3.2**
Moment of inertia J	**0.0081 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0101, p. 24 (PDF 24)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0101 (IE2)

1LE0101-1AB42-2FA4

2.2 kW / 1500 rpm

Frame 100 L | 4 poles | IM B5 | Article No. 1LE0101-1AB42-2FA4

GENERAL DATA

Series / efficiency class	**1LE0101 / IE2**
Housing	**Cast iron**
Frame size	**100 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**33 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**2.55 kW**
Rated speed (50 Hz)	**1435 rpm**
Rated torque	**14.6 Nm**
Rated current	**4.8 A**
Power factor	**0.79**
Efficiency 4/4 | 3/4 | 2/4	**84.3 | 85 | 83.1 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**7 | 3 | 3.2**
Moment of inertia J	**0.0081 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0101, p. 24 (PDF 24)**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0101 (IE2)

1LE0101-1AB42-2KA4

2.2 kW / 1500 rpm

Frame 100 L | 4 poles | IM B14 | Article No. 1LE0101-1AB42-2KA4

GENERAL DATA

Series / efficiency class	**1LE0101 / IE2**
Housing	**Cast iron**
Frame size	**100 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**33 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**2.55 kW**
Rated speed (50 Hz)	**1435 rpm**
Rated torque	**14.6 Nm**
Rated current	**4.8 A**
Power factor	**0.79**
Efficiency 4/4 | 3/4 | 2/4	**84.3 | 85 | 83.1 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**7 | 3 | 3.2**
Moment of inertia J	**0.0081 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0101, p. 24 (PDF 24)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0101 (IE2)

1LE0101-1AB43-4AA4

2.2 kW / 1500 rpm

Frame 100 L | 4 poles | IM B3 | Article No. 1LE0101-1AB43-4AA4

GENERAL DATA

Series / efficiency class	**1LE0101 / IE2**
Housing	**Cast iron**
Frame size	**100 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**33 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**2.55 kW**
Rated speed (50 Hz)	**1435 rpm**
Rated torque	**14.6 Nm**
Rated current	**4.75 A**
Power factor	**0.79**
Efficiency 4/4 | 3/4 | 2/4	**84.3 | 85 | 83.1 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**7 | 3 | 3.2**
Moment of inertia J	**0.0081 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0101, p. 24 (PDF 24)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0101 (IE2)

1LE0101-1AB43-4FA4

2.2 kW / 1500 rpm

Frame 100 L | 4 poles | IM B5 | Article No. 1LE0101-1AB43-4FA4

GENERAL DATA

Series / efficiency class	**1LE0101 / IE2**
Housing	**Cast iron**
Frame size	**100 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**33 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**2.55 kW**
Rated speed (50 Hz)	**1435 rpm**
Rated torque	**14.6 Nm**
Rated current	**4.75 A**
Power factor	**0.79**
Efficiency 4/4 | 3/4 | 2/4	**84.3 | 85 | 83.1 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**7 | 3 | 3.2**
Moment of inertia J	**0.0081 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0101, p. 24 (PDF 24)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0101 (IE2)

1LE0101-1AB43-4KA4

2.2 kW / 1500 rpm

Frame 100 L | 4 poles | IM B14 | Article No. 1LE0101-1AB43-4KA4

GENERAL DATA

Series / efficiency class	**1LE0101 / IE2**
Housing	**Cast iron**
Frame size	**100 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**33 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**2.55 kW**
Rated speed (50 Hz)	**1435 rpm**
Rated torque	**14.6 Nm**
Rated current	**4.75 A**
Power factor	**0.79**
Efficiency 4/4 | 3/4 | 2/4	**84.3 | 85 | 83.1 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**7 | 3 | 3.2**
Moment of inertia J	**0.0081 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0101, p. 24 (PDF 24)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0101 (IE2)

1LE0101-1AB44-1AA4

2.2 kW / 1500 rpm

Frame 100 L | 4 poles | IM B3 | Article No. 1LE0101-1AB44-1AA4

GENERAL DATA

Series / efficiency class	**1LE0101 / IE2**
Housing	**Cast iron**
Frame size	**100 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**525 V D**
Net weight (IM B3)	**33 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**2.55 kW**
Rated speed (50 Hz)	**1435 rpm**
Rated torque	**14.6 Nm**
Rated current	**3.6 A**
Power factor	**0.79**
Efficiency 4/4 | 3/4 | 2/4	**84.3 | 85 | 83.1 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**7 | 3 | 3.2**
Moment of inertia J	**0.0081 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0101, p. 28 (PDF 28)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0101 (IE2)

1LE0101-1AB44-1FA4

2.2 kW / 1500 rpm

Frame 100 L | 4 poles | IM B5 | Article No. 1LE0101-1AB44-1FA4

GENERAL DATA

Series / efficiency class	**1LE0101 / IE2**
Housing	**Cast iron**
Frame size	**100 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**525 V D**
Net weight (IM B3)	**33 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**2.55 kW**
Rated speed (50 Hz)	**1435 rpm**
Rated torque	**14.6 Nm**
Rated current	**3.6 A**
Power factor	**0.79**
Efficiency 4/4 | 3/4 | 2/4	**84.3 | 85 | 83.1 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**7 | 3 | 3.2**
Moment of inertia J	**0.0081 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0101, p. 28 (PDF 28)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0101 (IE2)

1LE0101-1AB44-1KA4

2.2 kW / 1500 rpm

Frame 100 L | 4 poles | IM B14 | Article No. 1LE0101-1AB44-1KA4

GENERAL DATA

Series / efficiency class	**1LE0101 / IE2**
Housing	**Cast iron**
Frame size	**100 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**525 V D**
Net weight (IM B3)	**33 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**2.55 kW**
Rated speed (50 Hz)	**1435 rpm**
Rated torque	**14.6 Nm**
Rated current	**3.6 A**
Power factor	**0.79**
Efficiency 4/4 | 3/4 | 2/4	**84.3 | 85 | 83.1 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**7 | 3 | 3.2**
Moment of inertia J	**0.0081 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0101, p. 28 (PDF 28)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1501 (IE2)

1LE1501-1AB42-2AA4

2.2 kW / 1500 rpm

Frame 100 L | 4 poles | IM B3 | Article No. 1LE1501-1AB42-2AA4

GENERAL DATA

Series / efficiency class	**1LE1501 / IE2**
Housing	**Cast iron**
Frame size	**100 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**32 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**2.55 kW**
Rated speed (50 Hz)	**1455 rpm**
Rated torque	**14 Nm**
Rated current	**4.65 A**
Power factor	**0.81**
Efficiency 4/4 | 3/4 | 2/4	**84.3 | 85.1 | 84.2 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**6.9 | 2.1 | 3.3**
Moment of inertia J	**0.0086 kgm2**
Sound pressure / power LpfA | LWA	**60 | 72 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1501, p. 2/33 (PDF 151)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1501 (IE2)

1LE1501-1AB42-2FA4

2.2 kW / 1500 rpm

Frame 100 L | 4 poles | IM B5 | Article No. 1LE1501-1AB42-2FA4

GENERAL DATA

Series / efficiency class	**1LE1501 / IE2**
Housing	**Cast iron**
Frame size	**100 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**32 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**2.55 kW**
Rated speed (50 Hz)	**1455 rpm**
Rated torque	**14 Nm**
Rated current	**4.65 A**
Power factor	**0.81**
Efficiency 4/4 | 3/4 | 2/4	**84.3 | 85.1 | 84.2 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**6.9 | 2.1 | 3.3**
Moment of inertia J	**0.0086 kgm2**
Sound pressure / power LpfA | LWA	**60 | 72 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1501, p. 2/33 (PDF 151)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1501 (IE2)

1LE1501-1AB42-2KA4

2.2 kW / 1500 rpm

Frame 100 L | 4 poles | IM B14 | Article No. 1LE1501-1AB42-2KA4

GENERAL DATA

Series / efficiency class	**1LE1501 / IE2**
Housing	**Cast iron**
Frame size	**100 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**32 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**2.55 kW**
Rated speed (50 Hz)	**1455 rpm**
Rated torque	**14 Nm**
Rated current	**4.65 A**
Power factor	**0.81**
Efficiency 4/4 | 3/4 | 2/4	**84.3 | 85.1 | 84.2 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**6.9 | 2.1 | 3.3**
Moment of inertia J	**0.0086 kgm2**
Sound pressure / power LpfA | LWA	**60 | 72 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1501, p. 2/33 (PDF 151)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1503 (IE3)

1LE1503-1AB42-2AA4

2.2 kW / 1500 rpm

Frame 100 L | 4 poles | IM B3 | Article No. 1LE1503-1AB42-2AA4

GENERAL DATA

Series / efficiency class	**1LE1503 / IE3**
Housing	**Cast iron**
Frame size	**100 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**40 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**2.55 kW**
Rated speed (50 Hz)	**1455 rpm**
Rated torque	**14.4 Nm**
Rated current	**4.45 A**
Power factor	**0.82**
Efficiency 4/4 | 3/4 | 2/4	**86.7 | 87.2 | 86.3 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**8.3 | 3 | 3.8**
Moment of inertia J	**0.0101 kgm2**
Sound pressure / power LpfA | LWA	**67 | 75 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (09/2023), table 1LE1503, p. 3/20**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1503 (IE3)

1LE1503-1AB42-2FA4

2.2 kW / 1500 rpm

Frame 100 L | 4 poles | IM B5 | Article No. 1LE1503-1AB42-2FA4

GENERAL DATA

Series / efficiency class	**1LE1503 / IE3**
Housing	**Cast iron**
Frame size	**100 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**40 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**2.55 kW**
Rated speed (50 Hz)	**1455 rpm**
Rated torque	**14.4 Nm**
Rated current	**4.45 A**
Power factor	**0.82**
Efficiency 4/4 | 3/4 | 2/4	**86.7 | 87.2 | 86.3 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**8.3 | 3 | 3.8**
Moment of inertia J	**0.0101 kgm2**
Sound pressure / power LpfA | LWA	**67 | 75 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (09/2023), table 1LE1503, p. 3/20**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1543 (IE3)

1LE1543-1AB42-2AA4

2.2 kW / 1500 rpm

Frame 100 L | 4 poles | IM B3 | Article No. 1LE1543-1AB42-2AA4

GENERAL DATA

Series / efficiency class	**1LE1543 / IE3**
Housing	**Cast iron**
Frame size	**100 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**40 kg**

ELECTRICAL DATA - CATALOG VALUES AT 60 HZ (APAC LINE)

Rated power (P50 rating)	**2.2 kW (about 3 HP)**
Rated power (P60 rating)	**2.55 kW**
Rated speed (60 Hz)	**1760 rpm**
Rated torque (60 Hz)	**11.9 Nm**
Rated current (460 V, 60 Hz)	**3.85 A**
Power factor (60 Hz)	**0.8**
Efficiency 4/4 | 3/4 | 2/4 (60 Hz)	**89.5 | 89.5 | 88 %**
I_LR/I_N | T_LR/T_N | T_B/T_N (60 Hz)	**9.9 | 3.5 | 4.6**
Moment of inertia J	**0.0101 kgm2**
Sound pressure / power LpfA | LWA (60 Hz)	**70 | 78 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (09/2023), table 1LE1543, p. 3/66**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
APAC Line: the catalog lists operating values at 60 Hz only; 50 Hz speed/efficiency are not listed (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1543 (IE3)

1LE1543-1AB42-2FA4

2.2 kW / 1500 rpm

Frame 100 L | 4 poles | IM B5 | Article No. 1LE1543-1AB42-2FA4

GENERAL DATA

Series / efficiency class	**1LE1543 / IE3**
Housing	**Cast iron**
Frame size	**100 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**40 kg**

ELECTRICAL DATA - CATALOG VALUES AT 60 HZ (APAC LINE)

Rated power (P50 rating)	**2.2 kW (about 3 HP)**
Rated power (P60 rating)	**2.55 kW**
Rated speed (60 Hz)	**1760 rpm**
Rated torque (60 Hz)	**11.9 Nm**
Rated current (460 V, 60 Hz)	**3.85 A**
Power factor (60 Hz)	**0.8**
Efficiency 4/4 | 3/4 | 2/4 (60 Hz)	**89.5 | 89.5 | 88 %**
I_LR/I_N | T_LR/T_N | T_B/T_N (60 Hz)	**9.9 | 3.5 | 4.6**
Moment of inertia J	**0.0101 kgm2**
Sound pressure / power LpfA | LWA (60 Hz)	**70 | 78 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (09/2023), table 1LE1543, p. 3/66**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
APAC Line: the catalog lists operating values at 60 Hz only; 50 Hz speed/efficiency are not listed (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1504 (IE4)

1LE1504-1AB42-2AA4

2.2 kW / 1500 rpm

Frame 100 L | 4 poles | IM B3 | Article No. 1LE1504-1AB42-2AA4

GENERAL DATA

Series / efficiency class	**1LE1504 / IE4**
Housing	**Cast iron**
Frame size	**100 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**41 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**2.55 kW**
Rated speed (50 Hz)	**1465 rpm**
Rated torque	**14 Nm**
Rated current	**4.5 A**
Power factor	**0.79**
Efficiency 4/4 | 3/4 | 2/4	**89.5 | 89.6 | 88.3 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**8.5 | 3.3 | 4.7**
Moment of inertia J	**0.014 kgm2**
Sound pressure / power LpfA | LWA	**59 | 71 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1504, p. 2/10 (PDF 128)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1504 (IE4)

1LE1504-1AB42-2FA4

2.2 kW / 1500 rpm

Frame 100 L | 4 poles | IM B5 | Article No. 1LE1504-1AB42-2FA4

GENERAL DATA

Series / efficiency class	**1LE1504 / IE4**
Housing	**Cast iron**
Frame size	**100 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**41 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**2.55 kW**
Rated speed (50 Hz)	**1465 rpm**
Rated torque	**14 Nm**
Rated current	**4.5 A**
Power factor	**0.79**
Efficiency 4/4 | 3/4 | 2/4	**89.5 | 89.6 | 88.3 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**8.5 | 3.3 | 4.7**
Moment of inertia J	**0.014 kgm2**
Sound pressure / power LpfA | LWA	**59 | 71 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1504, p. 2/10 (PDF 128)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1504 (IE4)

1LE1504-1AB42-2KA4

2.2 kW / 1500 rpm

Frame 100 L | 4 poles | IM B14 | Article No. 1LE1504-1AB42-2KA4

GENERAL DATA

Series / efficiency class	**1LE1504 / IE4**
Housing	**Cast iron**
Frame size	**100 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**41 kg**

ELECTRICAL DATA

Rated power 50 Hz	**2.2 kW (about 3 HP)**
Rated power 60 Hz	**2.55 kW**
Rated speed (50 Hz)	**1465 rpm**
Rated torque	**14 Nm**
Rated current	**4.5 A**
Power factor	**0.79**
Efficiency 4/4 | 3/4 | 2/4	**89.5 | 89.6 | 88.3 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**8.5 | 3.3 | 4.7**
Moment of inertia J	**0.014 kgm2**
Sound pressure / power LpfA | LWA	**59 | 71 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1504, p. 2/10 (PDF 128)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).