Data sheets - Siemens SIMOTICS GP motors

200 kW / 1500 rpm - 12 article numbers in this file

Article No.	Page
1LE0102-3AB73-4AA4	2
1LE0102-3AB73-4FA4	3
1LE0102-3AB74-1AA4	4
1LE0102-3AB74-1FA4	5
1LE0101-3AB73-4AB4	6
1LE0101-3AB73-4FB4	7
1LE0101-3AB74-1AB4	8
1LE0101-3AB74-1FB4	9
1LE1501-3AB53-4AA4	10
1LE1503-3AB53-4AA4	11
1LE1543-3AB53-4AA4	12
1LE1504-3AB53-4AA4	13

محور نیرو

Tel: 0935 186 4634

info@mehvarniro.com | mehvarniro.com

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0102 (IE1)

1LE0102-3AB73-4AA4

200 kW / 1500 rpm

Frame 315 L | 4 poles | IM B3 | Article No. 1LE0102-3AB73-4AA4

GENERAL DATA

Series / efficiency class	**1LE0102 / IE1**
Housing	**Cast iron**
Frame size	**315 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**1070 kg**

ELECTRICAL DATA

Rated power 50 Hz	**200 kW (about 270 HP)**
Rated power 60 Hz	**230 kW**
Rated speed (50 Hz)	**1488 rpm**
Rated torque	**1285 Nm**
Rated current	**345 A**
Power factor	**0.88**
Efficiency 4/4 | 3/4 | 2/4	**94 | 94.3 | 94.1 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**7.4 | 3 | 3**
Moment of inertia J	**3.7 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0102, p. 21 (PDF 21)**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0102 (IE1)

1LE0102-3AB73-4FA4

200 kW / 1500 rpm

Frame 315 L | 4 poles | IM B5 | Article No. 1LE0102-3AB73-4FA4

GENERAL DATA

Series / efficiency class	**1LE0102 / IE1**
Housing	**Cast iron**
Frame size	**315 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**1070 kg**

ELECTRICAL DATA

Rated power 50 Hz	**200 kW (about 270 HP)**
Rated power 60 Hz	**230 kW**
Rated speed (50 Hz)	**1488 rpm**
Rated torque	**1285 Nm**
Rated current	**345 A**
Power factor	**0.88**
Efficiency 4/4 | 3/4 | 2/4	**94 | 94.3 | 94.1 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**7.4 | 3 | 3**
Moment of inertia J	**3.7 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0102, p. 21 (PDF 21)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0102 (IE1)

1LE0102-3AB74-1AA4

200 kW / 1500 rpm

Frame 315 L | 4 poles | IM B3 | Article No. 1LE0102-3AB74-1AA4

GENERAL DATA

Series / efficiency class	**1LE0102 / IE1**
Housing	**Cast iron**
Frame size	**315 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**525 V D**
Net weight (IM B3)	**1070 kg**

ELECTRICAL DATA

Rated power 50 Hz	**200 kW (about 270 HP)**
Rated power 60 Hz	**230 kW**
Rated speed (50 Hz)	**1488 rpm**
Rated torque	**1285 Nm**
Rated current	**265 A**
Power factor	**0.88**
Efficiency 4/4 | 3/4 | 2/4	**94 | 94.3 | 94.1 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**7.4 | 3 | 3**
Moment of inertia J	**3.7 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0102, p. 27 (PDF 27)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0102 (IE1)

1LE0102-3AB74-1FA4

200 kW / 1500 rpm

Frame 315 L | 4 poles | IM B5 | Article No. 1LE0102-3AB74-1FA4

GENERAL DATA

Series / efficiency class	**1LE0102 / IE1**
Housing	**Cast iron**
Frame size	**315 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**525 V D**
Net weight (IM B3)	**1070 kg**

ELECTRICAL DATA

Rated power 50 Hz	**200 kW (about 270 HP)**
Rated power 60 Hz	**230 kW**
Rated speed (50 Hz)	**1488 rpm**
Rated torque	**1285 Nm**
Rated current	**265 A**
Power factor	**0.88**
Efficiency 4/4 | 3/4 | 2/4	**94 | 94.3 | 94.1 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**7.4 | 3 | 3**
Moment of inertia J	**3.7 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0102, p. 27 (PDF 27)**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0101 (IE2)

1LE0101-3AB73-4AB4

200 kW / 1500 rpm

Frame 315 L | 4 poles | IM B3 | Article No. 1LE0101-3AB73-4AB4

GENERAL DATA

Series / efficiency class	**1LE0101 / IE2**
Housing	**Cast iron**
Frame size	**315 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**1080 kg**

ELECTRICAL DATA

Rated power 50 Hz	**200 kW (about 270 HP)**
Rated power 60 Hz	**230 kW**
Rated speed (50 Hz)	**1488 rpm**
Rated torque	**1284 Nm**
Rated current	**345 A**
Power factor	**0.88**
Efficiency 4/4 | 3/4 | 2/4	**95.1 | 95.1 | 95.1 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**7.4 | 3 | 3**
Moment of inertia J	**3.7 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0101, p. 24 (PDF 24)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0101 (IE2)

1LE0101-3AB73-4FB4

200 kW / 1500 rpm

Frame 315 L | 4 poles | IM B5 | Article No. 1LE0101-3AB73-4FB4

GENERAL DATA

Series / efficiency class	**1LE0101 / IE2**
Housing	**Cast iron**
Frame size	**315 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**1080 kg**

ELECTRICAL DATA

Rated power 50 Hz	**200 kW (about 270 HP)**
Rated power 60 Hz	**230 kW**
Rated speed (50 Hz)	**1488 rpm**
Rated torque	**1284 Nm**
Rated current	**345 A**
Power factor	**0.88**
Efficiency 4/4 | 3/4 | 2/4	**95.1 | 95.1 | 95.1 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**7.4 | 3 | 3**
Moment of inertia J	**3.7 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0101, p. 24 (PDF 24)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0101 (IE2)

1LE0101-3AB74-1AB4

200 kW / 1500 rpm

Frame 315 L | 4 poles | IM B3 | Article No. 1LE0101-3AB74-1AB4

GENERAL DATA

Series / efficiency class	**1LE0101 / IE2**
Housing	**Cast iron**
Frame size	**315 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**525 V D**
Net weight (IM B3)	**1080 kg**

ELECTRICAL DATA

Rated power 50 Hz	**200 kW (about 270 HP)**
Rated power 60 Hz	**230 kW**
Rated speed (50 Hz)	**1488 rpm**
Rated torque	**1284 Nm**
Rated current	**265 A**
Power factor	**0.88**
Efficiency 4/4 | 3/4 | 2/4	**95.1 | 95.1 | 95.1 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**7.4 | 3 | 3**
Moment of inertia J	**3.7 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0101, p. 29 (PDF 29)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0101 (IE2)

1LE0101-3AB74-1FB4

200 kW / 1500 rpm

Frame 315 L | 4 poles | IM B5 | Article No. 1LE0101-3AB74-1FB4

GENERAL DATA

Series / efficiency class	**1LE0101 / IE2**
Housing	**Cast iron**
Frame size	**315 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**525 V D**
Net weight (IM B3)	**1080 kg**

ELECTRICAL DATA

Rated power 50 Hz	**200 kW (about 270 HP)**
Rated power 60 Hz	**230 kW**
Rated speed (50 Hz)	**1488 rpm**
Rated torque	**1284 Nm**
Rated current	**265 A**
Power factor	**0.88**
Efficiency 4/4 | 3/4 | 2/4	**95.1 | 95.1 | 95.1 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**7.4 | 3 | 3**
Moment of inertia J	**3.7 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0101, p. 29 (PDF 29)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1501 (IE2)

1LE1501-3AB53-4AA4

200 kW / 1500 rpm

Frame 315 L | 4 poles | IM B3 | Article No. 1LE1501-3AB53-4AA4

GENERAL DATA

Series / efficiency class	**1LE1501 / IE2**
Housing	**Cast iron**
Frame size	**315 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**1140 kg**

ELECTRICAL DATA

Rated power 50 Hz	**200 kW (about 270 HP)**
Rated power 60 Hz	**230 kW**
Rated speed (50 Hz)	**1490 rpm**
Rated torque	**1282 Nm**
Rated current	**350 A**
Power factor	**0.87**
Efficiency 4/4 | 3/4 | 2/4	**95.1 | 95.3 | 94.7 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**7.5 | 3.1 | 3.2**
Moment of inertia J	**3.5 kgm2**
Sound pressure / power LpfA | LWA	**77 | 92 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1501, p. 2/33 (PDF 151)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1503 (IE3)

1LE1503-3AB53-4AA4

200 kW / 1500 rpm

Frame 315 L | 4 poles | IM B3 | Article No. 1LE1503-3AB53-4AA4

GENERAL DATA

Series / efficiency class	**1LE1503 / IE3**
Housing	**Cast iron**
Frame size	**315 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**1190 kg**

ELECTRICAL DATA

Rated power 50 Hz	**200 kW (about 270 HP)**
Rated power 60 Hz	**230 kW**
Rated speed (50 Hz)	**1488 rpm**
Rated torque	**1284 Nm**
Rated current	**340 A**
Power factor	**0.88**
Efficiency 4/4 | 3/4 | 2/4	**96 | 96.3 | 96.1 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**7.4 | 3.2 | 3**
Moment of inertia J	**3.7 kgm2**
Sound pressure / power LpfA | LWA	**73 | 87 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1503, p. 2/18 (PDF 136)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1543 (IE3)

1LE1543-3AB53-4AA4

200 kW / 1500 rpm

Frame 315 L | 4 poles | IM B3 | Article No. 1LE1543-3AB53-4AA4

GENERAL DATA

Series / efficiency class	**1LE1543 / IE3**
Housing	**Cast iron**
Frame size	**315 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**1190 kg**

ELECTRICAL DATA - CATALOG VALUES AT 60 HZ (APAC LINE)

Rated power (P50 rating)	**200 kW (about 270 HP)**
Rated power (P60 rating)	**230 kW**
Rated speed (60 Hz)	**1791 rpm**
Rated torque (60 Hz)	**1066 Nm**
Rated current (460 V, 60 Hz)	**300 A**
Power factor (60 Hz)	**0.87**
Efficiency 4/4 | 3/4 | 2/4 (60 Hz)	**96.2 | 96.2 | 95.5 %**
I_LR/I_N | T_LR/T_N | T_B/T_N (60 Hz)	**8.7 | 3.5 | 3.2**
Moment of inertia J	**3.7 kgm2**
Sound pressure / power LpfA | LWA (60 Hz)	**78 | 93 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1543, p. 2/58 (PDF 176)**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
APAC Line: the catalog lists operating values at 60 Hz only; 50 Hz speed/efficiency are not listed (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1504 (IE4)

1LE1504-3AB53-4AA4

200 kW / 1500 rpm

Frame 315 L | 4 poles | IM B3 | Article No. 1LE1504-3AB53-4AA4

GENERAL DATA

Series / efficiency class	**1LE1504 / IE4**
Housing	**Cast iron**
Frame size	**315 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**1300 kg**

ELECTRICAL DATA

Rated power 50 Hz	**200 kW (about 270 HP)**
Rated power 60 Hz	**230 kW**
Rated speed (50 Hz)	**1490 rpm**
Rated torque	**1282 Nm**
Rated current	**345 A**
Power factor	**0.86**
Efficiency 4/4 | 3/4 | 2/4	**96.7 | 96.9 | 96.6 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**9.2 | 3.8 | 3.4**
Moment of inertia J	**4.4 kgm2**
Sound pressure / power LpfA | LWA	**76 | 90 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1504, p. 2/10 (PDF 128)**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).