Data sheets - Siemens SIMOTICS GP motors

30 kW / 1000 rpm - 28 article numbers in this file

Article No.	Page
1LE1502-2BC23-4AA4	2
1LE1502-2BC23-4FA4	3
1LE1001-2AC63-4AA4	4
1LE1001-2AC63-4FA4	5
1LE1003-2AC63-4AA4	6
1LE1003-2AC63-4FA4	7
1LE0102-2BC23-4AA4	8
1LE0102-2BC23-4FA4	9
1LE0102-2BC24-1AA4	10
1LE0102-2BC24-1FA4	11
1LE1501-2BC23-4AA4	12
1LE1501-2BC23-4FA4	13
1LE1502-2AC63-4AA4	14
1LE1502-2AC63-4FA4	15
1LE1541-2BC23-4FA4	16
1LE0101-2BC23-4AB4	17
1LE0101-2BC23-4FB4	18
1LE0101-2BC24-1AB4	19
1LE0101-2BC24-1FB4	20
1LE1501-2AC63-4AA4	21
1LE1501-2AC63-4FA4	22
1LE1503-2BC23-4AA4	23
1LE1503-2BC23-4FA4	24
1LE1503-2AC63-4AA4	25
1LE1503-2AC63-4FA4	26
1LE1541-2AC63-4FA4	27
1LE1543-2AC63-4AA4	28
1LE1543-2AC63-4FA4	29

محور نیرو

Tel: 0935 186 4634

info@mehvarniro.com | mehvarniro.com

Data sheet

1LE1502-2BC23-4AA4

SIMOTICS GP low-voltage motor - cast-iron series 1LE1502 Basic Line (IE1)

30 kW / 1000 rpm

Frame size 225 M | Article No. 1LE1502-2BC23-4AA4 | mounting IM B3

GENERAL DATA

Motor series	**1LE1502 Basic Line (cast iron)**
Article No.	**1LE1502-2BC23-4AA4**
Frame size	**225 M**
Number of poles	**6**
Housing material	**Cast iron**
Degree of protection	**IP55**
Cooling	**Self-ventilated (IC 411)**
Insulation / utilization	**Thermal class 155 (F) / utilized to 130 (B)**
Duty type	**S1 (continuous duty)**
Rotor	**Squirrel-cage**
Efficiency class (IEC 60034-30)	**IE1**
Voltage / connection	**400 V Δ / 690 V Y (50 Hz), 460 V Δ (60 Hz)**
Type of construction	**IM B3 (basic type, without flange)**
Net weight (IM B3)	**270 kg**

ELECTRICAL DATA - 400 V, 50 HZ

Rated power, 50 Hz	**30 kW (40 HP)**
Rated speed, 50 Hz	**978 rpm (synchronous 1000 rpm)**
Rated torque	**293 Nm**
Rated current at 400 V	**59 A**
Power factor cos φ	**0.82**
Efficiency at 4/4 | 3/4 | 2/4 load	**90.2 | 91.0 | 90.7 %**
Locked-rotor current ratio (I_LR/I_N)	**6**
Locked-rotor torque ratio (T_LR/T_N)	**2.7**
Breakdown torque ratio (T_B/T_N)	**2.5**
Moment of inertia J	**0.49 kgm²**
Sound pressure level LpfA (50 Hz)	**65 dB(A)**
Sound power level LWA (50 Hz)	**77 dB(A)**

60 HZ OPERATION

Rated power at 60 Hz (460 V)	**36 kW**
Synchronous speed at 60 Hz	**1200 rpm**
Speed / efficiency / current at 60 Hz	**not listed in the catalog (DT Configurator)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Source: Siemens Catalog D 81.1 (05/2018), p. 2/50. Dimensions: see the same catalog.
Compiled from the manufacturer's catalog data for reference. It is not an official Siemens document - verify against the current Siemens data sheet before ordering.
Data at rated power, 400 V / 50 Hz, ambient 40 °C, altitude up to 1000 m.

Data sheet

1LE1502-2BC23-4FA4

SIMOTICS GP low-voltage motor - cast-iron series 1LE1502 Basic Line (IE1)

30 kW / 1000 rpm

Frame size 225 M | Article No. 1LE1502-2BC23-4FA4 | mounting IM B5

GENERAL DATA

Motor series	**1LE1502 Basic Line (cast iron)**
Article No.	**1LE1502-2BC23-4FA4**
Frame size	**225 M**
Number of poles	**6**
Housing material	**Cast iron**
Degree of protection	**IP55**
Cooling	**Self-ventilated (IC 411)**
Insulation / utilization	**Thermal class 155 (F) / utilized to 130 (B)**
Duty type	**S1 (continuous duty)**
Rotor	**Squirrel-cage**
Efficiency class (IEC 60034-30)	**IE1**
Voltage / connection	**400 V Δ / 690 V Y (50 Hz), 460 V Δ (60 Hz)**
Type of construction	**IM B5 (flange)**
Net weight (IM B3)	**270 kg**

ELECTRICAL DATA - 400 V, 50 HZ

Rated power, 50 Hz	**30 kW (40 HP)**
Rated speed, 50 Hz	**978 rpm (synchronous 1000 rpm)**
Rated torque	**293 Nm**
Rated current at 400 V	**59 A**
Power factor cos φ	**0.82**
Efficiency at 4/4 | 3/4 | 2/4 load	**90.2 | 91.0 | 90.7 %**
Locked-rotor current ratio (I_LR/I_N)	**6**
Locked-rotor torque ratio (T_LR/T_N)	**2.7**
Breakdown torque ratio (T_B/T_N)	**2.5**
Moment of inertia J	**0.49 kgm²**
Sound pressure level LpfA (50 Hz)	**65 dB(A)**
Sound power level LWA (50 Hz)	**77 dB(A)**

60 HZ OPERATION

Rated power at 60 Hz (460 V)	**36 kW**
Synchronous speed at 60 Hz	**1200 rpm**
Speed / efficiency / current at 60 Hz	**not listed in the catalog (DT Configurator)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Source: Siemens Catalog D 81.1 (05/2018), p. 2/50. Dimensions: see the same catalog.
Compiled from the manufacturer's catalog data for reference. It is not an official Siemens document - verify against the current Siemens data sheet before ordering.
Data at rated power, 400 V / 50 Hz, ambient 40 °C, altitude up to 1000 m.

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1001 (IE2)

1LE1001-2AC63-4AA4

30 kW / 1000 rpm

Frame 200 L | 6 poles | IM B3 | Article No. 1LE1001-2AC63-4AA4

GENERAL DATA

Series / efficiency class	**1LE1001 / IE2**
Housing	**Aluminum**
Frame size	**200 L**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**192 kg**

ELECTRICAL DATA

Rated power 50 Hz	**30 kW (about 40 HP)**
Rated power 60 Hz	**34.5 kW**
Rated speed (50 Hz)	**975 rpm**
Rated torque	**294 Nm**
Rated current	**61 A**
Power factor	**0.77**
Efficiency 4/4 | 3/4 | 2/4	**91.7 | 92.5 | 92.4 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**6.3 | 2.6 | 2.7**
Moment of inertia J	**0.381 kgm2**
Sound pressure / power LpfA | LWA	**68 | 75 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1001, p. 2/31 (PDF 149)**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1001 (IE2)

1LE1001-2AC63-4FA4

30 kW / 1000 rpm

Frame 200 L | 6 poles | IM B5 | Article No. 1LE1001-2AC63-4FA4

GENERAL DATA

Series / efficiency class	**1LE1001 / IE2**
Housing	**Aluminum**
Frame size	**200 L**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**192 kg**

ELECTRICAL DATA

Rated power 50 Hz	**30 kW (about 40 HP)**
Rated power 60 Hz	**34.5 kW**
Rated speed (50 Hz)	**975 rpm**
Rated torque	**294 Nm**
Rated current	**61 A**
Power factor	**0.77**
Efficiency 4/4 | 3/4 | 2/4	**91.7 | 92.5 | 92.4 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**6.3 | 2.6 | 2.7**
Moment of inertia J	**0.381 kgm2**
Sound pressure / power LpfA | LWA	**68 | 75 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1001, p. 2/31 (PDF 149)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1003 (IE3)

1LE1003-2AC63-4AA4

30 kW / 1000 rpm

Frame 200 L | 6 poles | IM B3 | Article No. 1LE1003-2AC63-4AA4

GENERAL DATA

Series / efficiency class	**1LE1003 / IE3**
Housing	**Aluminum**
Frame size	**200 L**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**220 kg**

ELECTRICAL DATA

Rated power 50 Hz	**30 kW (about 40 HP)**
Rated power 60 Hz	**not listed (catalog 09/2023)**
Rated speed (50 Hz)	**978 rpm**
Rated torque	**295 Nm**
Rated current	**59 A**
Power factor	**0.79**
Efficiency 4/4 | 3/4 | 2/4	**92.9 | 93.6 | 93.7 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**6.5 | 2.8 | 2.8**
Moment of inertia J	**0.421 kgm2**
Sound pressure / power LpfA | LWA	**61 | 68 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (09/2023), table 1LE1003, p. 3/17**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1003 (IE3)

1LE1003-2AC63-4FA4

30 kW / 1000 rpm

Frame 200 L | 6 poles | IM B5 | Article No. 1LE1003-2AC63-4FA4

GENERAL DATA

Series / efficiency class	**1LE1003 / IE3**
Housing	**Aluminum**
Frame size	**200 L**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**220 kg**

ELECTRICAL DATA

Rated power 50 Hz	**30 kW (about 40 HP)**
Rated power 60 Hz	**not listed (catalog 09/2023)**
Rated speed (50 Hz)	**978 rpm**
Rated torque	**295 Nm**
Rated current	**59 A**
Power factor	**0.79**
Efficiency 4/4 | 3/4 | 2/4	**92.9 | 93.6 | 93.7 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**6.5 | 2.8 | 2.8**
Moment of inertia J	**0.421 kgm2**
Sound pressure / power LpfA | LWA	**61 | 68 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (09/2023), table 1LE1003, p. 3/17**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0102 (IE1)

1LE0102-2BC23-4AA4

30 kW / 1000 rpm

Frame 225 M | 6 poles | IM B3 | Article No. 1LE0102-2BC23-4AA4

GENERAL DATA

Series / efficiency class	**1LE0102 / IE1**
Housing	**Cast iron**
Frame size	**225 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**290 kg**

ELECTRICAL DATA

Rated power 50 Hz	**30 kW (about 40 HP)**
Rated power 60 Hz	**36 kW**
Rated speed (50 Hz)	**978 rpm**
Rated torque	**293 Nm**
Rated current	**58 A**
Power factor	**0.83**
Efficiency 4/4 | 3/4 | 2/4	**90.2 | 91.4 | 90.5 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**6.7 | 2.4 | 2.8**
Moment of inertia J	**0.6 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0102, p. 22 (PDF 22)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0102 (IE1)

1LE0102-2BC23-4FA4

30 kW / 1000 rpm

Frame 225 M | 6 poles | IM B5 | Article No. 1LE0102-2BC23-4FA4

GENERAL DATA

Series / efficiency class	**1LE0102 / IE1**
Housing	**Cast iron**
Frame size	**225 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**290 kg**

ELECTRICAL DATA

Rated power 50 Hz	**30 kW (about 40 HP)**
Rated power 60 Hz	**36 kW**
Rated speed (50 Hz)	**978 rpm**
Rated torque	**293 Nm**
Rated current	**58 A**
Power factor	**0.83**
Efficiency 4/4 | 3/4 | 2/4	**90.2 | 91.4 | 90.5 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**6.7 | 2.4 | 2.8**
Moment of inertia J	**0.6 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0102, p. 22 (PDF 22)**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0102 (IE1)

1LE0102-2BC24-1AA4

30 kW / 1000 rpm

Frame 225 M | 6 poles | IM B3 | Article No. 1LE0102-2BC24-1AA4

GENERAL DATA

Series / efficiency class	**1LE0102 / IE1**
Housing	**Cast iron**
Frame size	**225 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**525 V D**
Net weight (IM B3)	**290 kg**

ELECTRICAL DATA

Rated power 50 Hz	**30 kW (about 40 HP)**
Rated power 60 Hz	**36 kW**
Rated speed (50 Hz)	**978 rpm**
Rated torque	**293 Nm**
Rated current	**44 A**
Power factor	**0.83**
Efficiency 4/4 | 3/4 | 2/4	**90.2 | 91.4 | 90.5 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**6.7 | 2.4 | 2.8**
Moment of inertia J	**0.6 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0102, p. 27 (PDF 27)**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0102 (IE1)

1LE0102-2BC24-1FA4

30 kW / 1000 rpm

Frame 225 M | 6 poles | IM B5 | Article No. 1LE0102-2BC24-1FA4

GENERAL DATA

Series / efficiency class	**1LE0102 / IE1**
Housing	**Cast iron**
Frame size	**225 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**525 V D**
Net weight (IM B3)	**290 kg**

ELECTRICAL DATA

Rated power 50 Hz	**30 kW (about 40 HP)**
Rated power 60 Hz	**36 kW**
Rated speed (50 Hz)	**978 rpm**
Rated torque	**293 Nm**
Rated current	**44 A**
Power factor	**0.83**
Efficiency 4/4 | 3/4 | 2/4	**90.2 | 91.4 | 90.5 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**6.7 | 2.4 | 2.8**
Moment of inertia J	**0.6 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0102, p. 27 (PDF 27)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1501 (IE2)

1LE1501-2BC23-4AA4

30 kW / 1000 rpm

Frame 225 M | 6 poles | IM B3 | Article No. 1LE1501-2BC23-4AA4

GENERAL DATA

Series / efficiency class	**1LE1501 / IE2**
Housing	**Cast iron**
Frame size	**225 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**300 kg**

ELECTRICAL DATA

Rated power 50 Hz	**30 kW (about 40 HP)**
Rated power 60 Hz	**36 kW**
Rated speed (50 Hz)	**980 rpm**
Rated torque	**292 Nm**
Rated current	**57 A**
Power factor	**0.83**
Efficiency 4/4 | 3/4 | 2/4	**91.7 | 92.5 | 92.3 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5.6 | 2.5 | 2.7**
Moment of inertia J	**0.58 kgm2**
Sound pressure / power LpfA | LWA	**65 | 78 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1501, p. 2/34 (PDF 152)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1501 (IE2)

1LE1501-2BC23-4FA4

30 kW / 1000 rpm

Frame 225 M | 6 poles | IM B5 | Article No. 1LE1501-2BC23-4FA4

GENERAL DATA

Series / efficiency class	**1LE1501 / IE2**
Housing	**Cast iron**
Frame size	**225 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**300 kg**

ELECTRICAL DATA

Rated power 50 Hz	**30 kW (about 40 HP)**
Rated power 60 Hz	**36 kW**
Rated speed (50 Hz)	**980 rpm**
Rated torque	**292 Nm**
Rated current	**57 A**
Power factor	**0.83**
Efficiency 4/4 | 3/4 | 2/4	**91.7 | 92.5 | 92.3 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5.6 | 2.5 | 2.7**
Moment of inertia J	**0.58 kgm2**
Sound pressure / power LpfA | LWA	**65 | 78 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1501, p. 2/34 (PDF 152)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1502 (IE1)

1LE1502-2AC63-4AA4

30 kW / 1000 rpm

Frame 200 L | 6 poles | IM B3 | Article No. 1LE1502-2AC63-4AA4

GENERAL DATA

Series / efficiency class	**1LE1502 / IE1**
Housing	**Cast iron**
Frame size	**200 L**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**245 kg**

ELECTRICAL DATA

Rated power 50 Hz	**30 kW (about 40 HP)**
Rated power 60 Hz	**34.5 kW**
Rated speed (50 Hz)	**975 rpm**
Rated torque	**294 Nm**
Rated current	**62 A**
Power factor	**0.78**
Efficiency 4/4 | 3/4 | 2/4	**90.2 | 91.4 | 91.7 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**6 | 2.6 | 2.7**
Moment of inertia J	**0.381 kgm2**
Sound pressure / power LpfA | LWA	**61 | 75 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1502, p. 2/53 (PDF 171)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1502 (IE1)

1LE1502-2AC63-4FA4

30 kW / 1000 rpm

Frame 200 L | 6 poles | IM B5 | Article No. 1LE1502-2AC63-4FA4

GENERAL DATA

Series / efficiency class	**1LE1502 / IE1**
Housing	**Cast iron**
Frame size	**200 L**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**245 kg**

ELECTRICAL DATA

Rated power 50 Hz	**30 kW (about 40 HP)**
Rated power 60 Hz	**34.5 kW**
Rated speed (50 Hz)	**975 rpm**
Rated torque	**294 Nm**
Rated current	**62 A**
Power factor	**0.78**
Efficiency 4/4 | 3/4 | 2/4	**90.2 | 91.4 | 91.7 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**6 | 2.6 | 2.7**
Moment of inertia J	**0.381 kgm2**
Sound pressure / power LpfA | LWA	**61 | 75 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1502, p. 2/53 (PDF 171)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1541 (IE2)

1LE1541-2BC23-4FA4

30 kW / 1000 rpm

Frame 225 M | 6 poles | IM B5 | Article No. 1LE1541-2BC23-4FA4

GENERAL DATA

Series / efficiency class	**1LE1541 / IE2**
Housing	**Cast iron**
Frame size	**225 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**300 kg**

ELECTRICAL DATA - CATALOG VALUES AT 60 HZ (APAC LINE)

Rated power (P50 rating)	**30 kW (about 40 HP)**
Rated power (P60 rating)	**36 kW**
Rated speed (60 Hz)	**1182 rpm**
Rated torque (60 Hz)	**242 Nm**
Rated current (460 V, 60 Hz)	**49 A**
Power factor (60 Hz)	**0.83**
Efficiency 4/4 | 3/4 | 2/4 (60 Hz)	**93 | 93.3 | 92.6 %**
I_LR/I_N | T_LR/T_N | T_B/T_N (60 Hz)	**7 | 2.9 | 3.1**
Moment of inertia J	**0.58 kgm2**
Sound pressure / power LpfA | LWA (60 Hz)	**66 | 79 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1541, p. 2/69 (PDF 187)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
APAC Line: the catalog lists operating values at 60 Hz only; 50 Hz speed/efficiency are not listed (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0101 (IE2)

1LE0101-2BC23-4AB4

30 kW / 1000 rpm

Frame 225 M | 6 poles | IM B3 | Article No. 1LE0101-2BC23-4AB4

GENERAL DATA

Series / efficiency class	**1LE0101 / IE2**
Housing	**Cast iron**
Frame size	**225 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**294 kg**

ELECTRICAL DATA

Rated power 50 Hz	**30 kW (about 40 HP)**
Rated power 60 Hz	**36 kW**
Rated speed (50 Hz)	**980 rpm**
Rated torque	**292 Nm**
Rated current	**57 A**
Power factor	**0.83**
Efficiency 4/4 | 3/4 | 2/4	**91.7 | 92.3 | 92.7 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**6.7 | 2.4 | 2.8**
Moment of inertia J	**0.62 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0101, p. 25 (PDF 25)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0101 (IE2)

1LE0101-2BC23-4FB4

30 kW / 1000 rpm

Frame 225 M | 6 poles | IM B5 | Article No. 1LE0101-2BC23-4FB4

GENERAL DATA

Series / efficiency class	**1LE0101 / IE2**
Housing	**Cast iron**
Frame size	**225 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**294 kg**

ELECTRICAL DATA

Rated power 50 Hz	**30 kW (about 40 HP)**
Rated power 60 Hz	**36 kW**
Rated speed (50 Hz)	**980 rpm**
Rated torque	**292 Nm**
Rated current	**57 A**
Power factor	**0.83**
Efficiency 4/4 | 3/4 | 2/4	**91.7 | 92.3 | 92.7 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**6.7 | 2.4 | 2.8**
Moment of inertia J	**0.62 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0101, p. 25 (PDF 25)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0101 (IE2)

1LE0101-2BC24-1AB4

30 kW / 1000 rpm

Frame 225 M | 6 poles | IM B3 | Article No. 1LE0101-2BC24-1AB4

GENERAL DATA

Series / efficiency class	**1LE0101 / IE2**
Housing	**Cast iron**
Frame size	**225 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**525 V D**
Net weight (IM B3)	**294 kg**

ELECTRICAL DATA

Rated power 50 Hz	**30 kW (about 40 HP)**
Rated power 60 Hz	**36 kW**
Rated speed (50 Hz)	**980 rpm**
Rated torque	**292 Nm**
Rated current	**43.5 A**
Power factor	**0.83**
Efficiency 4/4 | 3/4 | 2/4	**91.7 | 92.3 | 92.7 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**6.7 | 2.4 | 2.8**
Moment of inertia J	**0.62 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0101, p. 29 (PDF 29)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0101 (IE2)

1LE0101-2BC24-1FB4

30 kW / 1000 rpm

Frame 225 M | 6 poles | IM B5 | Article No. 1LE0101-2BC24-1FB4

GENERAL DATA

Series / efficiency class	**1LE0101 / IE2**
Housing	**Cast iron**
Frame size	**225 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**525 V D**
Net weight (IM B3)	**294 kg**

ELECTRICAL DATA

Rated power 50 Hz	**30 kW (about 40 HP)**
Rated power 60 Hz	**36 kW**
Rated speed (50 Hz)	**980 rpm**
Rated torque	**292 Nm**
Rated current	**43.5 A**
Power factor	**0.83**
Efficiency 4/4 | 3/4 | 2/4	**91.7 | 92.3 | 92.7 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**6.7 | 2.4 | 2.8**
Moment of inertia J	**0.62 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0101, p. 29 (PDF 29)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1501 (IE2)

1LE1501-2AC63-4AA4

30 kW / 1000 rpm

Frame 200 L | 6 poles | IM B3 | Article No. 1LE1501-2AC63-4AA4

GENERAL DATA

Series / efficiency class	**1LE1501 / IE2**
Housing	**Cast iron**
Frame size	**200 L**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**240 kg**

ELECTRICAL DATA

Rated power 50 Hz	**30 kW (about 40 HP)**
Rated power 60 Hz	**34.5 kW**
Rated speed (50 Hz)	**975 rpm**
Rated torque	**294 Nm**
Rated current	**61 A**
Power factor	**0.77**
Efficiency 4/4 | 3/4 | 2/4	**91.7 | 92.5 | 92.4 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**6.3 | 2.6 | 2.7**
Moment of inertia J	**0.381 kgm2**
Sound pressure / power LpfA | LWA	**68 | 75 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1501, p. 2/41 (PDF 159)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1501 (IE2)

1LE1501-2AC63-4FA4

30 kW / 1000 rpm

Frame 200 L | 6 poles | IM B5 | Article No. 1LE1501-2AC63-4FA4

GENERAL DATA

Series / efficiency class	**1LE1501 / IE2**
Housing	**Cast iron**
Frame size	**200 L**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**240 kg**

ELECTRICAL DATA

Rated power 50 Hz	**30 kW (about 40 HP)**
Rated power 60 Hz	**34.5 kW**
Rated speed (50 Hz)	**975 rpm**
Rated torque	**294 Nm**
Rated current	**61 A**
Power factor	**0.77**
Efficiency 4/4 | 3/4 | 2/4	**91.7 | 92.5 | 92.4 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**6.3 | 2.6 | 2.7**
Moment of inertia J	**0.381 kgm2**
Sound pressure / power LpfA | LWA	**68 | 75 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1501, p. 2/41 (PDF 159)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1503 (IE3)

1LE1503-2BC23-4AA4

30 kW / 1000 rpm

Frame 225 M | 6 poles | IM B3 | Article No. 1LE1503-2BC23-4AA4

GENERAL DATA

Series / efficiency class	**1LE1503 / IE3**
Housing	**Cast iron**
Frame size	**225 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**325 kg**

ELECTRICAL DATA

Rated power 50 Hz	**30 kW (about 40 HP)**
Rated power 60 Hz	**not listed (catalog 09/2023)**
Rated speed (50 Hz)	**982 rpm**
Rated torque	**290 Nm**
Rated current	**56 A**
Power factor	**0.83**
Efficiency 4/4 | 3/4 | 2/4	**92.9 | 93.6 | 93.5 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**6.6 | 2.6 | 3**
Moment of inertia J	**0.67 kgm2**
Sound pressure / power LpfA | LWA	**64 | 77 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (09/2023), table 1LE1503, p. 3/21**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1503 (IE3)

1LE1503-2BC23-4FA4

30 kW / 1000 rpm

Frame 225 M | 6 poles | IM B5 | Article No. 1LE1503-2BC23-4FA4

GENERAL DATA

Series / efficiency class	**1LE1503 / IE3**
Housing	**Cast iron**
Frame size	**225 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**325 kg**

ELECTRICAL DATA

Rated power 50 Hz	**30 kW (about 40 HP)**
Rated power 60 Hz	**not listed (catalog 09/2023)**
Rated speed (50 Hz)	**982 rpm**
Rated torque	**290 Nm**
Rated current	**56 A**
Power factor	**0.83**
Efficiency 4/4 | 3/4 | 2/4	**92.9 | 93.6 | 93.5 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**6.6 | 2.6 | 3**
Moment of inertia J	**0.67 kgm2**
Sound pressure / power LpfA | LWA	**64 | 77 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (09/2023), table 1LE1503, p. 3/21**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1503 (IE3)

1LE1503-2AC63-4AA4

30 kW / 1000 rpm

Frame 200 L | 6 poles | IM B3 | Article No. 1LE1503-2AC63-4AA4

GENERAL DATA

Series / efficiency class	**1LE1503 / IE3**
Housing	**Cast iron**
Frame size	**200 L**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**264 kg**

ELECTRICAL DATA

Rated power 50 Hz	**30 kW (about 40 HP)**
Rated power 60 Hz	**not listed (catalog 09/2023)**
Rated speed (50 Hz)	**978 rpm**
Rated torque	**295 Nm**
Rated current	**59 A**
Power factor	**0.79**
Efficiency 4/4 | 3/4 | 2/4	**92.9 | 93.6 | 93.7 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**6.5 | 2.8 | 2.8**
Moment of inertia J	**0.434 kgm2**
Sound pressure / power LpfA | LWA	**61 | 68 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (09/2023), table 1LE1503, p. 3/28**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1503 (IE3)

1LE1503-2AC63-4FA4

30 kW / 1000 rpm

Frame 200 L | 6 poles | IM B5 | Article No. 1LE1503-2AC63-4FA4

GENERAL DATA

Series / efficiency class	**1LE1503 / IE3**
Housing	**Cast iron**
Frame size	**200 L**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**264 kg**

ELECTRICAL DATA

Rated power 50 Hz	**30 kW (about 40 HP)**
Rated power 60 Hz	**not listed (catalog 09/2023)**
Rated speed (50 Hz)	**978 rpm**
Rated torque	**295 Nm**
Rated current	**59 A**
Power factor	**0.79**
Efficiency 4/4 | 3/4 | 2/4	**92.9 | 93.6 | 93.7 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**6.5 | 2.8 | 2.8**
Moment of inertia J	**0.434 kgm2**
Sound pressure / power LpfA | LWA	**61 | 68 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (09/2023), table 1LE1503, p. 3/28**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1541 (IE2)

1LE1541-2AC63-4FA4

30 kW / 1000 rpm

Frame 200 L | 6 poles | IM B5 | Article No. 1LE1541-2AC63-4FA4

GENERAL DATA

Series / efficiency class	**1LE1541 / IE2**
Housing	**Cast iron**
Frame size	**200 L**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**240 kg**

ELECTRICAL DATA - CATALOG VALUES AT 60 HZ (APAC LINE)

Rated power (P50 rating)	**30 kW (about 40 HP)**
Rated power (P60 rating)	**34.5 kW**
Rated speed (60 Hz)	**1180 rpm**
Rated torque (60 Hz)	**243 Nm**
Rated current (460 V, 60 Hz)	**53 A**
Power factor (60 Hz)	**0.77**
Efficiency 4/4 | 3/4 | 2/4 (60 Hz)	**93 | 93.4 | 93 %**
I_LR/I_N | T_LR/T_N | T_B/T_N (60 Hz)	**7.4 | 2.9 | 3.1**
Moment of inertia J	**0.381 kgm2**
Sound pressure / power LpfA | LWA (60 Hz)	**71 | 78 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1541, p. 2/70 (PDF 188)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
APAC Line: the catalog lists operating values at 60 Hz only; 50 Hz speed/efficiency are not listed (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1543 (IE3)

1LE1543-2AC63-4AA4

30 kW / 1000 rpm

Frame 200 L | 6 poles | IM B3 | Article No. 1LE1543-2AC63-4AA4

GENERAL DATA

Series / efficiency class	**1LE1543 / IE3**
Housing	**Cast iron**
Frame size	**200 L**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**270 kg**

ELECTRICAL DATA - CATALOG VALUES AT 60 HZ (APAC LINE)

Rated power (P50 rating)	**30 kW (about 40 HP)**
Rated power (P60 rating)	**36 kW**
Rated speed (60 Hz)	**1182 rpm**
Rated torque (60 Hz)	**242 Nm**
Rated current (460 V, 60 Hz)	**52 A**
Power factor (60 Hz)	**0.77**
Efficiency 4/4 | 3/4 | 2/4 (60 Hz)	**94.1 | 94.5 | 94.2 %**
I_LR/I_N | T_LR/T_N | T_B/T_N (60 Hz)	**7.6 | 3.2 | 3.2**
Moment of inertia J	**0.434 kgm2**
Sound pressure / power LpfA | LWA (60 Hz)	**63 | 70 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1543, p. 2/63 (PDF 181)**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
APAC Line: the catalog lists operating values at 60 Hz only; 50 Hz speed/efficiency are not listed (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1543 (IE3)

1LE1543-2AC63-4FA4

30 kW / 1000 rpm

Frame 200 L | 6 poles | IM B5 | Article No. 1LE1543-2AC63-4FA4

GENERAL DATA

Series / efficiency class	**1LE1543 / IE3**
Housing	**Cast iron**
Frame size	**200 L**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**270 kg**

ELECTRICAL DATA - CATALOG VALUES AT 60 HZ (APAC LINE)

Rated power (P50 rating)	**30 kW (about 40 HP)**
Rated power (P60 rating)	**36 kW**
Rated speed (60 Hz)	**1182 rpm**
Rated torque (60 Hz)	**242 Nm**
Rated current (460 V, 60 Hz)	**52 A**
Power factor (60 Hz)	**0.77**
Efficiency 4/4 | 3/4 | 2/4 (60 Hz)	**94.1 | 94.5 | 94.2 %**
I_LR/I_N | T_LR/T_N | T_B/T_N (60 Hz)	**7.6 | 3.2 | 3.2**
Moment of inertia J	**0.434 kgm2**
Sound pressure / power LpfA | LWA (60 Hz)	**63 | 70 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1543, p. 2/63 (PDF 181)**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
APAC Line: the catalog lists operating values at 60 Hz only; 50 Hz speed/efficiency are not listed (see Siemens DT Configurator).