Data sheets - Siemens SIMOTICS GP motors

30 kW / 1500 rpm - 42 article numbers in this file

Article No.	Page
1LE1002-2AB53-4AA4	2
1LE1002-2AB53-4FA4	3
1LE1001-2AB53-4AA4	4
1LE1001-2AB53-4FA4	5
1LE1001-1EB63-4AA4	6
1LE1001-1EB63-4FA4	7
1LE1003-2AB53-4AA4	8
1LE1003-2AB53-4FA4	9
1LE1043-2AB53-4AA4	10
1LE1043-2AB53-4FA4	11
1LE1043-1EB63-4AA4	12
1LE1043-1EB63-4FA4	13
1LE1003-1EB63-4AA4	14
1LE1003-1EB63-4FA4	15
1LE1004-2AB53-4AA4	16
1LE1004-2AB53-4FA4	17
1LE0102-2AB43-4AA4	18
1LE0102-2AB43-4FA4	19
1LE0102-2AB44-1AA4	20
1LE0102-2AB44-1FA4	21
1LE1502-1EB63-4AA4	22
1LE1502-1EB63-4FA4	23
1LE0101-2AB43-4AB4	24
1LE0101-2AB43-4FB4	25
1LE0101-2AB44-1AB4	26
1LE0101-2AB44-1FB4	27
1LE1501-2AB53-4AA4	28
1LE1501-2AB53-4FA4	29
1LE1501-1EB63-4AA4	30
1LE1501-1EB63-4FA4	31
1LE1503-2AB53-4AA4	32
1LE1503-2AB53-4FA4	33
1LE1503-1EB63-4AA4	34
1LE1503-1EB63-4FA4	35
1LE1541-2AB53-4FA4	36
1LE1541-1EB63-4FA4	37
1LE1543-2AB53-4AA4	38
1LE1543-2AB53-4FA4	39
1LE1543-1EB63-4AA4	40
1LE1543-1EB63-4FA4	41
1LE1504-2AB53-4AA4	42
1LE1504-2AB53-4FA4	43

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1002 (IE1)

1LE1002-2AB53-4AA4

30 kW / 1500 rpm

Frame 200 L | 4 poles | IM B3 | Article No. 1LE1002-2AB53-4AA4

GENERAL DATA

Series / efficiency class	**1LE1002 / IE1**
Housing	**Aluminum**
Frame size	**200 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**169 kg**

ELECTRICAL DATA

Rated power 50 Hz	**30 kW (about 40 HP)**
Rated power 60 Hz	**34.5 kW**
Rated speed (50 Hz)	**1472 rpm**
Rated torque	**195 Nm**
Rated current	**58 A**
Power factor	**0.83**
Efficiency 4/4 | 3/4 | 2/4	**90.7 | 91.5 | 91.4 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**6.9 | 2.3 | 3.1**
Moment of inertia J	**0.2 kgm2**
Sound pressure / power LpfA | LWA	**64 | 78 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1002, p. 2/45 (PDF 163)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1002 (IE1)

1LE1002-2AB53-4FA4

30 kW / 1500 rpm

Frame 200 L | 4 poles | IM B5 | Article No. 1LE1002-2AB53-4FA4

GENERAL DATA

Series / efficiency class	**1LE1002 / IE1**
Housing	**Aluminum**
Frame size	**200 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**169 kg**

ELECTRICAL DATA

Rated power 50 Hz	**30 kW (about 40 HP)**
Rated power 60 Hz	**34.5 kW**
Rated speed (50 Hz)	**1472 rpm**
Rated torque	**195 Nm**
Rated current	**58 A**
Power factor	**0.83**
Efficiency 4/4 | 3/4 | 2/4	**90.7 | 91.5 | 91.4 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**6.9 | 2.3 | 3.1**
Moment of inertia J	**0.2 kgm2**
Sound pressure / power LpfA | LWA	**64 | 78 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1002, p. 2/45 (PDF 163)**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1001 (IE2)

1LE1001-2AB53-4AA4

30 kW / 1500 rpm

Frame 200 L | 4 poles | IM B3 | Article No. 1LE1001-2AB53-4AA4

GENERAL DATA

Series / efficiency class	**1LE1001 / IE2**
Housing	**Aluminum**
Frame size	**200 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**173 kg**

ELECTRICAL DATA

Rated power 50 Hz	**30 kW (about 40 HP)**
Rated power 60 Hz	**34.5 kW**
Rated speed (50 Hz)	**1470 rpm**
Rated torque	**195 Nm**
Rated current	**56 A**
Power factor	**0.84**
Efficiency 4/4 | 3/4 | 2/4	**92.3 | 92.9 | 92.6 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**6.7 | 2.5 | 3.3**
Moment of inertia J	**0.2 kgm2**
Sound pressure / power LpfA | LWA	**70 | 77 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1001, p. 2/27 (PDF 145)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1001 (IE2)

1LE1001-2AB53-4FA4

30 kW / 1500 rpm

Frame 200 L | 4 poles | IM B5 | Article No. 1LE1001-2AB53-4FA4

GENERAL DATA

Series / efficiency class	**1LE1001 / IE2**
Housing	**Aluminum**
Frame size	**200 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**173 kg**

ELECTRICAL DATA

Rated power 50 Hz	**30 kW (about 40 HP)**
Rated power 60 Hz	**34.5 kW**
Rated speed (50 Hz)	**1470 rpm**
Rated torque	**195 Nm**
Rated current	**56 A**
Power factor	**0.84**
Efficiency 4/4 | 3/4 | 2/4	**92.3 | 92.9 | 92.6 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**6.7 | 2.5 | 3.3**
Moment of inertia J	**0.2 kgm2**
Sound pressure / power LpfA | LWA	**70 | 77 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1001, p. 2/27 (PDF 145)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1001 (IE2)

1LE1001-1EB63-4AA4

30 kW / 1500 rpm

Frame 180 L | 4 poles | IM B3 | Article No. 1LE1001-1EB63-4AA4

GENERAL DATA

Series / efficiency class	**1LE1001 / IE2**
Housing	**Aluminum**
Frame size	**180 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**148 kg**

ELECTRICAL DATA

Rated power 50 Hz	**30 kW (about 40 HP)**
Rated power 60 Hz	**34.5 kW**
Rated speed (50 Hz)	**1465 rpm**
Rated torque	**196 Nm**
Rated current	**58 A**
Power factor	**0.81**
Efficiency 4/4 | 3/4 | 2/4	**92.3 | 93 | 92.9 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**7.3 | 2.5 | 3.3**
Moment of inertia J	**0.159 kgm2**
Sound pressure / power LpfA | LWA	**70 | 77 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1001, p. 2/30 (PDF 148)**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1001 (IE2)

1LE1001-1EB63-4FA4

30 kW / 1500 rpm

Frame 180 L | 4 poles | IM B5 | Article No. 1LE1001-1EB63-4FA4

GENERAL DATA

Series / efficiency class	**1LE1001 / IE2**
Housing	**Aluminum**
Frame size	**180 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**148 kg**

ELECTRICAL DATA

Rated power 50 Hz	**30 kW (about 40 HP)**
Rated power 60 Hz	**34.5 kW**
Rated speed (50 Hz)	**1465 rpm**
Rated torque	**196 Nm**
Rated current	**58 A**
Power factor	**0.81**
Efficiency 4/4 | 3/4 | 2/4	**92.3 | 93 | 92.9 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**7.3 | 2.5 | 3.3**
Moment of inertia J	**0.159 kgm2**
Sound pressure / power LpfA | LWA	**70 | 77 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1001, p. 2/30 (PDF 148)**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1003 (IE3)

1LE1003-2AB53-4AA4

30 kW / 1500 rpm

Frame 200 L | 4 poles | IM B3 | Article No. 1LE1003-2AB53-4AA4

GENERAL DATA

Series / efficiency class	**1LE1003 / IE3**
Housing	**Aluminum**
Frame size	**200 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**189 kg**

ELECTRICAL DATA

Rated power 50 Hz	**30 kW (about 40 HP)**
Rated power 60 Hz	**34.5 kW**
Rated speed (50 Hz)	**1470 rpm**
Rated torque	**195 Nm**
Rated current	**55 A**
Power factor	**0.84**
Efficiency 4/4 | 3/4 | 2/4	**93.6 | 94 | 93.7 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**7.3 | 2.6 | 3.1**
Moment of inertia J	**0.22 kgm2**
Sound pressure / power LpfA | LWA	**65 | 72 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1003, p. 2/14 (PDF 132)**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1003 (IE3)

1LE1003-2AB53-4FA4

30 kW / 1500 rpm

Frame 200 L | 4 poles | IM B5 | Article No. 1LE1003-2AB53-4FA4

GENERAL DATA

Series / efficiency class	**1LE1003 / IE3**
Housing	**Aluminum**
Frame size	**200 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**189 kg**

ELECTRICAL DATA

Rated power 50 Hz	**30 kW (about 40 HP)**
Rated power 60 Hz	**34.5 kW**
Rated speed (50 Hz)	**1470 rpm**
Rated torque	**195 Nm**
Rated current	**55 A**
Power factor	**0.84**
Efficiency 4/4 | 3/4 | 2/4	**93.6 | 94 | 93.7 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**7.3 | 2.6 | 3.1**
Moment of inertia J	**0.22 kgm2**
Sound pressure / power LpfA | LWA	**65 | 72 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1003, p. 2/14 (PDF 132)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1043 (IE3)

1LE1043-2AB53-4AA4

30 kW / 1500 rpm

Frame 200 L | 4 poles | IM B3 | Article No. 1LE1043-2AB53-4AA4

GENERAL DATA

Series / efficiency class	**1LE1043 / IE3**
Housing	**Aluminum**
Frame size	**200 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**189 kg**

ELECTRICAL DATA - CATALOG VALUES AT 60 HZ (APAC LINE)

Rated power (P50 rating)	**30 kW (about 40 HP)**
Rated power (P60 rating)	**34.5 kW**
Rated speed (60 Hz)	**1778 rpm**
Rated torque (60 Hz)	**161 Nm**
Rated current (460 V, 60 Hz)	**48 A**
Power factor (60 Hz)	**0.83**
Efficiency 4/4 | 3/4 | 2/4 (60 Hz)	**94.1 | 94.3 | 93.8 %**
I_LR/I_N | T_LR/T_N | T_B/T_N (60 Hz)	**8.1 | 3 | 3.5**
Moment of inertia J	**0.22 kgm2**
Sound pressure / power LpfA | LWA (60 Hz)	**70 | 77 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1043, p. 2/54 (PDF 172)**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
APAC Line: the catalog lists operating values at 60 Hz only; 50 Hz speed/efficiency are not listed (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1043 (IE3)

1LE1043-2AB53-4FA4

30 kW / 1500 rpm

Frame 200 L | 4 poles | IM B5 | Article No. 1LE1043-2AB53-4FA4

GENERAL DATA

Series / efficiency class	**1LE1043 / IE3**
Housing	**Aluminum**
Frame size	**200 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**189 kg**

ELECTRICAL DATA - CATALOG VALUES AT 60 HZ (APAC LINE)

Rated power (P50 rating)	**30 kW (about 40 HP)**
Rated power (P60 rating)	**34.5 kW**
Rated speed (60 Hz)	**1778 rpm**
Rated torque (60 Hz)	**161 Nm**
Rated current (460 V, 60 Hz)	**48 A**
Power factor (60 Hz)	**0.83**
Efficiency 4/4 | 3/4 | 2/4 (60 Hz)	**94.1 | 94.3 | 93.8 %**
I_LR/I_N | T_LR/T_N | T_B/T_N (60 Hz)	**8.1 | 3 | 3.5**
Moment of inertia J	**0.22 kgm2**
Sound pressure / power LpfA | LWA (60 Hz)	**70 | 77 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1043, p. 2/54 (PDF 172)**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
APAC Line: the catalog lists operating values at 60 Hz only; 50 Hz speed/efficiency are not listed (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1043 (IE3)

1LE1043-1EB63-4AA4

30 kW / 1500 rpm

Frame 180 L | 4 poles | IM B3 | Article No. 1LE1043-1EB63-4AA4

GENERAL DATA

Series / efficiency class	**1LE1043 / IE3**
Housing	**Aluminum**
Frame size	**180 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**154 kg**

ELECTRICAL DATA - CATALOG VALUES AT 60 HZ (APAC LINE)

Rated power (P50 rating)	**30 kW (about 40 HP)**
Rated power (P60 rating)	**34.5 kW**
Rated speed (60 Hz)	**1775 rpm**
Rated torque (60 Hz)	**161 Nm**
Rated current (460 V, 60 Hz)	**51 A**
Power factor (60 Hz)	**0.78**
Efficiency 4/4 | 3/4 | 2/4 (60 Hz)	**94.1 | 94.4 | 94 %**
I_LR/I_N | T_LR/T_N | T_B/T_N (60 Hz)	**8.8 | 3.1 | 4.1**
Moment of inertia J	**0.173 kgm2**
Sound pressure / power LpfA | LWA (60 Hz)	**70 | 77 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1043, p. 2/56 (PDF 174)**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
APAC Line: the catalog lists operating values at 60 Hz only; 50 Hz speed/efficiency are not listed (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1043 (IE3)

1LE1043-1EB63-4FA4

30 kW / 1500 rpm

Frame 180 L | 4 poles | IM B5 | Article No. 1LE1043-1EB63-4FA4

GENERAL DATA

Series / efficiency class	**1LE1043 / IE3**
Housing	**Aluminum**
Frame size	**180 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**154 kg**

ELECTRICAL DATA - CATALOG VALUES AT 60 HZ (APAC LINE)

Rated power (P50 rating)	**30 kW (about 40 HP)**
Rated power (P60 rating)	**34.5 kW**
Rated speed (60 Hz)	**1775 rpm**
Rated torque (60 Hz)	**161 Nm**
Rated current (460 V, 60 Hz)	**51 A**
Power factor (60 Hz)	**0.78**
Efficiency 4/4 | 3/4 | 2/4 (60 Hz)	**94.1 | 94.4 | 94 %**
I_LR/I_N | T_LR/T_N | T_B/T_N (60 Hz)	**8.8 | 3.1 | 4.1**
Moment of inertia J	**0.173 kgm2**
Sound pressure / power LpfA | LWA (60 Hz)	**70 | 77 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1043, p. 2/56 (PDF 174)**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
APAC Line: the catalog lists operating values at 60 Hz only; 50 Hz speed/efficiency are not listed (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1003 (IE3)

1LE1003-1EB63-4AA4

30 kW / 1500 rpm

Frame 180 L | 4 poles | IM B3 | Article No. 1LE1003-1EB63-4AA4

GENERAL DATA

Series / efficiency class	**1LE1003 / IE3**
Housing	**Aluminum**
Frame size	**180 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**154 kg**

ELECTRICAL DATA

Rated power 50 Hz	**30 kW (about 40 HP)**
Rated power 60 Hz	**34.5 kW**
Rated speed (50 Hz)	**1470 rpm**
Rated torque	**195 Nm**
Rated current	**59 A**
Power factor	**0.79**
Efficiency 4/4 | 3/4 | 2/4	**93.6 | 94 | 93.8 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**8.2 | 3 | 3.8**
Moment of inertia J	**0.173 kgm2**
Sound pressure / power LpfA | LWA	**66 | 74 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (06/2020), table 1LE1003, p. 2/16**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1003 (IE3)

1LE1003-1EB63-4FA4

30 kW / 1500 rpm

Frame 180 L | 4 poles | IM B5 | Article No. 1LE1003-1EB63-4FA4

GENERAL DATA

Series / efficiency class	**1LE1003 / IE3**
Housing	**Aluminum**
Frame size	**180 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**154 kg**

ELECTRICAL DATA

Rated power 50 Hz	**30 kW (about 40 HP)**
Rated power 60 Hz	**34.5 kW**
Rated speed (50 Hz)	**1470 rpm**
Rated torque	**195 Nm**
Rated current	**59 A**
Power factor	**0.79**
Efficiency 4/4 | 3/4 | 2/4	**93.6 | 94 | 93.8 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**8.2 | 3 | 3.8**
Moment of inertia J	**0.173 kgm2**
Sound pressure / power LpfA | LWA	**66 | 74 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (06/2020), table 1LE1003, p. 2/16**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1004 (IE4)

1LE1004-2AB53-4AA4

30 kW / 1500 rpm

Frame 200 L | 4 poles | IM B3 | Article No. 1LE1004-2AB53-4AA4

GENERAL DATA

Series / efficiency class	**1LE1004 / IE4**
Housing	**Aluminum**
Frame size	**200 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**205 kg**

ELECTRICAL DATA

Rated power 50 Hz	**30 kW (about 40 HP)**
Rated power 60 Hz	**34.5 kW**
Rated speed (50 Hz)	**1475 rpm**
Rated torque	**194 Nm**
Rated current	**56 A**
Power factor	**0.81**
Efficiency 4/4 | 3/4 | 2/4	**94.9 | 95.2 | 94.9 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**7.3 | 3.2 | 3.6**
Moment of inertia J	**0.27 kgm2**
Sound pressure / power LpfA | LWA	**60 | 73 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1004, p. 2/8 (PDF 126)**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1004 (IE4)

1LE1004-2AB53-4FA4

30 kW / 1500 rpm

Frame 200 L | 4 poles | IM B5 | Article No. 1LE1004-2AB53-4FA4

GENERAL DATA

Series / efficiency class	**1LE1004 / IE4**
Housing	**Aluminum**
Frame size	**200 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**205 kg**

ELECTRICAL DATA

Rated power 50 Hz	**30 kW (about 40 HP)**
Rated power 60 Hz	**34.5 kW**
Rated speed (50 Hz)	**1475 rpm**
Rated torque	**194 Nm**
Rated current	**56 A**
Power factor	**0.81**
Efficiency 4/4 | 3/4 | 2/4	**94.9 | 95.2 | 94.9 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**7.3 | 3.2 | 3.6**
Moment of inertia J	**0.27 kgm2**
Sound pressure / power LpfA | LWA	**60 | 73 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1004, p. 2/8 (PDF 126)**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0102 (IE1)

1LE0102-2AB43-4AA4

30 kW / 1500 rpm

Frame 200 L | 4 poles | IM B3 | Article No. 1LE0102-2AB43-4AA4

GENERAL DATA

Series / efficiency class	**1LE0102 / IE1**
Housing	**Cast iron**
Frame size	**200 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**235 kg**

ELECTRICAL DATA

Rated power 50 Hz	**30 kW (about 40 HP)**
Rated power 60 Hz	**34.5 kW**
Rated speed (50 Hz)	**1470 rpm**
Rated torque	**195 Nm**
Rated current	**56 A**
Power factor	**0.85**
Efficiency 4/4 | 3/4 | 2/4	**90.7 | 91.6 | 90.5 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**7.4 | 2.4 | 3.1**
Moment of inertia J	**0.22 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0102, p. 21 (PDF 21)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0102 (IE1)

1LE0102-2AB43-4FA4

30 kW / 1500 rpm

Frame 200 L | 4 poles | IM B5 | Article No. 1LE0102-2AB43-4FA4

GENERAL DATA

Series / efficiency class	**1LE0102 / IE1**
Housing	**Cast iron**
Frame size	**200 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**235 kg**

ELECTRICAL DATA

Rated power 50 Hz	**30 kW (about 40 HP)**
Rated power 60 Hz	**34.5 kW**
Rated speed (50 Hz)	**1470 rpm**
Rated torque	**195 Nm**
Rated current	**56 A**
Power factor	**0.85**
Efficiency 4/4 | 3/4 | 2/4	**90.7 | 91.6 | 90.5 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**7.4 | 2.4 | 3.1**
Moment of inertia J	**0.22 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0102, p. 21 (PDF 21)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0102 (IE1)

1LE0102-2AB44-1AA4

30 kW / 1500 rpm

Frame 200 L | 4 poles | IM B3 | Article No. 1LE0102-2AB44-1AA4

GENERAL DATA

Series / efficiency class	**1LE0102 / IE1**
Housing	**Cast iron**
Frame size	**200 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**525 V D**
Net weight (IM B3)	**235 kg**

ELECTRICAL DATA

Rated power 50 Hz	**30 kW (about 40 HP)**
Rated power 60 Hz	**34.5 kW**
Rated speed (50 Hz)	**1470 rpm**
Rated torque	**195 Nm**
Rated current	**42.5 A**
Power factor	**0.85**
Efficiency 4/4 | 3/4 | 2/4	**90.7 | 91.6 | 90.5 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**7.4 | 2.4 | 3.1**
Moment of inertia J	**0.22 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0102, p. 26 (PDF 26)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0102 (IE1)

1LE0102-2AB44-1FA4

30 kW / 1500 rpm

Frame 200 L | 4 poles | IM B5 | Article No. 1LE0102-2AB44-1FA4

GENERAL DATA

Series / efficiency class	**1LE0102 / IE1**
Housing	**Cast iron**
Frame size	**200 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**525 V D**
Net weight (IM B3)	**235 kg**

ELECTRICAL DATA

Rated power 50 Hz	**30 kW (about 40 HP)**
Rated power 60 Hz	**34.5 kW**
Rated speed (50 Hz)	**1470 rpm**
Rated torque	**195 Nm**
Rated current	**42.5 A**
Power factor	**0.85**
Efficiency 4/4 | 3/4 | 2/4	**90.7 | 91.6 | 90.5 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**7.4 | 2.4 | 3.1**
Moment of inertia J	**0.22 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0102, p. 26 (PDF 26)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1502 (IE1)

1LE1502-1EB63-4AA4

30 kW / 1500 rpm

Frame 180 L | 4 poles | IM B3 | Article No. 1LE1502-1EB63-4AA4

GENERAL DATA

Series / efficiency class	**1LE1502 / IE1**
Housing	**Cast iron**
Frame size	**180 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**185 kg**

ELECTRICAL DATA

Rated power 50 Hz	**30 kW (about 40 HP)**
Rated power 60 Hz	**34.5 kW**
Rated speed (50 Hz)	**1465 rpm**
Rated torque	**196 Nm**
Rated current	**60 A**
Power factor	**0.79**
Efficiency 4/4 | 3/4 | 2/4	**90.7 | 91.7 | 91.9 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**7.2 | 2.6 | 3.4**
Moment of inertia J	**0.159 kgm2**
Sound pressure / power LpfA | LWA	**64 | 77 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1502, p. 2/52 (PDF 170)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1502 (IE1)

1LE1502-1EB63-4FA4

30 kW / 1500 rpm

Frame 180 L | 4 poles | IM B5 | Article No. 1LE1502-1EB63-4FA4

GENERAL DATA

Series / efficiency class	**1LE1502 / IE1**
Housing	**Cast iron**
Frame size	**180 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**185 kg**

ELECTRICAL DATA

Rated power 50 Hz	**30 kW (about 40 HP)**
Rated power 60 Hz	**34.5 kW**
Rated speed (50 Hz)	**1465 rpm**
Rated torque	**196 Nm**
Rated current	**60 A**
Power factor	**0.79**
Efficiency 4/4 | 3/4 | 2/4	**90.7 | 91.7 | 91.9 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**7.2 | 2.6 | 3.4**
Moment of inertia J	**0.159 kgm2**
Sound pressure / power LpfA | LWA	**64 | 77 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1502, p. 2/52 (PDF 170)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0101 (IE2)

1LE0101-2AB43-4AB4

30 kW / 1500 rpm

Frame 200 L | 4 poles | IM B3 | Article No. 1LE0101-2AB43-4AB4

GENERAL DATA

Series / efficiency class	**1LE0101 / IE2**
Housing	**Cast iron**
Frame size	**200 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**238 kg**

ELECTRICAL DATA

Rated power 50 Hz	**30 kW (about 40 HP)**
Rated power 60 Hz	**34.5 kW**
Rated speed (50 Hz)	**1470 rpm**
Rated torque	**195 Nm**
Rated current	**55 A**
Power factor	**0.85**
Efficiency 4/4 | 3/4 | 2/4	**92.3 | 92.9 | 92.9 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**7.3 | 2.7 | 3.2**
Moment of inertia J	**0.22 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0101, p. 24 (PDF 24)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0101 (IE2)

1LE0101-2AB43-4FB4

30 kW / 1500 rpm

Frame 200 L | 4 poles | IM B5 | Article No. 1LE0101-2AB43-4FB4

GENERAL DATA

Series / efficiency class	**1LE0101 / IE2**
Housing	**Cast iron**
Frame size	**200 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**238 kg**

ELECTRICAL DATA

Rated power 50 Hz	**30 kW (about 40 HP)**
Rated power 60 Hz	**34.5 kW**
Rated speed (50 Hz)	**1470 rpm**
Rated torque	**195 Nm**
Rated current	**55 A**
Power factor	**0.85**
Efficiency 4/4 | 3/4 | 2/4	**92.3 | 92.9 | 92.9 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**7.3 | 2.7 | 3.2**
Moment of inertia J	**0.22 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0101, p. 24 (PDF 24)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0101 (IE2)

1LE0101-2AB44-1AB4

30 kW / 1500 rpm

Frame 200 L | 4 poles | IM B3 | Article No. 1LE0101-2AB44-1AB4

GENERAL DATA

Series / efficiency class	**1LE0101 / IE2**
Housing	**Cast iron**
Frame size	**200 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**525 V D**
Net weight (IM B3)	**238 kg**

ELECTRICAL DATA

Rated power 50 Hz	**30 kW (about 40 HP)**
Rated power 60 Hz	**34.5 kW**
Rated speed (50 Hz)	**1470 rpm**
Rated torque	**195 Nm**
Rated current	**42 A**
Power factor	**0.85**
Efficiency 4/4 | 3/4 | 2/4	**92.3 | 92.9 | 92.9 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**7.3 | 2.7 | 3.2**
Moment of inertia J	**0.22 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0101, p. 28 (PDF 28)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0101 (IE2)

1LE0101-2AB44-1FB4

30 kW / 1500 rpm

Frame 200 L | 4 poles | IM B5 | Article No. 1LE0101-2AB44-1FB4

GENERAL DATA

Series / efficiency class	**1LE0101 / IE2**
Housing	**Cast iron**
Frame size	**200 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**525 V D**
Net weight (IM B3)	**238 kg**

ELECTRICAL DATA

Rated power 50 Hz	**30 kW (about 40 HP)**
Rated power 60 Hz	**34.5 kW**
Rated speed (50 Hz)	**1470 rpm**
Rated torque	**195 Nm**
Rated current	**42 A**
Power factor	**0.85**
Efficiency 4/4 | 3/4 | 2/4	**92.3 | 92.9 | 92.9 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**7.3 | 2.7 | 3.2**
Moment of inertia J	**0.22 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0101, p. 28 (PDF 28)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1501 (IE2)

1LE1501-2AB53-4AA4

30 kW / 1500 rpm

Frame 200 L | 4 poles | IM B3 | Article No. 1LE1501-2AB53-4AA4

GENERAL DATA

Series / efficiency class	**1LE1501 / IE2**
Housing	**Cast iron**
Frame size	**200 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**230 kg**

ELECTRICAL DATA

Rated power 50 Hz	**30 kW (about 40 HP)**
Rated power 60 Hz	**34.5 kW**
Rated speed (50 Hz)	**1470 rpm**
Rated torque	**195 Nm**
Rated current	**56 A**
Power factor	**0.84**
Efficiency 4/4 | 3/4 | 2/4	**92.3 | 92.9 | 92.6 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**6.7 | 2.5 | 3.3**
Moment of inertia J	**0.2 kgm2**
Sound pressure / power LpfA | LWA	**70 | 77 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1501, p. 2/33 (PDF 151)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1501 (IE2)

1LE1501-2AB53-4FA4

30 kW / 1500 rpm

Frame 200 L | 4 poles | IM B5 | Article No. 1LE1501-2AB53-4FA4

GENERAL DATA

Series / efficiency class	**1LE1501 / IE2**
Housing	**Cast iron**
Frame size	**200 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**230 kg**

ELECTRICAL DATA

Rated power 50 Hz	**30 kW (about 40 HP)**
Rated power 60 Hz	**34.5 kW**
Rated speed (50 Hz)	**1470 rpm**
Rated torque	**195 Nm**
Rated current	**56 A**
Power factor	**0.84**
Efficiency 4/4 | 3/4 | 2/4	**92.3 | 92.9 | 92.6 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**6.7 | 2.5 | 3.3**
Moment of inertia J	**0.2 kgm2**
Sound pressure / power LpfA | LWA	**70 | 77 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1501, p. 2/33 (PDF 151)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1501 (IE2)

1LE1501-1EB63-4AA4

30 kW / 1500 rpm

Frame 180 L | 4 poles | IM B3 | Article No. 1LE1501-1EB63-4AA4

GENERAL DATA

Series / efficiency class	**1LE1501 / IE2**
Housing	**Cast iron**
Frame size	**180 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**185 kg**

ELECTRICAL DATA

Rated power 50 Hz	**30 kW (about 40 HP)**
Rated power 60 Hz	**34.5 kW**
Rated speed (50 Hz)	**1465 rpm**
Rated torque	**196 Nm**
Rated current	**58 A**
Power factor	**0.81**
Efficiency 4/4 | 3/4 | 2/4	**92.3 | 93 | 92.9 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**7.3 | 2.5 | 3.3**
Moment of inertia J	**0.159 kgm2**
Sound pressure / power LpfA | LWA	**70 | 77 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1501, p. 2/40 (PDF 158)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1501 (IE2)

1LE1501-1EB63-4FA4

30 kW / 1500 rpm

Frame 180 L | 4 poles | IM B5 | Article No. 1LE1501-1EB63-4FA4

GENERAL DATA

Series / efficiency class	**1LE1501 / IE2**
Housing	**Cast iron**
Frame size	**180 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**185 kg**

ELECTRICAL DATA

Rated power 50 Hz	**30 kW (about 40 HP)**
Rated power 60 Hz	**34.5 kW**
Rated speed (50 Hz)	**1465 rpm**
Rated torque	**196 Nm**
Rated current	**58 A**
Power factor	**0.81**
Efficiency 4/4 | 3/4 | 2/4	**92.3 | 93 | 92.9 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**7.3 | 2.5 | 3.3**
Moment of inertia J	**0.159 kgm2**
Sound pressure / power LpfA | LWA	**70 | 77 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1501, p. 2/40 (PDF 158)**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1503 (IE3)

1LE1503-2AB53-4AA4

30 kW / 1500 rpm

Frame 200 L | 4 poles | IM B3 | Article No. 1LE1503-2AB53-4AA4

GENERAL DATA

Series / efficiency class	**1LE1503 / IE3**
Housing	**Cast iron**
Frame size	**200 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**240 kg**

ELECTRICAL DATA

Rated power 50 Hz	**30 kW (about 40 HP)**
Rated power 60 Hz	**34.5 kW**
Rated speed (50 Hz)	**1470 rpm**
Rated torque	**195 Nm**
Rated current	**55 A**
Power factor	**0.84**
Efficiency 4/4 | 3/4 | 2/4	**93.6 | 94 | 93.7 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**7.3 | 2.6 | 3.1**
Moment of inertia J	**0.22 kgm2**
Sound pressure / power LpfA | LWA	**65 | 72 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1503, p. 2/18 (PDF 136)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1503 (IE3)

1LE1503-2AB53-4FA4

30 kW / 1500 rpm

Frame 200 L | 4 poles | IM B5 | Article No. 1LE1503-2AB53-4FA4

GENERAL DATA

Series / efficiency class	**1LE1503 / IE3**
Housing	**Cast iron**
Frame size	**200 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**240 kg**

ELECTRICAL DATA

Rated power 50 Hz	**30 kW (about 40 HP)**
Rated power 60 Hz	**34.5 kW**
Rated speed (50 Hz)	**1470 rpm**
Rated torque	**195 Nm**
Rated current	**55 A**
Power factor	**0.84**
Efficiency 4/4 | 3/4 | 2/4	**93.6 | 94 | 93.7 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**7.3 | 2.6 | 3.1**
Moment of inertia J	**0.22 kgm2**
Sound pressure / power LpfA | LWA	**65 | 72 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1503, p. 2/18 (PDF 136)**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1503 (IE3)

1LE1503-1EB63-4AA4

30 kW / 1500 rpm

Frame 180 L | 4 poles | IM B3 | Article No. 1LE1503-1EB63-4AA4

GENERAL DATA

Series / efficiency class	**1LE1503 / IE3**
Housing	**Cast iron**
Frame size	**180 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**193 kg**

ELECTRICAL DATA

Rated power 50 Hz	**30 kW (about 40 HP)**
Rated power 60 Hz	**34.5 kW**
Rated speed (50 Hz)	**1470 rpm**
Rated torque	**195 Nm**
Rated current	**59 A**
Power factor	**0.79**
Efficiency 4/4 | 3/4 | 2/4	**93.6 | 94.2 | 94.1 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**7.8 | 2.8 | 3.7**
Moment of inertia J	**0.173 kgm2**
Sound pressure / power LpfA | LWA	**68 | 75 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1503, p. 2/24 (PDF 142)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1503 (IE3)

1LE1503-1EB63-4FA4

30 kW / 1500 rpm

Frame 180 L | 4 poles | IM B5 | Article No. 1LE1503-1EB63-4FA4

GENERAL DATA

Series / efficiency class	**1LE1503 / IE3**
Housing	**Cast iron**
Frame size	**180 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**193 kg**

ELECTRICAL DATA

Rated power 50 Hz	**30 kW (about 40 HP)**
Rated power 60 Hz	**34.5 kW**
Rated speed (50 Hz)	**1470 rpm**
Rated torque	**195 Nm**
Rated current	**59 A**
Power factor	**0.79**
Efficiency 4/4 | 3/4 | 2/4	**93.6 | 94.2 | 94.1 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**7.8 | 2.8 | 3.7**
Moment of inertia J	**0.173 kgm2**
Sound pressure / power LpfA | LWA	**68 | 75 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1503, p. 2/24 (PDF 142)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1541 (IE2)

1LE1541-2AB53-4FA4

30 kW / 1500 rpm

Frame 200 L | 4 poles | IM B5 | Article No. 1LE1541-2AB53-4FA4

GENERAL DATA

Series / efficiency class	**1LE1541 / IE2**
Housing	**Cast iron**
Frame size	**200 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**230 kg**

ELECTRICAL DATA - CATALOG VALUES AT 60 HZ (APAC LINE)

Rated power (P50 rating)	**30 kW (about 40 HP)**
Rated power (P60 rating)	**34.5 kW**
Rated speed (60 Hz)	**1778 rpm**
Rated torque (60 Hz)	**161 Nm**
Rated current (460 V, 60 Hz)	**48 A**
Power factor (60 Hz)	**0.84**
Efficiency 4/4 | 3/4 | 2/4 (60 Hz)	**93 | 93.1 | 92.2 %**
I_LR/I_N | T_LR/T_N | T_B/T_N (60 Hz)	**8.2 | 3.2 | 3.7**
Moment of inertia J	**0.2 kgm2**
Sound pressure / power LpfA | LWA (60 Hz)	**72 | 79 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1541, p. 2/68 (PDF 186)**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
APAC Line: the catalog lists operating values at 60 Hz only; 50 Hz speed/efficiency are not listed (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1541 (IE2)

1LE1541-1EB63-4FA4

30 kW / 1500 rpm

Frame 180 L | 4 poles | IM B5 | Article No. 1LE1541-1EB63-4FA4

GENERAL DATA

Series / efficiency class	**1LE1541 / IE2**
Housing	**Cast iron**
Frame size	**180 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**185 kg**

ELECTRICAL DATA - CATALOG VALUES AT 60 HZ (APAC LINE)

Rated power (P50 rating)	**30 kW (about 40 HP)**
Rated power (P60 rating)	**34.5 kW**
Rated speed (60 Hz)	**1770 rpm**
Rated torque (60 Hz)	**162 Nm**
Rated current (460 V, 60 Hz)	**51 A**
Power factor (60 Hz)	**0.8**
Efficiency 4/4 | 3/4 | 2/4 (60 Hz)	**93 | 93.2 | 92.7 %**
I_LR/I_N | T_LR/T_N | T_B/T_N (60 Hz)	**8.7 | 2.6 | 3.9**
Moment of inertia J	**0.159 kgm2**
Sound pressure / power LpfA | LWA (60 Hz)	**71 | 78 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1541, p. 2/70 (PDF 188)**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
APAC Line: the catalog lists operating values at 60 Hz only; 50 Hz speed/efficiency are not listed (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1543 (IE3)

1LE1543-2AB53-4AA4

30 kW / 1500 rpm

Frame 200 L | 4 poles | IM B3 | Article No. 1LE1543-2AB53-4AA4

GENERAL DATA

Series / efficiency class	**1LE1543 / IE3**
Housing	**Cast iron**
Frame size	**200 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**240 kg**

ELECTRICAL DATA - CATALOG VALUES AT 60 HZ (APAC LINE)

Rated power (P50 rating)	**30 kW (about 40 HP)**
Rated power (P60 rating)	**34.5 kW**
Rated speed (60 Hz)	**1778 rpm**
Rated torque (60 Hz)	**161 Nm**
Rated current (460 V, 60 Hz)	**48 A**
Power factor (60 Hz)	**0.83**
Efficiency 4/4 | 3/4 | 2/4 (60 Hz)	**94.1 | 94.3 | 93.8 %**
I_LR/I_N | T_LR/T_N | T_B/T_N (60 Hz)	**8.1 | 3 | 3.5**
Moment of inertia J	**0.22 kgm2**
Sound pressure / power LpfA | LWA (60 Hz)	**70 | 77 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1543, p. 2/58 (PDF 176)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
APAC Line: the catalog lists operating values at 60 Hz only; 50 Hz speed/efficiency are not listed (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1543 (IE3)

1LE1543-2AB53-4FA4

30 kW / 1500 rpm

Frame 200 L | 4 poles | IM B5 | Article No. 1LE1543-2AB53-4FA4

GENERAL DATA

Series / efficiency class	**1LE1543 / IE3**
Housing	**Cast iron**
Frame size	**200 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**240 kg**

ELECTRICAL DATA - CATALOG VALUES AT 60 HZ (APAC LINE)

Rated power (P50 rating)	**30 kW (about 40 HP)**
Rated power (P60 rating)	**34.5 kW**
Rated speed (60 Hz)	**1778 rpm**
Rated torque (60 Hz)	**161 Nm**
Rated current (460 V, 60 Hz)	**48 A**
Power factor (60 Hz)	**0.83**
Efficiency 4/4 | 3/4 | 2/4 (60 Hz)	**94.1 | 94.3 | 93.8 %**
I_LR/I_N | T_LR/T_N | T_B/T_N (60 Hz)	**8.1 | 3 | 3.5**
Moment of inertia J	**0.22 kgm2**
Sound pressure / power LpfA | LWA (60 Hz)	**70 | 77 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1543, p. 2/58 (PDF 176)**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
APAC Line: the catalog lists operating values at 60 Hz only; 50 Hz speed/efficiency are not listed (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1543 (IE3)

1LE1543-1EB63-4AA4

30 kW / 1500 rpm

Frame 180 L | 4 poles | IM B3 | Article No. 1LE1543-1EB63-4AA4

GENERAL DATA

Series / efficiency class	**1LE1543 / IE3**
Housing	**Cast iron**
Frame size	**180 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**192 kg**

ELECTRICAL DATA - CATALOG VALUES AT 60 HZ (APAC LINE)

Rated power (P50 rating)	**30 kW (about 40 HP)**
Rated power (P60 rating)	**34.5 kW**
Rated speed (60 Hz)	**1775 rpm**
Rated torque (60 Hz)	**161 Nm**
Rated current (460 V, 60 Hz)	**51 A**
Power factor (60 Hz)	**0.78**
Efficiency 4/4 | 3/4 | 2/4 (60 Hz)	**94.1 | 94.4 | 94 %**
I_LR/I_N | T_LR/T_N | T_B/T_N (60 Hz)	**8.8 | 3.1 | 4.1**
Moment of inertia J	**0.173 kgm2**
Sound pressure / power LpfA | LWA (60 Hz)	**70 | 77 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1543, p. 2/63 (PDF 181)**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
APAC Line: the catalog lists operating values at 60 Hz only; 50 Hz speed/efficiency are not listed (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1543 (IE3)

1LE1543-1EB63-4FA4

30 kW / 1500 rpm

Frame 180 L | 4 poles | IM B5 | Article No. 1LE1543-1EB63-4FA4

GENERAL DATA

Series / efficiency class	**1LE1543 / IE3**
Housing	**Cast iron**
Frame size	**180 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**192 kg**

ELECTRICAL DATA - CATALOG VALUES AT 60 HZ (APAC LINE)

Rated power (P50 rating)	**30 kW (about 40 HP)**
Rated power (P60 rating)	**34.5 kW**
Rated speed (60 Hz)	**1775 rpm**
Rated torque (60 Hz)	**161 Nm**
Rated current (460 V, 60 Hz)	**51 A**
Power factor (60 Hz)	**0.78**
Efficiency 4/4 | 3/4 | 2/4 (60 Hz)	**94.1 | 94.4 | 94 %**
I_LR/I_N | T_LR/T_N | T_B/T_N (60 Hz)	**8.8 | 3.1 | 4.1**
Moment of inertia J	**0.173 kgm2**
Sound pressure / power LpfA | LWA (60 Hz)	**70 | 77 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1543, p. 2/63 (PDF 181)**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
APAC Line: the catalog lists operating values at 60 Hz only; 50 Hz speed/efficiency are not listed (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1504 (IE4)

1LE1504-2AB53-4AA4

30 kW / 1500 rpm

Frame 200 L | 4 poles | IM B3 | Article No. 1LE1504-2AB53-4AA4

GENERAL DATA

Series / efficiency class	**1LE1504 / IE4**
Housing	**Cast iron**
Frame size	**200 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**258 kg**

ELECTRICAL DATA

Rated power 50 Hz	**30 kW (about 40 HP)**
Rated power 60 Hz	**34.5 kW**
Rated speed (50 Hz)	**1475 rpm**
Rated torque	**194 Nm**
Rated current	**56 A**
Power factor	**0.81**
Efficiency 4/4 | 3/4 | 2/4	**94.9 | 95.2 | 94.9 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**7.3 | 3.2 | 3.6**
Moment of inertia J	**0.27 kgm2**
Sound pressure / power LpfA | LWA	**60 | 73 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1504, p. 2/10 (PDF 128)**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1504 (IE4)

1LE1504-2AB53-4FA4

30 kW / 1500 rpm

Frame 200 L | 4 poles | IM B5 | Article No. 1LE1504-2AB53-4FA4

GENERAL DATA

Series / efficiency class	**1LE1504 / IE4**
Housing	**Cast iron**
Frame size	**200 L**
Poles	**4**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**258 kg**

ELECTRICAL DATA

Rated power 50 Hz	**30 kW (about 40 HP)**
Rated power 60 Hz	**34.5 kW**
Rated speed (50 Hz)	**1475 rpm**
Rated torque	**194 Nm**
Rated current	**56 A**
Power factor	**0.81**
Efficiency 4/4 | 3/4 | 2/4	**94.9 | 95.2 | 94.9 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**7.3 | 3.2 | 3.6**
Moment of inertia J	**0.27 kgm2**
Sound pressure / power LpfA | LWA	**60 | 73 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1504, p. 2/10 (PDF 128)**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).