# Data sheets - Siemens SIMOTICS GP motors

3 kW / 750 rpm - 15 article numbers in this file


| Article No. | Page |
|---|---|
| 1LE1502-1CD23-4AA4 | 2 |
| 1LE1502-1CD23-4FA4 | 3 |
| 1LE1502-1CD23-4KA4 | 4 |
| 1LE1001-1CD23-4AA4 | 5 |
| 1LE1001-1CD23-4FA4 | 6 |
| 1LE1001-1CD23-4KA4 | 7 |
| 1LE1002-1CD23-4AA4 | 8 |
| 1LE1002-1CD23-4FA4 | 9 |
| 1LE1002-1CD23-4KA4 | 10 |
| 1LE1003-1CD23-4AA4 | 11 |
| 1LE1003-1CD23-4FA4 | 12 |
| 1LE1003-1CD23-4KA4 | 13 |
| 1LE1501-1CD23-4AA4 | 14 |
| 1LE1501-1CD23-4FA4 | 15 |
| 1LE1501-1CD23-4KA4 | 16 |



محور نیرو

Tel: 0935 186 4634

info@mehvarniro.com | mehvarniro.com

# Data sheet

**1LE1502-1CD23-4AA4**

SIMOTICS GP low-voltage motor - cast-iron series 1LE1502 Basic Line (IE1)

# 3 kW / 750 rpm

Frame size 132 M | Article No. 1LE1502-1CD23-4AA4 | mounting IM B3

## GENERAL DATA

| | |
|---|---|
| Motor series | **1LE1502 Basic Line (cast iron)** |
| Article No. | **1LE1502-1CD23-4AA4** |
| Frame size | **132 M** |
| Number of poles | **8** |
| Housing material | **Cast iron** |
| Degree of protection | **IP55** |
| Cooling | **Self-ventilated (IC 411)** |
| Insulation / utilization | **Thermal class 155 (F) / utilized to 130 (B)** |
| Duty type | **S1 (continuous duty)** |
| Rotor | **Squirrel-cage** |
| Efficiency class (IEC 60034-30) | **IE1** |
| Voltage / connection | **400 V Δ / 690 V Y (50 Hz), 460 V Δ (60 Hz)** |
| Type of construction | **IM B3 (basic type, without flange)** |
| Net weight (IM B3) | **62 kg** |

## ELECTRICAL DATA - 400 V, 50 HZ

| | |
|---|---|
| Rated power, 50 Hz | **3 kW (4 HP)** |
| Rated speed, 50 Hz | **715 rpm (synchronous 750 rpm)** |
| Rated torque | **40 Nm** |
| Rated current at 400 V | **8.3 A** |
| Power factor cos φ | **0.68** |
| Efficiency at 4/4 \| 3/4 \| 2/4 load | **77.0 \| 77.4 \| 75.2 %** |
| Locked-rotor current ratio (I_LR/I_N) | **3.9** |
| Locked-rotor torque ratio (T_LR/T_N) | **1.8** |
| Breakdown torque ratio (T_B/T_N) | **2.2** |
| Moment of inertia J | **0.024 kgm²** |
| Sound pressure level LpfA (50 Hz) | **63 dB(A)** |
| Sound power level LWA (50 Hz) | **75 dB(A)** |

## 60 HZ OPERATION

| | |
|---|---|
| Rated power at 60 Hz (460 V) | **3.45 kW** |
| Synchronous speed at 60 Hz | **900 rpm** |
| Speed / efficiency / current at 60 Hz | **not listed in the catalog (DT Configurator)** |

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Source: Siemens Catalog D 81.1 (05/2018), p. 2/51. Dimensions: see the same catalog.
Compiled from the manufacturer's catalog data for reference. It is not an official Siemens document - verify against the current Siemens data sheet before ordering.
Data at rated power, 400 V / 50 Hz, ambient 40 °C, altitude up to 1000 m.

# Data sheet

**1LE1502-1CD23-4FA4**

SIMOTICS GP low-voltage motor - cast-iron series 1LE1502 Basic Line (IE1)

# 3 kW / 750 rpm

Frame size 132 M | Article No. 1LE1502-1CD23-4FA4 | mounting IM B5

## GENERAL DATA

| | |
|---|---|
| Motor series | **1LE1502 Basic Line (cast iron)** |
| Article No. | **1LE1502-1CD23-4FA4** |
| Frame size | **132 M** |
| Number of poles | **8** |
| Housing material | **Cast iron** |
| Degree of protection | **IP55** |
| Cooling | **Self-ventilated (IC 411)** |
| Insulation / utilization | **Thermal class 155 (F) / utilized to 130 (B)** |
| Duty type | **S1 (continuous duty)** |
| Rotor | **Squirrel-cage** |
| Efficiency class (IEC 60034-30) | **IE1** |
| Voltage / connection | **400 V Δ / 690 V Y (50 Hz), 460 V Δ (60 Hz)** |
| Type of construction | **IM B5 (flange)** |
| Net weight (IM B3) | **62 kg** |

## ELECTRICAL DATA - 400 V, 50 HZ

| | |
|---|---|
| Rated power, 50 Hz | **3 kW (4 HP)** |
| Rated speed, 50 Hz | **715 rpm (synchronous 750 rpm)** |
| Rated torque | **40 Nm** |
| Rated current at 400 V | **8.3 A** |
| Power factor cos φ | **0.68** |
| Efficiency at 4/4 \| 3/4 \| 2/4 load | **77.0 \| 77.4 \| 75.2 %** |
| Locked-rotor current ratio (I_LR/I_N) | **3.9** |
| Locked-rotor torque ratio (T_LR/T_N) | **1.8** |
| Breakdown torque ratio (T_B/T_N) | **2.2** |
| Moment of inertia J | **0.024 kgm²** |
| Sound pressure level LpfA (50 Hz) | **63 dB(A)** |
| Sound power level LWA (50 Hz) | **75 dB(A)** |

## 60 HZ OPERATION

| | |
|---|---|
| Rated power at 60 Hz (460 V) | **3.45 kW** |
| Synchronous speed at 60 Hz | **900 rpm** |
| Speed / efficiency / current at 60 Hz | **not listed in the catalog (DT Configurator)** |

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Source: Siemens Catalog D 81.1 (05/2018), p. 2/51. Dimensions: see the same catalog.
Compiled from the manufacturer's catalog data for reference. It is not an official Siemens document - verify against the current Siemens data sheet before ordering.
Data at rated power, 400 V / 50 Hz, ambient 40 °C, altitude up to 1000 m.

# Data sheet

**1LE1502-1CD23-4KA4**

SIMOTICS GP low-voltage motor - cast-iron series 1LE1502 Basic Line (IE1)

# 3 kW / 750 rpm

Frame size 132 M | Article No. 1LE1502-1CD23-4KA4 | mounting IM B14

## GENERAL DATA

| | |
|---|---|
| Motor series | **1LE1502 Basic Line (cast iron)** |
| Article No. | **1LE1502-1CD23-4KA4** |
| Frame size | **132 M** |
| Number of poles | **8** |
| Housing material | **Cast iron** |
| Degree of protection | **IP55** |
| Cooling | **Self-ventilated (IC 411)** |
| Insulation / utilization | **Thermal class 155 (F) / utilized to 130 (B)** |
| Duty type | **S1 (continuous duty)** |
| Rotor | **Squirrel-cage** |
| Efficiency class (IEC 60034-30) | **IE1** |
| Voltage / connection | **400 V Δ / 690 V Y (50 Hz), 460 V Δ (60 Hz)** |
| Type of construction | **IM B14 (flange)** |
| Net weight (IM B3) | **62 kg** |

## ELECTRICAL DATA - 400 V, 50 HZ

| | |
|---|---|
| Rated power, 50 Hz | **3 kW (4 HP)** |
| Rated speed, 50 Hz | **715 rpm (synchronous 750 rpm)** |
| Rated torque | **40 Nm** |
| Rated current at 400 V | **8.3 A** |
| Power factor cos φ | **0.68** |
| Efficiency at 4/4 \| 3/4 \| 2/4 load | **77.0 \| 77.4 \| 75.2 %** |
| Locked-rotor current ratio (I_LR/I_N) | **3.9** |
| Locked-rotor torque ratio (T_LR/T_N) | **1.8** |
| Breakdown torque ratio (T_B/T_N) | **2.2** |
| Moment of inertia J | **0.024 kgm²** |
| Sound pressure level LpfA (50 Hz) | **63 dB(A)** |
| Sound power level LWA (50 Hz) | **75 dB(A)** |

## 60 HZ OPERATION

| | |
|---|---|
| Rated power at 60 Hz (460 V) | **3.45 kW** |
| Synchronous speed at 60 Hz | **900 rpm** |
| Speed / efficiency / current at 60 Hz | **not listed in the catalog (DT Configurator)** |

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Source: Siemens Catalog D 81.1 (05/2018), p. 2/51. Dimensions: see the same catalog.
Compiled from the manufacturer's catalog data for reference. It is not an official Siemens document - verify against the current Siemens data sheet before ordering.
Data at rated power, 400 V / 50 Hz, ambient 40 °C, altitude up to 1000 m.

# Data sheet

SIMOTICS GP low-voltage motor - series 1LE1001 (IE2)

**1LE1001-1CD23-4AA4**

# 3 kW / 750 rpm

Frame 132 M | 8 poles | IM B3 | Article No. 1LE1001-1CD23-4AA4

## GENERAL DATA

| | |
|---|---|
| Series / efficiency class | **1LE1001 / IE2** |
| Housing | **Aluminum** |
| Frame size | **132 M** |
| Poles | **8** |
| Degree of protection | **IP55** |
| Duty type | **S1** |
| Insulation | **Thermal class 155 (F), utilized to 130 (B)** |
| Voltage | **400 D / 690 Y V (50 Hz)** |
| Net weight (IM B3) | **52 kg** |

## ELECTRICAL DATA

| | |
|---|---|
| Rated power 50 Hz | **3 kW (about 4 HP)** |
| Rated power 60 Hz | **3.45 kW** |
| Rated speed (50 Hz) | **720 rpm** |
| Rated torque | **40 Nm** |
| Rated current | **8.7 A** |
| Power factor | **0.62** |
| Efficiency 4/4 \| 3/4 \| 2/4 | **80 \| 80.7 \| 79.2 %** |
| I_LR/I_N \| T_LR/T_N \| T_B/T_N | **3.7 \| 1.4 \| 2** |
| Moment of inertia J | **0.037 kgm2** |
| Sound pressure / power LpfA \| LWA | **63 \| 75 dB(A)** |

## SOURCE OF DATA

| | |
|---|---|
| Catalog 1 | **Catalog D 81.1 (05/2018), table 1LE1001, p. 2/29 (PDF 147)** |

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

# Data sheet

SIMOTICS GP low-voltage motor - series 1LE1001 (IE2)

**1LE1001-1CD23-4FA4**

# 3 kW / 750 rpm

Frame 132 M | 8 poles | IM B5 | Article No. 1LE1001-1CD23-4FA4

## GENERAL DATA

| | |
|---|---|
| Series / efficiency class | **1LE1001 / IE2** |
| Housing | **Aluminum** |
| Frame size | **132 M** |
| Poles | **8** |
| Degree of protection | **IP55** |
| Duty type | **S1** |
| Insulation | **Thermal class 155 (F), utilized to 130 (B)** |
| Voltage | **400 D / 690 Y V (50 Hz)** |
| Net weight (IM B3) | **52 kg** |

## ELECTRICAL DATA

| | |
|---|---|
| Rated power 50 Hz | **3 kW (about 4 HP)** |
| Rated power 60 Hz | **3.45 kW** |
| Rated speed (50 Hz) | **720 rpm** |
| Rated torque | **40 Nm** |
| Rated current | **8.7 A** |
| Power factor | **0.62** |
| Efficiency 4/4 \| 3/4 \| 2/4 | **80 \| 80.7 \| 79.2 %** |
| I_LR/I_N \| T_LR/T_N \| T_B/T_N | **3.7 \| 1.4 \| 2** |
| Moment of inertia J | **0.037 kgm2** |
| Sound pressure / power LpfA \| LWA | **63 \| 75 dB(A)** |

## SOURCE OF DATA

| | |
|---|---|
| Catalog 1 | **Catalog D 81.1 (05/2018), table 1LE1001, p. 2/29 (PDF 147)** |

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

# Data sheet

SIMOTICS GP low-voltage motor - series 1LE1001 (IE2)

**1LE1001-1CD23-4KA4**

# 3 kW / 750 rpm

Frame 132 M | 8 poles | IM B14 | Article No. 1LE1001-1CD23-4KA4

## GENERAL DATA

| | |
|---|---|
| Series / efficiency class | **1LE1001 / IE2** |
| Housing | **Aluminum** |
| Frame size | **132 M** |
| Poles | **8** |
| Degree of protection | **IP55** |
| Duty type | **S1** |
| Insulation | **Thermal class 155 (F), utilized to 130 (B)** |
| Voltage | **400 D / 690 Y V (50 Hz)** |
| Net weight (IM B3) | **52 kg** |

## ELECTRICAL DATA

| | |
|---|---|
| Rated power 50 Hz | **3 kW (about 4 HP)** |
| Rated power 60 Hz | **3.45 kW** |
| Rated speed (50 Hz) | **720 rpm** |
| Rated torque | **40 Nm** |
| Rated current | **8.7 A** |
| Power factor | **0.62** |
| Efficiency 4/4 \| 3/4 \| 2/4 | **80 \| 80.7 \| 79.2 %** |
| I_LR/I_N \| T_LR/T_N \| T_B/T_N | **3.7 \| 1.4 \| 2** |
| Moment of inertia J | **0.037 kgm2** |
| Sound pressure / power LpfA \| LWA | **63 \| 75 dB(A)** |

## SOURCE OF DATA

| | |
|---|---|
| Catalog 1 | **Catalog D 81.1 (05/2018), table 1LE1001, p. 2/29 (PDF 147)** |

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

# Data sheet

SIMOTICS GP low-voltage motor - series 1LE1002 (IE1)

**1LE1002-1CD23-4AA4**

# 3 kW / 750 rpm

Frame 132 M | 8 poles | IM B3 | Article No. 1LE1002-1CD23-4AA4

## GENERAL DATA

| | |
|---|---|
| Series / efficiency class | **1LE1002 / IE1** |
| Housing | **Aluminum** |
| Frame size | **132 M** |
| Poles | **8** |
| Degree of protection | **IP55** |
| Duty type | **S1** |
| Insulation | **Thermal class 155 (F), utilized to 130 (B)** |
| Voltage | **400 D / 690 Y V (50 Hz)** |
| Net weight (IM B3) | **44 kg** |

## ELECTRICAL DATA

| | |
|---|---|
| Rated power 50 Hz | **3 kW (about 4 HP)** |
| Rated power 60 Hz | **3.45 kW** |
| Rated speed (50 Hz) | **715 rpm** |
| Rated torque | **40 Nm** |
| Rated current | **8.3 A** |
| Power factor | **0.68** |
| Efficiency 4/4 \| 3/4 \| 2/4 | **77 \| 77.4 \| 75.2 %** |
| I_LR/I_N \| T_LR/T_N \| T_B/T_N | **3.9 \| 1.8 \| 2.2** |
| Moment of inertia J | **0.024 kgm2** |
| Sound pressure / power LpfA \| LWA | **63 \| 75 dB(A)** |

## SOURCE OF DATA

| | |
|---|---|
| Catalog 1 | **Catalog D 81.1 (05/2018), table 1LE1002, p. 2/46 (PDF 164)** |

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

# Data sheet

SIMOTICS GP low-voltage motor - series 1LE1002 (IE1)

**1LE1002-1CD23-4FA4**

# 3 kW / 750 rpm

Frame 132 M | 8 poles | IM B5 | Article No. 1LE1002-1CD23-4FA4

## GENERAL DATA

| | |
|---|---|
| Series / efficiency class | **1LE1002 / IE1** |
| Housing | **Aluminum** |
| Frame size | **132 M** |
| Poles | **8** |
| Degree of protection | **IP55** |
| Duty type | **S1** |
| Insulation | **Thermal class 155 (F), utilized to 130 (B)** |
| Voltage | **400 D / 690 Y V (50 Hz)** |
| Net weight (IM B3) | **44 kg** |

## ELECTRICAL DATA

| | |
|---|---|
| Rated power 50 Hz | **3 kW (about 4 HP)** |
| Rated power 60 Hz | **3.45 kW** |
| Rated speed (50 Hz) | **715 rpm** |
| Rated torque | **40 Nm** |
| Rated current | **8.3 A** |
| Power factor | **0.68** |
| Efficiency 4/4 \| 3/4 \| 2/4 | **77 \| 77.4 \| 75.2 %** |
| I_LR/I_N \| T_LR/T_N \| T_B/T_N | **3.9 \| 1.8 \| 2.2** |
| Moment of inertia J | **0.024 kgm2** |
| Sound pressure / power LpfA \| LWA | **63 \| 75 dB(A)** |

## SOURCE OF DATA

| | |
|---|---|
| Catalog 1 | **Catalog D 81.1 (05/2018), table 1LE1002, p. 2/46 (PDF 164)** |

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

# Data sheet

SIMOTICS GP low-voltage motor - series 1LE1002 (IE1)

**1LE1002-1CD23-4KA4**

# 3 kW / 750 rpm

Frame 132 M | 8 poles | IM B14 | Article No. 1LE1002-1CD23-4KA4

## GENERAL DATA

| | |
|---|---|
| Series / efficiency class | **1LE1002 / IE1** |
| Housing | **Aluminum** |
| Frame size | **132 M** |
| Poles | **8** |
| Degree of protection | **IP55** |
| Duty type | **S1** |
| Insulation | **Thermal class 155 (F), utilized to 130 (B)** |
| Voltage | **400 D / 690 Y V (50 Hz)** |
| Net weight (IM B3) | **44 kg** |

## ELECTRICAL DATA

| | |
|---|---|
| Rated power 50 Hz | **3 kW (about 4 HP)** |
| Rated power 60 Hz | **3.45 kW** |
| Rated speed (50 Hz) | **715 rpm** |
| Rated torque | **40 Nm** |
| Rated current | **8.3 A** |
| Power factor | **0.68** |
| Efficiency 4/4 \| 3/4 \| 2/4 | **77 \| 77.4 \| 75.2 %** |
| I_LR/I_N \| T_LR/T_N \| T_B/T_N | **3.9 \| 1.8 \| 2.2** |
| Moment of inertia J | **0.024 kgm2** |
| Sound pressure / power LpfA \| LWA | **63 \| 75 dB(A)** |

## SOURCE OF DATA

| | |
|---|---|
| Catalog 1 | **Catalog D 81.1 (05/2018), table 1LE1002, p. 2/46 (PDF 164)** |

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

# Data sheet

SIMOTICS GP low-voltage motor - series 1LE1003 (IE3)

**1LE1003-1CD23-4AA4**

# 3 kW / 750 rpm

Frame 132 M | 8 poles | IM B3 | Article No. 1LE1003-1CD23-4AA4

## GENERAL DATA

| | |
|---|---|
| Series / efficiency class | **1LE1003 / IE3** |
| Housing | **Aluminum** |
| Frame size | **132 M** |
| Poles | **8** |
| Degree of protection | **IP55** |
| Duty type | **S1** |
| Insulation | **Thermal class 155 (F), utilized to 130 (B)** |
| Voltage | **400 D / 690 Y V (50 Hz)** |
| Net weight (IM B3) | **58 kg** |

## ELECTRICAL DATA

| | |
|---|---|
| Rated power 50 Hz | **3 kW (about 4 HP)** |
| Rated power 60 Hz | **not listed (catalog 09/2023)** |
| Rated speed (50 Hz) | **725 rpm** |
| Rated torque | **39.5 Nm** |
| Rated current | **7.1 A** |
| Power factor | **0.72** |
| Efficiency 4/4 \| 3/4 \| 2/4 | **83.5 \| 83.8 \| 82.2 %** |
| I_LR/I_N \| T_LR/T_N \| T_B/T_N | **5.2 \| 2 \| 2.5** |
| Moment of inertia J | **0.061 kgm2** |
| Sound pressure / power LpfA \| LWA | **70 \| 78 dB(A)** |

## SOURCE OF DATA

| | |
|---|---|
| Catalog 1 | **Catalog D 81.1 (09/2023), table 1LE1003, p. 3/16** |

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

# Data sheet

SIMOTICS GP low-voltage motor - series 1LE1003 (IE3)

**1LE1003-1CD23-4FA4**

# 3 kW / 750 rpm

Frame 132 M | 8 poles | IM B5 | Article No. 1LE1003-1CD23-4FA4

## GENERAL DATA

| | |
|---|---|
| Series / efficiency class | **1LE1003 / IE3** |
| Housing | **Aluminum** |
| Frame size | **132 M** |
| Poles | **8** |
| Degree of protection | **IP55** |
| Duty type | **S1** |
| Insulation | **Thermal class 155 (F), utilized to 130 (B)** |
| Voltage | **400 D / 690 Y V (50 Hz)** |
| Net weight (IM B3) | **58 kg** |

## ELECTRICAL DATA

| | |
|---|---|
| Rated power 50 Hz | **3 kW (about 4 HP)** |
| Rated power 60 Hz | **not listed (catalog 09/2023)** |
| Rated speed (50 Hz) | **725 rpm** |
| Rated torque | **39.5 Nm** |
| Rated current | **7.1 A** |
| Power factor | **0.72** |
| Efficiency 4/4 \| 3/4 \| 2/4 | **83.5 \| 83.8 \| 82.2 %** |
| I_LR/I_N \| T_LR/T_N \| T_B/T_N | **5.2 \| 2 \| 2.5** |
| Moment of inertia J | **0.061 kgm2** |
| Sound pressure / power LpfA \| LWA | **70 \| 78 dB(A)** |

## SOURCE OF DATA

| | |
|---|---|
| Catalog 1 | **Catalog D 81.1 (09/2023), table 1LE1003, p. 3/16** |

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

# Data sheet

SIMOTICS GP low-voltage motor - series 1LE1003 (IE3)

**1LE1003-1CD23-4KA4**

# 3 kW / 750 rpm

Frame 132 M | 8 poles | IM B14 | Article No. 1LE1003-1CD23-4KA4

## GENERAL DATA

| | |
|---|---|
| Series / efficiency class | **1LE1003 / IE3** |
| Housing | **Aluminum** |
| Frame size | **132 M** |
| Poles | **8** |
| Degree of protection | **IP55** |
| Duty type | **S1** |
| Insulation | **Thermal class 155 (F), utilized to 130 (B)** |
| Voltage | **400 D / 690 Y V (50 Hz)** |
| Net weight (IM B3) | **58 kg** |

## ELECTRICAL DATA

| | |
|---|---|
| Rated power 50 Hz | **3 kW (about 4 HP)** |
| Rated power 60 Hz | **not listed (catalog 09/2023)** |
| Rated speed (50 Hz) | **725 rpm** |
| Rated torque | **39.5 Nm** |
| Rated current | **7.1 A** |
| Power factor | **0.72** |
| Efficiency 4/4 \| 3/4 \| 2/4 | **83.5 \| 83.8 \| 82.2 %** |
| I_LR/I_N \| T_LR/T_N \| T_B/T_N | **5.2 \| 2 \| 2.5** |
| Moment of inertia J | **0.061 kgm2** |
| Sound pressure / power LpfA \| LWA | **70 \| 78 dB(A)** |

## SOURCE OF DATA

| | |
|---|---|
| Catalog 1 | **Catalog D 81.1 (09/2023), table 1LE1003, p. 3/16** |

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

# Data sheet

SIMOTICS GP low-voltage motor - series 1LE1501 (IE2)

**1LE1501-1CD23-4AA4**

# 3 kW / 750 rpm

Frame 132 M | 8 poles | IM B3 | Article No. 1LE1501-1CD23-4AA4

## GENERAL DATA

| | |
|---|---|
| Series / efficiency class | **1LE1501 / IE2** |
| Housing | **Cast iron** |
| Frame size | **132 M** |
| Poles | **8** |
| Degree of protection | **IP55** |
| Duty type | **S1** |
| Insulation | **Thermal class 155 (F), utilized to 130 (B)** |
| Voltage | **400 D / 690 Y V (50 Hz)** |
| Net weight (IM B3) | **67 kg** |

## ELECTRICAL DATA

| | |
|---|---|
| Rated power 50 Hz | **3 kW (about 4 HP)** |
| Rated power 60 Hz | **3.45 kW** |
| Rated speed (50 Hz) | **720 rpm** |
| Rated torque | **40 Nm** |
| Rated current | **8.7 A** |
| Power factor | **0.62** |
| Efficiency 4/4 \| 3/4 \| 2/4 | **80 \| 80.7 \| 79.2 %** |
| I_LR/I_N \| T_LR/T_N \| T_B/T_N | **3.7 \| 1.4 \| 2** |
| Moment of inertia J | **0.037 kgm2** |
| Sound pressure / power LpfA \| LWA | **63 \| 75 dB(A)** |

## SOURCE OF DATA

| | |
|---|---|
| Catalog 1 | **Catalog D 81.1 (05/2018), table 1LE1501, p. 2/35 (PDF 153)** |

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

# Data sheet

SIMOTICS GP low-voltage motor - series 1LE1501 (IE2)

**1LE1501-1CD23-4FA4**

# 3 kW / 750 rpm

Frame 132 M | 8 poles | IM B5 | Article No. 1LE1501-1CD23-4FA4

## GENERAL DATA

| | |
|---|---|
| Series / efficiency class | **1LE1501 / IE2** |
| Housing | **Cast iron** |
| Frame size | **132 M** |
| Poles | **8** |
| Degree of protection | **IP55** |
| Duty type | **S1** |
| Insulation | **Thermal class 155 (F), utilized to 130 (B)** |
| Voltage | **400 D / 690 Y V (50 Hz)** |
| Net weight (IM B3) | **67 kg** |

## ELECTRICAL DATA

| | |
|---|---|
| Rated power 50 Hz | **3 kW (about 4 HP)** |
| Rated power 60 Hz | **3.45 kW** |
| Rated speed (50 Hz) | **720 rpm** |
| Rated torque | **40 Nm** |
| Rated current | **8.7 A** |
| Power factor | **0.62** |
| Efficiency 4/4 \| 3/4 \| 2/4 | **80 \| 80.7 \| 79.2 %** |
| I_LR/I_N \| T_LR/T_N \| T_B/T_N | **3.7 \| 1.4 \| 2** |
| Moment of inertia J | **0.037 kgm2** |
| Sound pressure / power LpfA \| LWA | **63 \| 75 dB(A)** |

## SOURCE OF DATA

| | |
|---|---|
| Catalog 1 | **Catalog D 81.1 (05/2018), table 1LE1501, p. 2/35 (PDF 153)** |

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

# Data sheet

SIMOTICS GP low-voltage motor - series 1LE1501 (IE2)

**1LE1501-1CD23-4KA4**

# 3 kW / 750 rpm

Frame 132 M | 8 poles | IM B14 | Article No. 1LE1501-1CD23-4KA4

## GENERAL DATA

| | |
|---|---|
| Series / efficiency class | **1LE1501 / IE2** |
| Housing | **Cast iron** |
| Frame size | **132 M** |
| Poles | **8** |
| Degree of protection | **IP55** |
| Duty type | **S1** |
| Insulation | **Thermal class 155 (F), utilized to 130 (B)** |
| Voltage | **400 D / 690 Y V (50 Hz)** |
| Net weight (IM B3) | **67 kg** |

## ELECTRICAL DATA

| | |
|---|---|
| Rated power 50 Hz | **3 kW (about 4 HP)** |
| Rated power 60 Hz | **3.45 kW** |
| Rated speed (50 Hz) | **720 rpm** |
| Rated torque | **40 Nm** |
| Rated current | **8.7 A** |
| Power factor | **0.62** |
| Efficiency 4/4 \| 3/4 \| 2/4 | **80 \| 80.7 \| 79.2 %** |
| I_LR/I_N \| T_LR/T_N \| T_B/T_N | **3.7 \| 1.4 \| 2** |
| Moment of inertia J | **0.037 kgm2** |
| Sound pressure / power LpfA \| LWA | **63 \| 75 dB(A)** |

## SOURCE OF DATA

| | |
|---|---|
| Catalog 1 | **Catalog D 81.1 (05/2018), table 1LE1501, p. 2/35 (PDF 153)** |

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).