Data sheets - Siemens SIMOTICS GP motors

4 kW / 1000 rpm - 40 article numbers in this file

Article No.	Page
1LE1002-1CC23-4KA4	2
1LE1001-1CC23-4AA4	3
1LE1001-1CC23-4FA4	4
1LE1001-1CC23-4KA4	5
1LE1003-1CC23-4AA4	6
1LE1003-1CC23-4FA4	7
1LE1003-1CC23-4KA4	8
1LE1041-1CC23-4FA4	9
1LE1041-1CC23-4KA4	10
1LE1043-1CC23-4AA4	11
1LE1043-1CC23-4FA4	12
1LE1043-1CC23-4KA4	13
1LE0102-1CC22-2AA4	14
1LE0102-1CC22-2FA4	15
1LE0102-1CC22-2KA4	16
1LE0102-1CC23-4AA4	17
1LE0102-1CC23-4FA4	18
1LE0102-1CC23-4KA4	19
1LE0102-1CC24-1AA4	20
1LE0102-1CC24-1FA4	21
1LE0102-1CC24-1KA4	22
1LE1502-1CC23-4AA4	23
1LE1502-1CC23-4FA4	24
1LE1502-1CC23-4KA4	25
1LE0101-1CC22-2AA4	26
1LE0101-1CC22-2FA4	27
1LE0101-1CC22-2KA4	28
1LE0101-1CC23-4AA4	29
1LE0101-1CC23-4FA4	30
1LE0101-1CC23-4KA4	31
1LE0101-1CC24-1AA4	32
1LE0101-1CC24-1FA4	33
1LE0101-1CC24-1KA4	34
1LE1501-1CC23-4AA4	35
1LE1501-1CC23-4FA4	36
1LE1501-1CC23-4KA4	37
1LE1503-1CC23-4AA4	38
1LE1503-1CC23-4FA4	39
1LE1543-1CC23-4AA4	40
1LE1543-1CC23-4FA4	41

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1002 (IE1)

1LE1002-1CC23-4KA4

4 kW / 1000 rpm

Frame 132 M | 6 poles | IM B14 | Article No. 1LE1002-1CC23-4KA4

GENERAL DATA

Series / efficiency class	**1LE1002 / IE1**
Housing	**Aluminum**
Frame size	**132 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**39 kg**

ELECTRICAL DATA

Rated power 50 Hz	**4 kW (about 5.5 HP)**
Rated power 60 Hz	**4.55 kW**
Rated speed (50 Hz)	**955 rpm**
Rated torque	**40 Nm**
Rated current	**9.3 A**
Power factor	**0.76**
Efficiency 4/4 | 3/4 | 2/4	**81.4 | 82.6 | 81.9 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5.2 | 2.3 | 2.6**
Moment of inertia J	**0.021 kgm2**
Sound pressure / power LpfA | LWA	**63 | 75 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1002, p. 2/46 (PDF 164)**
Catalog 2	**Brochure 07/2014 (14050629), p. 18 (PDF 18)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1001 (IE2)

1LE1001-1CC23-4AA4

4 kW / 1000 rpm

Frame 132 M | 6 poles | IM B3 | Article No. 1LE1001-1CC23-4AA4

GENERAL DATA

Series / efficiency class	**1LE1001 / IE2**
Housing	**Aluminum**
Frame size	**132 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**43 kg**

ELECTRICAL DATA

Rated power 50 Hz	**4 kW (about 5.5 HP)**
Rated power 60 Hz	**4.55 kW**
Rated speed (50 Hz)	**970 rpm**
Rated torque	**39 Nm**
Rated current	**9.1 A**
Power factor	**0.75**
Efficiency 4/4 | 3/4 | 2/4	**84.6 | 85.5 | 84.3 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5 | 1.6 | 2.3**
Moment of inertia J	**0.029 kgm2**
Sound pressure / power LpfA | LWA	**63 | 75 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1001, p. 2/28 (PDF 146)**
Catalog 2	**Brochure 07/2014 (14050629), p. 19 (PDF 19)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

4 kW / 1000 rpm

Frame 132 M | 6 poles | IM B5 | Article No. 1LE1001-1CC23-4FA4

GENERAL DATA

Series / efficiency class	**1LE1001 / IE2**
Housing	**Aluminum**
Frame size	**132 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**43 kg**

ELECTRICAL DATA

Rated power 50 Hz	**4 kW (about 5.5 HP)**
Rated power 60 Hz	**4.55 kW**
Rated speed (50 Hz)	**970 rpm**
Rated torque	**39 Nm**
Rated current	**9.1 A**
Power factor	**0.75**
Efficiency 4/4 | 3/4 | 2/4	**84.6 | 85.5 | 84.3 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5 | 1.6 | 2.3**
Moment of inertia J	**0.029 kgm2**
Sound pressure / power LpfA | LWA	**63 | 75 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1001, p. 2/28 (PDF 146)**
Catalog 2	**Brochure 07/2014 (14050629), p. 19 (PDF 19)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1001 (IE2)

1LE1001-1CC23-4KA4

4 kW / 1000 rpm

Frame 132 M | 6 poles | IM B14 | Article No. 1LE1001-1CC23-4KA4

GENERAL DATA

Series / efficiency class	**1LE1001 / IE2**
Housing	**Aluminum**
Frame size	**132 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**43 kg**

ELECTRICAL DATA

Rated power 50 Hz	**4 kW (about 5.5 HP)**
Rated power 60 Hz	**4.55 kW**
Rated speed (50 Hz)	**970 rpm**
Rated torque	**39 Nm**
Rated current	**9.1 A**
Power factor	**0.75**
Efficiency 4/4 | 3/4 | 2/4	**84.6 | 85.5 | 84.3 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5 | 1.6 | 2.3**
Moment of inertia J	**0.029 kgm2**
Sound pressure / power LpfA | LWA	**63 | 75 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1001, p. 2/28 (PDF 146)**
Catalog 2	**Brochure 07/2014 (14050629), p. 19 (PDF 19)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1003 (IE3)

1LE1003-1CC23-4AA4

4 kW / 1000 rpm

Frame 132 M | 6 poles | IM B3 | Article No. 1LE1003-1CC23-4AA4

GENERAL DATA

Series / efficiency class	**1LE1003 / IE3**
Housing	**Aluminum**
Frame size	**132 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**61 kg**

ELECTRICAL DATA

Rated power 50 Hz	**4 kW (about 5.5 HP)**
Rated power 60 Hz	**not listed (catalog 09/2023)**
Rated speed (50 Hz)	**975 rpm**
Rated torque	**39 Nm**
Rated current	**9.1 A**
Power factor	**0.73**
Efficiency 4/4 | 3/4 | 2/4	**86.8 | 87.3 | 86.2 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**6.2 | 2.2 | 3**
Moment of inertia J	**0.037 kgm2**
Sound pressure / power LpfA | LWA	**67 | 75 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (09/2023), table 1LE1003, p. 3/15**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1003 (IE3)

1LE1003-1CC23-4FA4

4 kW / 1000 rpm

Frame 132 M | 6 poles | IM B5 | Article No. 1LE1003-1CC23-4FA4

GENERAL DATA

Series / efficiency class	**1LE1003 / IE3**
Housing	**Aluminum**
Frame size	**132 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**61 kg**

ELECTRICAL DATA

Rated power 50 Hz	**4 kW (about 5.5 HP)**
Rated power 60 Hz	**not listed (catalog 09/2023)**
Rated speed (50 Hz)	**975 rpm**
Rated torque	**39 Nm**
Rated current	**9.1 A**
Power factor	**0.73**
Efficiency 4/4 | 3/4 | 2/4	**86.8 | 87.3 | 86.2 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**6.2 | 2.2 | 3**
Moment of inertia J	**0.037 kgm2**
Sound pressure / power LpfA | LWA	**67 | 75 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (09/2023), table 1LE1003, p. 3/15**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1003 (IE3)

1LE1003-1CC23-4KA4

4 kW / 1000 rpm

Frame 132 M | 6 poles | IM B14 | Article No. 1LE1003-1CC23-4KA4

GENERAL DATA

Series / efficiency class	**1LE1003 / IE3**
Housing	**Aluminum**
Frame size	**132 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**61 kg**

ELECTRICAL DATA

Rated power 50 Hz	**4 kW (about 5.5 HP)**
Rated power 60 Hz	**not listed (catalog 09/2023)**
Rated speed (50 Hz)	**975 rpm**
Rated torque	**39 Nm**
Rated current	**9.1 A**
Power factor	**0.73**
Efficiency 4/4 | 3/4 | 2/4	**86.8 | 87.3 | 86.2 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**6.2 | 2.2 | 3**
Moment of inertia J	**0.037 kgm2**
Sound pressure / power LpfA | LWA	**67 | 75 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (09/2023), table 1LE1003, p. 3/15**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1041 (IE2)

1LE1041-1CC23-4FA4

4 kW / 1000 rpm

Frame 132 M | 6 poles | IM B5 | Article No. 1LE1041-1CC23-4FA4

GENERAL DATA

Series / efficiency class	**1LE1041 / IE2**
Housing	**Aluminum**
Frame size	**132 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**43 kg**

ELECTRICAL DATA - CATALOG VALUES AT 60 HZ (APAC LINE)

Rated power (P50 rating)	**4 kW (about 5.5 HP)**
Rated power (P60 rating)	**4.55 kW**
Rated speed (60 Hz)	**1180 rpm**
Rated torque (60 Hz)	**30 Nm**
Rated current (460 V, 60 Hz)	**7.5 A**
Power factor (60 Hz)	**0.71**
Efficiency 4/4 | 3/4 | 2/4 (60 Hz)	**87.5 | 87.5 | 85.7 %**
I_LR/I_N | T_LR/T_N | T_B/T_N (60 Hz)	**6.2 | 1.9 | 3**
Moment of inertia J	**0.029 kgm2**
Sound pressure / power LpfA | LWA (60 Hz)	**67 | 79 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1041, p. 2/66 (PDF 184)**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
APAC Line: the catalog lists operating values at 60 Hz only; 50 Hz speed/efficiency are not listed (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1041 (IE2)

1LE1041-1CC23-4KA4

4 kW / 1000 rpm

Frame 132 M | 6 poles | IM B14 | Article No. 1LE1041-1CC23-4KA4

GENERAL DATA

Series / efficiency class	**1LE1041 / IE2**
Housing	**Aluminum**
Frame size	**132 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**43 kg**

ELECTRICAL DATA - CATALOG VALUES AT 60 HZ (APAC LINE)

Rated power (P50 rating)	**4 kW (about 5.5 HP)**
Rated power (P60 rating)	**4.55 kW**
Rated speed (60 Hz)	**1180 rpm**
Rated torque (60 Hz)	**30 Nm**
Rated current (460 V, 60 Hz)	**7.5 A**
Power factor (60 Hz)	**0.71**
Efficiency 4/4 | 3/4 | 2/4 (60 Hz)	**87.5 | 87.5 | 85.7 %**
I_LR/I_N | T_LR/T_N | T_B/T_N (60 Hz)	**6.2 | 1.9 | 3**
Moment of inertia J	**0.029 kgm2**
Sound pressure / power LpfA | LWA (60 Hz)	**67 | 79 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1041, p. 2/66 (PDF 184)**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
APAC Line: the catalog lists operating values at 60 Hz only; 50 Hz speed/efficiency are not listed (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1043 (IE3)

1LE1043-1CC23-4AA4

4 kW / 1000 rpm

Frame 132 M | 6 poles | IM B3 | Article No. 1LE1043-1CC23-4AA4

GENERAL DATA

Series / efficiency class	**1LE1043 / IE3**
Housing	**Aluminum**
Frame size	**132 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**61 kg**

ELECTRICAL DATA - CATALOG VALUES AT 60 HZ (APAC LINE)

Rated power (P50 rating)	**4 kW (about 5.5 HP)**
Rated power (P60 rating)	**4.55 kW**
Rated speed (60 Hz)	**1180 rpm**
Rated torque (60 Hz)	**30 Nm**
Rated current (460 V, 60 Hz)	**7.5 A**
Power factor (60 Hz)	**0.69**
Efficiency 4/4 | 3/4 | 2/4 (60 Hz)	**89.5 | 89.2 | 87.5 %**
I_LR/I_N | T_LR/T_N | T_B/T_N (60 Hz)	**7.5 | 2.8 | 3.8**
Moment of inertia J	**0.037 kgm2**
Sound pressure / power LpfA | LWA (60 Hz)	**64 | 72 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (09/2023), table 1LE1043, p. 3/63**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
APAC Line: the catalog lists operating values at 60 Hz only; 50 Hz speed/efficiency are not listed (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1043 (IE3)

1LE1043-1CC23-4FA4

4 kW / 1000 rpm

Frame 132 M | 6 poles | IM B5 | Article No. 1LE1043-1CC23-4FA4

GENERAL DATA

Series / efficiency class	**1LE1043 / IE3**
Housing	**Aluminum**
Frame size	**132 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**61 kg**

ELECTRICAL DATA - CATALOG VALUES AT 60 HZ (APAC LINE)

Rated power (P50 rating)	**4 kW (about 5.5 HP)**
Rated power (P60 rating)	**4.55 kW**
Rated speed (60 Hz)	**1180 rpm**
Rated torque (60 Hz)	**30 Nm**
Rated current (460 V, 60 Hz)	**7.5 A**
Power factor (60 Hz)	**0.69**
Efficiency 4/4 | 3/4 | 2/4 (60 Hz)	**89.5 | 89.2 | 87.5 %**
I_LR/I_N | T_LR/T_N | T_B/T_N (60 Hz)	**7.5 | 2.8 | 3.8**
Moment of inertia J	**0.037 kgm2**
Sound pressure / power LpfA | LWA (60 Hz)	**64 | 72 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (09/2023), table 1LE1043, p. 3/63**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
APAC Line: the catalog lists operating values at 60 Hz only; 50 Hz speed/efficiency are not listed (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1043 (IE3)

1LE1043-1CC23-4KA4

4 kW / 1000 rpm

Frame 132 M | 6 poles | IM B14 | Article No. 1LE1043-1CC23-4KA4

GENERAL DATA

Series / efficiency class	**1LE1043 / IE3**
Housing	**Aluminum**
Frame size	**132 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**61 kg**

ELECTRICAL DATA - CATALOG VALUES AT 60 HZ (APAC LINE)

Rated power (P50 rating)	**4 kW (about 5.5 HP)**
Rated power (P60 rating)	**4.55 kW**
Rated speed (60 Hz)	**1180 rpm**
Rated torque (60 Hz)	**30 Nm**
Rated current (460 V, 60 Hz)	**7.5 A**
Power factor (60 Hz)	**0.69**
Efficiency 4/4 | 3/4 | 2/4 (60 Hz)	**89.5 | 89.2 | 87.5 %**
I_LR/I_N | T_LR/T_N | T_B/T_N (60 Hz)	**7.5 | 2.8 | 3.8**
Moment of inertia J	**0.037 kgm2**
Sound pressure / power LpfA | LWA (60 Hz)	**64 | 72 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (09/2023), table 1LE1043, p. 3/63**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
APAC Line: the catalog lists operating values at 60 Hz only; 50 Hz speed/efficiency are not listed (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0102 (IE1)

1LE0102-1CC22-2AA4

4 kW / 1000 rpm

Frame 132 M | 6 poles | IM B3 | Article No. 1LE0102-1CC22-2AA4

GENERAL DATA

Series / efficiency class	**1LE0102 / IE1**
Housing	**Cast iron**
Frame size	**132 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**65 kg**

ELECTRICAL DATA

Rated power 50 Hz	**4 kW (about 5.5 HP)**
Rated power 60 Hz	**4.55 kW**
Rated speed (50 Hz)	**955 rpm**
Rated torque	**40 Nm**
Rated current	**9.7 A**
Power factor	**0.73**
Efficiency 4/4 | 3/4 | 2/4	**81.4 | 82.2 | 79.4 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5.6 | 2.1 | 2.9**
Moment of inertia J	**0.023 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0102, p. 22 (PDF 22)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0102 (IE1)

1LE0102-1CC22-2FA4

4 kW / 1000 rpm

Frame 132 M | 6 poles | IM B5 | Article No. 1LE0102-1CC22-2FA4

GENERAL DATA

Series / efficiency class	**1LE0102 / IE1**
Housing	**Cast iron**
Frame size	**132 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**65 kg**

ELECTRICAL DATA

Rated power 50 Hz	**4 kW (about 5.5 HP)**
Rated power 60 Hz	**4.55 kW**
Rated speed (50 Hz)	**955 rpm**
Rated torque	**40 Nm**
Rated current	**9.7 A**
Power factor	**0.73**
Efficiency 4/4 | 3/4 | 2/4	**81.4 | 82.2 | 79.4 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5.6 | 2.1 | 2.9**
Moment of inertia J	**0.023 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0102, p. 22 (PDF 22)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0102 (IE1)

1LE0102-1CC22-2KA4

4 kW / 1000 rpm

Frame 132 M | 6 poles | IM B14 | Article No. 1LE0102-1CC22-2KA4

GENERAL DATA

Series / efficiency class	**1LE0102 / IE1**
Housing	**Cast iron**
Frame size	**132 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**65 kg**

ELECTRICAL DATA

Rated power 50 Hz	**4 kW (about 5.5 HP)**
Rated power 60 Hz	**4.55 kW**
Rated speed (50 Hz)	**955 rpm**
Rated torque	**40 Nm**
Rated current	**9.7 A**
Power factor	**0.73**
Efficiency 4/4 | 3/4 | 2/4	**81.4 | 82.2 | 79.4 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5.6 | 2.1 | 2.9**
Moment of inertia J	**0.023 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0102, p. 22 (PDF 22)**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0102 (IE1)

1LE0102-1CC23-4AA4

4 kW / 1000 rpm

Frame 132 M | 6 poles | IM B3 | Article No. 1LE0102-1CC23-4AA4

GENERAL DATA

Series / efficiency class	**1LE0102 / IE1**
Housing	**Cast iron**
Frame size	**132 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**65 kg**

ELECTRICAL DATA

Rated power 50 Hz	**4 kW (about 5.5 HP)**
Rated power 60 Hz	**4.55 kW**
Rated speed (50 Hz)	**955 rpm**
Rated torque	**40 Nm**
Rated current	**9.7 A**
Power factor	**0.73**
Efficiency 4/4 | 3/4 | 2/4	**81.4 | 82.2 | 79.4 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5.6 | 2.1 | 2.9**
Moment of inertia J	**0.023 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0102, p. 22 (PDF 22)**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0102 (IE1)

1LE0102-1CC23-4FA4

4 kW / 1000 rpm

Frame 132 M | 6 poles | IM B5 | Article No. 1LE0102-1CC23-4FA4

GENERAL DATA

Series / efficiency class	**1LE0102 / IE1**
Housing	**Cast iron**
Frame size	**132 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**65 kg**

ELECTRICAL DATA

Rated power 50 Hz	**4 kW (about 5.5 HP)**
Rated power 60 Hz	**4.55 kW**
Rated speed (50 Hz)	**955 rpm**
Rated torque	**40 Nm**
Rated current	**9.7 A**
Power factor	**0.73**
Efficiency 4/4 | 3/4 | 2/4	**81.4 | 82.2 | 79.4 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5.6 | 2.1 | 2.9**
Moment of inertia J	**0.023 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0102, p. 22 (PDF 22)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0102 (IE1)

1LE0102-1CC23-4KA4

4 kW / 1000 rpm

Frame 132 M | 6 poles | IM B14 | Article No. 1LE0102-1CC23-4KA4

GENERAL DATA

Series / efficiency class	**1LE0102 / IE1**
Housing	**Cast iron**
Frame size	**132 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**65 kg**

ELECTRICAL DATA

Rated power 50 Hz	**4 kW (about 5.5 HP)**
Rated power 60 Hz	**4.55 kW**
Rated speed (50 Hz)	**955 rpm**
Rated torque	**40 Nm**
Rated current	**9.7 A**
Power factor	**0.73**
Efficiency 4/4 | 3/4 | 2/4	**81.4 | 82.2 | 79.4 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5.6 | 2.1 | 2.9**
Moment of inertia J	**0.023 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0102, p. 22 (PDF 22)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0102 (IE1)

1LE0102-1CC24-1AA4

4 kW / 1000 rpm

Frame 132 M | 6 poles | IM B3 | Article No. 1LE0102-1CC24-1AA4

GENERAL DATA

Series / efficiency class	**1LE0102 / IE1**
Housing	**Cast iron**
Frame size	**132 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**525 V D**
Net weight (IM B3)	**65 kg**

ELECTRICAL DATA

Rated power 50 Hz	**4 kW (about 5.5 HP)**
Rated power 60 Hz	**4.55 kW**
Rated speed (50 Hz)	**955 rpm**
Rated torque	**40 Nm**
Rated current	**7.4 A**
Power factor	**0.73**
Efficiency 4/4 | 3/4 | 2/4	**81.4 | 82.2 | 79.4 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5.6 | 2.1 | 2.9**
Moment of inertia J	**0.023 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0102, p. 27 (PDF 27)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0102 (IE1)

1LE0102-1CC24-1FA4

4 kW / 1000 rpm

Frame 132 M | 6 poles | IM B5 | Article No. 1LE0102-1CC24-1FA4

GENERAL DATA

Series / efficiency class	**1LE0102 / IE1**
Housing	**Cast iron**
Frame size	**132 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**525 V D**
Net weight (IM B3)	**65 kg**

ELECTRICAL DATA

Rated power 50 Hz	**4 kW (about 5.5 HP)**
Rated power 60 Hz	**4.55 kW**
Rated speed (50 Hz)	**955 rpm**
Rated torque	**40 Nm**
Rated current	**7.4 A**
Power factor	**0.73**
Efficiency 4/4 | 3/4 | 2/4	**81.4 | 82.2 | 79.4 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5.6 | 2.1 | 2.9**
Moment of inertia J	**0.023 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0102, p. 27 (PDF 27)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0102 (IE1)

1LE0102-1CC24-1KA4

4 kW / 1000 rpm

Frame 132 M | 6 poles | IM B14 | Article No. 1LE0102-1CC24-1KA4

GENERAL DATA

Series / efficiency class	**1LE0102 / IE1**
Housing	**Cast iron**
Frame size	**132 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**525 V D**
Net weight (IM B3)	**65 kg**

ELECTRICAL DATA

Rated power 50 Hz	**4 kW (about 5.5 HP)**
Rated power 60 Hz	**4.55 kW**
Rated speed (50 Hz)	**955 rpm**
Rated torque	**40 Nm**
Rated current	**7.4 A**
Power factor	**0.73**
Efficiency 4/4 | 3/4 | 2/4	**81.4 | 82.2 | 79.4 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5.6 | 2.1 | 2.9**
Moment of inertia J	**0.023 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0102, p. 27 (PDF 27)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1502 (IE1)

1LE1502-1CC23-4AA4

4 kW / 1000 rpm

Frame 132 M | 6 poles | IM B3 | Article No. 1LE1502-1CC23-4AA4

GENERAL DATA

Series / efficiency class	**1LE1502 / IE1**
Housing	**Cast iron**
Frame size	**132 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**57 kg**

ELECTRICAL DATA

Rated power 50 Hz	**4 kW (about 5.5 HP)**
Rated power 60 Hz	**4.55 kW**
Rated speed (50 Hz)	**955 rpm**
Rated torque	**40 Nm**
Rated current	**9.3 A**
Power factor	**0.76**
Efficiency 4/4 | 3/4 | 2/4	**81.4 | 82.6 | 81.9 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5.2 | 2.3 | 2.6**
Moment of inertia J	**0.021 kgm2**
Sound pressure / power LpfA | LWA	**65 | 78 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1502, p. 2/50 (PDF 168)**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1502 (IE1)

1LE1502-1CC23-4FA4

4 kW / 1000 rpm

Frame 132 M | 6 poles | IM B5 | Article No. 1LE1502-1CC23-4FA4

GENERAL DATA

Series / efficiency class	**1LE1502 / IE1**
Housing	**Cast iron**
Frame size	**132 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**57 kg**

ELECTRICAL DATA

Rated power 50 Hz	**4 kW (about 5.5 HP)**
Rated power 60 Hz	**4.55 kW**
Rated speed (50 Hz)	**955 rpm**
Rated torque	**40 Nm**
Rated current	**9.3 A**
Power factor	**0.76**
Efficiency 4/4 | 3/4 | 2/4	**81.4 | 82.6 | 81.9 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5.2 | 2.3 | 2.6**
Moment of inertia J	**0.021 kgm2**
Sound pressure / power LpfA | LWA	**65 | 78 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1502, p. 2/50 (PDF 168)**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1502 (IE1)

1LE1502-1CC23-4KA4

4 kW / 1000 rpm

Frame 132 M | 6 poles | IM B14 | Article No. 1LE1502-1CC23-4KA4

GENERAL DATA

Series / efficiency class	**1LE1502 / IE1**
Housing	**Cast iron**
Frame size	**132 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**57 kg**

ELECTRICAL DATA

Rated power 50 Hz	**4 kW (about 5.5 HP)**
Rated power 60 Hz	**4.55 kW**
Rated speed (50 Hz)	**955 rpm**
Rated torque	**40 Nm**
Rated current	**9.3 A**
Power factor	**0.76**
Efficiency 4/4 | 3/4 | 2/4	**81.4 | 82.6 | 81.9 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5.2 | 2.3 | 2.6**
Moment of inertia J	**0.021 kgm2**
Sound pressure / power LpfA | LWA	**65 | 78 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1502, p. 2/50 (PDF 168)**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0101 (IE2)

1LE0101-1CC22-2AA4

4 kW / 1000 rpm

Frame 132 M | 6 poles | IM B3 | Article No. 1LE0101-1CC22-2AA4

GENERAL DATA

Series / efficiency class	**1LE0101 / IE2**
Housing	**Cast iron**
Frame size	**132 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**66 kg**

ELECTRICAL DATA

Rated power 50 Hz	**4 kW (about 5.5 HP)**
Rated power 60 Hz	**4.55 kW**
Rated speed (50 Hz)	**960 rpm**
Rated torque	**39.8 Nm**
Rated current	**9.4 A**
Power factor	**0.73**
Efficiency 4/4 | 3/4 | 2/4	**84.6 | 85.4 | 84.5 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5.6 | 2.1 | 2.9**
Moment of inertia J	**0.024 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0101, p. 25 (PDF 25)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0101 (IE2)

1LE0101-1CC22-2FA4

4 kW / 1000 rpm

Frame 132 M | 6 poles | IM B5 | Article No. 1LE0101-1CC22-2FA4

GENERAL DATA

Series / efficiency class	**1LE0101 / IE2**
Housing	**Cast iron**
Frame size	**132 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**66 kg**

ELECTRICAL DATA

Rated power 50 Hz	**4 kW (about 5.5 HP)**
Rated power 60 Hz	**4.55 kW**
Rated speed (50 Hz)	**960 rpm**
Rated torque	**39.8 Nm**
Rated current	**9.4 A**
Power factor	**0.73**
Efficiency 4/4 | 3/4 | 2/4	**84.6 | 85.4 | 84.5 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5.6 | 2.1 | 2.9**
Moment of inertia J	**0.024 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0101, p. 25 (PDF 25)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0101 (IE2)

1LE0101-1CC22-2KA4

4 kW / 1000 rpm

Frame 132 M | 6 poles | IM B14 | Article No. 1LE0101-1CC22-2KA4

GENERAL DATA

Series / efficiency class	**1LE0101 / IE2**
Housing	**Cast iron**
Frame size	**132 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**230 D / 400 Y V (50 Hz)**
Net weight (IM B3)	**66 kg**

ELECTRICAL DATA

Rated power 50 Hz	**4 kW (about 5.5 HP)**
Rated power 60 Hz	**4.55 kW**
Rated speed (50 Hz)	**960 rpm**
Rated torque	**39.8 Nm**
Rated current	**9.4 A**
Power factor	**0.73**
Efficiency 4/4 | 3/4 | 2/4	**84.6 | 85.4 | 84.5 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5.6 | 2.1 | 2.9**
Moment of inertia J	**0.024 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0101, p. 25 (PDF 25)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0101 (IE2)

1LE0101-1CC23-4AA4

4 kW / 1000 rpm

Frame 132 M | 6 poles | IM B3 | Article No. 1LE0101-1CC23-4AA4

GENERAL DATA

Series / efficiency class	**1LE0101 / IE2**
Housing	**Cast iron**
Frame size	**132 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**66 kg**

ELECTRICAL DATA

Rated power 50 Hz	**4 kW (about 5.5 HP)**
Rated power 60 Hz	**4.55 kW**
Rated speed (50 Hz)	**960 rpm**
Rated torque	**39.8 Nm**
Rated current	**9.3 A**
Power factor	**0.73**
Efficiency 4/4 | 3/4 | 2/4	**84.6 | 85.4 | 84.5 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5.6 | 2.1 | 2.9**
Moment of inertia J	**0.024 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0101, p. 25 (PDF 25)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0101 (IE2)

1LE0101-1CC23-4FA4

4 kW / 1000 rpm

Frame 132 M | 6 poles | IM B5 | Article No. 1LE0101-1CC23-4FA4

GENERAL DATA

Series / efficiency class	**1LE0101 / IE2**
Housing	**Cast iron**
Frame size	**132 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**66 kg**

ELECTRICAL DATA

Rated power 50 Hz	**4 kW (about 5.5 HP)**
Rated power 60 Hz	**4.55 kW**
Rated speed (50 Hz)	**960 rpm**
Rated torque	**39.8 Nm**
Rated current	**9.3 A**
Power factor	**0.73**
Efficiency 4/4 | 3/4 | 2/4	**84.6 | 85.4 | 84.5 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5.6 | 2.1 | 2.9**
Moment of inertia J	**0.024 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0101, p. 25 (PDF 25)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0101 (IE2)

1LE0101-1CC23-4KA4

4 kW / 1000 rpm

Frame 132 M | 6 poles | IM B14 | Article No. 1LE0101-1CC23-4KA4

GENERAL DATA

Series / efficiency class	**1LE0101 / IE2**
Housing	**Cast iron**
Frame size	**132 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**66 kg**

ELECTRICAL DATA

Rated power 50 Hz	**4 kW (about 5.5 HP)**
Rated power 60 Hz	**4.55 kW**
Rated speed (50 Hz)	**960 rpm**
Rated torque	**39.8 Nm**
Rated current	**9.3 A**
Power factor	**0.73**
Efficiency 4/4 | 3/4 | 2/4	**84.6 | 85.4 | 84.5 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5.6 | 2.1 | 2.9**
Moment of inertia J	**0.024 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0101, p. 25 (PDF 25)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0101 (IE2)

1LE0101-1CC24-1AA4

4 kW / 1000 rpm

Frame 132 M | 6 poles | IM B3 | Article No. 1LE0101-1CC24-1AA4

GENERAL DATA

Series / efficiency class	**1LE0101 / IE2**
Housing	**Cast iron**
Frame size	**132 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**525 V D**
Net weight (IM B3)	**66 kg**

ELECTRICAL DATA

Rated power 50 Hz	**4 kW (about 5.5 HP)**
Rated power 60 Hz	**4.55 kW**
Rated speed (50 Hz)	**960 rpm**
Rated torque	**39.8 Nm**
Rated current	**7.1 A**
Power factor	**0.73**
Efficiency 4/4 | 3/4 | 2/4	**84.6 | 85.4 | 84.5 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5.6 | 2.1 | 2.9**
Moment of inertia J	**0.024 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0101, p. 29 (PDF 29)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0101 (IE2)

1LE0101-1CC24-1FA4

4 kW / 1000 rpm

Frame 132 M | 6 poles | IM B5 | Article No. 1LE0101-1CC24-1FA4

GENERAL DATA

Series / efficiency class	**1LE0101 / IE2**
Housing	**Cast iron**
Frame size	**132 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**525 V D**
Net weight (IM B3)	**66 kg**

ELECTRICAL DATA

Rated power 50 Hz	**4 kW (about 5.5 HP)**
Rated power 60 Hz	**4.55 kW**
Rated speed (50 Hz)	**960 rpm**
Rated torque	**39.8 Nm**
Rated current	**7.1 A**
Power factor	**0.73**
Efficiency 4/4 | 3/4 | 2/4	**84.6 | 85.4 | 84.5 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5.6 | 2.1 | 2.9**
Moment of inertia J	**0.024 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0101, p. 29 (PDF 29)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0101 (IE2)

1LE0101-1CC24-1KA4

4 kW / 1000 rpm

Frame 132 M | 6 poles | IM B14 | Article No. 1LE0101-1CC24-1KA4

GENERAL DATA

Series / efficiency class	**1LE0101 / IE2**
Housing	**Cast iron**
Frame size	**132 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**525 V D**
Net weight (IM B3)	**66 kg**

ELECTRICAL DATA

Rated power 50 Hz	**4 kW (about 5.5 HP)**
Rated power 60 Hz	**4.55 kW**
Rated speed (50 Hz)	**960 rpm**
Rated torque	**39.8 Nm**
Rated current	**7.1 A**
Power factor	**0.73**
Efficiency 4/4 | 3/4 | 2/4	**84.6 | 85.4 | 84.5 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5.6 | 2.1 | 2.9**
Moment of inertia J	**0.024 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0101, p. 29 (PDF 29)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1501 (IE2)

1LE1501-1CC23-4AA4

4 kW / 1000 rpm

Frame 132 M | 6 poles | IM B3 | Article No. 1LE1501-1CC23-4AA4

GENERAL DATA

Series / efficiency class	**1LE1501 / IE2**
Housing	**Cast iron**
Frame size	**132 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**61 kg**

ELECTRICAL DATA

Rated power 50 Hz	**4 kW (about 5.5 HP)**
Rated power 60 Hz	**4.55 kW**
Rated speed (50 Hz)	**970 rpm**
Rated torque	**39 Nm**
Rated current	**9.1 A**
Power factor	**0.75**
Efficiency 4/4 | 3/4 | 2/4	**84.6 | 85.5 | 84.3 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5 | 1.6 | 2.3**
Moment of inertia J	**0.029 kgm2**
Sound pressure / power LpfA | LWA	**63 | 75 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1501, p. 2/34 (PDF 152)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1501 (IE2)

1LE1501-1CC23-4FA4

4 kW / 1000 rpm

Frame 132 M | 6 poles | IM B5 | Article No. 1LE1501-1CC23-4FA4

GENERAL DATA

Series / efficiency class	**1LE1501 / IE2**
Housing	**Cast iron**
Frame size	**132 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**61 kg**

ELECTRICAL DATA

Rated power 50 Hz	**4 kW (about 5.5 HP)**
Rated power 60 Hz	**4.55 kW**
Rated speed (50 Hz)	**970 rpm**
Rated torque	**39 Nm**
Rated current	**9.1 A**
Power factor	**0.75**
Efficiency 4/4 | 3/4 | 2/4	**84.6 | 85.5 | 84.3 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5 | 1.6 | 2.3**
Moment of inertia J	**0.029 kgm2**
Sound pressure / power LpfA | LWA	**63 | 75 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1501, p. 2/34 (PDF 152)**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1501 (IE2)

1LE1501-1CC23-4KA4

4 kW / 1000 rpm

Frame 132 M | 6 poles | IM B14 | Article No. 1LE1501-1CC23-4KA4

GENERAL DATA

Series / efficiency class	**1LE1501 / IE2**
Housing	**Cast iron**
Frame size	**132 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**61 kg**

ELECTRICAL DATA

Rated power 50 Hz	**4 kW (about 5.5 HP)**
Rated power 60 Hz	**4.55 kW**
Rated speed (50 Hz)	**970 rpm**
Rated torque	**39 Nm**
Rated current	**9.1 A**
Power factor	**0.75**
Efficiency 4/4 | 3/4 | 2/4	**84.6 | 85.5 | 84.3 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5 | 1.6 | 2.3**
Moment of inertia J	**0.029 kgm2**
Sound pressure / power LpfA | LWA	**63 | 75 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1501, p. 2/34 (PDF 152)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1503 (IE3)

1LE1503-1CC23-4AA4

4 kW / 1000 rpm

Frame 132 M | 6 poles | IM B3 | Article No. 1LE1503-1CC23-4AA4

GENERAL DATA

Series / efficiency class	**1LE1503 / IE3**
Housing	**Cast iron**
Frame size	**132 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**64 kg**

ELECTRICAL DATA

Rated power 50 Hz	**4 kW (about 5.5 HP)**
Rated power 60 Hz	**not listed (catalog 09/2023)**
Rated speed (50 Hz)	**975 rpm**
Rated torque	**39 Nm**
Rated current	**9.1 A**
Power factor	**0.73**
Efficiency 4/4 | 3/4 | 2/4	**86.8 | 87.3 | 86.2 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**6.2 | 2.2 | 3**
Moment of inertia J	**0.037 kgm2**
Sound pressure / power LpfA | LWA	**67 | 75 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (09/2023), table 1LE1503, p. 3/21**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1503 (IE3)

1LE1503-1CC23-4FA4

4 kW / 1000 rpm

Frame 132 M | 6 poles | IM B5 | Article No. 1LE1503-1CC23-4FA4

GENERAL DATA

Series / efficiency class	**1LE1503 / IE3**
Housing	**Cast iron**
Frame size	**132 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**64 kg**

ELECTRICAL DATA

Rated power 50 Hz	**4 kW (about 5.5 HP)**
Rated power 60 Hz	**not listed (catalog 09/2023)**
Rated speed (50 Hz)	**975 rpm**
Rated torque	**39 Nm**
Rated current	**9.1 A**
Power factor	**0.73**
Efficiency 4/4 | 3/4 | 2/4	**86.8 | 87.3 | 86.2 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**6.2 | 2.2 | 3**
Moment of inertia J	**0.037 kgm2**
Sound pressure / power LpfA | LWA	**67 | 75 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (09/2023), table 1LE1503, p. 3/21**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1543 (IE3)

1LE1543-1CC23-4AA4

4 kW / 1000 rpm

Frame 132 M | 6 poles | IM B3 | Article No. 1LE1543-1CC23-4AA4

GENERAL DATA

Series / efficiency class	**1LE1543 / IE3**
Housing	**Cast iron**
Frame size	**132 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**80 kg**

ELECTRICAL DATA - CATALOG VALUES AT 60 HZ (APAC LINE)

Rated power (P50 rating)	**4 kW (about 5.5 HP)**
Rated power (P60 rating)	**4.55 kW**
Rated speed (60 Hz)	**1180 rpm**
Rated torque (60 Hz)	**30 Nm**
Rated current (460 V, 60 Hz)	**7.5 A**
Power factor (60 Hz)	**0.69**
Efficiency 4/4 | 3/4 | 2/4 (60 Hz)	**89.5 | 89.2 | 87.5 %**
I_LR/I_N | T_LR/T_N | T_B/T_N (60 Hz)	**7.5 | 2.8 | 3.8**
Moment of inertia J	**0.037 kgm2**
Sound pressure / power LpfA | LWA (60 Hz)	**64 | 72 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (09/2023), table 1LE1543, p. 3/67**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
APAC Line: the catalog lists operating values at 60 Hz only; 50 Hz speed/efficiency are not listed (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1543 (IE3)

1LE1543-1CC23-4FA4

4 kW / 1000 rpm

Frame 132 M | 6 poles | IM B5 | Article No. 1LE1543-1CC23-4FA4

GENERAL DATA

Series / efficiency class	**1LE1543 / IE3**
Housing	**Cast iron**
Frame size	**132 M**
Poles	**6**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**80 kg**

ELECTRICAL DATA - CATALOG VALUES AT 60 HZ (APAC LINE)

Rated power (P50 rating)	**4 kW (about 5.5 HP)**
Rated power (P60 rating)	**4.55 kW**
Rated speed (60 Hz)	**1180 rpm**
Rated torque (60 Hz)	**30 Nm**
Rated current (460 V, 60 Hz)	**7.5 A**
Power factor (60 Hz)	**0.69**
Efficiency 4/4 | 3/4 | 2/4 (60 Hz)	**89.5 | 89.2 | 87.5 %**
I_LR/I_N | T_LR/T_N | T_B/T_N (60 Hz)	**7.5 | 2.8 | 3.8**
Moment of inertia J	**0.037 kgm2**
Sound pressure / power LpfA | LWA (60 Hz)	**64 | 72 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (09/2023), table 1LE1543, p. 3/67**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
APAC Line: the catalog lists operating values at 60 Hz only; 50 Hz speed/efficiency are not listed (see Siemens DT Configurator).