Data sheets - Siemens SIMOTICS GP motors

7.5 kW / 750 rpm - 15 article numbers in this file

Article No.	Page
1LE1502-1DD43-4AA4	2
1LE1502-1DD43-4FA4	3
1LE1502-1DD43-4KA4	4
1LE1002-1DD43-4AA4	5
1LE1002-1DD43-4FA4	6
1LE1002-1DD43-4KA4	7
1LE1001-1DD43-4AA4	8
1LE1001-1DD43-4FA4	9
1LE1001-1DD43-4KA4	10
1LE1003-1DD43-4AA4	11
1LE1003-1DD43-4FA4	12
1LE1003-1DD43-4KA4	13
1LE1501-1DD43-4AA4	14
1LE1501-1DD43-4FA4	15
1LE1501-1DD43-4KA4	16

محور نیرو

Tel: 0935 186 4634

info@mehvarniro.com | mehvarniro.com

Data sheet

1LE1502-1DD43-4AA4

SIMOTICS GP low-voltage motor - cast-iron series 1LE1502 Basic Line (IE1)

7.5 kW / 750 rpm

Frame size 160 L | Article No. 1LE1502-1DD43-4AA4 | mounting IM B3

GENERAL DATA

Motor series	**1LE1502 Basic Line (cast iron)**
Article No.	**1LE1502-1DD43-4AA4**
Frame size	**160 L**
Number of poles	**8**
Housing material	**Cast iron**
Degree of protection	**IP55**
Cooling	**Self-ventilated (IC 411)**
Insulation / utilization	**Thermal class 155 (F) / utilized to 130 (B)**
Duty type	**S1 (continuous duty)**
Rotor	**Squirrel-cage**
Efficiency class (IEC 60034-30)	**IE1**
Voltage / connection	**400 V Δ / 690 V Y (50 Hz), 460 V Δ (60 Hz)**
Type of construction	**IM B3 (basic type, without flange)**
Net weight (IM B3)	**120 kg**

ELECTRICAL DATA - 400 V, 50 HZ

Rated power, 50 Hz	**7.5 kW (10 HP)**
Rated speed, 50 Hz	**715 rpm (synchronous 750 rpm)**
Rated torque	**100 Nm**
Rated current at 400 V	**18.9 A**
Power factor cos φ	**0.69**
Efficiency at 4/4 | 3/4 | 2/4 load	**83.1 | 83.7 | 82.4 %**
Locked-rotor current ratio (I_LR/I_N)	**3.8**
Locked-rotor torque ratio (T_LR/T_N)	**1.7**
Breakdown torque ratio (T_B/T_N)	**2.2**
Moment of inertia J	**0.077 kgm²**
Sound pressure level LpfA (50 Hz)	**63 dB(A)**
Sound power level LWA (50 Hz)	**75 dB(A)**

60 HZ OPERATION

Rated power at 60 Hz (460 V)	**8.6 kW**
Synchronous speed at 60 Hz	**900 rpm**
Speed / efficiency / current at 60 Hz	**not listed in the catalog (DT Configurator)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Source: Siemens Catalog D 81.1 (05/2018), p. 2/51. Dimensions: see the same catalog.
Compiled from the manufacturer's catalog data for reference. It is not an official Siemens document - verify against the current Siemens data sheet before ordering.
Data at rated power, 400 V / 50 Hz, ambient 40 °C, altitude up to 1000 m.

Data sheet

1LE1502-1DD43-4FA4

SIMOTICS GP low-voltage motor - cast-iron series 1LE1502 Basic Line (IE1)

7.5 kW / 750 rpm

Frame size 160 L | Article No. 1LE1502-1DD43-4FA4 | mounting IM B5

GENERAL DATA

Motor series	**1LE1502 Basic Line (cast iron)**
Article No.	**1LE1502-1DD43-4FA4**
Frame size	**160 L**
Number of poles	**8**
Housing material	**Cast iron**
Degree of protection	**IP55**
Cooling	**Self-ventilated (IC 411)**
Insulation / utilization	**Thermal class 155 (F) / utilized to 130 (B)**
Duty type	**S1 (continuous duty)**
Rotor	**Squirrel-cage**
Efficiency class (IEC 60034-30)	**IE1**
Voltage / connection	**400 V Δ / 690 V Y (50 Hz), 460 V Δ (60 Hz)**
Type of construction	**IM B5 (flange)**
Net weight (IM B3)	**120 kg**

ELECTRICAL DATA - 400 V, 50 HZ

Rated power, 50 Hz	**7.5 kW (10 HP)**
Rated speed, 50 Hz	**715 rpm (synchronous 750 rpm)**
Rated torque	**100 Nm**
Rated current at 400 V	**18.9 A**
Power factor cos φ	**0.69**
Efficiency at 4/4 | 3/4 | 2/4 load	**83.1 | 83.7 | 82.4 %**
Locked-rotor current ratio (I_LR/I_N)	**3.8**
Locked-rotor torque ratio (T_LR/T_N)	**1.7**
Breakdown torque ratio (T_B/T_N)	**2.2**
Moment of inertia J	**0.077 kgm²**
Sound pressure level LpfA (50 Hz)	**63 dB(A)**
Sound power level LWA (50 Hz)	**75 dB(A)**

60 HZ OPERATION

Rated power at 60 Hz (460 V)	**8.6 kW**
Synchronous speed at 60 Hz	**900 rpm**
Speed / efficiency / current at 60 Hz	**not listed in the catalog (DT Configurator)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Source: Siemens Catalog D 81.1 (05/2018), p. 2/51. Dimensions: see the same catalog.
Compiled from the manufacturer's catalog data for reference. It is not an official Siemens document - verify against the current Siemens data sheet before ordering.
Data at rated power, 400 V / 50 Hz, ambient 40 °C, altitude up to 1000 m.

Data sheet

1LE1502-1DD43-4KA4

SIMOTICS GP low-voltage motor - cast-iron series 1LE1502 Basic Line (IE1)

7.5 kW / 750 rpm

Frame size 160 L | Article No. 1LE1502-1DD43-4KA4 | mounting IM B14

GENERAL DATA

Motor series	**1LE1502 Basic Line (cast iron)**
Article No.	**1LE1502-1DD43-4KA4**
Frame size	**160 L**
Number of poles	**8**
Housing material	**Cast iron**
Degree of protection	**IP55**
Cooling	**Self-ventilated (IC 411)**
Insulation / utilization	**Thermal class 155 (F) / utilized to 130 (B)**
Duty type	**S1 (continuous duty)**
Rotor	**Squirrel-cage**
Efficiency class (IEC 60034-30)	**IE1**
Voltage / connection	**400 V Δ / 690 V Y (50 Hz), 460 V Δ (60 Hz)**
Type of construction	**IM B14 (flange)**
Net weight (IM B3)	**120 kg**

ELECTRICAL DATA - 400 V, 50 HZ

Rated power, 50 Hz	**7.5 kW (10 HP)**
Rated speed, 50 Hz	**715 rpm (synchronous 750 rpm)**
Rated torque	**100 Nm**
Rated current at 400 V	**18.9 A**
Power factor cos φ	**0.69**
Efficiency at 4/4 | 3/4 | 2/4 load	**83.1 | 83.7 | 82.4 %**
Locked-rotor current ratio (I_LR/I_N)	**3.8**
Locked-rotor torque ratio (T_LR/T_N)	**1.7**
Breakdown torque ratio (T_B/T_N)	**2.2**
Moment of inertia J	**0.077 kgm²**
Sound pressure level LpfA (50 Hz)	**63 dB(A)**
Sound power level LWA (50 Hz)	**75 dB(A)**

60 HZ OPERATION

Rated power at 60 Hz (460 V)	**8.6 kW**
Synchronous speed at 60 Hz	**900 rpm**
Speed / efficiency / current at 60 Hz	**not listed in the catalog (DT Configurator)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Source: Siemens Catalog D 81.1 (05/2018), p. 2/51. Dimensions: see the same catalog.
Compiled from the manufacturer's catalog data for reference. It is not an official Siemens document - verify against the current Siemens data sheet before ordering.
Data at rated power, 400 V / 50 Hz, ambient 40 °C, altitude up to 1000 m.

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1002 (IE1)

1LE1002-1DD43-4AA4

7.5 kW / 750 rpm

Frame 160 L | 8 poles | IM B3 | Article No. 1LE1002-1DD43-4AA4

GENERAL DATA

Series / efficiency class	**1LE1002 / IE1**
Housing	**Aluminum**
Frame size	**160 L**
Poles	**8**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**91 kg**

ELECTRICAL DATA

Rated power 50 Hz	**7.5 kW (about 10 HP)**
Rated power 60 Hz	**8.6 kW**
Rated speed (50 Hz)	**715 rpm**
Rated torque	**100 Nm**
Rated current	**18.9 A**
Power factor	**0.69**
Efficiency 4/4 | 3/4 | 2/4	**83.1 | 83.7 | 82.4 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**3.8 | 1.7 | 2.2**
Moment of inertia J	**0.077 kgm2**
Sound pressure / power LpfA | LWA	**63 | 75 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1002, p. 2/46 (PDF 164)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1002 (IE1)

1LE1002-1DD43-4FA4

7.5 kW / 750 rpm

Frame 160 L | 8 poles | IM B5 | Article No. 1LE1002-1DD43-4FA4

GENERAL DATA

Series / efficiency class	**1LE1002 / IE1**
Housing	**Aluminum**
Frame size	**160 L**
Poles	**8**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**91 kg**

ELECTRICAL DATA

Rated power 50 Hz	**7.5 kW (about 10 HP)**
Rated power 60 Hz	**8.6 kW**
Rated speed (50 Hz)	**715 rpm**
Rated torque	**100 Nm**
Rated current	**18.9 A**
Power factor	**0.69**
Efficiency 4/4 | 3/4 | 2/4	**83.1 | 83.7 | 82.4 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**3.8 | 1.7 | 2.2**
Moment of inertia J	**0.077 kgm2**
Sound pressure / power LpfA | LWA	**63 | 75 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1002, p. 2/46 (PDF 164)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1002 (IE1)

1LE1002-1DD43-4KA4

7.5 kW / 750 rpm

Frame 160 L | 8 poles | IM B14 | Article No. 1LE1002-1DD43-4KA4

GENERAL DATA

Series / efficiency class	**1LE1002 / IE1**
Housing	**Aluminum**
Frame size	**160 L**
Poles	**8**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**91 kg**

ELECTRICAL DATA

Rated power 50 Hz	**7.5 kW (about 10 HP)**
Rated power 60 Hz	**8.6 kW**
Rated speed (50 Hz)	**715 rpm**
Rated torque	**100 Nm**
Rated current	**18.9 A**
Power factor	**0.69**
Efficiency 4/4 | 3/4 | 2/4	**83.1 | 83.7 | 82.4 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**3.8 | 1.7 | 2.2**
Moment of inertia J	**0.077 kgm2**
Sound pressure / power LpfA | LWA	**63 | 75 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1002, p. 2/46 (PDF 164)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1001 (IE2)

1LE1001-1DD43-4AA4

7.5 kW / 750 rpm

Frame 160 L | 8 poles | IM B3 | Article No. 1LE1001-1DD43-4AA4

GENERAL DATA

Series / efficiency class	**1LE1001 / IE2**
Housing	**Aluminum**
Frame size	**160 L**
Poles	**8**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**94 kg**

ELECTRICAL DATA

Rated power 50 Hz	**7.5 kW (about 10 HP)**
Rated power 60 Hz	**8.6 kW**
Rated speed (50 Hz)	**725 rpm**
Rated torque	**99 Nm**
Rated current	**18.1 A**
Power factor	**0.7**
Efficiency 4/4 | 3/4 | 2/4	**85.3 | 86.4 | 86 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**3.8 | 1.6 | 1.9**
Moment of inertia J	**0.098 kgm2**
Sound pressure / power LpfA | LWA	**63 | 75 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1001, p. 2/29 (PDF 147)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1001 (IE2)

1LE1001-1DD43-4FA4

7.5 kW / 750 rpm

Frame 160 L | 8 poles | IM B5 | Article No. 1LE1001-1DD43-4FA4

GENERAL DATA

Series / efficiency class	**1LE1001 / IE2**
Housing	**Aluminum**
Frame size	**160 L**
Poles	**8**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**94 kg**

ELECTRICAL DATA

Rated power 50 Hz	**7.5 kW (about 10 HP)**
Rated power 60 Hz	**8.6 kW**
Rated speed (50 Hz)	**725 rpm**
Rated torque	**99 Nm**
Rated current	**18.1 A**
Power factor	**0.7**
Efficiency 4/4 | 3/4 | 2/4	**85.3 | 86.4 | 86 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**3.8 | 1.6 | 1.9**
Moment of inertia J	**0.098 kgm2**
Sound pressure / power LpfA | LWA	**63 | 75 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1001, p. 2/29 (PDF 147)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1001 (IE2)

1LE1001-1DD43-4KA4

7.5 kW / 750 rpm

Frame 160 L | 8 poles | IM B14 | Article No. 1LE1001-1DD43-4KA4

GENERAL DATA

Series / efficiency class	**1LE1001 / IE2**
Housing	**Aluminum**
Frame size	**160 L**
Poles	**8**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**94 kg**

ELECTRICAL DATA

Rated power 50 Hz	**7.5 kW (about 10 HP)**
Rated power 60 Hz	**8.6 kW**
Rated speed (50 Hz)	**725 rpm**
Rated torque	**99 Nm**
Rated current	**18.1 A**
Power factor	**0.7**
Efficiency 4/4 | 3/4 | 2/4	**85.3 | 86.4 | 86 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**3.8 | 1.6 | 1.9**
Moment of inertia J	**0.098 kgm2**
Sound pressure / power LpfA | LWA	**63 | 75 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1001, p. 2/29 (PDF 147)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1003 (IE3)

1LE1003-1DD43-4AA4

7.5 kW / 750 rpm

Frame 160 L | 8 poles | IM B3 | Article No. 1LE1003-1DD43-4AA4

GENERAL DATA

Series / efficiency class	**1LE1003 / IE3**
Housing	**Aluminum**
Frame size	**160 L**
Poles	**8**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**86 kg**

ELECTRICAL DATA

Rated power 50 Hz	**7.5 kW (about 10 HP)**
Rated power 60 Hz	**not listed (catalog 09/2023)**
Rated speed (50 Hz)	**730 rpm**
Rated torque	**98 Nm**
Rated current	**16.9 A**
Power factor	**0.73**
Efficiency 4/4 | 3/4 | 2/4	**87.3 | 87.9 | 86.9 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5.8 | 2.3 | 2.7**
Moment of inertia J	**0.13 kgm2**
Sound pressure / power LpfA | LWA	**70 | 78 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (09/2023), table 1LE1003, p. 3/16**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1003 (IE3)

1LE1003-1DD43-4FA4

7.5 kW / 750 rpm

Frame 160 L | 8 poles | IM B5 | Article No. 1LE1003-1DD43-4FA4

GENERAL DATA

Series / efficiency class	**1LE1003 / IE3**
Housing	**Aluminum**
Frame size	**160 L**
Poles	**8**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**86 kg**

ELECTRICAL DATA

Rated power 50 Hz	**7.5 kW (about 10 HP)**
Rated power 60 Hz	**not listed (catalog 09/2023)**
Rated speed (50 Hz)	**730 rpm**
Rated torque	**98 Nm**
Rated current	**16.9 A**
Power factor	**0.73**
Efficiency 4/4 | 3/4 | 2/4	**87.3 | 87.9 | 86.9 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5.8 | 2.3 | 2.7**
Moment of inertia J	**0.13 kgm2**
Sound pressure / power LpfA | LWA	**70 | 78 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (09/2023), table 1LE1003, p. 3/16**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1003 (IE3)

1LE1003-1DD43-4KA4

7.5 kW / 750 rpm

Frame 160 L | 8 poles | IM B14 | Article No. 1LE1003-1DD43-4KA4

GENERAL DATA

Series / efficiency class	**1LE1003 / IE3**
Housing	**Aluminum**
Frame size	**160 L**
Poles	**8**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**86 kg**

ELECTRICAL DATA

Rated power 50 Hz	**7.5 kW (about 10 HP)**
Rated power 60 Hz	**not listed (catalog 09/2023)**
Rated speed (50 Hz)	**730 rpm**
Rated torque	**98 Nm**
Rated current	**16.9 A**
Power factor	**0.73**
Efficiency 4/4 | 3/4 | 2/4	**87.3 | 87.9 | 86.9 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**5.8 | 2.3 | 2.7**
Moment of inertia J	**0.13 kgm2**
Sound pressure / power LpfA | LWA	**70 | 78 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (09/2023), table 1LE1003, p. 3/16**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1501 (IE2)

1LE1501-1DD43-4AA4

7.5 kW / 750 rpm

Frame 160 L | 8 poles | IM B3 | Article No. 1LE1501-1DD43-4AA4

GENERAL DATA

Series / efficiency class	**1LE1501 / IE2**
Housing	**Cast iron**
Frame size	**160 L**
Poles	**8**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**123 kg**

ELECTRICAL DATA

Rated power 50 Hz	**7.5 kW (about 10 HP)**
Rated power 60 Hz	**8.6 kW**
Rated speed (50 Hz)	**725 rpm**
Rated torque	**99 Nm**
Rated current	**18.1 A**
Power factor	**0.7**
Efficiency 4/4 | 3/4 | 2/4	**85.3 | 86.4 | 86 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**3.8 | 1.6 | 1.9**
Moment of inertia J	**0.098 kgm2**
Sound pressure / power LpfA | LWA	**63 | 75 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1501, p. 2/35 (PDF 153)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1501 (IE2)

1LE1501-1DD43-4FA4

7.5 kW / 750 rpm

Frame 160 L | 8 poles | IM B5 | Article No. 1LE1501-1DD43-4FA4

GENERAL DATA

Series / efficiency class	**1LE1501 / IE2**
Housing	**Cast iron**
Frame size	**160 L**
Poles	**8**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**123 kg**

ELECTRICAL DATA

Rated power 50 Hz	**7.5 kW (about 10 HP)**
Rated power 60 Hz	**8.6 kW**
Rated speed (50 Hz)	**725 rpm**
Rated torque	**99 Nm**
Rated current	**18.1 A**
Power factor	**0.7**
Efficiency 4/4 | 3/4 | 2/4	**85.3 | 86.4 | 86 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**3.8 | 1.6 | 1.9**
Moment of inertia J	**0.098 kgm2**
Sound pressure / power LpfA | LWA	**63 | 75 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1501, p. 2/35 (PDF 153)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1501 (IE2)

1LE1501-1DD43-4KA4

7.5 kW / 750 rpm

Frame 160 L | 8 poles | IM B14 | Article No. 1LE1501-1DD43-4KA4

GENERAL DATA

Series / efficiency class	**1LE1501 / IE2**
Housing	**Cast iron**
Frame size	**160 L**
Poles	**8**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**123 kg**

ELECTRICAL DATA

Rated power 50 Hz	**7.5 kW (about 10 HP)**
Rated power 60 Hz	**8.6 kW**
Rated speed (50 Hz)	**725 rpm**
Rated torque	**99 Nm**
Rated current	**18.1 A**
Power factor	**0.7**
Efficiency 4/4 | 3/4 | 2/4	**85.3 | 86.4 | 86 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**3.8 | 1.6 | 1.9**
Moment of inertia J	**0.098 kgm2**
Sound pressure / power LpfA | LWA	**63 | 75 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1501, p. 2/35 (PDF 153)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).