Data sheets - Siemens SIMOTICS GP motors

75 kW / 3000 rpm - 27 article numbers in this file

Article No.	Page
1LE0102-2DA03-4AA4	2
1LE0102-2DA03-4FA4	3
1LE0102-2DA04-1AA4	4
1LE0102-2DA04-1FA4	5
1LE1502-2DA03-4FA4	6
1LE1502-2CA63-4AA4	7
1LE1502-2CA63-4FA4	8
1LE0101-2DA03-4AB4	9
1LE0101-2DA03-4FB4	10
1LE0101-2DA04-1AB4	11
1LE0101-2DA04-1FB4	12
1LE1501-2DA03-4AA4	13
1LE1501-2DA03-4FA4	14
1LE1501-2CA63-4AA4	15
1LE1501-2CA63-4FA4	16
1LE1503-2DA03-4AA4	17
1LE1503-2DA03-4FA4	18
1LE1541-2DA03-4FA4	19
1LE1541-2CA63-4FA4	20
1LE1543-2DA03-4AA4	21
1LE1543-2DA03-4FA4	22
1LE1503-2CA63-4AA4	23
1LE1503-2CA63-4FA4	24
1LE1543-2CA63-4AA4	25
1LE1543-2CA63-4FA4	26
1LE1504-2DA03-4AA4	27
1LE1504-2DA03-4FA4	28

محور نیرو

Tel: 0935 186 4634

info@mehvarniro.com | mehvarniro.com

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0102 (IE1)

1LE0102-2DA03-4AA4

75 kW / 3000 rpm

Frame 280 S | 2 poles | IM B3 | Article No. 1LE0102-2DA03-4AA4

GENERAL DATA

Series / efficiency class	**1LE0102 / IE1**
Housing	**Cast iron**
Frame size	**280 S**
Poles	**2**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**540 kg**

ELECTRICAL DATA

Rated power 50 Hz	**75 kW (about 101 HP)**
Rated power 60 Hz	**84 kW**
Rated speed (50 Hz)	**2970 rpm**
Rated torque	**241 Nm**
Rated current	**134 A**
Power factor	**0.87**
Efficiency 4/4 | 3/4 | 2/4	**92.7 | 92.6 | 91.1 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**6.7 | 2.7 | 3**
Moment of inertia J	**0.7 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0102, p. 20 (PDF 20)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0102 (IE1)

1LE0102-2DA03-4FA4

75 kW / 3000 rpm

Frame 280 S | 2 poles | IM B5 | Article No. 1LE0102-2DA03-4FA4

GENERAL DATA

Series / efficiency class	**1LE0102 / IE1**
Housing	**Cast iron**
Frame size	**280 S**
Poles	**2**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**540 kg**

ELECTRICAL DATA

Rated power 50 Hz	**75 kW (about 101 HP)**
Rated power 60 Hz	**84 kW**
Rated speed (50 Hz)	**2970 rpm**
Rated torque	**241 Nm**
Rated current	**134 A**
Power factor	**0.87**
Efficiency 4/4 | 3/4 | 2/4	**92.7 | 92.6 | 91.1 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**6.7 | 2.7 | 3**
Moment of inertia J	**0.7 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0102, p. 20 (PDF 20)**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0102 (IE1)

1LE0102-2DA04-1AA4

75 kW / 3000 rpm

Frame 280 S | 2 poles | IM B3 | Article No. 1LE0102-2DA04-1AA4

GENERAL DATA

Series / efficiency class	**1LE0102 / IE1**
Housing	**Cast iron**
Frame size	**280 S**
Poles	**2**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**525 V D**
Net weight (IM B3)	**540 kg**

ELECTRICAL DATA

Rated power 50 Hz	**75 kW (about 101 HP)**
Rated power 60 Hz	**84 kW**
Rated speed (50 Hz)	**2970 rpm**
Rated torque	**241 Nm**
Rated current	**102 A**
Power factor	**0.87**
Efficiency 4/4 | 3/4 | 2/4	**92.7 | 92.6 | 91.1 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**6.7 | 2.7 | 3**
Moment of inertia J	**0.7 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0102, p. 26 (PDF 26)**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0102 (IE1)

1LE0102-2DA04-1FA4

75 kW / 3000 rpm

Frame 280 S | 2 poles | IM B5 | Article No. 1LE0102-2DA04-1FA4

GENERAL DATA

Series / efficiency class	**1LE0102 / IE1**
Housing	**Cast iron**
Frame size	**280 S**
Poles	**2**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**525 V D**
Net weight (IM B3)	**540 kg**

ELECTRICAL DATA

Rated power 50 Hz	**75 kW (about 101 HP)**
Rated power 60 Hz	**84 kW**
Rated speed (50 Hz)	**2970 rpm**
Rated torque	**241 Nm**
Rated current	**102 A**
Power factor	**0.87**
Efficiency 4/4 | 3/4 | 2/4	**92.7 | 92.6 | 91.1 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**6.7 | 2.7 | 3**
Moment of inertia J	**0.7 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0102, p. 26 (PDF 26)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1502 (IE1)

1LE1502-2DA03-4FA4

75 kW / 3000 rpm

Frame 280 S | 2 poles | IM B5 | Article No. 1LE1502-2DA03-4FA4

GENERAL DATA

Series / efficiency class	**1LE1502 / IE1**
Housing	**Cast iron**
Frame size	**280 S**
Poles	**2**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**470 kg**

ELECTRICAL DATA

Rated power 50 Hz	**75 kW (about 101 HP)**
Rated power 60 Hz	**84 kW**
Rated speed (50 Hz)	**2975 rpm**
Rated torque	**241 Nm**
Rated current	**136 A**
Power factor	**0.86**
Efficiency 4/4 | 3/4 | 2/4	**92.7 | 92.5 | 91.3 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**6.8 | 2.2 | 3**
Moment of inertia J	**0.72 kgm2**
Sound pressure / power LpfA | LWA	**78 | 92 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1502, p. 2/48 (PDF 166)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1502 (IE1)

1LE1502-2CA63-4AA4

75 kW / 3000 rpm

Frame 250 M | 2 poles | IM B3 | Article No. 1LE1502-2CA63-4AA4

GENERAL DATA

Series / efficiency class	**1LE1502 / IE1**
Housing	**Cast iron**
Frame size	**250 M**
Poles	**2**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**420 kg**

ELECTRICAL DATA

Rated power 50 Hz	**75 kW (about 101 HP)**
Rated power 60 Hz	**84 kW**
Rated speed (50 Hz)	**2970 rpm**
Rated torque	**241 Nm**
Rated current	**134 A**
Power factor	**0.87**
Efficiency 4/4 | 3/4 | 2/4	**92.7 | 92.8 | 92.1 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**7.3 | 2.4 | 3.1**
Moment of inertia J	**0.48 kgm2**
Sound pressure / power LpfA | LWA	**76 | 89 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1502, p. 2/52 (PDF 170)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1502 (IE1)

1LE1502-2CA63-4FA4

75 kW / 3000 rpm

Frame 250 M | 2 poles | IM B5 | Article No. 1LE1502-2CA63-4FA4

GENERAL DATA

Series / efficiency class	**1LE1502 / IE1**
Housing	**Cast iron**
Frame size	**250 M**
Poles	**2**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**420 kg**

ELECTRICAL DATA

Rated power 50 Hz	**75 kW (about 101 HP)**
Rated power 60 Hz	**84 kW**
Rated speed (50 Hz)	**2970 rpm**
Rated torque	**241 Nm**
Rated current	**134 A**
Power factor	**0.87**
Efficiency 4/4 | 3/4 | 2/4	**92.7 | 92.8 | 92.1 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**7.3 | 2.4 | 3.1**
Moment of inertia J	**0.48 kgm2**
Sound pressure / power LpfA | LWA	**76 | 89 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1502, p. 2/52 (PDF 170)**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0101 (IE2)

1LE0101-2DA03-4AB4

75 kW / 3000 rpm

Frame 280 S | 2 poles | IM B3 | Article No. 1LE0101-2DA03-4AB4

GENERAL DATA

Series / efficiency class	**1LE0101 / IE2**
Housing	**Cast iron**
Frame size	**280 S**
Poles	**2**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**550 kg**

ELECTRICAL DATA

Rated power 50 Hz	**75 kW (about 101 HP)**
Rated power 60 Hz	**84 kW**
Rated speed (50 Hz)	**2975 rpm**
Rated torque	**241 Nm**
Rated current	**133 A**
Power factor	**0.87**
Efficiency 4/4 | 3/4 | 2/4	**93.8 | 93.8 | 92.7 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**7.5 | 2.8 | 3**
Moment of inertia J	**0.75 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0101, p. 23 (PDF 23)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0101 (IE2)

1LE0101-2DA03-4FB4

75 kW / 3000 rpm

Frame 280 S | 2 poles | IM B5 | Article No. 1LE0101-2DA03-4FB4

GENERAL DATA

Series / efficiency class	**1LE0101 / IE2**
Housing	**Cast iron**
Frame size	**280 S**
Poles	**2**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**550 kg**

ELECTRICAL DATA

Rated power 50 Hz	**75 kW (about 101 HP)**
Rated power 60 Hz	**84 kW**
Rated speed (50 Hz)	**2975 rpm**
Rated torque	**241 Nm**
Rated current	**133 A**
Power factor	**0.87**
Efficiency 4/4 | 3/4 | 2/4	**93.8 | 93.8 | 92.7 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**7.5 | 2.8 | 3**
Moment of inertia J	**0.75 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0101, p. 23 (PDF 23)**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0101 (IE2)

1LE0101-2DA04-1AB4

75 kW / 3000 rpm

Frame 280 S | 2 poles | IM B3 | Article No. 1LE0101-2DA04-1AB4

GENERAL DATA

Series / efficiency class	**1LE0101 / IE2**
Housing	**Cast iron**
Frame size	**280 S**
Poles	**2**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**525 V D**
Net weight (IM B3)	**550 kg**

ELECTRICAL DATA

Rated power 50 Hz	**75 kW (about 101 HP)**
Rated power 60 Hz	**84 kW**
Rated speed (50 Hz)	**2975 rpm**
Rated torque	**241 Nm**
Rated current	**101 A**
Power factor	**0.87**
Efficiency 4/4 | 3/4 | 2/4	**93.8 | 93.8 | 92.7 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**7.5 | 2.8 | 3**
Moment of inertia J	**0.75 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0101, p. 28 (PDF 28)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE0101 (IE2)

1LE0101-2DA04-1FB4

75 kW / 3000 rpm

Frame 280 S | 2 poles | IM B5 | Article No. 1LE0101-2DA04-1FB4

GENERAL DATA

Series / efficiency class	**1LE0101 / IE2**
Housing	**Cast iron**
Frame size	**280 S**
Poles	**2**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**525 V D**
Net weight (IM B3)	**550 kg**

ELECTRICAL DATA

Rated power 50 Hz	**75 kW (about 101 HP)**
Rated power 60 Hz	**84 kW**
Rated speed (50 Hz)	**2975 rpm**
Rated torque	**241 Nm**
Rated current	**101 A**
Power factor	**0.87**
Efficiency 4/4 | 3/4 | 2/4	**93.8 | 93.8 | 92.7 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**7.5 | 2.8 | 3**
Moment of inertia J	**0.75 kgm2**

SOURCE OF DATA

Catalog 1	**Brochure 07/2014 (14050629), table 1LE0101, p. 28 (PDF 28)**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1501 (IE2)

1LE1501-2DA03-4AA4

75 kW / 3000 rpm

Frame 280 S | 2 poles | IM B3 | Article No. 1LE1501-2DA03-4AA4

GENERAL DATA

Series / efficiency class	**1LE1501 / IE2**
Housing	**Cast iron**
Frame size	**280 S**
Poles	**2**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**490 kg**

ELECTRICAL DATA

Rated power 50 Hz	**75 kW (about 101 HP)**
Rated power 60 Hz	**84 kW**
Rated speed (50 Hz)	**2978 rpm**
Rated torque	**240 Nm**
Rated current	**134 A**
Power factor	**0.86**
Efficiency 4/4 | 3/4 | 2/4	**93.8 | 93.6 | 92.4 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**7.2 | 2.5 | 3.2**
Moment of inertia J	**0.71 kgm2**
Sound pressure / power LpfA | LWA	**76 | 89 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1501, p. 2/32 (PDF 150)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1501 (IE2)

1LE1501-2DA03-4FA4

75 kW / 3000 rpm

Frame 280 S | 2 poles | IM B5 | Article No. 1LE1501-2DA03-4FA4

GENERAL DATA

Series / efficiency class	**1LE1501 / IE2**
Housing	**Cast iron**
Frame size	**280 S**
Poles	**2**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**490 kg**

ELECTRICAL DATA

Rated power 50 Hz	**75 kW (about 101 HP)**
Rated power 60 Hz	**84 kW**
Rated speed (50 Hz)	**2978 rpm**
Rated torque	**240 Nm**
Rated current	**134 A**
Power factor	**0.86**
Efficiency 4/4 | 3/4 | 2/4	**93.8 | 93.6 | 92.4 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**7.2 | 2.5 | 3.2**
Moment of inertia J	**0.71 kgm2**
Sound pressure / power LpfA | LWA	**76 | 89 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1501, p. 2/32 (PDF 150)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1501 (IE2)

1LE1501-2CA63-4AA4

75 kW / 3000 rpm

Frame 250 M | 2 poles | IM B3 | Article No. 1LE1501-2CA63-4AA4

GENERAL DATA

Series / efficiency class	**1LE1501 / IE2**
Housing	**Cast iron**
Frame size	**250 M**
Poles	**2**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**390 kg**

ELECTRICAL DATA

Rated power 50 Hz	**75 kW (about 101 HP)**
Rated power 60 Hz	**84 kW**
Rated speed (50 Hz)	**2970 rpm**
Rated torque	**241 Nm**
Rated current	**137 A**
Power factor	**0.84**
Efficiency 4/4 | 3/4 | 2/4	**93.8 | 93.6 | 92.6 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**7 | 2.2 | 3.3**
Moment of inertia J	**0.46 kgm2**
Sound pressure / power LpfA | LWA	**75 | 89 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1501, p. 2/40 (PDF 158)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1501 (IE2)

1LE1501-2CA63-4FA4

75 kW / 3000 rpm

Frame 250 M | 2 poles | IM B5 | Article No. 1LE1501-2CA63-4FA4

GENERAL DATA

Series / efficiency class	**1LE1501 / IE2**
Housing	**Cast iron**
Frame size	**250 M**
Poles	**2**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**390 kg**

ELECTRICAL DATA

Rated power 50 Hz	**75 kW (about 101 HP)**
Rated power 60 Hz	**84 kW**
Rated speed (50 Hz)	**2970 rpm**
Rated torque	**241 Nm**
Rated current	**137 A**
Power factor	**0.84**
Efficiency 4/4 | 3/4 | 2/4	**93.8 | 93.6 | 92.6 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**7 | 2.2 | 3.3**
Moment of inertia J	**0.46 kgm2**
Sound pressure / power LpfA | LWA	**75 | 89 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1501, p. 2/40 (PDF 158)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1503 (IE3)

1LE1503-2DA03-4AA4

75 kW / 3000 rpm

Frame 280 S | 2 poles | IM B3 | Article No. 1LE1503-2DA03-4AA4

GENERAL DATA

Series / efficiency class	**1LE1503 / IE3**
Housing	**Cast iron**
Frame size	**280 S**
Poles	**2**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**510 kg**

ELECTRICAL DATA

Rated power 50 Hz	**75 kW (about 101 HP)**
Rated power 60 Hz	**84 kW**
Rated speed (50 Hz)	**2975 rpm**
Rated torque	**241 Nm**
Rated current	**128 A**
Power factor	**0.89**
Efficiency 4/4 | 3/4 | 2/4	**94.7 | 94.8 | 94.1 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**6.8 | 2.4 | 3**
Moment of inertia J	**0.77 kgm2**
Sound pressure / power LpfA | LWA	**74 | 88 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1503, p. 2/17 (PDF 135)**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1503 (IE3)

1LE1503-2DA03-4FA4

75 kW / 3000 rpm

Frame 280 S | 2 poles | IM B5 | Article No. 1LE1503-2DA03-4FA4

GENERAL DATA

Series / efficiency class	**1LE1503 / IE3**
Housing	**Cast iron**
Frame size	**280 S**
Poles	**2**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**510 kg**

ELECTRICAL DATA

Rated power 50 Hz	**75 kW (about 101 HP)**
Rated power 60 Hz	**84 kW**
Rated speed (50 Hz)	**2975 rpm**
Rated torque	**241 Nm**
Rated current	**128 A**
Power factor	**0.89**
Efficiency 4/4 | 3/4 | 2/4	**94.7 | 94.8 | 94.1 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**6.8 | 2.4 | 3**
Moment of inertia J	**0.77 kgm2**
Sound pressure / power LpfA | LWA	**74 | 88 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1503, p. 2/17 (PDF 135)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1541 (IE2)

1LE1541-2DA03-4FA4

75 kW / 3000 rpm

Frame 280 S | 2 poles | IM B5 | Article No. 1LE1541-2DA03-4FA4

GENERAL DATA

Series / efficiency class	**1LE1541 / IE2**
Housing	**Cast iron**
Frame size	**280 S**
Poles	**2**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**490 kg**

ELECTRICAL DATA - CATALOG VALUES AT 60 HZ (APAC LINE)

Rated power (P50 rating)	**75 kW (about 101 HP)**
Rated power (P60 rating)	**84 kW**
Rated speed (60 Hz)	**3580 rpm**
Rated torque (60 Hz)	**200 Nm**
Rated current (460 V, 60 Hz)	**116 A**
Power factor (60 Hz)	**0.87**
Efficiency 4/4 | 3/4 | 2/4 (60 Hz)	**93.6 | 92.9 | 91.1 %**
I_LR/I_N | T_LR/T_N | T_B/T_N (60 Hz)	**7.7 | 2.8 | 3.5**
Moment of inertia J	**0.71 kgm2**
Sound pressure / power LpfA | LWA (60 Hz)	**81 | 95 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1541, p. 2/68 (PDF 186)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
APAC Line: the catalog lists operating values at 60 Hz only; 50 Hz speed/efficiency are not listed (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1541 (IE2)

1LE1541-2CA63-4FA4

75 kW / 3000 rpm

Frame 250 M | 2 poles | IM B5 | Article No. 1LE1541-2CA63-4FA4

GENERAL DATA

Series / efficiency class	**1LE1541 / IE2**
Housing	**Cast iron**
Frame size	**250 M**
Poles	**2**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**390 kg**

ELECTRICAL DATA - CATALOG VALUES AT 60 HZ (APAC LINE)

Rated power (P50 rating)	**75 kW (about 101 HP)**
Rated power (P60 rating)	**84 kW**
Rated speed (60 Hz)	**3578 rpm**
Rated torque (60 Hz)	**200 Nm**
Rated current (460 V, 60 Hz)	**118 A**
Power factor (60 Hz)	**0.85**
Efficiency 4/4 | 3/4 | 2/4 (60 Hz)	**93.6 | 93.1 | 91.6 %**
I_LR/I_N | T_LR/T_N | T_B/T_N (60 Hz)	**7.7 | 2.4 | 3.5**
Moment of inertia J	**0.46 kgm2**
Sound pressure / power LpfA | LWA (60 Hz)	**80 | 94 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1541, p. 2/70 (PDF 188)**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
APAC Line: the catalog lists operating values at 60 Hz only; 50 Hz speed/efficiency are not listed (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1543 (IE3)

1LE1543-2DA03-4AA4

75 kW / 3000 rpm

Frame 280 S | 2 poles | IM B3 | Article No. 1LE1543-2DA03-4AA4

GENERAL DATA

Series / efficiency class	**1LE1543 / IE3**
Housing	**Cast iron**
Frame size	**280 S**
Poles	**2**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**510 kg**

ELECTRICAL DATA - CATALOG VALUES AT 60 HZ (APAC LINE)

Rated power (P50 rating)	**75 kW (about 101 HP)**
Rated power (P60 rating)	**84 kW**
Rated speed (60 Hz)	**3578 rpm**
Rated torque (60 Hz)	**200 Nm**
Rated current (460 V, 60 Hz)	**112 A**
Power factor (60 Hz)	**0.89**
Efficiency 4/4 | 3/4 | 2/4 (60 Hz)	**94.1 | 93.9 | 92.7 %**
I_LR/I_N | T_LR/T_N | T_B/T_N (60 Hz)	**7.6 | 2.7 | 3.2**
Moment of inertia J	**0.77 kgm2**
Sound pressure / power LpfA | LWA (60 Hz)	**78 | 92 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1543, p. 2/57 (PDF 175)**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
APAC Line: the catalog lists operating values at 60 Hz only; 50 Hz speed/efficiency are not listed (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1543 (IE3)

1LE1543-2DA03-4FA4

75 kW / 3000 rpm

Frame 280 S | 2 poles | IM B5 | Article No. 1LE1543-2DA03-4FA4

GENERAL DATA

Series / efficiency class	**1LE1543 / IE3**
Housing	**Cast iron**
Frame size	**280 S**
Poles	**2**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**510 kg**

ELECTRICAL DATA - CATALOG VALUES AT 60 HZ (APAC LINE)

Rated power (P50 rating)	**75 kW (about 101 HP)**
Rated power (P60 rating)	**84 kW**
Rated speed (60 Hz)	**3578 rpm**
Rated torque (60 Hz)	**200 Nm**
Rated current (460 V, 60 Hz)	**112 A**
Power factor (60 Hz)	**0.89**
Efficiency 4/4 | 3/4 | 2/4 (60 Hz)	**94.1 | 93.9 | 92.7 %**
I_LR/I_N | T_LR/T_N | T_B/T_N (60 Hz)	**7.6 | 2.7 | 3.2**
Moment of inertia J	**0.77 kgm2**
Sound pressure / power LpfA | LWA (60 Hz)	**78 | 92 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1543, p. 2/57 (PDF 175)**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
APAC Line: the catalog lists operating values at 60 Hz only; 50 Hz speed/efficiency are not listed (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1503 (IE3)

1LE1503-2CA63-4AA4

75 kW / 3000 rpm

Frame 250 M | 2 poles | IM B3 | Article No. 1LE1503-2CA63-4AA4

GENERAL DATA

Series / efficiency class	**1LE1503 / IE3**
Housing	**Cast iron**
Frame size	**250 M**
Poles	**2**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**455 kg**

ELECTRICAL DATA

Rated power 50 Hz	**75 kW (about 101 HP)**
Rated power 60 Hz	**84 kW**
Rated speed (50 Hz)	**2970 rpm**
Rated torque	**241 Nm**
Rated current	**127 A**
Power factor	**0.9**
Efficiency 4/4 | 3/4 | 2/4	**94.7 | 94.9 | 94.5 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**6.8 | 2.2 | 2.9**
Moment of inertia J	**0.56 kgm2**
Sound pressure / power LpfA | LWA	**78 | 92 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1503, p. 2/24 (PDF 142)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1503 (IE3)

1LE1503-2CA63-4FA4

75 kW / 3000 rpm

Frame 250 M | 2 poles | IM B5 | Article No. 1LE1503-2CA63-4FA4

GENERAL DATA

Series / efficiency class	**1LE1503 / IE3**
Housing	**Cast iron**
Frame size	**250 M**
Poles	**2**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**455 kg**

ELECTRICAL DATA

Rated power 50 Hz	**75 kW (about 101 HP)**
Rated power 60 Hz	**84 kW**
Rated speed (50 Hz)	**2970 rpm**
Rated torque	**241 Nm**
Rated current	**127 A**
Power factor	**0.9**
Efficiency 4/4 | 3/4 | 2/4	**94.7 | 94.9 | 94.5 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**6.8 | 2.2 | 2.9**
Moment of inertia J	**0.56 kgm2**
Sound pressure / power LpfA | LWA	**78 | 92 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1503, p. 2/24 (PDF 142)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1543 (IE3)

1LE1543-2CA63-4AA4

75 kW / 3000 rpm

Frame 250 M | 2 poles | IM B3 | Article No. 1LE1543-2CA63-4AA4

GENERAL DATA

Series / efficiency class	**1LE1543 / IE3**
Housing	**Cast iron**
Frame size	**250 M**
Poles	**2**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**455 kg**

ELECTRICAL DATA - CATALOG VALUES AT 60 HZ (APAC LINE)

Rated power (P50 rating)	**75 kW (about 101 HP)**
Rated power (P60 rating)	**84 kW**
Rated speed (60 Hz)	**3575 rpm**
Rated torque (60 Hz)	**200 Nm**
Rated current (460 V, 60 Hz)	**111 A**
Power factor (60 Hz)	**0.9**
Efficiency 4/4 | 3/4 | 2/4 (60 Hz)	**94.1 | 93.9 | 92.9 %**
I_LR/I_N | T_LR/T_N | T_B/T_N (60 Hz)	**7.5 | 2.5 | 3.2**
Moment of inertia J	**0.56 kgm2**
Sound pressure / power LpfA | LWA (60 Hz)	**82 | 96 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1543, p. 2/63 (PDF 181)**

Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com
محور نیرو

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
APAC Line: the catalog lists operating values at 60 Hz only; 50 Hz speed/efficiency are not listed (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1543 (IE3)

1LE1543-2CA63-4FA4

75 kW / 3000 rpm

Frame 250 M | 2 poles | IM B5 | Article No. 1LE1543-2CA63-4FA4

GENERAL DATA

Series / efficiency class	**1LE1543 / IE3**
Housing	**Cast iron**
Frame size	**250 M**
Poles	**2**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**455 kg**

ELECTRICAL DATA - CATALOG VALUES AT 60 HZ (APAC LINE)

Rated power (P50 rating)	**75 kW (about 101 HP)**
Rated power (P60 rating)	**84 kW**
Rated speed (60 Hz)	**3575 rpm**
Rated torque (60 Hz)	**200 Nm**
Rated current (460 V, 60 Hz)	**111 A**
Power factor (60 Hz)	**0.9**
Efficiency 4/4 | 3/4 | 2/4 (60 Hz)	**94.1 | 93.9 | 92.9 %**
I_LR/I_N | T_LR/T_N | T_B/T_N (60 Hz)	**7.5 | 2.5 | 3.2**
Moment of inertia J	**0.56 kgm2**
Sound pressure / power LpfA | LWA (60 Hz)	**82 | 96 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1543, p. 2/63 (PDF 181)**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
APAC Line: the catalog lists operating values at 60 Hz only; 50 Hz speed/efficiency are not listed (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1504 (IE4)

1LE1504-2DA03-4AA4

75 kW / 3000 rpm

Frame 280 S | 2 poles | IM B3 | Article No. 1LE1504-2DA03-4AA4

GENERAL DATA

Series / efficiency class	**1LE1504 / IE4**
Housing	**Cast iron**
Frame size	**280 S**
Poles	**2**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**610 kg**

ELECTRICAL DATA

Rated power 50 Hz	**75 kW (about 101 HP)**
Rated power 60 Hz	**84 kW**
Rated speed (50 Hz)	**2980 rpm**
Rated torque	**240 Nm**
Rated current	**127 A**
Power factor	**0.89**
Efficiency 4/4 | 3/4 | 2/4	**95.6 | 95.6 | 95 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**8.4 | 2.7 | 3.5**
Moment of inertia J	**0.94 kgm2**
Sound pressure / power LpfA | LWA	**73 | 87 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1504, p. 2/9 (PDF 127)**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).

Data sheet

SIMOTICS GP low-voltage motor - series 1LE1504 (IE4)

1LE1504-2DA03-4FA4

75 kW / 3000 rpm

Frame 280 S | 2 poles | IM B5 | Article No. 1LE1504-2DA03-4FA4

GENERAL DATA

Series / efficiency class	**1LE1504 / IE4**
Housing	**Cast iron**
Frame size	**280 S**
Poles	**2**
Degree of protection	**IP55**
Duty type	**S1**
Insulation	**Thermal class 155 (F), utilized to 130 (B)**
Voltage	**400 D / 690 Y V (50 Hz)**
Net weight (IM B3)	**610 kg**

ELECTRICAL DATA

Rated power 50 Hz	**75 kW (about 101 HP)**
Rated power 60 Hz	**84 kW**
Rated speed (50 Hz)	**2980 rpm**
Rated torque	**240 Nm**
Rated current	**127 A**
Power factor	**0.89**
Efficiency 4/4 | 3/4 | 2/4	**95.6 | 95.6 | 95 %**
I_LR/I_N | T_LR/T_N | T_B/T_N	**8.4 | 2.7 | 3.5**
Moment of inertia J	**0.94 kgm2**
Sound pressure / power LpfA | LWA	**73 | 87 dB(A)**

SOURCE OF DATA

Catalog 1	**Catalog D 81.1 (05/2018), table 1LE1504, p. 2/9 (PDF 127)**

محور نیرو
Tel: 0935 186 4634
info@mehvarniro.com | mehvarniro.com

Compiled from manufacturer catalog data for reference. NOT an official Siemens document - verify against the current Siemens data sheet before ordering.
60 Hz speed/efficiency are not listed in the catalogs (see Siemens DT Configurator).